

SCHEDULES OF QUANTITIES

XZ193400 SURVEY MARKER TYPE 2 (SPECIAL)

	STATION	EACH
STALEY	237+00.00	1
	241+85.06	1
	246+85.57	1
	254+33.23	1
	255+83.97	1
	257+00.00	1
W CURTIS	40+00.00	1
CURTIS	21+32.44	1
	S. N. 010-0272 BENCHMARK	1
	35+06.49	1
	51+03.29	1
RAMP A	12+40.00	1
	16+21.96	1
	18+66.98	1
	25+56.36	1
	37+06.40	1
RAMP B	5+00.00	1
	13+00.23	1
	19+41.02	1
	21+86.03	1
	25+41.35	1
RAMP C	32+40.00	1
	36+22.69	1
	38+67.70	1
	45+57.95	1
	57+07.95	1
RAMP D	20+00.00	1
	28+00.04	1
	34+42.76	1
	36+87.78	1
	40+44.06	1
TOTAL =		31

USE = 31 EACH

Z0030330 IMPACT ATTENUATORS, TEMPORARY (FULLY REDIRECTIVE), TEST LEVEL 3

	STATION	EACH
I-57	292+70 RT	1
	301+70 LT	1
TOTAL =		2

USE = 2 EACH

Z0040530 PIPE UNDERDRAIN REMOVAL

	STATION	IO	STATION	FEET
I-57	STA. 272+30, 56' LT		STA. 284+79, 56' LT	1,249
	STA. 276+18, 56' RT		STA. 283+13, 56' RT	695
	STA. 295+50, 56' LT		STA. 300+00, 56' LT	450
	STA. 295+50, 31' LT		STA. 300+00, 31' LT	450
	STA. 295+50, 31' RT		STA. 300+00, 31' RT	450
	STA. 295+50, 56' RT		STA. 300+00, 56' RT	450
	STA. 309+57, 56' RT		STA. 322+10, 56' RT	1,253
	STA. 311+13, 56' LT		STA. 318+25, 56' LT	712
TOTAL =				5,709

USE = 5,709 FEET

Z0070100 SURVEY MONUMENT COVER ASSEMBLY

	STATION	EACH
CURTIS	26+43.03, 4.77' RT	1

USE = 1 EACH

Z0013825 CONTROLLED LOW STRENGTH MATERIAL

	LOCATION	CU. YD.
STALEY	CULVERT NO. 25	194
	CULVERT NO. 26	268
	STA 246+66	61
	STA 247+07	61
W. CURTIS	STA 41+08	9
TOTAL =		593

USE = 593 CU. YD.

Z0030150 IMPACT ATTENUATORS (NON-REDIRECTIVE), TEST LEVEL 3

	STATION	EACH
I-57	296+75	1
	297+65	1
TOTAL =		2

USE = 2 EACH

Z0030250 IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 3

	STATION	EACH
I-57	293+70 RT	1
	300+70 LT	1
TOTAL =		2

USE = 2 EACH

THICKNESS OF VARIABLE DEPTH LEVEL BINDER

STALEY ROAD STATION	LEFT				RIGHT				LEFT AREA (SQ FT)	RIGHT AREA (SQ FT)	TOTAL AREA (SQ FT)	TOTAL VOL (CU FT)
	EX EOP		CL*		CL*		EX EOP					
	DEPTH (INCH)	OFFSET (FEET)	DEPTH (INCH)	OFFSET (FEET)	DEPTH (INCH)	OFFSET (FEET)	DEPTH (INCH)	OFFSET (FEET)				
257+00.00	2.20	11.96	0	0	0	0	1.92	12.12	1.10	0.97	2.07	
256+00.00	0	11.26	0	0	0	0	2.25	11.07	0.00	1.04	1.04	155.2
255+00.00	0	11.14	0	0	0	0	2.51	10.96	0.00	1.15	1.15	109.2
254+00.00	0.43	11.13	0	0	0	0	2.27	11.00	0.20	1.04	1.24	119.3
253+00.00	0.55	11.00	0	0	0	0	1.77	11.15	0.25	0.82	1.07	115.7
252+00.00	0.68	10.92	0	0	0	0	1.31	11.20	0.31	0.61	0.92	99.8
251+00.00	0.36	11.02	0	0	0	0	0.92	11.02	0.17	0.42	0.59	75.4
250+00.00	0.49	11.02	0	0	0	0	0.82	11.00	0.22	0.38	0.60	59.4
249+00.00	0.66	11.06	0	0	0	0	0.78	11.01	0.30	0.36	0.66	63.1
248+00.00	1.05	11.02	0	0	0	0	0.66	11.18	0.48	0.31	0.79	72.6
247+00.00	0.40	11.00	0	0	0	0	1.10	11.34	0.18	0.52	0.70	74.6
246+00.00	0.77	11.00	0	0	0	0	1.61	11.41	0.35	0.77	1.12	91.1
245+00.00	0.38	10.91	0	0	0	0	1.46	11.46	0.17	0.70	0.87	99.4
244+00.00	0.24	10.87	0	0	0	0	1.32	11.46	0.11	0.63	0.74	80.4
243+00.00	0.73	10.95	0	0	0	0	1.22	11.32	0.33	0.58	0.91	82.4
242+00.00	1.04	11.03	0	0	0	0	1.05	11.20	0.48	0.49	0.97	93.8
241+00.00	0.89	10.89	0	0	0	5.98	0.52	11.41	0.40	0.12	0.52	74.5
240+00.00	0.74	10.71	0	0	0	2.66	1.00	11.38	0.33	0.36	0.69	60.8
239+00.00	0	10.92	0	0	0	1.63	1.14	11.32	0.00	0.46	0.46	57.7
238+00.00	1.038	11.40	0	6.63	0	4.80	2.13	11.28	0.21	0.58	0.78	62.1
237+00.00	0	11.94	0	0	0	0.00	0	10.48	0.00	0.00	0.00	39.1

* AT LOCATIONS WHERE CENTERLINE OFFSET IS NOT ZERO, LOCATION OF ZERO THICKNESS BEGINS AT THE SPECIFIED OFFSET AND CONTINUES TO THE CENTERLINE. SEE CROSS SECTION FOR ADDITIONAL INFORMATION.

TOTAL VAR. DEPTH CU FT = 1685.6
TOTAL VAR. DEPTH TONS = 125.9