

INDEX OF SHEETS

- 1 COVER SHEET
- 2 GENERAL INFORMATION
- 3-4 SUMMARY OF QUANTITIES
- 5 TYPICAL CROSS SECTION
- 6 RESURFACING DETAIL
- 7 MAX WIDTH SIGNING
- 8 VERTICAL ADJUSTMENT OF SPBGR DETAIL
- 9 BRIDGE PLAN & PROFILE
- 10 TRAFFIC STAGING DETAIL
- 11 EXISTING CROSS SECTION
- 12 RE-BAR PLAN
- 13 KEYWAY REPAIR DETAIL
- 14 EXPANSION JOINT DETAIL
- 15 RAIL RETROFIT DETAIL
- 16 EXISTING RAIL PLANS

GENERAL NOTES

- STANDARDS
 701001-01
 701006-02
 701201-02
 701301-02
 701321-08
 702001-05

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	
DIVISION OF HIGHWAYS	
DISTRICT 6	
EXAMINED <u>Mar 21</u> 20 <u>05</u>	<i>[Signature]</i> ENGINEER OF OPERATIONS
EXAMINED <u>FEB 28</u> 20 <u>05</u>	<i>[Signature]</i> ENGINEER OF PROGRAM IMPLEMENTATION
EXAMINED <u>MARCH 8</u> 20 <u>05</u>	<i>[Signature]</i> ENGINEER OF PROGRAM DEVELOPMENT

APPLICATION RATES

BIT. PAVING = 0.056 TON / SQ YD - IN
 BIT MATL. (PRIME CT) = 0.00038 TON / SQ YD
 AGG. (PRIME CT) = 0.002 TON / SQ YD
 AGG. SHLDR, TY. B = 2.05 TON / CU YD

BITUMINOUS MIX REQUIREMENTS

MIX	BIT. SURF. CSE. SP, MIX C, N50	BIT. SHLDR. SUPERPAVE	BIT. BIND. CSE. SUPERPAVE, N 50
AC/PG	PG 64-22	PG 58-22	PG 64-22
RAP % (MAX)	15%	15%	15%
DESIGN AIR VOIDS	4.0% @ N DESIGN = 50	2.0% @ N DESIGN = 30	4.0% @ N DESIGN=50
GRADATION MIXTURE	IL 9.5 OR 12.5	BAM	IL 19.0
FRICTION AGGREGATE	MIX "C"	N/A	N/A

GENERAL INFORMATION
 FAP 614 (IL 78)
 SECTION (144BR-3)D
 CASS COUNTY