

teasleyck
4/1/2005
c:\projects\74059d\03904pa.dgn
GN & I

FAS SYL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
8736	(110) RS-4	JEFFERSON		2
FED. ROAD DIST. NO. 7		ILLINOIS	FED. AID PROJECT NO.	

CONTRACT NO. 74059

GENERAL NOTES

THIS SECTION SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE PLANS, THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", ADOPTED JANUARY 1, 2002, THE "SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS" INDICATED ON THE CHECK SHEET, AND "THE SPECIAL PROVISIONS" INCLUDED IN THE PROPOSAL.

THE WORK INCLUDED IN THIS SECTION (110) RS-4 CONSISTS OF MILLING, SURFACE COURSE, PAVEMENT MARKING AND ANY OTHER INCIDENTAL WORK NECESSARY TO COMPLETE THE SECTION.

THE CONTRACTOR WILL PROVIDE INTERNET ACCESSIBILITY TO THE BITUMINOUS PLANT QUALITY CONTROL LAB SO THAT REPORTS CAN BE E-MAILED TO THE DISTRICT HEADQUARTERS. THIS WORK SHALL BE INCLUDED IN THE COST OF ALL BITUMINOUS ITEMS.

FOR THE PAY ITEM BITUMINOUS MATERIALS (PRIME COAT), THE CONTRACTOR SHALL USE EITHER RC-70 OR SS-1HP.

A BITUMINOUS WEDGE SHALL BE PLACED AROUND ALL MANHOLES AND VALVE BOXES AFTER BITUMINOUS SURFACE REMOVAL. THE COST SHALL BE INCLUDED WITH THE COST OF THE BITUMINOUS SURFACE REMOVAL 1 1/2".

THE ACTUAL LOCATIONS OF PAVEMENT PATCHING SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.

SHORT TERM PAVEMENT MARKINGS ON MILLED SURFACES SHALL BE PAINT. ALL OTHER SHORT TERM PAVEMENT MARKINGS SHALL BE TAPE.

VIBRATORY ROLLERS WILL NOT BE ALLOWED. DENSITY REQUIREMENTS SHALL REMAIN AS SPECIFIED.

THE FOLLOWING BITUMINOUS CONCRETE MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT.

MIXTURE USE(S): BITUMINOUS CONCRETE SURFACE COURSE,
SUPERPAVE MIX "D" N70

AC/PG: PG 64-22
RAP %: 15%
DESIGN AIR VOIDS: 4.0% @ NDESIGN=70
MIXTURE COMPOSITION: IL-9.5
FRICTION AGGREGATE: MIXTURE D

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	GENERAL NOTES & INDEX OF SHEETS
3	SUMMARY OF QUANTITIES
4	TYPICAL SECTIONS & DETAILS
5-5A	PAVEMENT MARKING DETAILS
6	SCHEDULES
7-8	TIES
9-14	PLAN SHEETS STANDARDS

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED AFTER THE PLAN SHEETS

STD. NO.	DESCRIPTION
000001-04	STANDARD SYMBOLS, ABBREVIATIONS, PATTERNS
001006	DECIMAL OF AN INCH AND OF A FOOT
442201-01	CLASS C AND D PATCHES
701301-02	LANE CLOSURE 2L, 2W SHORT TIME OPERATIONS
701311-02	LANE CLOSURE 2L, 2W MOVING OPERATIONS - DAY ONLY
701006-02	OFF-RD OPERATIONS, 2L, 2W, 4.5 m (15') TO 600 mm (24") FROM PAVEMENT EDGE
701501-03	URBAN LANE CLOSURE 2L, 2W UNDIVIDED
702001-05	TRAFFIC CONTROL DEVICES
780001-01	TYPICAL PAVEMENT MARKINGS
781001-02	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
**GENERAL NOTES
&
INDEX OF SHEETS**

SCALE: VERT.
HORIZ.
DATE

DRAWN BY
CHECKED BY