



NOTES:

1. ALL FINAL PAVEMENT MARKINGS SHALL BE THERMOPLASTIC (OF THE EXTRUDED TYPE) AND SHOULD BE PLACED IN ACCORDANCE WITH "DISTRICT ONE TYPICAL PAVEMENT MARKINGS" DETAIL STANDARD TC-13.
2. ALL RAISED REFLECTIVE PAVEMENT MARKERS SHALL BE PLACED IN ACCORDANCE WITH "TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT)" STANDARD TC-11.
3. THE RESIDENT ENGINEER SHALL VERIFY THE LOCATIONS OF ALL EXISTING PAVEMENT MARKINGS PRIOR TO MILLING OR RESURFACING.

THERMOPLASTIC PAVEMENT MARKING LEGEND

- ① 4" EDGE LINE - SOLID WHITE
- ② 4" DOUBLE YELLOW - SOLID LINE
- ③ 6" TURN LANE - WHITE
- ④ LETTERS & SYMBOLS - WHITE
- ⑤ 12" DIAGONALS - YELLOW @ 45°
- ⑥ 24" STOP BAR - WHITE
- ⑦ 4" YELLOW DOTTED EXTENSION (2' LINE - 6' SPACE)

LANDSCAPING NOTES

- ① TOPSOIL, 4" SHALL BE PROVIDED IN ALL AREAS OF SEEDING
- ② SUPPLEMENTARY WATERING SHALL BE PLACED ON ALL SEEDED AREAS
- ③ EROSION CONTROL BLANKET SHALL BE PLACED ON ALL SEEDED AREAS

LEGEND

- TEMPORARY AND PERMANENT SEEDING, CLASS 2A AREA
APPLY NITROGEN FERTILIZER NUTRIENT, PHOSPHOROUS FERTILIZER NUTRIENT AND POTASSIUM FERTILIZER NUTRIENT TO ALL SEEDING CLASS 2A AREAS.

FILE NAME =	USER NAME = abreuh	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	PROPOSED PAVEMENT MARKING & LANDSCAPING PLAN IL. RTE. 38 AT MEREDITH RD.			F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
es:\pw_work\p\dot\obreuh\d0139641\PI15388-sht-pmk.dgn	PLOT SCALE = 50,0000' / IN.	DRAWN -	REVISED -					567	5 R-N-1	KANE	77	36
PLOT DATE = 2/3/2011	DATE -	CHECKED -	REVISED -		SCALE: 1"=50' SHEET NO. OF SHEETS STA. TO STA.			CONTRACT NO. 60K65				
		DATE -	REVISED -		ILLINOIS FED. AID PROJECT							