



HMA MIXTURE TABLE		% AIR VOIDS
MIXTURE TYPE		@ Ndes
PATCHING		
CLASS D PATCHES, TYPE I, 9 INCH (HMA BINDER, IL-19 mm) (IN 3 UFTS)		4% @ 70 GYR.
HOT-MIX ASPHALT REPLACEMENT OVER PATCHES, 4" (HMA BINDER, IL-19 mm)		4% @ 70 GYR.
TEMPORARY PAVEMENT, 10"		
HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N50, 8-1/2" (IN 3 UFTS)		4% @ 50 GYR.
HOT-MIX ASPHALT SURFACE COURSE MIX D, N50, 1-1/2" (IL-9.5 mm)		4% @ 50 GYR.

- NOTES:**
1. THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURES IS 112 LBS/SQ YD/IN.
 2. THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70 -22" AND FOR NON-POLYMERIZED HMA, THE "AC TYPE" SHALL BE "PG 64 -22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.
 3. FOR "PERCENT OF RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.
 4. IF THE CONTRACTOR CHOOSES TO USE CONCRETE FOR TEMPORARY PAVEMENT, THE THICKNESS WILL BE 10".