COMMITMENTS

Commitments are not to be altered without the written approval of all parties to which the commitment was made.

NO COMMITMENTS HAVE BEEN MADE FOR THIS PROJECT

GENERAL NOTES

UTILITIES - LOCATIONS /INFORMATION ON PLANS

The locations of existing water mains, gas mains, sewers, electric power lines, telephone lines and other utilities as shown on the plans are based on careful field investigation and the best information available, but they are not guaranteed. Unless elevations are shown —— all utility locations shown on the cross sections are based on the approximate depth supplied by the utility company. It shall be the Contractor's responsibility to ascertain their exact location from the utility companies and by field inspection.

PLAN ELEVATIONS - U. S. G. S. MEAN SEA LEVEL DATUM

Use one of the following two options.

1. All elevations shown on the plans are established from U. S. G. S. mean sea level datum.

ENVIRONMENTAL REVIEWS

Prior to the use of any proposed borrow areas, use areas (temporary access roads, detours, run—arounds, etc.) and/or waste areas, the Contractor shall file the required environmental resource request surveys according to Section 107.22 of the Standard Specifications. These surveys are required in order for the Department to conduct cultural and biological resource surveys for the proposed site.

Prior to any waste materials being removed from the construction site the required environmental resource surveys will need to be obtained and filed by the Contractor. Excess waste products removed from the construction site shall be disposed of as required in Section 202.03 of the Standard Specifications.

Any protruding metal bars shall be removed prior to the disposal of broken concrete at approved disposal sites.

The required environmental resource documentation shall include the following:

- * BDE Form 2289 (Environmental Survey Request)
- * A location map showing the size limits and location of the use area
- * Signed property owner agreement form-D4 PI0100
- * Color photographs depicting the use area
- * Borrow Area Entry Agreement form-D4 PI0101

Please note that a minimum of two weeks shall be allowed for the District to obtain the required environmental clearances.

| FILE NAME = | USER NAME = lababidism | DESIGNED - | REVISED - |
|---|------------------------------|------------|-----------|
| Cover sheet_Typicals_GN_Stands.Line Diagr | am.dgn | DRAWN - | REVISED - |
| | PLOT SCALE = 100.0000 '/ IN. | CHECKED - | REVISED |
| | PLOT DATE = 2/9/2011 | DATE | REVISED - |

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

| A-11-1-1 | | F.A.I. RTE. | SECTION | COUNTY | TOTAL | SHEET NO. |
|-----------------------|---------|----------------|-----------------|-----------|--------|--------------|
| GENERAL NOTES | | 474 | ((72, 90)5B)I-2 | PEO-TAZ | 129 | 2 |
| | | | | CONTRA | CT NO. | 68069 |
| ET NO. OF SHEETS STA. | TO STA. | | ILLINOIS FED. A | ID PROJEC | | |

BRIDGE OVERLAY NOTIFICATION

After placement of the bridge deck overlay, the Resident Engineer shall notify the District Bridge Maintenance Engineer of the "as constructed" milling depth and overlay thickness for updating the Illinois Highway Information System.

HOT-MIX ASPHALT MIXTURE REQUIREMENTS
CROSS OVERS

| Mixture Use(s): | POLYMER SURFACE COURSE P HMA SC "D" N70 (2") | BINDER COURSE HMA BC IL 19.0 N70 (8") | POLYMER SURFACE COURSE HMA SHOULDERS (2") | BINDER COURSE HMA SHOULDERS (8") |
|---|--|---|---|--|
| AC/PG: | PG 64-22 | PG 64-22 | PG 64-22 | PG 64-22 |
| RAP% (Max): ** | 10% | 15% | 10% | 15% |
| Design Air Voids: | 4.0% @ N=70 | 4.0% @ N = 70 | 4.0% @ N = 70 | 4.0% @ N=70 |
| Mixture Composition: (Gradation Mixture) | IL 9.5 or IL12.5 | IL 19.0 | IL 9.5 or IL12.5 | IL 19.0 |
| Friction Aggregate: | Mixture E | N.A. | Mixture E | N.A. |

^{**} If the RAP option is selected, the asphalt cement grade may need to be adjusted; this will be determined by the Engineer.

PAVING SURFACE COURSE

Continuous paving operations on the main roadway shall be maintained at all times during the construction of the hot—mix asphalt surface. No interruptions for side roads, entrances, turn lanes, etc. will be allowed.

ORDERING LENGTH CONFIRMATION - DRAINAGE ITEMS

The Contractor shall consult with the Engineer in regard to the exact length of the box/pipe culverts, storm sewers, and/or pipe drains required prior to ordering these items.

SIGNING

Sign locations may vary from the stations shown on the plans in accordance with directions from the Engineer at the time of construction. Sign locations may be adjusted in the field to avoid any found utilities.

All wood post locations shall be verified with the Bureau of Operations, Traffic Section, before installation.