

PORTLAND CEMENT CONCRETE SHOULDERS 12"

STA	TO	STA	DIRECTION	AVG WIDTH (LF)	AREA (SQ YD)
1158+00.00	TO	1164+00.00	EB	13.00	866.7
1158+00.00	TO	1164+00.00	EB	9.00	600.0
1158+00.00	TO	1164+00.00	WB	13.00	866.7
1158+00.00	TO	1164+00.00	WB	9.00	600.0
1164+00.00	TO	1177+00.00	EB	13.00	1,877.8
1164+00.00	TO	1177+00.00	EB	9.00	1,300.0
1164+00.00	TO	1177+00.00	WB	13.00	1,877.8
1164+00.00	TO	1177+00.00	WB	9.00	1,300.0
1177+00.00	TO	1189+50.00	EB	13.00	1,805.6
1189+50.00	TO	1190+00.00	EB	13.85	76.9
1177+00.00	TO	1177+40.00	EB	12.20	54.2
1177+40.00	TO	1178+00.00	EB	10.54	70.3
1178+00.00	TO	1185+65.28	EB	6.51	553.3
1185+65.28	TO	1190+00.00	EB	4.00	193.2
1177+00.00	TO	1189+50.00	WB	13.00	1,805.6
1189+50.00	TO	1190+00.00	WB	14.25	79.2
1177+00.00	TO	1177+40.00	WB	6.00	26.7
1177+40.00	TO	1178+00.00	WB	7.04	46.9
1178+13.51	TO	1185+33.62	WB	6.04	483.3
1185+33.62	TO	1190+00.00	WB	4.00	207.3
1190+00.00	TO	1191+30.00	EB	17.00	245.6
1191+30.00	TO	1191+72.51	EB	19.00	89.7
1190+00.00	TO	1191+72.51	EB	4.00	76.7
1190+00.00	TO	1191+30.00	WB	16.83	243.1
1191+30.00	TO	1191+72.51	WB	19.00	89.7
1190+00.00	TO	1191+72.51	WB	4.00	76.7
1212+12.26	TO	1212+93.60	EB	4.00	36.2
1212+93.60	TO	1213+50.00	EB	5.50	34.5
1212+12.26	TO	1219+00.00	EB	4.00	305.7
1217+18.47	TO	1218+92.99	WB	10.00	193.9
1218+92.99	TO	1219+00.00	WB	9.50	7.4
1212+12.26	TO	1219+00.00	WB	4.00	305.7
21186+50.00	TO	21188+23.17	WB	4.00	77.0
11213+50.00	TO	11214+19.35	EB	6.00	46.2
11214+19.35	TO	11214+43.35	EB	8.00	21.3
11214+43.35	TO	11214+78.36	EB	10.00	38.9
11214+78.36	TO	11214+83.91	EB	9.50	5.9
11214+83.91	TO	11217+62.95	EB	9.00	279.0
11217+62.95	TO	11219+00.00	EB	6.00	91.4
1221+47.59	TO	1229+92.61	EB	10.00	938.9
1229+92.61	TO	1230+16.61	EB	12.00	32.0
1230+16.61	TO	1230+51.61	EB	14.00	54.4
1230+51.61	TO	1230+57.61	EB	13.50	9.0
1230+57.61	TO	1231+32.00	EB	13.00	107.5
1219+00.00	TO	1222+31.38	EB	4.00	147.3
1222+31.38	TO	1224+74.07	EB	6.00	161.9
1224+74.07	TO	1225+50.00	EB	9.00	75.9
1225+50.00	TO	1227+00.00	EB	11.00	183.3
1227+00.00	TO	1230+00.00	EB	13.00	433.3
1230+00.00	TO	1230+50.00	EB	14.00	77.8
1230+50.00	TO	1231+32.00	EB	15.00	136.7
1219+00.00	TO	1229+30.00	WB	10.00	1,144.4
1229+30.00	TO	1230+50.00	WB	8.00	106.7
1230+50.00	TO	1231+57.00	WB	6.00	71.3
1219+00.00	TO	1221+28.66	WB	4.00	101.6
1221+28.66	TO	1225+00.00	WB	10.66	439.6
1225+00.00	TO	1226+48.33	WB	14.67	241.7
1226+48.33	TO	1231+57.00	WB	17.00	960.8
21184+00.00	TO	21186+50.00	WB	4.00	111.1
11219+00.00	TO	11226+34.29	EB	6.00	489.5
11221+39.17	TO	11226+34.29	EB	4.00	220.1

ROUNDING ADJUSTMENT = 0.1  
TOTAL = 23,201

PROTECTIVE COAT

STA	TO	STA	DIRECTION	AVG WIDTH (LF)	AREA (SQ YD)
1158+00.00	TO	1164+00.00	EB	13.00	1,733.3
1158+00.00	TO	1164+00.00	EB	9.00	1,200.0
1158+00.00	TO	1164+00.00	WB	13.00	1,733.3
1158+00.00	TO	1164+00.00	WB	9.00	1,200.0
1164+00.00	TO	1177+00.00	EB	13.00	3,755.6
1164+00.00	TO	1177+00.00	EB	9.00	2,600.0
1164+00.00	TO	1177+00.00	WB	13.00	3,755.6
1164+00.00	TO	1177+00.00	WB	9.00	2,600.0
1177+00.00	TO	1189+50.00	EB	13.00	3,611.1
1189+50.00	TO	1190+00.00	EB	13.85	153.9
1177+00.00	TO	1177+40.00	EB	12.20	108.4
1177+40.00	TO	1178+00.00	EB	10.54	140.5
1178+00.00	TO	1185+65.28	EB	6.51	1,106.5
1185+65.28	TO	1190+00.00	EB	4.00	388.4
1177+00.00	TO	1189+50.00	WB	13.00	3,611.1
1189+50.00	TO	1190+00.00	WB	14.25	158.3
1177+00.00	TO	1177+40.00	WB	6.00	53.3
1177+40.00	TO	1178+00.00	WB	7.04	93.9
1178+13.51	TO	1185+33.62	WB	6.04	966.5
1185+33.62	TO	1190+00.00	WB	4.00	414.6
1190+00.00	TO	1191+30.00	EB	17.00	491.1
1191+30.00	TO	1191+72.51	EB	19.00	179.5
1190+00.00	TO	1191+72.51	EB	4.00	153.3
1190+00.00	TO	1191+30.00	WB	16.83	486.2
1191+30.00	TO	1191+72.51	WB	19.00	179.5
1190+00.00	TO	1191+72.51	WB	4.00	153.3
1212+12.26	TO	1212+93.60	EB	4.00	72.3
1212+93.60	TO	1213+50.00	EB	5.50	68.9
1212+12.26	TO	1219+00.00	EB	4.00	611.3
1217+18.47	TO	1218+92.99	WB	10.00	387.8
1218+92.99	TO	1219+00.00	WB	9.50	14.8
1212+12.26	TO	1219+00.00	WB	4.00	611.3
21186+50.00	TO	21188+23.17	WB	4.00	153.9
11213+50.00	TO	11214+19.35	EB	6.00	92.5
11214+19.35	TO	11214+43.35	EB	8.00	42.7
11214+43.35	TO	11214+78.36	EB	10.00	77.8
11214+78.36	TO	11214+83.91	EB	9.50	11.7
11214+83.91	TO	11217+62.95	EB	9.00	558.1
11217+62.95	TO	11219+00.00	EB	6.00	182.7
1221+47.59	TO	1229+92.61	EB	10.00	1,877.8
1229+92.61	TO	1230+16.61	EB	12.00	64.0
1230+16.61	TO	1230+51.61	EB	14.00	108.9
1230+51.61	TO	1230+57.61	EB	13.50	18.0
1230+57.61	TO	1231+32.00	EB	13.00	214.9
1219+00.00	TO	1222+31.38	EB	4.00	294.6
1222+31.38	TO	1224+74.07	EB	6.00	323.7
1224+74.07	TO	1225+50.00	EB	9.00	151.9
1225+50.00	TO	1227+00.00	EB	11.00	366.7
1227+00.00	TO	1230+00.00	EB	13.00	866.7
1230+00.00	TO	1230+50.00	EB	14.00	155.6
1230+50.00	TO	1231+32.00	EB	15.00	273.3
1219+00.00	TO	1229+30.00	WB	10.00	2,288.9
1229+30.00	TO	1230+50.00	WB	8.00	213.3
1230+50.00	TO	1231+57.00	WB	6.00	142.7
1219+00.00	TO	1221+28.66	WB	4.00	203.3
1221+28.66	TO	1225+00.00	WB	10.66	879.3
1225+00.00	TO	1226+48.33	WB	14.67	483.4
1226+48.33	TO	1231+57.00	WB	17.00	1,921.6
21184+00.00	TO	21186+50.00	WB	4.00	222.2
11219+00.00	TO	11226+34.29	EB	6.00	979.1
11221+39.17	TO	11226+34.29	EB	4.00	440.1

21186+50.00 TO 21192+72.33 WB 6.00 829.8  
1212+12.26 TO 1212+72.34 WB 5.00 66.8  
21184+00.00 TO 21186+50.00 WB 6.00 333.3  
ROUNDING ADJUSTMENT = 0.1  
TOTAL = 47,631

CONCRETE BARRIER, DOUBLE FACE, 42 INCH HEIGHT

STA	TO	STA	SIDE	DIRECTION	LENGTH (FOOT)
I-270					
1177+00.00	TO	1191+73.00	MEDIAN		1,473.00
BRIDGE OMISSION					
1212+12.00	TO	1225+00.00	MEDIAN		1,288.00
TOTAL =					2,761
MODULAR GLARE SCREEN SYSTEM					
1155+00.00	TO	1164+00.00	WB 270		900
1164+00.00	TO	1173+00.00	WB 270		900
1224+00.00	TO	1233+00.00	WB 270		900
RELOCATED REDUCTION =					-900
TOTAL =					1800
REMOVE OVERHEAD SIGN STRUCTURE - SPAN					
222+25	RT	EB			1
TOTAL =					1
REMOVE GROUND MOUNTED SIGN SUPPORT					
159+00.23	87.23			2	2
164+00.25	65.57			2	2
169+42.73	91.05			3	3
179+11.28	70.41			2	2
189+00.27	89.10			3	3
213+38.95	68.72			2	2
217+00.13	85.74			2	2
225+88.16	310.44			2	2
TOTAL =					18
REMOVE CONCRETE FOUNDATION - GROUND MOUNT					
159+00.23	87.23			2	2
164+00.25	65.57			2	2
169+42.73	91.05			3	3
179+11.28	70.41			2	2
189+00.27	89.10			3	3
213+38.95	68.72			2	2
217+00.13	85.74			2	2
225+88.16	310.44			2	2
TOTAL =					18
REMOVE CONCRETE FOUNDATION - OVERHEAD					
222+25	RT	EB			2
TOTAL =					2

CONCRETE BARRIER, SINGLE FACE, 42 INCH HEIGHT (SPECIAL)

STA	TO	STA	DIRECTION	LENGTH (FOOT)
21193+32.40	TO	21184+00.00	WB	932.4
ROUNDING ADJUSTMENT =				0.6
TOTAL =				933
PAVED SHOULDER REMOVAL				
158+00.00	TO	164+00.00		10.50
158+00.00	TO	164+00.00		4.50
158+00.00	TO	164+00.00		10.20
1149+00.00	TO	1155+86.00		4.00
1150+00.00	TO	1155+86.00		Varies
1156+21.00	TO	1158+00.00		Varies
1156+21.00	TO	1158+00.00		Varies
1150+00.00	TO	1158+00.00		10.00
164+00.00	TO	176+94.00		10.20
164+00.00	TO	176+94.00		4.00
164+00.00	TO	176+94.00		10.50
164+00.00	TO	176+94.00		4.50
176+94.00	TO	189+79.00		10.10
176+94.00	TO	189+79.00		4.10
176+94.00	TO	189+79.00		10.80
176+94.00	TO	189+79.00		4.50
189+79.00	TO	191+31.00		8.50
189+79.00	TO	191+31.00		4.00
189+79.00	TO	191+73.00		10.50
189+79.00	TO	191+73.00		3.70
211+21.00	TO	218+60.00		10.00
211+21.00	TO	218+65.00		5.00
211+63.00	TO	215+09.00		10.00
215+09.00	TO	218+76.00		10.00
211+63.00	TO	218+69.00		6.50
223+31.00	TO	231+05.00		13.00
222+47.00	TO	225+00.00		11.00
225+00.00	TO	231+30.00		8.60
218+65.00	TO	231+05.00		6.50