

GUARDRAIL SCHEDULE

LOCATION	GUARDRAIL REMOVAL	STEEL PLATE BEAM GUARDRAIL, TYPE A, 9 FOOT POSTS	STEEL PLATE BEAM GUARDRAIL, ATTACHED TO STRUCTURES	LONG-SPAN GUARDRAIL OVER CULVERT, 12 FT 6 IN SPAN	LONG-SPAN GUARDRAIL OVER CULVERT, 25 FT SPAN	TRAFFIC BARRIER TERMINAL, TYPE 6	TRAFFIC BARRIER TERMINAL, TYPE 6A	TRAFFIC BARRIER TERMINAL, TYPE 6B	TRAFFIC BARRIER TERMINAL, TYPE 1 (SPECIAL) TANGENT	TRAFFIC BARRIER TERMINAL, TYPE 1 (SPECIAL) FLARED	STEEL PLATE BEAM GUARDRAIL (SHORT RADIUS)	GUARDRAIL MARKERS, TYPE A	TERMINAL MARKER - DIRECT APPLIED
SITE ID HAZARD STATION SIDE													
1 100+00 LT	217.0	87.5	25.0							1	33.0	2	1
1 100+00 RT	255.0	137.5	25.0							2		3	2
2 200+00 LT	453.0	62.5		162.5						2		3	2
2 200+00 RT	454.0	62.5		162.5						2		3	2
3 300+00 LT	130.0	150.0	25.0							2	64.0	3	2
3 300+00 RT	180.0	100.0			175.0					2		4	2
4 400+00	NO WORK												
5 500+00	NO WORK												
6 600+00 LT	267.0	50.0					2			2		2	2
6 600+00 RT	378.0	125.0					2			2		3	2
7 700+00 LT	190.0	112.5	12.5							2		2	2
7 700+00 RT	255.0	25.0		162.5						2		3	2
8 800+00 LT	255.0	162.5								2		3	2
9 900+00 LT	265.0	287.5	50.0							2		3	2
9 900+00 RT	167.0	250.0	50.0							2	60.0	5	2
10 1000+00 LT	105.0	62.5		162.5						2		3	2
10 1000+00 RT	104.0	50.0		162.5						2		3	2
11 1100+00 RT	105.0	12.5								2		1	2
12 1200+00 LT	854.0	550.0				2				4		9	4
12 1200+00 RT	473.0	225.0				2				4		5	4
13 1300+00 LT	512.0	237.5				2				3	27.0	5	3
13 1300+00 RT	445.0	162.5				2				3	12.0	4	3
14 1400+00 LT	330.0	375.0						2		3	16.0	7	3
14 1400+00 RT	365.0	112.5						2		2	16.0	3	3
15 1500+00 LT	180.0	75.0		162.5						2		3	2
15 1500+00 RT	180.0	87.5		162.5						2		4	2
16A 1600+00 LT	404.0	175.0						1		1		5	1
16A 1600+00 RT	479.0	250.0		162.5				1		1		6	1
16B 1600+00 LT	965.0	625.0			175.0			1		1		11	1
16B 1600+00 RT	891.0	550.0			175.0			1		1		10	1
17 1700+00 LT	304.0	75.0		162.5						2		3	2
17 1700+00 RT	329.0	125.0		162.5						2		4	2
18 1800+00 LT	534.0	475.0						2		2		8	2
18 1800+00 RT	496.0	462.5						2		2		8	2
19 1900+00 RT	279.0	75.0		162.5						2		3	2
20 2000+00 LT	241.0	50.0		162.5						2		3	2
20 2000+00 RT	241.0	162.5		162.5						1	1	5	2
21 2100+00 LT	166.0	137.5	12.5							1	1	2	2
21 2100+00 RT	291.0	187.5		162.5						2		5	2
22 2200+00 LT	254.0	137.5		162.5						2		4	2
22 2200+00 RT	217.0	37.5		162.5						1	1	3	2
23 2300+00 RT	217.0	262.5		162.5						2		6	2
24 2400+00	NO WORK												
25 2500+00 LT	267.0	387.5	37.5							2		6	2
25 2500+00 RT	267.0	375.0	37.5							2		6	2
26 2600+00 LT	172.0	100.0	25.0							1	1	2	2
26 2600+00 RT	178.0	125.0	25.0							2		2	2
27 2700+00	NO WORK												
28 2800+00 LT	175.0	87.5										2	2
28 2800+00 RT	113.0	137.5								1		2	1
29 2900+00 LT	348.0	225.0				1				1		4	1
29 2900+00 RT	348.0	250.0				1				1		4	1
TOTALS	15,235.0	9,037.5	325.0	2,925.0	525.0	10	4	12	86	10	228.0	202	96
USE	15,235	9,037.5	325.0	2,925.0	525.0	10	4	12	86	10	228.0	202	96

REVISÉ 6-3-11