

PLAN
(East approach shown, West approach similar)


TOP AND BOTTOM ELEVATIONS FOR APPROACH FOOTING

Point	West Approach		East Approach	
	Top	Bottom	Top	Bottom
A	668.41	667.58	665.16	664.33
B	668.73	667.90	665.48	664.65
C	668.33	667.50	665.08	664.25
D	668.48	667.65	665.03	664.20
E	668.81	667.98	665.35	664.52
F	668.40	667.57	664.95	664.12


Note A - 20-Bar Splicers (E) for #5 w(E) bars, top & bottom

- * (29-Stage I, 35-Stage II)
- ** (46-Stage I, 55-Stage II)
- *** (19-Stage I, 23-Stage II)

Notes:
PJF (per Article 1051.09 of the Standard Specifications) below the approach slab shall be bonded to the top of new abutment wingwalls with suitable adhesive as recommended by supplier.
See Sheet 20 of 37 for Section A-A and Bill of Material.
See Sheet 18 of 37 for additional bar details.
See Sheet 37 of 37 for Bar Splicer details.



BARS a3(E) & a4(E)



CROSS SECTION
(Looking East)

(Sheet 1 of 4)

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920008-017-Approach Slab.dgn
4/22/2022 9:25:51 AM



USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BRIDGE APPROACH SLAB DETAILS
STRUCTURE NO. 092-008

SHEET NO. 17 OF 37 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	301
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT



Notes:
 The joint opening shall be adjusted for temperature per Article 520.04 of the Standard Specifications. The length of bridge used to calculate the adjustment shall be equal to the distance from the fixed bearing to the end of the bridge approach slab.
 Parapet concrete shall be paid for as Concrete Superstructure.
 Approach slab shall be paid for as Concrete Superstructure (Approach Slab).
 Approach footing concrete shall be paid for as Concrete Structures.
 The approach footing maximum applied service bearing pressure (Qmax) = 2.0 ksf.
 Cost of excavation for approach footing included with Concrete Structures.
 For Granular Backfill for Structures and drainage treatment details, see sheet 2 of 37.
 Adjust the profile grade as needed across the length of the bridge approach slab to match the top of bridge deck overlay at the abutment.

*** Omit taper at departure ends with Type 5 Terminals
 **** Prior to 1/4" Diamond Grinding


Note A - a3(E), a4(E), a13(E), a14(E), a23(E), or a24(E)
 Note B - a5(E), a6(E), a15(E), a16(E), a25(E), or a26(E)
 Note C - w(E), w1(E), w10(E), w11(E), w20(E), or w21(E)
 Note D - b3(E), b14(E), or b15(E)

**STR. NO. 092-0008
 TWO APPROACHES
 BILL OF MATERIAL**


Bar	No.	Size	Length	Shape
a3(E)	92	#5	19'-2"	—
a4(E)	92	#5	23'-2"	—
a5(E)	120	#8	18'-9"	—
a6(E)	120	#8	22'-9"	—
a7(E)	92	#5	7'-4"	—
b(E)	128	#5	29'-8"	—
b1(E)	202	#9	29'-8"	—
b2(E)	8	#5	14'-8"	—
b3(E)	4	#4	14'-8"	—
d(E)	68	#5	3'-0"	—
d1(E)	68	#5	2'-7"	—
d2(E)	68	#4	3'-0"	—
d5(E)	68	#4	3'-4"	—
e(E)	24	#4	14'-8"	—
e1(E)	8	#8	14'-8"	—
e2(E)	8	#5	14'-8"	—
t(E)	168	#4	9'-8"	—
w(E)	80	#5	18'-9"	—
w1(E)	80	#5	22'-9"	—
Concrete Superstructure	Cu. Yd.	5.9		
Concrete Superstructure (Approach Slab)	Cu. Yd.	121.4		
Concrete Structures	Cu. Yd.	26.0		
Reinforcement Bars, Epoxy Coated	Pound	59930		

**STR. NO. 092-0009
 TWO APPROACHES
 BILL OF MATERIAL**


Bar	No.	Size	Length	Shape
a13(E)	35	#5	24'-10"	—
a14(E)	35	#5	40'-6"	—
a15(E)	46	#8	24'-6"	—
a16(E)	46	#8	40'-2"	—
a23(E)	46	#5	19'-2"	—
a24(E)	46	#5	31'-2"	—
a25(E)	60	#8	18'-9"	—
a26(E)	60	#8	30'-9"	—
a7(E)	82	#5	7'-4"	—
b(E)	152	#5	29'-8"	—
b1(E)	242	#9	29'-8"	—
b2(E)	4	#5	14'-8"	—
b3(E)	2	#4	14'-8"	—
b12(E)	2	#5	13'-5"	—
b13(E)	2	#5	15'-10"	—
b14(E)	1	#4	15'-3"	—
b15(E)	1	#4	13'-11"	—
d(E)	68	#5	3'-0"	—
d1(E)	68	#5	2'-7"	—
d2(E)	68	#4	3'-0"	—
d5(E)	68	#4	3'-4"	—
e(E)	24	#4	14'-8"	—
e1(E)	8	#8	14'-8"	—
e2(E)	8	#5	14'-8"	—
t10(E)	100	#4	12'-8"	—
t20(E)	100	#4	9'-8"	—
w10(E)	40	#5	24'-6"	—
w11(E)	40	#5	40'-2"	—
w20(E)	40	#5	18'-9"	—
w21(E)	40	#5	30'-9"	—
Concrete Superstructure	Cu. Yd.	5.9		
Concrete Superstructure (Approach Slab)	Cu. Yd.	144.1		
Concrete Structures	Cu. Yd.	35.7		
Reinforcement Bars, Epoxy Coated	Pound	58180		




INSIDE ELEVATION OF PARAPET AND CURB



*** 1" Ø ANCHOR BOLT**
 (Anchor bolt assemblies shall be galvanized according to Article 1006.09 of the Standard Specifications)



VIEW B-B



DETAIL A
 (@ Rt. L's)

* Cost included with Concrete Superstructure (Approach Slab).
 ** Per manufacturer recommendations

MODEL: Default
 FILE NAME: S:\237\2019\12\37\19020.00 (193-026 D5 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-02-0-Approach Slab Details.dgn
 4/22/2022 9:25:54 AM



USER NAME = baswanon	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**


**BRIDGE APPROACH SLAB DETAILS
 STRUCTURE NO. 092-0008 & 092-0009**

SHEET NO. 20 OF 37 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	304
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT


(Sheet 4 of 4)



PARTIAL FRAMING PLAN - S.N. 092-0009



PARTIAL FRAMING PLAN - S.N. 092-0008



GIRDER REACTION TABLE (EXIST.)				
	S.N. 092-0008 (EB)		S.N. 092-0009 (WB)	
	W. Abut.	E. Abut.	W. Abut.	E. Abut.
R _l	(k) 26.7	22.4	40.3	20.5
R _t	(k) 35.4	26.8	30.8	33.0
R _{IM}	(k) 9.2	7.6	7.8	9.4
R _{Total}	(k) 71.3	56.8	78.9	62.9

* GIRDER REACTION TABLE (PROP.)				
	S.N. 092-0008 (EB)		S.N. 092-0009 (WB)	
	W. Abut.	E. Abut.	W. Abut.	E. Abut.
R _l	(k) 53.5	49.7	70.5	47.3
R _t	(k) 43.3	41.5	44.6	40.9
R _{IM}	(k) 11.2	11.8	11.2	11.6
R _{Total}	(k) 108.0	103.0	126.3	99.8

* New bearing assembly loads (includes approach slab)

Notes:
 Removal of existing diaphragms shall be paid for as Structural Steel Removal.
 Removal of existing bearing assemblies shall be paid for as Jack and Remove Existing Bearings.
 See Sheet 23 of 37 for Bill of Material.

Callouts:

- (A) - Remove existing W12x40 end diaphragm, see Sheet 23 of 37 for details.
- (B) - Jack and remove existing bearing assembly, replace with new bearing assemblies as shown on Sheet 24 of 37.
- (C) - Install new side retainer and 1" Ø anchor bolt on each side of existing bearing assembly, see Sheet 24 of 37 for details.
- (D) - Install new side retainer and 1" Ø anchor bolt against existing bearing assembly, see Sheet 24 of 37 for details.

MODEL: Default
 FILE NAME: S:\237\2019\23719020\00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920008-022-5tr-Steel Plan.dgn
 4/22/2022 9:25:56 AM

MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - BAS	REVISED -
	PLOT SCALE =	CHECKED - LVM	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
		CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


STRUCTURAL STEEL REMOVAL
STRUCTURE NO. 092-0008 & 092-0009

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	306
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

FILL PLATE THICKNESS

S.N. 092-0008, W. Abut.		S.N. 092-0008, E. Abut.	
Beam 1	--	Beam 1	3/8"
Beam 2	1/2"	Beam 2	1/4"
Beam 3	1/4"	Beam 3	--
Beam 4	--	Beam 4	--
Beam 5	--	Beam 5	--
Beam 6	--	Beam 6	--
Beam 7	--	Beam 7	3/8"
S.N. 092-0009, W. Abut.		S.N. 092-0009, E. Abut.	
Beam 8	--	Beam 8	--
Beam 9	--	Beam 9	--
Beam 10	--	Beam 10	--
Beam 11	--	Beam 11	1/2"
Beam 12	--	Beam 12	1/4"
Beam 13	--	Beam 13	1/4"
Beam 14	--	Beam 14	--
Beam 15	--	Beam 15	--


See Sheet 24 of 37 for dimensions of associated bearing assembly plates.



**EXISTING BEARING
REMOVAL DETAIL**

END DIAPHRAGM REMOVAL

* Angle welded to Beam 7 at each abutment may remain in place. See note.



Notes:

Removal of the existing steel extensions and side retainers at the abutments shall be included in the cost of Jack and Remove Existing Bearings.

Minimum jack capacity shall be 45 tons.

Removal of steel end diaphragms shall be paid for as Structural Steel Removal.

Diaphragm connection angles welded to the beam webs may remain. If directed to be removed by the Engineer, these shall be removed utilizing air carbon arc cutting or other method approved by the Engineer. Remaining weld material shall be ground flush and inspected in accordance with general note.

Prior to pouring new concrete diaphragms, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the beam web in the vicinity of the removed diaphragms. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel, and the cost will be included with Structural Steel Removal.

**BILL OF MATERIAL
STR. NO. 092-0008**

Item	Unit	Quantity
Elastomeric Bearing Assembly, Type I	Each	14
Anchor Bolts, 1"	Each	52
Furnishing and Erecting Structural Steel	Pound	3520
Jack and Remove Existing Bearings	Each	14
Structural Steel Removal	Pound	3360

**BILL OF MATERIAL
STR. NO. 092-0009**

Item	Unit	Quantity
Elastomeric Bearing Assembly, Type I	Each	16
Anchor Bolts, 1"	Each	74
Furnishing and Erecting Structural Steel	Pound	4260
Jack and Remove Existing Bearings	Each	16
Structural Steel Removal	Pound	4640

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-02-3-Str Steel Details.dgn


MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - BAS	REVISED -
		CHECKED - LVM	REVISED -
	PLOT SCALE =	DRAWN - JDK	REVISED -
	PLOT DATE = 4/22/2022	CHECKED - BAS	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**STRUCTURAL STEEL DETAILS
STRUCTURE NO. 092-0008 & 092-0009**

SHEET NO. 23 OF 37 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	307
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




ELEVATION AT ABUT.




SECTION A-A

10"x14" TYPE I ELASTOMERIC EXP. BRG.
Beams 8 thru 15 at E. Abut., (WB)
Beams 1 thru 7 at E. Abut. & W. Abut., (EB)



** BEARING ASSEMBLY

Note:
Shim plates shall not be placed under Bearing Assembly.




SIDE RETAINER
Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.


SIDE RETAINER DIMENSIONS

Location	No. Req'd	Bearing	X	Y	Z
W. Abut. (EB)	** 14	10"x14"	6 1/2"	2 3/8"	6"
E. Abut. (EB)	** 14	10"x14"	6 1/2"	2 3/8"	6"
E. Abut. (WB)	** 16	10"x14"	6 1/2"	2 3/8"	6"
W. Abut. (WB)	** 16	11"x16"	4 3/4"	2 3/8"	6 1/2"
Pier 1 (EB)	12	12"x18"	7"	2 1/8"	4"
Pier 3 (EB)	12	10"x14"	7"	2 1/8"	4"
Pier 1 (WB) E. Brg.	14	10"x14"	7"	2 1/8"	4"
Pier 2 (WB) E. Brg.	14	7"x12"	5 1/2"	2 1/8"	4"
Pier 4 (WB)	14	10"x14"	7"	2 1/8"	4"

** Cost included with associated Elastomeric Bearing Assembly.




ELEVATION AT ABUT.




SECTION B-B

11"x16" TYPE I ELASTOMERIC EXP. BRG.
Beams 8 thru 15 at W. Abut., (WB)



** BEARING ASSEMBLY

Notes:
Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.
Steel extensions, shim plates, and connection bolts shall be paid for as Furnishing and Erecting Structural Steel.
Unless noted otherwise, side retainers shall be paid for as Furnishing and Erecting Structural Steel. Side retainers and stainless steel plates provided for new Elastomeric Bearing Assemblies shall be included in the cost of Elastomeric Bearing Assembly, Type I.
Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions.
Anchor bolts and side retainers at all supports shall be installed as each member is erected unless an equivalent temporary means of lateral restraint is used.
Provide two 1/8" adjusting shims for each bearing in addition to all other plates of the Bearing Assembly and placed as shown on the bearing details.
See sheet 23 of 37 for Fill Plate Thickness table and Bill of Material.
The Top Bearing Plates shall be shop painted with the inorganic zinc rich primer per AASHTO M300 Type I. Cost included with Elastomeric Bearing Assembly, Type I.



SECTION

ELEVATION


PLAN - TOP AND BOTTOM

STEEL EXTENSION


STEEL EXTENSION DIMENSIONS

Location	No. Req'd	A	B	H	C
W. Abut. (EB), Bms. 1-7	7	1'-4"	11"	9 1/8"	2"
E. Abut. (EB), Bms. 1-7	7	1'-4"	11"	10 7/8"	2"
E. Abut. (WB), Bms. 8-15	8	1'-4"	11"	8 3/8"	2"
W. Abut. (WB), Bms. 8-15	8	1'-6"	12"	9 3/8"	3"


MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-02-4-Bearing Details.dgn
5/5/2022 10:15:14 AM




PLAN




VIEW A-A



SECTION B-B





VIEW C-C




SECTION D-D

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal



ELEVATION
(Looking West)



SECTION E-E

Notes:
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened, and incorporated into the new construction as noted. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system at no cost to the Department. Cost included with Concrete Removal.
 See Sheet 2 of 37 for limits of Structure Excavation.
 See Sheet 26 of 37 for Bill of Material.

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5"	SRC >5"	SRC ≤5"	SRC >5"
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
1	2' x 1'	2			
2	1' x 1'	1			
Totals		3			

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-025-West Abut (EB) Removal.dgn



USER NAME = baswanon	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

WEST ABUTMENT REMOVAL
 STRUCTURE NO. 092-008


SHEET NO. 25 OF 37 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	309
CONTRACT NO. 70A29				


ILLINOIS FED. AID PROJECT



PLAN






VIEW A-A




VIEW B-B


* Top of back wall shall be ±6" above the highest beam bearing seat.




ELEVATION
(Looking West)



Bar h3(E)



Bar h4(E)



SECTION C-C

STR. NO. 092-0008
WEST ABUTMENT
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h(E)	4	#5	19'-3"	—
h1(E)	4	#5	23'-3"	—
h2(E)	8	#5	9'-11"	—
h3(E)	8	#5	10'-0"	—
h4(E)	8	#5	8'-0"	—
v1(E)	44	#4	3'-3"	—
Structure Excavation		Cu. Yd.	42	
Concrete Removal		Cu. Yd.	17.3	
Concrete Structures		Cu. Yd.	5.3	
Reinforcement Bars, Epoxy Coated		Pound	510	
Structural Repair of Concrete (Depth ≤ 5 in.)		Sq. Ft.	3	

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920008-026-West Abut (EB).dgn
4/22/2022 9:26:00 AM



USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


WEST ABUTMENT
STRUCTURE NO. 092-0008

SHEET NO. 26 OF 37 SHEETS



F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	310
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-027-East Abut. (EB) Removal.dgn




PLAN




ELEVATION
(Looking East)

LEGEND


	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal




VIEW A-A




SECTION B-B



VIEW C-C



SECTION D-D



SECTION E-E

Notes:
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened, and incorporated into the new construction as noted. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system at no cost to the Department. Cost included with Concrete Removal.
 See Sheet 2 of 37 for limits of Structure Excavation.
 See Sheet 28 of 37 for Bill of Material.

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5"	SRC >5"	SRC ≤5"	SRC >5"
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
1	2' x 1'	2			
Totals		2			




USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


EAST ABUTMENT REMOVAL
STRUCTURE NO. 092-008

SHEET NO. 27 OF 37 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	311
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




PLAN




* Top of back wall shall be ±6" above the highest beam bearing seat.




ELEVATION
(Looking East)




Bar h3(E)




Bar h4(E)



SECTION C-C



VIEW A-A



VIEW B-B

STR. NO. 092-0008
EAST ABUTMENT
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h(E)	4	#5	19'-3"	—
h1(E)	4	#5	23'-3"	—
h2(E)	8	#5	9'-11"	—
h3(E)	8	#5	10'-0"	—
h4(E)	8	#5	8'-0"	—
v1(E)	44	#4	3'-3"	—
Structure Excavation		Cu. Yd.	46	
Concrete Removal		Cu. Yd.	17.3	
Concrete Structures		Cu. Yd.	5.3	
Reinforcement Bars, Epoxy Coated		Pound	510	
Structural Repair of Concrete (Depth ≤ 5 in.)		Sq. Ft.	2	

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-02-8-East Abut. (EB).dgn
4/22/2022 9:26:02 AM



USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


EAST ABUTMENT
STRUCTURE NO. 092-0008

SHEET NO. 28 OF 37 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	312
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT


MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-029-West Abut (WB) Removal.dgn



PLAN

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal




ELEVATION
(Looking West)

STRUCTURAL REPAIR OF CONCRETE TABLE


Label	Size	Plan Qty.		As Built	
		SRC ≤ 5" Sq. Ft.	SRC > 5" Sq. Ft.	SRC ≤ 5" Sq. Ft.	SRC > 5" Sq. Ft.
1	2' x 1'	2			
2	1' x 1'	1			
3	1' x 1'	1			
Totals		4			

Notes:
 Existing reinforcement bars that will be reused in the new construction shall not be cut or damaged. Damaged bars shall be replaced with new reinforcement bars drilled and epoxy grouted into existing concrete at no cost to the Department.
 See Sheet 2 of 37 for limits of Structure Excavation.
 See Sheet 30 of 37 for Bill of Material.




VIEW A-A

SECTION B-B



VIEW C-C

SECTION D-D



SECTION E-E



USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -






STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

WEST ABUTMENT REMOVAL
STRUCTURE NO. 092-0009

SHEET NO. 29 OF 37 SHEETS

F.A.I. RTE. 74	SECTION (92-10,11,12)R	COUNTY VERMILION	TOTAL SHEETS 698	SHEET NO. 313
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT



STR. NO. 092-0009
WEST ABUTMENT
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h10(E)	4	#5	23'-1"	—
h11(E)	4	#5	40'-10"	—
h12(E)	4	#5	10'-8"	—
h13(E)	8	#5	9'-5"	—
h14(E)	4	#5	8'-0"	—
h15(E)	4	#5	8'-0"	—
h16(E)	4	#5	8'-3"	—
v1(E)	41	#4	3'-3"	—
Structure Excavation			Cu. Yd.	71
Concrete Removal			Cu. Yd.	22.0
Concrete Structures			Cu. Yd.	5.8
Reinforcement Bars, Epoxy Coated			Pound	580
Structural Repair of Concrete (Depth ≤ 5 in.)			Sq. Ft.	4

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920008-030-West Abut (WB).dgn



USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

WEST ABUTMENT
STRUCTURE NO. 092-0009

SHEET NO. 30 OF 37 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	314
CONTRACT NO. 70A29				


ILLINOIS FED. AID PROJECT



PLAN


LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal




VIEW A-A

SECTION B-B




VIEW C-C

SECTION D-D



ELEVATION
(Looking East)



SECTION E-E

Notes:
 Existing reinforcement bars that will be reused in the new construction shall not be cut or damaged. Damaged bars shall be replaced with new reinforcement bars drilled and epoxy grouted into existing concrete at no cost to the Department.
 See Sheet 2 of 37 for limits of Structure Excavation.
 See Sheet 32 of 37 for Bill of Material.

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.	SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.
Totals					

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-031-East Abut. (WB) Removal.dgn
 4/22/2022 9:26:05 AM




USER NAME = baswanon	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**EAST ABUTMENT REMOVAL
STRUCTURE NO. 092-0009**

SHEET NO. 31 OF 37 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	315
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




PLAN




VIEW A-A



VIEW B-B




ELEVATION
(Looking East)



Bar h3(E)

Bar h4(E)



SECTION C-C

STR. NO. 092-0009
EAST ABUTMENT
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h(E)	4	#5	19'-3"	—
h21(E)	4	#5	31'-3"	—
h2(E)	8	#5	9'-11"	—
h3(E)	8	#5	10'-0"	—
h4(E)	8	#5	8'-0"	┘
v1(E)	44	#4	3'-3"	—
Structure Excavation			Cu. Yd.	55
Concrete Removal			Cu. Yd.	18.9
Concrete Structures			Cu. Yd.	5.4
Reinforcement Bars, Epoxy Coated			Pound	540

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-032-East Abut. (WB).dgn
4/22/2022 9:26:05 AM



USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

EAST ABUTMENT
STRUCTURE NO. 092-0009

SHEET NO. 32 OF 37 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	316
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT


STRUCTURAL REPAIR OF CONCRETE TABLE

Notes:
 Pier repair areas shown are estimated from soundings on October 11 thru 16, 2020.
 Actual size and locations of completed repairs shall be shown on this sheet and documented in the provide tables under "As Built".


Label	Size	Plan Qty.		As Built	
		SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.	SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.
1	2' x 1'	2			
2	2' x 1'	2			
3	2' x 2'	4			
Totals		8			



ELEVATION - PIER 1
(Looking East)



ELEVATION - PIER 2
(Looking East)



ELEVATION - PIER 3
(Looking West)

BILL OF MATERIAL

Item	Unit	Quantity
Structural Repair of Concrete (Depth ≤ 5 in.)	Sq. Ft.	8

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Structural Repair of Concrete (Depth Greater Than 5 inches)

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920008-033-Substr Repair (EB).dgn



USER NAME = baswanson	DESIGNED - BAS	REVISED -
	CHECKED - LVM	REVISED -
PLOT SCALE =	DRAWN - JDK	REVISED -
PLOT DATE = 4/22/2022	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUBSTRUCTURE REPAIR - PIERS
S.N. 092-0008

SHEET NO. 33 OF 37 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	317

CONTRACT NO. 70A29

ILLINOIS FED. AID PROJECT

STRUCTURAL REPAIR OF CONCRETE TABLE

Notes:
 Pier repair areas shown are estimated from soundings on October 11 thru 16, 2020.
 Actual size and locations of completed repairs shall be shown on this sheet and documented in the provide tables under "As Built".
 The minimum jack capacity shall be 50% greater than the maximum expected load on the jack.

GIRDER REACTION TABLE				
	R_L (k)	R_T (k)	R_{IM} (k)	R_{Total} (k)
Span 1, Beam 9-15	40.3	36.1	9.2	85.6
Span 2, Beam 9	50.4	32.4	7.7	90.5
Span 2, Beam 10	47.2	31.7	7.8	86.7
Span 2, Beam 11	39.4	31.1	7.8	78.3
Span 2, Beam 12	36.4	30.3	7.8	74.5
Span 2, Beam 13	33.5	29.3	7.8	70.6
Span 2, Beam 14	30.6	28.2	7.7	66.5

Label	Size	Plan Qty.		As Built	
		SRC ≤5"	SRC >5"	SRC ≤5"	SRC >5"
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
1	2' x 1'	2			
2	1' x 1'	1			
3	4' x 2'	8			
4	1' x 1'	1			
5	1' x 1'	1			
6	8' x 1.5'	12			
7	9' x 1'	9			
8	9' x 2'	18			
9	8' x 4.5'	24			
10	6' x 1.5'	9			
11	8' x 4.5'	24			
12	16' x 2'	20			
13	5' x 4.5'	17			
14	1' x 1'	1			
15	1' x 1'	1			
16	1' x 1'	1			
17	3' x 1'	3			
18	4' x 2'	8			
19	8' x 4'		32		
20	6' x 4'	24			
21	1' x 1'	1			
22	1' x 1'	1			
23	4' x 2.5'	10			
24	4' x 2.5'	10			
25	4.5' x 4'	18			
26	4' x 1'	4			
Totals		228	32		


BILL OF MATERIAL

Item	Unit	Quantity
* Structural Repair of Concrete (Depth ≤ 5 in.)	Sq. Ft.	251
Structural Repair of Concrete (Depth > 5 in.)	Sq. Ft.	32
Concrete Sealer	Sq. Ft.	283
Temporary Shoring and Cribbing	Each	13
Jack, Remove, and Reinstall Existing Bearings	Each	2


* Includes 10% allowance for increase in deterioration.

LEGEND


	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Structural Repair of Concrete (Depth Greater Than 5 inches)




PLAN - TOP OF CAP BEAM



PLAN - BOTTOM OF CAP BEAM



ELEVATION
(Looking East)



ELEVATION
(Looking West)

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920008-034-Pier1_Repair (WB).dgn

MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - BAS	REVISED -
	PLOT SCALE =	CHECKED - LVM	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
		CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION



SUBSTRUCTURE REPAIR - PIER 1
S.N. 092-0009

SHEET NO. 34 OF 37 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	318
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

STRUCTURAL REPAIR OF CONCRETE TABLE


Notes:
 Pier repair areas shown are estimated from soundings on October 11 thru 16, 2020.
 Actual size and locations of completed repairs shall be shown on this sheet and documented in the provide tables under "As Built".
 The minimum jack capacity shall be 50% greater than the maximum expected load on the jack.




PLAN - TOP OF CAP BEAM



PLAN - BOTTOM OF CAP BEAM



**ELEVATION
(Looking East)**



**ELEVATION
(Looking West)**

GIRDER REACTION TABLE				
	R _L (k)	R _R (k)	R _{IM} (k)	R _{Total} (k)
Span 2, Beam 8	56.5	37.2	8.6	102.3
Span 2, Beam 9	50.4	36.9	8.8	96.1
Span 2, Beam 10	47.2	36.7	8.9	92.8
Span 2, Beam 11	39.4	36.3	9.1	84.8
Span 2, Beam 12	36.4	35.9	9.2	81.5
Span 2, Beam 13	33.5	35.4	9.4	78.3
Span 2, Beam 14	30.6	34.9	9.5	75.0
Span 2, Beam 15	29.5	34.2	9.6	73.3
Span 3, Beam 8-15	21.1	26.5	7.4	55.0

BILL OF MATERIAL

Item	Unit	Quantity
* Structural Repair of Concrete (Depth ≤ 5 in.)	Sq. Ft.	408
Structural Repair of Concrete (Depth > 5 in.)	Sq. Ft.	18
Concrete Sealer	Sq. Ft.	426
Temporary Shoring and Cribbing	Each	16

* Includes 10% allowance for increase in deterioration.

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Structural Repair of Concrete (Depth Greater Than 5 inches)

Label	Size	Plan Qty.		As Built	
		SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.	SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.
1	2' x 1'	2			
2	2' x 2'	4			
3	4' x 2'	8			
4	7' x 1'	7			
5	2' x 2'	4			
6	2' x 1'	2			
7	2' x 2'	4			
8	7' x 6'	25			
9	2' x 2'	4			
10	1' x 1'	1			
11	1' x 1'	1			
12	2' x 1'	2			
13	2' x 1'	2			
14	5' x 3'	10			
15	2' x 1'	2			
16	4' x 2'	8			
17	4' x 3'	12			
18	6' x 2'	12			
19	9' x 2'	18			
20	10' x 5'	50			
21	2' x 2'	4			
22	2' x 1'	2			
23	15' x 1'	15			
24	6' x 1'	6			
25	7' x 2'	14			
26	4' x 4'	13			
27	6' x 4'	24			
28	2' x 2'	4			
29	8' x 4.5'	36			
30	15' x 1'	15			
31	4' x 3'	12			
32	3' x 2'	6			
33	6' x 3'		18		
34	6' x 3'	18			
35	1' x 1'	1			
36	1' x 1'	1			
37	7' x 3'	21			
38	1' x 1'	1			
Totals		371	18		

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920008-035-Pier2_ Repair (WB).dgn
 4/22/2022 9:26:15 AM



USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - LVM	REVISED -
PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
	CHECKED - BAS	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**SUBSTRUCTURE REPAIR - PIER 2
 S.N. 092-0009**


SHEET NO. 35 OF 37 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	319
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				


STRUCTURAL REPAIR OF CONCRETE TABLE

Notes:
 Pier repair areas shown are estimated from soundings on October 11 thru 16, 2020.
 Actual size and locations of completed repairs shall be shown on this sheet and documented in the provide tables under "As Built".

Label	Size	Plan Qty.		As Built	
		SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.	SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.
1	1' x 1'	1			
2	1' x 1'	1			
3	4' x 1.5'	6			
Totals		8			



ELEVATION - PIER 3
 (Looking West)



ELEVATION - PIER 4
 (Looking West)

BILL OF MATERIAL

Item	Unit	Quantity
Structural Repair of Concrete (Depth ≤ 5 in.)	Sq. Ft.	8

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Structural Repair of Concrete (Depth Greater Than 5 inches)

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920008-036-Subsr Repair (WB).dgn

MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - BAS	REVISED -
	PLOT SCALE =	CHECKED - LVM	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - JDK	REVISED -
		CHECKED - BAS	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUBSTRUCTURE REPAIR - PIERS 3 & 4
S.N. 092-0009

SHEET NO. 36 OF 37 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	320
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT



STANDARD BAR SPLICER ASSEMBLY PLAN
(All components shall be provided from one supplier)

Threaded splicer bar length = min. lap length + 1 1/2" + thread length


* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

STR. NO. 092-0008

Location	Bar size	No. assemblies required	Minimum lap length
Bridge Deck	#5	24	3'-6"
Diaphragm	#6	10	4'-0"
Diaphragm	#4	4	2'-5"
Approach Slab	#5	92	3'-4"
Approach Slab	#8	120	4'-9"
Approach Footing	#5	80	3'-2"
Abutments	#5	8	3'-2"

STR. NO. 092-0009

Location	Bar size	No. assemblies required	Minimum lap length
Bridge Deck	#5	56	3'-6"
Diaphragm	#6	10	4'-0"
Diaphragm	#4	4	2'-5"
Approach Slab	#5	81	3'-4"
Approach Slab	#8	106	4'-9"
Approach Footing	#5	80	3'-2"
Abutments	#5	8	3'-2"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.


"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required



HEADED BAR SPLICER ASSEMBLY PLAN

Location	Bar size	No. assemblies required	A	B
Diaphragms -0008	#6	8	3'-0"	3'-0"
Diaphragms -0009, W. Abut.	#6	4	4'-2"	3'-4"
Diaphragms -0009, E. Abut.	#6	4	3'-3"	2'-7"

Notes:

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars.

Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.


See approved list of bar splicer assemblies and mechanical splicers for alternatives.

MODEL: Default
FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920008-037-Bar Splicers.dgn

Benchmark - Survey disk on top of the NW wingwall of Structure No. 092-0011. Elev. 656.07.
 Existing Structures - Structure No. 092-0010 & 092-0011 were built in 1962 as F.A.I. 74, Section 92-11HB-3. In 2000, the bridge decks were replaced. The structures consist of steel beam and reinforced concrete deck superstructures supported on pile bent abutments and multiple column piers. Overall bridge lengths are 117'-8", with clear widths between parapets of 40'-8". One lane of traffic in each direction is to be maintained using staged construction.
 Salvage - None.

PROPOSED SCOPE OF WORK

1. Rehabilitate bridge deck with scarification and latex concrete overlay
2. Remove and replace bridge approach slabs
3. Replace steel beam bearing assemblies at abutments
4. Remove existing abutment deck joints and reconstruct with jointless semi-integral abutments
5. Repair concrete deterioration on piers and abutments
6. Seal cracks in concrete slope walls
7. Straighten and reinforce steel fascia beam
8. Paint beam ends



ELEVATION


LOADING HS20-44

DESIGN SPECIFICATIONS
 2002 AASHTO Standard Specifications for Highway Bridges, 17th Edition (LFD)


DESIGN STRESSES
 FIELD UNITS

New Construction:
 $f'c = 3,500$ psi
 $f'c = 4,000$ psi (deck)
 $f_y = 60,000$ psi (Reinforcement)
 $f_y = 36,000$ psi (M270 Grade 36)

Exist. Structure:
 $f'c = 3,500$ psi
 $f_y = 60,000$ psi (deck reinf.)
 $f_s = 20,000$ psi (orig. substr. reinf.)
 $f_s = 18,000$ (structural steel)



PLAN



LOCATION SKETCH

GENERAL PLAN AND ELEVATION
I-74 OVER "G" ST.
F.A.I. 74 - SEC. (92-10,11,12)R
VERMILION COUNTY
STATION 1891+14.58
STR. NO. 092-0010 & 092-0011



Bryan Swanson
 Date Signed: 4-22-22
 Exp. Date: 11/30/2022

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-09200-10-001-GPE.dgn



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET NO. 1 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	322
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

GENERAL NOTES

All new fasteners shall be high-strength steel bolts. Holes for 3/4" Ø bolts shall be 13/16" Ø, unless noted otherwise. Holes for 7/8" Ø bolts shall be 15/16" Ø, unless noted otherwise.

No field welding is permitted except as specified in the contract documents.

Reinforcement bars designated (E) shall be epoxy coated.

Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.

As directed by the Engineer, existing construction accessories welded to the top flange of beams and girders shall be removed. The weld areas shall be ground flush and inspected for cracks using magnetic particle testing (MT) or dye penetrant testing (PT) by qualified personnel approved by the Engineer. Any cracks that can not be removed by grinding 1/4 in. deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. The cost of removing welded accessories, grinding and inspecting weld areas, and grinding cracks will be paid for according to Article 109.04 of the Standard Specifications.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work; however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Existing Name Plates shall be removed, cleaned and incorporated into the new construction. Cost included with Relocating Name Plates.

Synthetic Fibers shall be included in the bridge deck concrete overlay specified. See Special Provisions.

The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to deal with the presence of lead on this project.

Cleaning and painting of the existing structural steel shall be as specified in the special provision for "Cleaning and Painting Existing Steel Structures". After removal of deck ends and diaphragms, but prior to new bearing installation and encasement of the steel beams, all beams within 5 ft of the beam ends shall be cleaned per Near White Blast Cleaning (SSPC-SP10).

The designated areas cleaned per Near White Blast Cleaning (SSPC-SP10) shall be painted according to the requirements of Paint System 1 (OZ/E/U). The color of the final finish coat for all steel surfaces shall be Gray, Munsell No. 5B 7/1.

Care shall be taken not to damage rubber bearing or joint components during blasting and cleaning operations. Any damage to these components shall be repaired at the Contractor's expense.

SSPC-QP1 and SPC-QP2 Painting Contractor Certifications will be required for this contract.

Existing structural steel that will be in contact with new structural steel shall be cleaned and painted prior to erection as required by the Special Provision "Cleaning and Painting Contact Surface Areas of Existing Steel Structures".

All new structural steel shall be hot dip galvanized except where noted otherwise. See Special Provisions for "Hot Dip Galvanizing for Structural Steel."


Existing structure plans are available from the District upon request.

TOTAL BILL OF MATERIAL

ITEM	UNIT	-0010	-0011	TOTAL
Concrete Removal	Cu. Yd.	36.6	36.6	73.2
Protective Shield	Sq. Yd.	190	190	380
Structure Excavation	Cu Yd.	66	66	132
Concrete Structures	Cu. Yd.	33.9	33.9	67.8
Concrete Superstructure	Cu. Yd.	36.3	36.2	72.5
* Protective Coat	Sq. Yd.	832	832	1664
Concrete Superstructure (Approach Slab)	Cu. Yd.	123.4	123.4	246.8
Furnishing and Erecting Structural Steel	Pound	2980	2980	5960
Reinforcement Bars, Epoxy Coated	Pound	54930	54930	109860
Bar Splicers	Each	344	344	688
Elastomeric Bearing Assembly, Type I	Each	16	16	32
Anchor Bolts, 1"	Each	32	32	64
Temporary Sheet Piling	Sq. Ft.	148	148	296
Granular Backfill for Structures	Cu. Yd.	62	60	122
Geocomposite Wall Drain	Sq. Yd.	46	45	91
Pipe Underdrains for Structures 4"	Foot	128	128	256
Slope Wall Crack Sealing	Foot			214
Bridge Deck Grooving (Longitudinal)	Sq. Yd.	468	468	936
Jack and Remove Existing Bearings	Each	16	16	32
Structural Steel Removal	Pound	3680	3680	7360
Structural Steel Repair	Pound	250		250
Beam Straightening	L. Sum	1		1
Bridge Deck Latex Concrete Overlay 2 3/4"	Sq. Yd.	496	496	992
Bridge Deck Scarification 3/4"	Sq. Yd.	496	496	992
Containment and Disposal of Lead Paint Cleaning Residues No. 1	L. Sum	1		1
Containment and Disposal of Lead Paint Cleaning Residues No. 2	L. Sum		1	1
Cleaning and Painting Steel Bridge No. 1	L. Sum	1		1
Cleaning and Painting Steel Bridge No. 2	L. Sum		1	1
Structural Repair of Concrete (Depth Equal to or Less Than 5 Inches)	Sq. Ft.	5	10	15
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	2	2	4
Diamond Grinding (Bridge Section)	Sq. Yd.	716	716	1432
Relocating Name Plates	Each	2	2	4
Slope Wall Slurry Pumping	Cu. Yd.			7

* On new concrete superstructure, approach slabs, and latex concrete overlay.

2" PJF (per Article 1051.09 of the Standard Specifications) full width, bonded to back wall with suitable adhesive as recommended by supplier.



Fabric Reinforced Elastomeric Mat according to Section 1028 of the Standard Specifications. Fabric mat shall be 24" wide and attached full width and vertically at edges to the abutment cap with a 3/8" x 5" steel plate and 1/2" Ø studs with nuts and washers at 12" cts. Cost included with Concrete Superstructure.

SECTION THRU SEMI-INTEGRAL ABUTMENT

*Included in the cost of Pipe Underdrains for Structures 4".

Note:

All drainage system components shall extend between the wingwalls at each end of abutment, except an outlet pipe shall extend until intersecting with the side slopes or slope wall surface. Any slope wall removal and replacement required for the installation of the outlet pipe shall be included in the cost of Pipe Underdrains for Structures 4". The pipes shall drain into concrete headwalls. (See Article 601.05 of the Standard Specifications and Highway Standard 601101).


INDEX OF SHEETS

- General Plan and Elevation
- General Data
- Slope Wall Plan
- Stage Construction Details
- Temporary Concrete Barrier
- Deck Slab Repair Plan (S.N. 092-0010)
- Deck Slab Repair Plan (S.N. 092-0011)
- Superstructure Details
- Superstructure Details
- Diaphragm Details
- 11-12. Bridge Approach Slabs
- 13-15. Structural Steel
- Bearing Details
- 17-20. Abutments
- 21-22. Pier Repairs
23. Bar Splicer Assemblies

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-002-Gen Data.dgn
4/22/2022 10:05:05 AM

	USER NAME = baswanson	DESIGNED - LVM	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	GENERAL DATA STRUCTURE NO. 092-0010 & 092-0011	F.A.I. RTE. 74	SECTION (92-10,11,12)R	COUNTY VERMILION	TOTAL SHEETS 698	SHEET NO. 323
	PLOT SCALE =	DRAWN - LVM	REVISED -			CONTRACT NO. 70A29		ILLINOIS FED. AID PROJECT		
	PLOT DATE = 4/22/2022	CHECKED - BAS	REVISED -	SHEET NO. 2 OF 23 SHEETS						

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-003-SlopeWall.dgn
 4/22/2022 10:05:06 AM



SLOPE WALL REPAIR PLAN

LEGEND

# 	Slope Wall Slurry Pumping (Volume)
# 	Slope Wall Crack Sealing (Length)

Notes:
 The repair areas shown are estimated based on a field inspection conducted in December 2020. The actual repair areas required shall be verified according to the Special Provisions.

**SLOPE WALL
 BILL OF MATERIAL**

Item	Unit	Quantity
Slope Wall Slurry Pumping	Cu. Yd.	7
Slope Wall Crack Sealing	Foot	214




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**


**SLOPE WALL PLAN
 STRUCTURE NO. 092-0010 & 092-0011**

SHEET NO. 3 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	324
CONTRACT NO. 70A29				
ILLINOIS		FED. AID PROJECT		




S.N. 092-0011




S.N. 092-0010

STAGE I CONSTRUCTION
(Looking East)



S.N. 092-0011




S.N. 092-0010


STAGE II CONSTRUCTION
(Looking East)

Notes:

Sheet piling shall have a minimum section modulus of 2.5 in³/ft.
 If the Contractor chooses to alter the temporary cantilevered sheet piling design requirements shown on the plans, a design submittal including plan details and calculations will be required for review and acceptance by the Engineer.
 The Contractor shall connect the first sheet to the existing abutment wall to ensure stability of sheets driven to the top of the existing footing. This connection shall be reviewed and accepted by the Engineer and included in the cost for Temporary Sheet Piling.



WEST ABUTMENT



EAST ABUTMENT

TEMPORARY SHEET PILING
(Looking North, typ. both bridges)

MODEL: Default
 FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-004-Staging Plan.dgn
 4/22/2022 10:05:08 AM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

STAGING DETAILS
 STRUCTURE NO. 092-0010 & 092-0011


SHEET NO. 4 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	325
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



When "A" is 3'-1" or less, the temporary concrete barrier shall be restrained to the new slab according to Detail I, II or III. No restraint is required when "A" is greater than 3'-1".

NEW SLAB OR NEW DECK BEAM




Drill 3-1/4" Ø Holes in existing slab for 1" Ø restraining pins. Traffic side only. Cost of restraining pins are included with Temporary Concrete Barrier. No restraint is required when "A" is greater than 3'-1".

EXISTING SLAB


* When hot-mix asphalt wearing surface is present, embedment shall be 3" plus the wearing surface depth.

EXISTING DECK BEAM




RESTRAINING PIN


SECTIONS THRU SLAB OR DECK BEAM




DETAIL I




DETAIL II




DETAIL III



BAR SPLICER FOR #4 BAR - DETAIL III



STEEL RETAINER R 1" x 8" x "W" (Detail I and II)



STEEL RETAINER R 1" x "H" x 10" (Detail III)

Notes:
 Cost of retainer assembly is included with Temporary Concrete Barrier.
 A retainer assembly shall be located at the approximate $\frac{1}{2}$ of each temporary concrete barrier.
 The retainer plate shall not be removed until the concrete on the adjacent stage is ready to be poured. For Detail III applications the retainer plate shall not be removed until just prior to placing the adjacent beam.
 When the 'A' dimension is less than 1 1/2', the wood block shall be omitted and the barrier shall be placed in direct contact with the steel retainer plate. For deck beam applications the minimum required 'A' distance is 6" to accommodate the shear key clamping device.

Detail I - Installation for a new bridge deck or bridge slab.
 Detail II - Installation for a new deck beam with an initial concrete wearing surface. Additional bar splicers shall be provided at 6'-0" centers and paired with the bar splicers of the concrete wearing surface reinforcement to accommodate the installation of the retainer assemblies. The cost of the additional bar splicers is included with the concrete wearing surface.
 Detail III - Installation for a new deck beam with no initial wearing surface or with an initial hot-mix asphalt (HMA) wearing surface present. The deck beam directly beneath the temporary concrete barrier shall be fabricated with bar splicer inserts in the side of the beam, as detailed, to accommodate the installation of the retainer assemblies. A pair of bar splicers, 6" apart, shall be placed at 6'-0" centers along the length of the beam. The cost of the bar splicers is included with the deck beam.

RAILING CRITERIA

NCHRP 350 Test Level	3
Railing Weight (plf)	440

R-27 10-12-2021

MODEL: Default
 FILE NAME: S:\237\2019\12\19020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-005-Temp Conc Barrier.dgn



MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - LVM	REVISED -
	PLOT SCALE =	CHECKED - BAS	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
		CHECKED - BAS	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

TEMPORARY CONCRETE BARRIER
 STRUCTURE NO. 092-0010 & 092-0011

SHEET NO. 5 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	326
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



LEGEND


	Deck Slab Repair (Partial Depth) (For Information Only)
	Deck Slab Repair (Full Depth)
	Concrete Removal

PLAN - DECK SLAB REPAIRS

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.

DECK SLAB REPAIR TABLE

Label	Size	Plan Qty.			As Built	
		Deck Slab Repair (Part. Depth)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
A	4' x 2' x 2 Loc.			16		
Totals				16		



Notes:
 See Sheet 9 of 23 for cross section thru bridge deck.
 Deck survey performed on December 17, 2020. Locations and sizes shown in the plan view are approximate.
 Deck Slab Repair (Partial Depth) is an estimated quantity per the deck survey. This area shall not be paid for separately, but shall be addressed as stated in the Special Provision for Bridge Deck Latex Concrete Overlay.
 Actual size and locations of full-depth patches shall be shown on this sheet and documented in the Deck Slab Repair Table under "As Built".

**DECK SLAB (S.N. 092-0010)
BILL OF MATERIAL**

ITEM	UNIT	TOTAL
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	2
Bridge Deck Scarification 3/4"	Sq. Yd.	496
Bridge Deck Latex Concrete Overlay, 2 3/4 Inches	Sq. Yd.	496

(Sheet 1 of 5)

MODEL: Default
 FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-006-Deck Repair -0010.dgn
 4/22/2022 10:05:10 AM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**DECK SLAB REPAIR PLAN
STRUCTURE NO. 092-0010**

SHEET NO. 6 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	327
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



LEGEND

	Deck Slab Repair (Partial Depth) (For Information Only)
	Deck Slab Repair (Full Depth)
	Concrete Removal

PLAN - DECK SLAB REPAIRS

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.

DECK SLAB REPAIR TABLE

Label	Size	Plan Qty.			As Built	
		Deck Slab Repair (Part. Depth)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
A	4' x 2' x 2 Loc.			16		
Totals				16		

Notes:
 See Sheet 9 of 23 for cross section thru bridge deck.
 See Sheet 6 of 23 for Section A-A.
 Deck survey performed on December 15, 2020. Locations and sizes shown in the plan view are approximate.
 Deck Slab Repair (Partial Depth) is an estimated quantity per the deck survey. This area shall not be paid for separately, but shall be addressed as stated in the Special Provision for Bridge Deck Latex Concrete Overlay.
 Actual size and locations of full-depth patches shall be shown on this sheet and documented in the Deck Slab Repair Table under "As Built".

**DECK SLAB (S.N. 092-0011)
BILL OF MATERIAL**

ITEM	UNIT	TOTAL
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	2
Bridge Deck Scarification 3/4"	Sq. Yd.	496
Bridge Deck Latex Concrete Overlay, 2 3/4 Inches	Sq. Yd.	496

(Sheet 2 of 5)

MODEL: Default
 FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-007-Deck Repair -0011.dgn
 4/22/2022 10:05:11 AM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**DECK SLAB REPAIR PLAN
STRUCTURE NO. 092-0011**

SHEET NO. 7 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	328
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT




S.N. 092-0010 (EB) ①
 S.N. 092-0011 (WB) ①⑥

⑧
 ⑨

** Prior to 1/4" Diamond Grinding

CROSS SECTION
 (Looking East for East Bound,
 Looking West for West Bound)

Notes:
 See sheet 8 of 23 for Bill of Material, Section Thru Parapet, and bar details.
 Cross-hatched areas on parapets indicate Concrete Removal and replacement with Concrete Superstructure.



PARAPET ELEVATION

(Sheet 4 of 5)

MODEL: Default
 FILE NAME: S:\23\72019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-009-Super Section.dgn




USER NAME = baswanson	DESIGNED - LVM	REVISED -
	CHECKED - BAS	REVISED -
PLOT SCALE =	DRAWN - LVM	REVISED -
PLOT DATE = 4/22/2022	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

SUPERSTRUCTURE DETAILS
 STRUCTURE NO. 092-0010 & 092-0011

SHEET NO. 9 OF 23 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	330
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



DIAPHRAGM AT ABUTMENT
(East abutment shown,
West abutment opposite)


Notes:
See sheet 8 of 23 for Bill of Material, bar details, and reinforcement in the bridge deck over the diaphragm.
The approach slab seat shall have a constant slope determined from the control points shown.
See sheet 14 of 23 for hole locations thru beam web.

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.
** Prior to 1/4" Diamond Grinding




Note:
Cost of P.J.F., fabric reinforced elastomeric mat, galvanized plate, stainless steel expansion bolts with nuts and washers and installation are included in the cost of Concrete Superstructure.

VIEW C-C



SECTION B-B
(Showing Proposed)



SECTION D-D

(Sheet 5 of 5)

MODEL: Default
FILE NAME: S:\23\7\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-010-Diaphragm.dgn





USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**DIAPHRAGM DETAILS
STRUCTURE NO. 092-0010 & 092-0011**

SHEET NO. 10 OF 23 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	331
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




PLAN
(East approach shown, West approach similar)

TOP AND BOTTOM ELEVATIONS FOR APPROACH FOOTINGS


Point	West Approach		East Approach	
	Top	Bottom	Top	Bottom
A	652.36	651.53	650.97	650.14
B	652.67	651.84	651.28	650.45
C	652.24	651.41	650.85	650.02
D	652.44	651.61	650.88	650.05
E	652.75	651.92	651.19	650.36
F	652.33	651.50	650.76	649.93



BARS a3(E) & a4(E)



BAR a7(E)




BARS d(E) & d2(E)

BAR d1(E)

Note A - 20-Bar Splicers (E) for #5 w(E) bars, top & bottom


- * (28-Stage I, 37-Stage II)
- ** (45-Stage I, 59-Stage II)

Notes:
PJF (per Article 1051.09 of the Standard Specifications) below the approach slab shall be bonded to the top of new abutment wingwalls with suitable adhesive as recommended by supplier.
See Sheet 12 of 23 for Section A-A and Bill of Material.
See Sheet 23 of 23 for Bar Splicer details.



BAR d5(E)

- *** Omit taper at departure ends with Type 5 terminals
- **** Prior to 1/4\"/>



CROSS SECTION
(Looking East for EB I-74)
(Looking West for WB I-74)

AT APPROACH FOOTING

(Sheet 1 of 2)

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-011-Approach Slab.dgn
4/22/2022 10:05:15 AM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**BRIDGE APPROACH SLAB DETAILS
STRUCTURE NO. 092-0010 & 092-0011**

SHEET NO. 11 OF 23 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11.12)R	VERMILION	698	332
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT



Notes:
 The joint opening shall be adjusted for temperature per Article 520.04 of the Standard Specifications. The length of bridge used to calculate the adjustment shall be equal to the distance from the fixed bearing to the end of the bridge approach slab.
 Parapet concrete shall be paid for as Concrete Superstructure.
 Approach slab shall be paid for as Concrete Superstructure (Approach Slab).
 Approach footing concrete shall be paid for as Concrete Structures.
 The approach footing maximum applied service bearing pressure (Qmax) = 2.0 ksf.
 Cost of excavation for approach footing included with Concrete Structures.
 For Granular Backfill for Structures and drainage treatment details, see sheet 2 of 23.
 Adjust the profile grade as needed across the length of the bridge approach slab to match top of bridge deck overlay at the abutment.

*** Omit taper at departure ends with Type 5 Terminals
 **** Prior to 1/4" Diamond Grinding




INSIDE ELEVATION OF PARAPET AND CURB

STR. NO. 092-0010
 TWO APPROACHES
 BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a3(E)	92	#5	18'-6"	┌───┐
a4(E)	92	#5	24'-5"	┌───┐
a5(E)	120	#8	18'-1"	┌───┐
a6(E)	120	#8	24'-0"	┌───┐
a7(E)	92	#5	7'-4"	┌───┐
b(E)	130	#5	29'-8"	┌───┐
b1(E)	208	#9	29'-8"	┌───┐
b2(E)	8	#5	14'-8"	┌───┐
b3(E)	4	#4	14'-8"	┌───┐
d(E)	68	#5	3'-0"	┌──┐
d1(E)	68	#5	2'-7"	┌──┐
d2(E)	68	#4	3'-0"	┌──┐
d5(E)	68	#4	3'-4"	┌──┐
e(E)	24	#4	14'-8"	┌───┐
e1(E)	8	#8	14'-8"	┌───┐
e2(E)	8	#5	14'-8"	┌───┐
t(E)	176	#4	9'-8"	┌───┐
w(E)	80	#5	18'-1"	┌───┐
w1(E)	80	#5	24'-0"	┌───┐
Concrete Superstructure		Cu. Yd.	5.9	
Concrete Superstructure (Approach Slab)		Cu. Yd.	123.4	
Concrete Structures		Cu. Yd.	26.4	
Reinforcement Bars, Epoxy Coated		Pound	49470	

STR. NO. 092-0011
 TWO APPROACHES
 BILL OF MATERIAL



Bar	No.	Size	Length	Shape
a3(E)	92	#5	18'-6"	┌───┐
a4(E)	92	#5	24'-5"	┌───┐
a5(E)	120	#8	18'-1"	┌───┐
a6(E)	120	#8	24'-0"	┌───┐
a7(E)	92	#5	7'-4"	┌───┐
b(E)	130	#5	29'-8"	┌───┐
b1(E)	208	#9	29'-8"	┌───┐
b2(E)	8	#5	14'-8"	┌───┐
b3(E)	4	#4	14'-8"	┌───┐
d(E)	68	#5	3'-0"	┌──┐
d1(E)	68	#5	2'-7"	┌──┐
d2(E)	68	#4	3'-0"	┌──┐
d5(E)	68	#4	3'-4"	┌──┐
e(E)	24	#4	14'-8"	┌───┐
e1(E)	8	#8	14'-8"	┌───┐
e2(E)	8	#5	14'-8"	┌───┐
t(E)	176	#4	9'-8"	┌───┐
w(E)	80	#5	18'-1"	┌───┐
w1(E)	80	#5	24'-0"	┌───┐
Concrete Superstructure		Cu. Yd.	5.9	
Concrete Superstructure (Approach Slab)		Cu. Yd.	123.4	
Concrete Structures		Cu. Yd.	26.4	
Reinforcement Bars, Epoxy Coated		Pound	49470	



DETAIL A
 (@ Rt. L's)

* Cost included with Concrete Superstructure (Approach Slab).

** Per manufacturer recommendations



VIEW B-B

(Sheet 2 of 2)

MODEL: Default
 FILE NAME: S:\237\2019\12\37\19020.00 (193-026 D5 I-74 Danville)\CADD\CADD Sheets\70A29-0920010-012-Approach Slab.dgn
 4/22/2022 10:05:16 AM

MAURER-STUTZ
 ENGINEERS SURVEYORS


USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

BRIDGE APPROACH SLAB DETAILS
 STRUCTURE NO. 092-0010 & 092-0011


SHEET NO. 12 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	333
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



FRAMING PLAN - S.N. 092-0011

GIRDER REACTION TABLE (EXIST.)		S.N. 092-0010 & 092-0011	
		Abutments	
$R_{\bar{L}}$	(k)		14.2
$R_{\bar{L}}$	(k)		31.2
R_{IM}	(k)		9.4
R_{Total}	(k)		54.8



FRAMING PLAN - S.N. 092-0010

* GIRDER REACTION TABLE (PROP.)		S.N. 092-0010 & 092-0011	
		Abutments	
$R_{\bar{L}}$	(k)		39.0
$R_{\bar{L}}$	(k)		32.8
R_{IM}	(k)		9.9
R_{Total}	(k)		81.7


* New bearing assembly loads (includes approach slab)

Notes:
 Removal of existing diaphragms shall be paid for as Structural Steel Removal.
 Removal of existing bearing assemblies shall be paid for as Jack and Remove Existing Bearings.
 See Sheet 14 of 23 for Bill of Material.

Callouts:


- (A) - Remove existing W12x40 end diaphragm - see Sheet 14 of 23 for details.
- (B) - Jack and remove existing bearing assembly, replace with new bearing assemblies as shown on Sheet 16 of 23.
- (C) - Existing Beam to be Straightened & Strengthened - see Sheets 14 and 15 of 23 for details.

MODEL: Default
 FILE NAME: S:\23\7\2019\12\3719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-013-Str. Steel Plan.dgn
 4/22/2022 10:05:17 AM



**EXISTING BEARING
REMOVAL DETAIL**


To be removed



END DIAPHRAGM REMOVAL

Notes:

- Removal of the existing steel extensions and side retainers at the abutments shall be included in the cost of Jack and Remove Existing Bearings.
- Minimum jack capacity shall be 30 tons.
- Removal of steel end diaphragms shall be paid for as Structural Steel Removal.
- Strengthening plates shall be paid for as Structural Steel Repair.
- Beam ends shall be painted as noted in the General Notes. Cost included with Cleaning and Painting Steel Bridge No. 1 (S.N. 092-0010) and Cleaning and Painting Steel Bridge No. 2 (S.N. 092-0011).
- Following the beam straightening but prior to installation of the strengthening R , the beam flange area in contact with the strengthening R shall be cleaned and painted per the requirements for Primary Connections as specified in the Special Provision for "Cleaning and Painting Contact Surface Areas of Existing Steel Structures".
- "CVN" denotes Charpy-V-Notch impact energy requirements, zone 2.




STRENGTHENING DETAIL

**BILL OF MATERIAL
STR. NO. 092-0010**

Item	Unit	Total
Elastomeric Bearing Assembly, Type I	Each	16
Anchor Bolts, 1"	Each	32
Furnishing and Erecting Structural Steel	Pound	2980
Jack and Remove Existing Bearings	Each	16
Structural Steel Removal	Pound	3680
Structural Steel Repair	Pound	250

**BILL OF MATERIAL
STR. NO. 092-0011**

Item	Unit	Total
Elastomeric Bearing Assembly, Type I	Each	16
Anchor Bolts, 1"	Each	32
Furnishing and Erecting Structural Steel	Pound	2980
Jack and Remove Existing Bearings	Each	16
Structural Steel Removal	Pound	3680



BEAM 8 STRENGTHENING R
 R 1" x 4" x 9'-3" (CVN) (2 Required)

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-014-Str. Steel Details.dgn
4/22/2022 10:05:18 AM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**STRUCTURAL STEEL DETAILS
STRUCTURE NO. 092-0010 & 092-0011**

SHEET NO. 14 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	335
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




PULLING DEVICE

PARTIAL PLANS

PUSHING DEVICE


SUGGESTED BEAM STRAIGHTENING METHODS

Straightening force shall be maintained on all load transfer blocking during beam straightening.



SUGGESTED VERTICAL STRAIGHTENING DETAIL

(To correct flange rotation.)




SUGGESTED VERTICAL STRAIGHTENING DETAIL


(To correct localized vertical flange deformations.)

* Edge of plate shall line up with edge of deformation.


Note:
Braces and jack assembly shall be placed on same side of web.
Bent bottom flange shall be straightened before starting any horizontal straightening operations.



SECTION A-A




SECTION B-B



GRINDING DETAIL

Grind existing nicks, gouges and shallow cracks in the damaged beams as detailed. Ground surfaces shall be inspected for cracks using dye penetrant or magnetic particle testing prior to initiating any beam straightening operations. Any cracks that cannot be removed by grinding approximately 1/4 inch deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. Ground surfaces shall be spot cleaned and painted with an aluminum epoxy mastic primer followed by a finish coat to match the color of the existing beam. Cost of grinding, testing and spot painting included with Beam Straightening.



EXISTING DEFORMATION TO BE STRAIGHTENED

(Looking West)
(Approximate max. deflections)
Deflected length of beam to be straightened is approximately 10'-0"

BILL OF MATERIAL STR. NO. 092-0010

Item	Unit	Quantity
Beam Straightening	L. Sum	1

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-015-Beam Straightening Details.dgn
4/22/2022 10:05:19 AM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


BEAM STRAIGHTENING DETAILS
STRUCTURE NO. 092-0010

SHEET NO. 15 OF 23 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	336
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




ELEVATION AT ABUT.




SECTION A-A



SECTION



ELEVATION




PLAN - TOP AND BOTTOM R_L

TYPE I ELASTOMERIC EXP. BRG.

FILL PLATE THICKNESS


S.N. 092-0010, W. Abut.		S.N. 092-0010, E. Abut.	
Beam 1	5/8"	Beam 1	3/4"
Beam 2	3/8"	Beam 2	5/8"
Beam 3	--	Beam 3	5/8"
Beam 4	1/4"	Beam 4	1"
Beam 5	--	Beam 5	3/8"
Beam 6	--	Beam 6	1/2"
Beam 7	--	Beam 7	1/2"
Beam 8	--	Beam 8	3/8"
S.N. 092-0011, W. Abut.		S.N. 092-0011, E. Abut.	
Beam 9	--	Beam 9	3/8"
Beam 10	3/4"	Beam 10	3/8"
Beam 11	1/4"	Beam 11	--
Beam 12	1/4"	Beam 12	--
Beam 13	5/8"	Beam 13	1/4"
Beam 14	3/8"	Beam 14	3/4"
Beam 15	3/8"	Beam 15	5/8"
Beam 16	3/8"	Beam 16	3/4"



BEARING ASSEMBLY

(at Abutments)

Note:
Shim plates shall not be placed under bearing assembly.



SIDE RETAINER

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.

Notes:

Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Steel extensions, shim plates, and connection bolts shall be paid for as Furnishing and Erecting Structural Steel.

Side retainers and stainless steel plates shall be included in the cost of Elastomeric Bearing Assembly, Type I.

Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions.

Anchor bolts and side retainers at all supports shall be installed as each member is erected unless an equivalent temporary means of lateral restraint is used.

Provide two 1/8" adjusting shims for each bearing in addition to all other plates of the Bearing Assembly, and place as shown in the bearing details.

See sheet 14 of 23 for Bill of Material.

The Top Bearing Plates shall be shop painted with the inorganic zinc rich primer per AASHTO M300, Type 1. Cost included with Elastomeric Bearing Assembly, Type I.

MODEL: Default
FILE NAME: S:\237\2019\12\3719020\00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-016-Bearing_Details.dgn
4/22/2022 10:05:20 AM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


BEARING DETAILS
STRUCTURE NO. 092-0010 & 092-0011

SHEET NO. 16 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	337
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




S.N. 092-0010




S.N. 092-0011

ABUTMENT PLAN



S.N. 092-0010



S.N. 092-0011

ABUTMENT ELEVATION
(Looking West)

Notes:
Existing reinforcement bars extending into the removal area shall be cleaned, straightened, and incorporated into the new construction as noted. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system at no cost to the Department. Cost included with Concrete Removal. See Sheet 19 of 23 for Sections A-A, B-B, C-C, and D-D. See Sheet 20 of 23 for Bill of Material. See Sheet 2 of 23 for limits of Structure Excavation.

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5"	SRC >5"	SRC ≤5"	SRC >5"
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
1	1' x 2'	2			
Totals		2			

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal

MODEL: Default
FILE NAME: S:\23\7\2019\12\37190200.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-017-W Abut Removal.dgn



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

WEST ABUTMENT REMOVAL
STRUCTURE NO. 092-0010 & 092-0011


SHEET NO. 17 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	338
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT




S.N. 092-0011




S.N. 092-0010

ABUTMENT PLAN



S.N. 092-0011



S.N. 092-0010

ABUTMENT ELEVATION
(Looking East)

Notes:
Existing reinforcement bars extending into the removal area shall be cleaned, straightened, and incorporated into the new construction as noted. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system at no cost to the Department. Cost included with Concrete Removal. See Sheet 19 of 23 for Sections A-A, B-B, C-C, and D-D. See Sheet 20 of 23 for Bill of Material. See Sheet 2 of 23 for limits of Structure Excavation.

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5"	SRC >5"	SRC ≤5"	SRC >5"
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
1	1' x 1'	1			
Totals		1			

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal

MODEL: Default
FILE NAME: S:\23\7\2019\12\37\190200.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-018-E Abut. Removal.dgn
4/22/2022 10:05:21 AM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


EAST ABUTMENT REMOVAL
STRUCTURE NO. 092-0010 & 092-0011

SHEET NO. 18 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	339
CONTRACT NO. 70A29				


ILLINOIS FED. AID PROJECT

W. Abut. Elev. ±649.26
E. Abut. Elev. ±648.28



VIEW A-A
(Outside Wingwall)
(EB W. Abut. & WB E. Abut. Shown,
others opposite)


W. Abut. Elev. ±649.36
E. Abut. Elev. ±648.38



VIEW B-B
(Median Side Wingwall)
(EB W. Abut. & WB E. Abut. Shown,
others opposite)

1'-7³/₄"


Clean and incorporate
exist. vert. bars in
new construction



SECTION C-C

6" 12"

Clean and incorporate
exist. vert. bars in
new backwall



SECTION D-D

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-019-Abut. Removal Details.dgn



USER NAME = baswanson	DESIGNED - LVM	REVISED -
	CHECKED - BAS	REVISED -
PLOT SCALE =	DRAWN - LVM	REVISED -
PLOT DATE = 4/22/2022	CHECKED - BAS	REVISED -







STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ABUTMENT REMOVAL DETAILS
STRUCTURE NO. 092-0010 & 092-0011

SHEET NO. 19 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	340
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT



STR. NO. 092-0010
TWO ABUTMENTS
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h(E)	8	#5	20'-8"	—
h1(E)	8	#5	22'-7"	—
h2(E)	12	#5	8'-3"	—
h3(E)	12	#5	8'-3"	—
h4(E)	16	#5	8'-0"	┘
Structure Excavation			Cu. Yd.	66
Concrete Removal			Cu. Yd.	28.1
Concrete Structures			Cu. Yd.	7.5
Reinforcement Bars, Epoxy Coated			Pound	700
Structural Repair of Concrete (Depth ≤ 5 in.)			Sq. Ft.	2

STR. NO. 092-0011
TWO ABUTMENTS
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h(E)	8	#5	20'-8"	—
h1(E)	8	#5	22'-7"	—
h2(E)	12	#5	8'-3"	—
h3(E)	12	#5	8'-3"	—
h4(E)	16	#5	8'-0"	┘
Structure Excavation			Cu. Yd.	66
Concrete Removal			Cu. Yd.	28.1
Concrete Structures			Cu. Yd.	7.5
Reinforcement Bars, Epoxy Coated			Pound	700
Structural Repair of Concrete (Depth ≤ 5 in.)			Sq. Ft.	1

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-020-0-Abutments.dgn



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
	CHECKED - BAS	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


ABUTMENTS
STRUCTURE NO. 092-0010 & 092-0011
SHEET NO. 20 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	341
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				


STRUCTURAL REPAIR OF CONCRETE TABLE

Notes:
 Pier repair areas shown are estimated from soundings on October 11 thru 16, 2020.
 Actual size and locations of completed repairs shall be shown on this sheet and documented in the provide tables under "As Built".

Label	Size	Plan Qty.		As Built	
		SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.	SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.
1	3' x 1'	3			
2	3' x 1'	3			
3	1' x 1'	1			
4	2' x 1'	2			
Totals		9			



ELEVATION - PIER 1
(Looking west)



ELEVATION - PIER 2
(Looking west)

BILL OF MATERIAL

Item	Unit	Quantity
Structural Repair of Concrete (Depth ≤ 5 in.)	Sq. Ft.	9

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Structural Repair of Concrete (Depth Greater Than 5 inches)

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920010-022-Pier Repair (WB).dgn

MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - LVM	REVISED -
	PLOT SCALE =	CHECKED - BAS	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - LVM	REVISED -
		CHECKED - BAS	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUBSTRUCTURE REPAIR - PIERS
S.N. 092-0011

SHEET NO. 22 OF 23 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	343

CONTRACT NO. 70A29
 ILLINOIS FED. AID PROJECT



STANDARD BAR SPLICER ASSEMBLY PLAN
 (All components shall be provided from one supplier)

Threaded splicer bar length = min. lap length + 1 1/2" + thread length


* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

STR. NO. 092-0010

Location	Bar size	No. assemblies required	Minimum lap length
Bridge Deck	#5	24	3'-6"
Diaphragm	#6	8	4'-0"
Diaphragm	#4	4	2'-5"
Approach Slab	#5	92	3'-4"
Approach Slab	#8	120	4'-9"
Approach Footing	#5	80	3'-2"
Abutments	#5	8	3'-2"

STR. NO. 092-0011

Location	Bar size	No. assemblies required	Minimum lap length
Bridge Deck	#5	24	3'-6"
Diaphragm	#6	8	4'-0"
Diaphragm	#4	4	2'-5"
Approach Slab	#5	92	3'-4"
Approach Slab	#8	120	4'-9"
Approach Footing	#5	80	3'-2"
Abutments	#5	8	3'-2"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.


"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required



HEADED BAR SPLICER ASSEMBLY PLAN

Location	Bar size	No. assemblies required	A	B
Diaphragms -0010	#6	8	1'-9"	3'-6"
Diaphragms -0011	#6	8	1'-9"	3'-6"

Notes:

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.


All reinforcement shall be lapped and tied to the splicer bars.

Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.

See approved list of bar splicer assemblies and mechanical splicers for alternatives.

MODEL: Default
 FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920010-023-3-Bar Splicers.dgn
 4/22/2022 10:05:25 AM

Benchmark - Survey disk on top of the NW wingwall of Structure No. 092-0011 (at G Street). Elev. 656.07.
 Existing Structures - Dual Structures, S.N. 092-0012 (W.B.) & 092-0013 (E.B.), composed of four-span continuous wide flange steel beams. Superstructures are supported on pile-supported east stub abutments, west closed abutments, and piers. Built in 1964 as Section 92-11VB-1 at Sta. 1900+80.59; repaired in 1977; repaired in 1992 as Section (92-11VB-1)BR.
 Traffic to be maintained using staged construction.
 Salvage - None.



ELEVATION

PROPOSED SCOPE OF WORK


1. Rehabilitate bridge deck with scarification and latex concrete overlay
2. Remove and replace bridge approach slabs
3. Replace steel beam bearing assemblies at abutments
4. Remove and replace deck joints at west abutment with preformed joint strip seal
5. Remove existing east abutment deck joints and reconstruct with jointless semi-integral abutments
6. Repair concrete deterioration on abutments
7. Repair sections of concrete slope wall
8. Remove and replace steel diaphragms at west abutment
9. Paint beam ends
10. Add side retainers to Pier 1 & Pier 3 bearings

LOADING HS20-44


DESIGN SPECIFICATIONS
 2002 AASHTO Standard Specifications for Highway Bridges, 17th Edition (LFD)

DESIGN STRESSES

FIELD UNITS
 New Construction:
 $f'_c = 3,500$ psi
 $f'_c = 4,000$ psi (deck)
 $f_y = 60,000$ psi (Reinforcement)
 $f_y = 36,000$ psi (structural steel)
 Exist. Structure:
 $f'_c = 3,500$ psi
 $f_y = 60,000$ psi (deck reinf.)
 $f_y = 40,000$ psi (orig. substr. reinf.)
 $f_y = 36,000$ psi (structural steel)




PLAN



LOCATION SKETCH

GENERAL PLAN AND ELEVATION
 I-74 OVER F STREET, FAIRFIELD AVE.,
 AND CSXT RAILROAD

F.A.I. 74 - SEC. (92-10,11,12)R
 VERMILION COUNTY
 STA. 1900+74.44
 STR. NO. 092-0012 & 092-0013



Bryan Swanson
 Date Signed: 4-22-22
 Exp. Date: 11/30/2022

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-001-GPE.dgn
 4/22/2022 11:50:51 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

SHEET NO. 1 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	345
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

GENERAL NOTES

All new fasteners shall be 3/4" Ø high-strength steel bolts, unless noted otherwise.

No field welding is permitted except as specified in the contract documents.

Reinforcement bars designated (E) shall be epoxy coated.

Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.

As directed by the Engineer, existing construction accessories welded to the top flange of beams and girders shall be removed. The weld areas shall be ground flush and inspected for cracks using magnetic particle testing (MT) or dye penetrant testing (PT) by qualified personnel approved by the Engineer.

Any cracks that can not be removed by grinding 1/4 in. deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. The cost of removing welded accessories, grinding and inspecting weld areas, and grinding cracks will be paid for according to Article 109.04 of the Standard Specifications.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work; however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Joint openings shall be adjusted according to Article 503.10(c) of the Standard Specifications when the deck is poured at an ambient temperature other than 50°F.

Existing Name Plates shall be removed, cleaned and incorporated into the new construction. Cost included with Relocating Name Plates.

Synthetic Fibers shall be included in the bridge deck concrete overlay specified. See Special Provisions.

The existing structural steel contains lead. The Contractor shall take appropriate precautions to deal with the presence of lead on this project.

Cleaning and painting of the existing structural steel shall be as specified in the special provision for "Cleaning and Painting Existing Steel Structures". After removal of deck ends and diaphragms, but prior to new bearing installation and encasement of the steel beams, all beams and other existing structural steel within 5 ft of the beam ends shall be cleaned per Near White Blast Cleaning (SSPC-SP10).

The designated areas cleaned per Near White Blast Cleaning (SSPC-SP10) shall be painted according to the requirements of Paint System 1 (OZ/E/U). The color of the final finish coat for all steel surfaces shall be Gray, Munsell No. 5B 7/1.

Existing structural steel that will be in contact with new structural steel shall be cleaned and painted prior to erection as required by the Special Provision "Cleaning and Painting Contact Surface Areas of Existing Steel Structures".

Care shall be taken not to damage rubber bearing or joint components during blasting and cleaning operations. Any damage to these components shall be repaired at the Contractor's expense.

SSPC-QP1 and SPC-QP2 Painting Contractor Certifications will be required for this contract.

All new structural steel shall be hot dip galvanized unless noted otherwise. See Special Provision for "Hot Dip Galvanizing for Structural Steel".


Existing structure plans are available from the District upon request.

TOTAL BILL OF MATERIAL

ITEM	UNIT	-0012	-0013	TOTAL
Concrete Removal	Cu. Yd.	28.7	34.0	62.7
Protective Shield	Sq. Yd.	918	1171	2089
Structure Excavation	Cu Yd.	43	58	101
Concrete Structures	Cu. Yd.	32.1	40.0	72.1
Concrete Superstructure	Cu. Yd.	32.4	40.1	72.5
* Protective Coat	Sq. Yd.	1389	1783	3172
Concrete Superstructure (Approach Slab)	Cu. Yd.	122.8	157.1	279.9
Furnishing and Erecting Structural Steel	Pound	3640	6250	9890
Reinforcement Bars, Epoxy Coated	Pound	52280	67410	119690
Bar Splicers	Each	331	331	662
Preformed Joint Strip Seal	Foot	45	59	104
Elastomeric Bearing Assembly, Type I	Each	7	9	16
Elastomeric Bearing Assembly, Type II	Each	7	9	16
Anchor Bolts, 1"	Each	52	68	120
Temporary Sheet Piling	Sq. Ft.	89	95	184
Granular Backfill for Structures	Cu. Yd.	39	54	93
Epoxy Crack Injection	Foot	15	22	37
Geocomposite Wall Drain	Sq. Yd.	27	35	62
Pipe Underdrains for Structures 4"	Foot	66	76	142
Slope Wall Crack Sealing	Foot			12
Bridge Deck Grooving (Longitudinal)	Sq. Yd.	811	1311	2122
Jack and Remove Existing Bearings	Each	14	18	32
Structural Steel Removal	Pound	2400	4620	7020
Bridge Deck Latex Concrete Overlay 2 3/4"	Sq. Yd.	1061	1366	2427
Bridge Deck Scarification 3/4"	Sq. Yd.	1061	1366	2427
Containment and Disposal of Lead Paint Cleaning Residues No. 3	L. Sum	1		1
Containment and Disposal of Lead Paint Cleaning Residues No. 4	L. Sum		1	1
Cleaning and Painting Steel Bridge No. 3	L. Sum	1		1
Cleaning and Painting Steel Bridge No. 4	L. Sum		1	1
Structural Repair of Concrete (Depth Equal to or Less Than 5 Inches)	Sq. Ft.	98	88	186
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	1	1	2
Diamond Grinding (Bridge Section)	Sq. Yd.	1240	1634	2874
Slope Wall Repair	Sq. Yd.			202
Slope Wall Slurry Pumping	Cu. Yd.			6
Temporary Shoring and Cribbing	Each	3	5	8

* On new concrete superstructure, approach slabs, and latex concrete overlay.

2" PJF (per Article 1051.09 of the Standard Specifications) full width, bonded to back wall with suitable adhesive as recommended by supplier.



SECTION THRU SEMI-INTEGRAL ABUTMENT

(Horiz. dim. @ Rt. L's)
(East Abutment only)

*Included in the cost of Pipe Underdrains for Structures 4".

Note:

All drainage system components shall extend between the wingwalls at each end of abutment, except an outlet pipe shall extend until intersecting with the side slopes or slope wall surface. Any slope wall removal and replacement required for the installation of the outlet pipe shall be included in the cost of Pipe Underdrains for Structures 4". The pipes shall drain into concrete headwalls. (See Article 601.05 of the Standard Specifications and Highway Standard 601101).

INDEX OF SHEETS

- General Plan and Elevation
- General Data
- Slope Wall Plan
- Stage Construction Details
- Temporary Concrete Barrier
- Deck Slab Repair Plan (S.N. 092-0012)
- Superstructure Details (S.N. 092-0012)
- Diaphragm Details (S.N. 092-0012)
- Deck Slab Repair Plan (S.N. 092-0013)
- Superstructure Details (S.N. 092-0013)
- Diaphragm Details (S.N. 092-0013)
- Bridge Approach Slabs
- Preformed Joint Strip Seal
- Structural Steel Framing Plan
- Structural Steel Details
- Bearing Details
- West Abutments
- East Abutments
- Bar Splicer Assemblies

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-002-Gen Data.dgn




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**GENERAL DATA
STRUCTURE NO. 092-0012 & 092-0013**


SHEET NO. 2 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	346
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




LEGEND


	Remove and Replace Slope Wall (paid for as Slope Wall Repair)
	Slope Wall Slurry Pumping
	Slope Wall Crack Sealing (Length)



SECTION C-C



SECTION A-A



SECTION B-B

Notes:
 Slope wall shall be reinforced with welded wire fabric, 6 in. x 6 in. - W4.0 x W4.0, weighing 58 lbs. per 100 sq. ft.
 Voids below the replaced slope wall shall be filled prior to placement of the new concrete slab. Existing riprap not extending above the bottom of the new concrete may remain; fill the remaining void with controlled low-strength material per the Special Provision for Slope Wall Slurry Pumping.
 Layout and limits of the slope wall removal and repairs may be varied to suit conditions in the field as directed by the Engineer.
 Remove all dirt and riprap from on top of bottom of slope wall. Expose and clean out inlet located between bridges. Cost included with Slope Wall Repair.
 Set flow line of slope wall gutter to maintain positive drainage from Paved Ditch to Inlet.

**SLOPE WALL
BILL OF MATERIAL**

Item	Unit	Quantity
Slope Wall Repair	Sq. Yd.	202
Slope Wall Slurry Pumping	Cu. Yd.	6
Slope Wall Crack Sealing	Foot	12

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-003-SlopeWall.dgn




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**SLOPE WALL PLAN
STRUCTURE NO. 092-0012 & 092-0013**

SHEET NO. 3 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	347
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




S.N. 092-0012




S.N. 092-0013

STAGE I CONSTRUCTION

(Looking East)



S.N. 092-0012




S.N. 092-0013

STAGE II CONSTRUCTION


(Looking East)

Notes:

Sheet piling shall have a minimum section modulus of 3.1 in³/ft.
 If the Contractor chooses to alter the temporary cantilevered sheet piling design requirements shown on the plans, a design submittal including plan details and calculations will be required for review and acceptance by the Engineer.
 The Contractor shall connect the first sheet to the existing abutment wall to ensure stability of sheets driven to the top of the existing footing. This connection shall be reviewed and accepted by the Engineer and included in the cost for Temporary Sheet Piling.
 Temporary Sheet Piling will be driven into embankment fill soils consisting of Mixed Clay Loam with unconfined compressive strengths (Qu) varying from 1.0 to 2.2 tsf."



E. ABUT. (S.N. 092-0012)



E. ABUT. (S.N. 092-0013)

TEMPORARY SHEET PILING

(Looking North)

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-004-Staging_Plan.dgn
 4/22/2022 11:50:55 PM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

STAGING DETAILS
 STRUCTURE NO. 092-0012 & 092-0013


SHEET NO. 4 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	348
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



When "A" is 3'-1" or less, the temporary concrete barrier shall be restrained to the new slab according to Detail I, II or III. No restraint is required when "A" is greater than 3'-1".


NEW SLAB OR NEW DECK BEAM



Drill 3-1/4" Ø Holes in existing slab for 1" Ø restraining pins. Traffic side only. Cost of restraining pins are included with Temporary Concrete Barrier. No restraint is required when "A" is greater than 3'-1".

EXISTING SLAB


EXISTING DECK BEAM




RESTRAINING PIN

* When hot-mix asphalt wearing surface is present, embedment shall be 3" plus the wearing surface depth.


SECTIONS THRU SLAB OR DECK BEAM




DETAIL I



DETAIL II




DETAIL III




BAR SPLICER FOR #4 BAR - DETAIL III

Notes:
 Cost of retainer assembly is included with Temporary Concrete Barrier.
 A retainer assembly shall be located at the approximate \bar{c} of each temporary concrete barrier.
 The retainer plate shall not be removed until the concrete on the adjacent stage is ready to be poured. For Detail III applications the retainer plate shall not be removed until just prior to placing the adjacent beam.
 When the 'A' dimension is less than 1 1/2', the wood block shall be omitted and the barrier shall be placed in direct contact with the steel retainer plate. For deck beam applications the minimum required 'A' distance is 6" to accommodate the shear key clamping device.

Detail I - Installation for a new bridge deck or bridge slab.
Detail II - Installation for a new deck beam with an initial concrete wearing surface. Additional bar splicers shall be provided at 6'-0" centers and paired with the bar splicers of the concrete wearing surface reinforcement to accommodate the installation of the retainer assemblies. The cost of the additional bar splicers is included with the concrete wearing surface.
Detail III - Installation for a new deck beam with no initial wearing surface or with an initial hot-mix asphalt (HMA) wearing surface present. The deck beam directly beneath the temporary concrete barrier shall be fabricated with bar splicer inserts in the side of the beam, as detailed, to accommodate the installation of the retainer assemblies. A pair of bar splicers, 6" apart, shall be placed at 6'-0" centers along the length of the beam. The cost of the bar splicers is included with the deck beam.



STEEL RETAINER R 1" x 8" x "W"
(Detail I and II)



STEEL RETAINER R 1" x "H" x 10"
(Detail III)

RAILING CRITERIA

NCHRP 350 Test Level	3
Railing Weight (plf)	440

R-27 10-12-2021

MODEL: Default
 FILE NAME: S:\237\2019\12\19020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-005-Temp Conc Barrier.dgn


MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - LVM	REVISED -
	PLOT SCALE =	CHECKED - BAS	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
		CHECKED - LVM	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

TEMPORARY CONCRETE BARRIER
STRUCTURE NO. 092-0012 & 092-0013

SHEET NO. 5 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	349
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



PLAN - DECK SLAB REPAIRS

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.


LEGEND

	Deck Slab Repair (Partial Depth) (For Information Only)
	Deck Slab Repair (Full Depth)
	Concrete Removal

Notes:
 See sheet 8 of 34 for cross section thru bridge deck.
 Deck survey performed on December 17, 2020. Locations and sizes shown in the plan view are approximate.
 Deck Slab Repair (Partial Depth) is an estimated quantity per the deck survey. This area shall not be paid for separately, but shall be addressed as stated in the Special Provision for Bridge Deck Latex Concrete Overlay.
 Actual size and locations of full-depth patches shall be shown on this sheet and documented in the Deck Slab Repair Table under "As Built".

DECK SLAB REPAIR TABLE

Label	Size	Plan Qty.			As Built	
		Deck Slab Repair (Part. Depth)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
A	1' x 2' x 3 Loc.		6			
B	2' x 3'	6				
C	2' x 2'	4				
D	2' x 2'	4				
Totals		14	6			



SECTION A-A
(Showing Removal)


DECK SLAB (S.N. 092-0012)
BILL OF MATERIAL

ITEM	UNIT	TOTAL
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	1
Bridge Deck Scarification 3/4"	Sq. Yd.	1061
Bridge Deck Latex Concrete Overlay, 2 3/4 Inches	Sq. Yd.	1061
Concrete Removal	Cu. Yd.	8.4

(Sheet 1 of 5)

MODEL: Default
FILE NAME: S:\237\2019\12\3719020\00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-006-Deck Repair -0012.dgn

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-007-Super Plan -0012.dgn



PLAN - DECK AT ABUTMENTS

Notes:
 See sheet 9 of 34 for Section B-B, Bill of Material and bar details.
 See sheet 10 of 34 for Section C-C.
 Spacing for v(E) bars shall be at right angles to \hat{C} Rdwy.

(Sheet 2 of 5)




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**SUPERSTRUCTURE DETAILS
 STRUCTURE NO. 092-0012**

SHEET NO. 7 OF 34 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	351
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




** Prior to 1/4" Diamond Grinding

CROSS SECTION
(Looking West)

Notes:
See sheet 9 of 34 for Bill of Material, Section Thru Parapet, and bar details.
Cross-hatched area on parapets indicate Concrete Removal and replacement with Concrete Superstructure



NORTH PARAPET ELEVATION
(Looking North)



SOUTH PARAPET ELEVATION
(Looking South)

(Sheet 3 of 5)

MODEL: Default
FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-008-Super Section -01.dgn

MAURER-STUTZ
ENGINEERS SURVEYORS

USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUPERSTRUCTURE DETAILS
STRUCTURE NO. 092-0012

SHEET NO. 8 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	352
CONTRACT NO. 70A29				


ILLINOIS FED. AID PROJECT



SECTION B-B


* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.

** Prior to 1/4" Diamond Grinding




BARS d(E) & d2(E)


BAR d1(E)



BARS d3(E) & d4(E)




SECTION THRU PARAPET



**BARS s(E)
(Headed)**


**SUPERSTRUCTURE
STR. NO. 092-0012
BILL OF MATERIAL**

Bar	No.	Size	Length	Shape
a(E)	24	#5	19'-1"	—
a1(E)	24	#5	24'-9"	—
a2(E)	12	#6	6'-0"	—
d(E)	16	#5	3'-0"	┌┐
d1(E)	16	#5	2'-7"	┌┐
d2(E)	16	#4	3'-0"	┌┐
d3(E)	8	#4	4'-4"	┌┐
d4(E)	8	#4	3'-10"	┌┐
m(E)	5	#6	19'-7"	—
m1(E)	5	#6	25'-3"	—
m2(E)	10	#6	6'-0"	—
m3(E)	10	#6	6'-0"	—
m6(E)	4	#6	3'-2"	—
m7(E)	4	#6	2'-7"	—
m8(E)	2	#4	19'-7"	—
m9(E)	2	#4	25'-3"	—
m100(E)	21	#6	5'-0"	—
s(E)	56	#5	7'-6"	┌┐
s1(E)	42	#5	8'-10"	┌┐
u(E)	56	#4	5'-0"	┌┐
v(E)	45	#5	3'-1"	┌┐
Reinforcement Bars, Epoxy Coated		Pound	3300	
Concrete Superstructure		Cu. Yd.	26.0	
Structure Repair of Concrete (Depth ≤ 5")		Sq. Ft.	8	




CONDUIT AT ABUTMENT JOINT

(East Abutment, North Parapet)
(Looking South)




CONDUIT AT ABUTMENT JOINT


(West Abutment, North Parapet)
(Looking South)




BARS u(E)



BARS s1(E)



**BAR v(E)
(Headed)**



**BARS m2(E), m6(E), & m7(E)
(Headed)**

(Sheet 4 of 5)

MODEL: Default
FILE NAME: S:\237\2019\12\37\19020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-009-Super Details -0012.dgn
4/22/2022 11:51:00 PM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**SUPERSTRUCTURE DETAILS
STRUCTURE NO. 092-0012**

SHEET NO. 9 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	353
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




DIAPHRAGM AT ABUTMENT

Notes:

See sheet 7 of 34 for reinforcement in the bridge deck over the diaphragm.
 See sheet 9 of 34 for Bill of Material and bar details.
 The approach slab seat shall have a constant slope determined from the control points shown.
 See sheet 23 of 34 for hole locations thru beam web.


* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.

** Prior to 1/4" Diamond Grinding




VIEW D-D

Note:
 Cost of P.J.F., fabric reinforced elastomeric mat, galvanized plate, stainless steel expansion bolts with nuts and washers and installation are included in the cost of Concrete Superstructure.



SECTION C-C
 (Showing Proposed)




SECTION E-E

(Sheet 5 of 5)

MODEL: Default
 FILE NAME: S:\237\2019\12\31\19020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-010-Diaphragm -0012.dgn

	USER NAME = baswanson	DESIGNED - LVM	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	EAST ABUTMENT DIAPHRAGM STRUCTURE NO. 092-0012	F.A.I. RTE. 74	SECTION (92-10,11,12)R	COUNTY VERMILION	TOTAL SHEETS 698	SHEET NO. 354
	PLOT SCALE =	DRAWN - BAS	REVISED -			SHEET NO. 10 OF 34 SHEETS	CONTRACT NO. 70A29			
	PLOT DATE = 4/22/2022	CHECKED - LVM	REVISED -			ILLINOIS		FED. AID PROJECT		




PLAN - DECK SLAB REPAIRS

DECK SLAB REPAIR TABLE

Label	Size	Plan Qty.			As Built	
		Deck Slab Repair (Part. Depth)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)
A	1' x 2' x 3 Loc.	4	6			
	Span 1, Stage II	4				
	Span 2, Stage I	4				
	Span 2, Stage II	64				
	Span 3, Stage I	11				
	Span 3, Stage II	99				
	Span 4, Stage I	23				
	Span 4, Stage II	46				
Totals		251	6			

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.



LEGEND

	Deck Slab Repair (Partial Depth) (For Information Only)
	Deck Slab Repair (Full Depth)
	Concrete Removal

Notes:
 See sheet 13 of 34 for cross section thru bridge deck.
 Deck survey performed on December 17, 2020. Locations and sizes shown in the plan view are approximate.
 Deck Slab Repair (Partial Depth) is an estimated quantity per the deck survey. This area shall not be paid for separately, but shall be addressed as stated in the Special Provision for Bridge Deck Latex Concrete Overlay.
 Actual size and locations of full-depth patches shall be shown on this sheet and documented in the Deck Slab Repair Table under "As Built".

DECK SLAB (S.N. 092-0013) BILL OF MATERIAL

ITEM	UNIT	TOTAL
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	1
Bridge Deck Scarification 3/4"	Sq. Yd.	1366
Bridge Deck Latex Concrete Overlay, 2 3/4 Inches	Sq. Yd.	1366
Concrete Removal	Cu. Yd.	10.3

(Sheet 1 of 5)

MODEL: Default
 FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-011-Deck Repair -0013.dgn
 4/22/2022 11:51:01 PM


MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - LVM	REVISED -
	PLOT SCALE =	CHECKED - BAS	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
		CHECKED - LVM	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

DECK SLAB REPAIR PLAN
STRUCTURE NO. 092-0013

SHEET NO. 11 OF 34 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	355
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




CROSS SECTION
(Looking East)

** Prior to 1/4" Diamond Grinding

Notes:
See Sheet 14 of 34 for Bill of Material, Section Thru Parapet, and bar details.
Cross-hatched area on parapets indicate Concrete Removal and replacement with Concrete Superstructure



NORTH PARAPET ELEVATION
(Looking North)



SOUTH PARAPET ELEVATION
(Looking South)

(Sheet 3 of 5)

MODEL: Default
FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-013-Super Section -0013.dgn



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUPERSTRUCTURE DETAILS
STRUCTURE NO. 092-0013

SHEET NO. 13 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	357
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT




SECTION B-B


Pour hatched area after deck forms are removed, see sheet 28 of 34 for details and reinf.

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.


** Prior to 1/4" Diamond Grinding




BARS d(E) & d2(E)




BAR d1(E)




BARS d3(E)




BARS s(E)
(Headed)




BARS u(E)




BARS s1(E)




BAR v(E)
(Headed)




BARS m12(E), m14(E), m16(E), & m17(E)
(Headed)



SECTION THRU PARAPET



CONDUIT AT ABUTMENT JOINT
(West Abutment, South Parapet)
(Looking North)



CONDUIT AT ABUTMENT JOINT
(East Abutment, South Parapet)
(Looking North)

SUPERSTRUCTURE
STR. NO. 092-0013
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a2(E)	12	#6	6'-0"	▬
a20(E)	12	#5	19'-1"	▬
a21(E)	12	#5	38'-8"	▬
a30(E)	12	#5	19'-1"	▬
a31(E)	12	#5	35'-2"	▬
d(E)	16	#5	3'-0"	└┘
d1(E)	16	#5	2'-7"	└┘
d2(E)	16	#4	3'-0"	└┘
d3(E)	16	#4	4'-4"	└┘
m10(E)	5	#6	19'-7"	▬
m11(E)	5	#6	35'-8"	▬
m12(E)	12	#6	6'-0"	▬
m13(E)	12	#6	6'-0"	▬
m14(E)	2	#6	3'-2"	▬
m15(E)	2	#6	3'-2"	▬
m16(E)	8	#6	3'-3"	▬
m18(E)	2	#4	19'-7"	▬
m19(E)	2	#4	35'-8"	▬
m100(E)	27	#6	5'-0"	▬
s(E)	68	#5	7'-6"	▬
s1(E)	51	#5	8'-10"	▬
u(E)	68	#4	5'-0"	▬
v(E)	56	#5	3'-1"	└┘
Reinforcement Bars, Epoxy Coated			Pound	4060
Concrete Superstructure Structure Repair of Concrete (Depth ≤ 5")			Cu. Yd.	32.2
			Sq. Ft.	1

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-014-Super Details -0013.dgn
4/22/2022 11:51:03 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUPERSTRUCTURE DETAILS
STRUCTURE NO. 092-0013

SHEET NO. 14 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	358
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				


(Sheet 4 of 5)



DIAPHRAGM AT ABUTMENT


Notes:
 See sheet 14 of 34 for Bill of Material, bar details, and reinforcement in the bridge deck over the diaphragm.
 The approach slab seat shall have a constant slope determined from the control points shown.
 See sheet 23 of 34 for hole locations thru beam web.

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.
 ** Prior to 1/4" Diamond Grinding




VIEW D-D

Note:
 Cost of P.J.F., fabric reinforced elastomeric mat, galvanized plate, stainless steel expansion bolts with nuts and washers and installation are included in the cost of Concrete Superstructure.



SECTION C-C (Showing Proposed)



SECTION E-E

(Sheet 5 of 5)

MODEL: Default
 FILE NAME: S:\237\2019\12\19020\00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-015-Diaphragm -0013.dgn
 4/22/2022 11:51:04 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**


**EAST ABUTMENT DIAPHRAGM
 STRUCTURE NO. 092-0013**

SHEET NO. 15 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	359
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

TOP AND BOTTOM ELEVATIONS
FOR APPROACH FOOTING

Point	Top	Bottom
A	644.40	643.57
B	644.79	643.96
C	644.46	643.63
D	644.49	643.66
E	644.88	644.05
F	644.55	643.72




PLAN - WEST APPROACH

Note A - 20-Bar Splicers (E) for #5 w(E) bars, top & bottom

Notes:
See sheet 20 of 34 for Section A-A and Bill of Material.
See sheet 34 of 34 for Bar Splicer details.
See sheet 27 of 34 for details of new hatch block & parapets.

Abutment Wing End Post,
See sheets 26 and 27 of 34



CROSS SECTION
(Looking East)

AT APPROACH FOOTING

(Sheet 1 of 5)

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-016-W Appr. Slab -0012.dgn

MAURER-STUTZ ENGINEERS SURVYORS	USER NAME = baswanson	DESIGNED - LVM	REVISED -
	PLOT SCALE =	CHECKED - BAS	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
		CHECKED - LVM	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BRIDGE APPROACH SLAB DETAILS
STRUCTURE NO. 092-0012

SHEET NO. 16 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	360
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT






PLAN - EAST APPROACH

TOP AND BOTTOM ELEVATIONS FOR APPROACH FOOTING

Point	Top	Bottom
A	641.96	641.13
B	642.35	641.52
C	642.00	641.17
D	641.87	641.04
E	642.26	641.43
F	641.91	641.08

Note A - 20-Bar Splicers (E) for #5 w10(E) bars, top & bottom

Notes:
 PJF (per Article 1051.09 of the Standard Specifications) below the approach slab shall be bonded to the top of new abutment wingwalls with suitable adhesive as recommended by supplier.
 See sheet 20 of 34 for Section B-B, Bill of Material and additional bar details.
 See sheet 34 of 34 for Bar Splicer details.



CROSS SECTION

(Looking East)

(Sheet 2 of 5)

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-017-E Appr Slab -0012.dgn
 4/22/2022 11:51:06 PM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

BRIDGE APPROACH SLAB DETAILS
 STRUCTURE NO. 092-0012

SHEET NO. 17 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	361
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



**TOP AND BOTTOM ELEVATIONS
FOR APPROACH FOOTING**

Point	Top	Bottom
A	644.41	643.58
B	644.68	643.85
C	643.93	643.10
D	644.49	643.66
E	644.76	643.93
F	644.01	643.18

MIN. BAR LAP


#5 bar = 3'-4"
#8 bar = 5'-4"

Note A - 20-Bar Splicers (E) for #5 w20(E) bars, top & bottom

Notes:
See sheet 20 of 34 for Section A-A and Bill of Material.
See sheet 34 of 34 for Bar Splicer details.
See sheet 29 of 34 for details of new hatch block & parapets.
Bars indicated thus 45 x 2-#5 etc. indicates 45 lines of bars with 2 lengths per line.

PLAN - WEST APPROACH

Abutment Wing End Post, See sheets 28 and 29 of 34



**CROSS SECTION
(Looking East)**

(Sheet 3 of 5)

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-018-W Appr Slab -0013.dgn



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**




**BRIDGE APPROACH SLAB DETAILS
STRUCTURE NO. 092-0013**

SHEET NO. 18 OF 34 SHEETS



F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	362

CONTRACT NO. 70A29

ILLINOIS FED. AID PROJECT



Notes:
 The joint opening shall be adjusted for temperature per Article 520.04 of the Standard Specifications. The length of bridge used to calculate the adjustment shall be equal to the distance from the fixed bearing to the end of the bridge approach slab.
 Parapet concrete shall be paid for as Concrete Superstructure.
 Approach slab shall be paid for as Concrete Superstructure (Approach Slab).
 Approach footing concrete shall be paid for as Concrete Structures.
 The approach footing maximum applied service bearing pressure (Q_{max}) = 2.0 ksf.
 Cost of excavation for approach footing included with Concrete Structures.
 For Granular Backfill for Structures and drainage treatment details, See Sheet 2 of 34.
 Adjust the profile grade as needed across the length of the bridge approach slab to match the top of bridge deck overlay at the abutment.



* Prior to 1/4" Diamond Grinding
 ** Cost included with Concrete Superstructure (Approach Slab).
 *** Per manufacturer recommendations

**STR. NO. 092-0012
 TWO APPROACHES
 BILL OF MATERIAL**

Bar	No.	Size	Length	Shape
a3(E)	45	#5	18'-0"	—
a4(E)	45	#5	24'-4"	—
a5(E)	59	#8	18'-0"	—
a6(E)	59	#8	24'-4"	—
a7(E)	46	#5	7'-4"	—
a13(E)	45	#5	19'-6"	—
a14(E)	45	#5	25'-2"	—
a15(E)	59	#8	19'-1"	—
a16(E)	59	#8	24'-9"	—
b(E)	129	#5	29'-8"	—
b1(E)	205	#9	29'-8"	—
b2(E)	2	#5	14'-10"	—
b3(E)	2	#5	14'-6"	—
b4(E)	1	#4	14'-5"	—
b5(E)	1	#4	14'-10"	—
d(E)	34	#5	3'-0"	—
d1(E)	34	#5	2'-7"	—
d2(E)	34	#4	3'-0"	—
d5(E)	34	#4	3'-4"	—
e(E)	12	#4	14'-8"	—
e1(E)	4	#8	14'-8"	—
e2(E)	4	#5	14'-8"	—
t(E)	174	#4	9'-10"	—
w(E)	40	#5	17'-11"	—
w1(E)	40	#5	24'-4"	—
w10(E)	40	#5	19'-1"	—
w11(E)	40	#5	24'-9"	—
Concrete Superstructure		Cu. Yd.	2.9	
Concrete Superstructure (Approach Slab)		Cu. Yd.	122.8	
Concrete Structures		Cu. Yd.	27.0	
Reinforcement Bars, Epoxy Coated		Pound	48170	

**STR. NO. 092-0013
 TWO APPROACHES
 BILL OF MATERIAL**

Bar	No.	Size	Length	Shape
a7(E)	46	#5	7'-4"	—
a23(E)	45	#5	18'-0"	—
a24(E)	90	#5	20'-9"	—
a25(E)	59	#8	18'-0"	—
a26(E)	118	#8	21'-9"	—
a33(E)	45	#5	19'-6"	—
a34(E)	45	#5	35'-7"	—
a35(E)	59	#8	19'-1"	—
a36(E)	59	#8	35'-2"	—
b(E)	165	#5	29'-8"	—
b1(E)	263	#9	29'-8"	—
b2(E)	2	#5	14'-10"	—
b3(E)	2	#5	14'-6"	—
b4(E)	1	#4	14'-5"	—
b5(E)	1	#4	14'-10"	—
d(E)	34	#5	3'-0"	—
d1(E)	34	#5	2'-7"	—
d2(E)	34	#4	3'-0"	—
d5(E)	34	#4	3'-4"	—
e(E)	12	#4	14'-8"	—
e1(E)	4	#8	14'-8"	—
e2(E)	4	#5	14'-8"	—
t(E)	222	#4	9'-10"	—
w20(E)	40	#5	17'-11"	—
w21(E)	40	#5	38'-1"	—
w30(E)	40	#5	19'-1"	—
w31(E)	40	#5	35'-2"	—
Concrete Superstructure		Cu. Yd.	2.9	
Concrete Superstructure (Approach Slab)		Cu. Yd.	157.1	
Concrete Structures		Cu. Yd.	34.5	
Reinforcement Bars, Epoxy Coated		Pound	62410	

(Sheet 5 of 5)

MODEL: Default
 FILE NAME: S:\237\2019\12\19\2020\00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-02-0-Appr. Slab Details.dgn
 4/22/2022 11:51:09 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

BRIDGE APPROACH SLAB DETAILS
 STRUCTURE NO. 092-0012 & 092-0013


SHEET NO. 20 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	364
CONTRACT NO. 70A29				


ILLINOIS FED. AID PROJECT



FOR SKEWS ≤ 30°
PLAN AT PARAPET




SECTION AT PARAPET



DETAIL A

** Prior to 1/4" Diamond Grinding




SHOWING ROLLED RAIL JOINT

* 5/8" Ø x 6" studs @ 6" cts. (alternate angled/bent studs with horizontal studs)


3/8" Ø threaded rods in 1/16" Ø holes at ±4'-0" cts. for holding the proper joint opening based on the temperature during the deck pour. Place to miss studs. All rods shall be burned, or sawed off flush with the plates after concrete is set.

SECTION A-A


* Granular or solid flux filled headed studs conforming to Article 1006.32 of the Std. Specs., automatically end welded.




SHOWING WELDED RAIL JOINT



ROLLED (EXTRUDED) RAIL



WELDED RAIL



LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue. Rolled rail shown, welded rail similar.

LOCKING EDGE RAILS

*** Back gouge not required if complete joint penetration is verified by mock-up.

BILL OF MATERIAL
STR. NO. 092-0012

Item	Unit	Total
Preformed Joint Strip Seal	Foot	45

BILL OF MATERIAL
STR. NO. 092-0013

Item	Unit	Total
Preformed Joint Strip Seal	Foot	59

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-02-1-PISS.dgn
4/22/2022 11:51:10 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREFORMED JOINT STRIP SEAL
STRUCTURE NO. 092-0012 & 092-0013


SHEET NO. 21 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	365
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT



PARTIAL FRAMING PLAN - S.N. 092-0012



PARTIAL FRAMING PLAN - S.N. 092-0013

Notes:
 Removal of existing diaphragms shall be paid for as Structural Steel Removal.
 Removal of existing bearing assemblies shall be paid for as Jack and Remove Existing Bearings.
 See sheet 23 of 34 for Bill of Material.

- Callouts:**
- D1 - Remove and replace W12x40 end diaphragm and clip angles, see sheet 23 of 34 for details.
 - (A) - Remove existing W12x40 end diaphragm, see sheet 23 of 34 for details.
 - (B) - Jack and remove existing bearing assembly, replace with new bearing assemblies as shown on sheet 24 or 25 of 34.
 - (C) - Install new side retainer and 1" Ø anchor bolt on each side of existing bearing assembly, see sheet 25 of 34 for details.
 - (D) - Install new side retainer and 1" Ø anchor bolt against existing bearing assembly, see sheet 25 of 34 for details.

GIRDER REACTION TABLE (EXIST.)			
S.N. 092-0012 & 092-0013			
		W. Abut.	E. Abut.
R _D	(k)	20.6	20.6
R _L	(k)	33.3	33.3
R _{IM}	(k)	9.5	9.5
R _{Total}	(k)	63.4	63.4

GIRDER REACTION TABLE (PROP.)			
S.N. 092-0012 & 092-0013			
		W. Abut.	*E. Abut.
R _D	(k)	20.6	47.3
R _L	(k)	33.3	41.3
R _{IM}	(k)	9.5	11.8
R _{Total}	(k)	63.4	100.4

* New bearing assembly loads (includes approach slab)

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-022-Str Steel Plan.dgn
 4/22/2022 11:51:11 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**STRUCTURAL STEEL FRAMING PLAN
 STRUCTURE NO. 092-0012 & 092-0013**

SHEET NO. 22 OF 34 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	366
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

** In lieu of drilling holes through web repair plates on Beam 9, Contractor may remove 3 exist. bolts in the approximate locations of the proposed holes and install in their place 3/4" Ø x 5'-0" long threaded rods fastened to the beam at center with two nuts and washers. Bend rod to fit within diaphragm. These rods replace the corresponding m100(E) bars in diaphragm. Cost included with Reinforcement Bars, Epoxy Coated.



To be removed

Notes:
 Removal of the existing steel extensions and side retainers at the abutments shall be included in the cost of Jack and Remove Existing Bearings.
 Minimum jack capacity shall be 30 tons.
 Removal of steel end diaphragms shall be paid for as Structural Steel Removal.
 New diaphragms shall be paid for as Furnishing and Erecting Structural Steel.



DIAPHRAGM CLIP ANGLE SIZES

S.N. 092-0012, W. Abut.		
(of web)	N. Side	S. Side
Beam 10	--	exist.
Beam 11	exist.	exist.
Beam 12	* L6x4x3/4	L6x4x3/4
Beam 13	L6x4x3/4	L6x4x3/4
Beam 14	L6x4x3/4	* L6x4x3/4
Beam 15	exist.	exist.
Beam 16	exist.	--
S.N. 092-0013, W. Abut.		
(of web)	N. Side	S. Side
Beam 1	--	L6x4x3/4
Beam 2	L6x4x3/4	L6x4x3/4
Beam 3	L6x4x3/4	L6x4x3/4
Beam 4	L6x4x3/4	L6x4x3/4
Beam 5	L7x4x3/4	L6x4x3/4
Beam 6	L8x4x3/4	L6x4x3/4
Beam 7	L8x4x3/4	L6x4x3/4
Beam 8	L8x4x3/4	L6x4x3/4
Beam 9	L6x4x3/4	--

NEW DIAPHRAGM D1
 (10 diaphragms at West Abutment)

* Field drill all holes in angle to match holes in exist. beam web and exist. diaphragm

BILL OF MATERIAL
STR. NO. 092-0012

Item	Unit	Quantity
Elastomeric Bearing Assembly, Type I	Each	7
Elastomeric Bearing Assembly, Type II	Each	7
Anchor Bolts, 1"	Each	52
Furnishing and Erecting Structural Steel	Pound	3640
Jack and Remove Existing Bearings	Each	14
Structural Steel Removal	Pound	2400

BILL OF MATERIAL
STR. NO. 092-0013

Item	Unit	Quantity
Elastomeric Bearing Assembly, Type I	Each	9
Elastomeric Bearing Assembly, Type II	Each	9
Anchor Bolts, 1"	Each	68
Furnishing and Erecting Structural Steel	Pound	6250
Jack and Remove Existing Bearings	Each	18
Structural Steel Removal	Pound	4620

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-02-3-Str. Steel Details.dgn
 4/22/2022 11:51:11 PM


MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = baswanson	DESIGNED - LVM	REVISED -
	PLOT SCALE =	CHECKED - BAS	REVISED -
	PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
		CHECKED - LVM	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


STRUCTURAL STEEL DETAILS
STRUCTURE NO. 092-0012 & 092-0013

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	367
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

* Additional 1/2" thick angle on top of beam flange at Beams 9, 10, 14, and 15. Field drill 7/8" Ø holes thru angle for installation of bolts. Cost included with Furnishing and Erecting Structural Steel.




ELEVATION AT ABUT.




SECTION A-A


TYPE II ELASTOMERIC EXP. BRG.
(typ. at West Abutments)




TOP BEARING ASSEMBLY
(Looking North)




PLAN-PTFE SURFACE




BOTTOM BEARING ASSEMBLY




SECTION THRU PTFE



SECTION




PLAN - TOP & BOTTOM



ELEVATION


STEEL EXTENSION



SIDE RETAINER
(at W. Abut.)

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates. (Cost included with Elastomeric Bearing Assemblies, Type II)

Notes:
Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.
Steel extensions, shim plates, and connection bolts shall be paid for as Furnishing and Erecting Structural Steel.
Side retainers and stainless steel plates provided for new Elastomeric Bearing Assemblies shall be included in the cost of Elastomeric Bearing Assembly, of the corresponding type.
Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions.
Anchor bolts and side retainers at all supports shall be installed as each member is erected unless an equivalent temporary means of lateral restraint is used.
Provide two 1/8" adjusting shims for each bearing in addition to all other plates of the Bearing Assembly and placed as shown on the bearing details.
See sheet 23 of 34 for Bill of Material.
The Top and Bottom Bearing Plates shall be shop painted with the inorganic zinc rich primer per AASHTO M300 Type I. Cost included with Elastomeric Bearing Assembly, Type II.



BELOW 50°F. ABOVE 50°F.
D = 1/8" per each 100' of expansion for every 15° temp. change from the normal temp. of 50°F.

EXPANSION BEARING ORIENTATION

The above diagrams are for informational purposes only to show the amount of expected offset "D" for the current temperature in the field.

MODEL: Default
FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-02-4-Bearing Details (W Abut).dgn
4/22/2022 11:51:12 PM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


BEARING DETAILS - WEST ABUTMENTS
STRUCTURE NO. 092-0012 & 092-0013

SHEET NO. 24 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	368
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



ELEVATION AT ABUT.




SECTION A-A


TYPE I ELASTOMERIC EXP. BRG.
 (typ. at East Abutments)

Note:
 Shim plates shall not be placed under Bearing Assembly.


* Install bolts with nut and washer on top of beam flange, encase in concrete diaphragm
 ** Additional 1/2" angle on top of beam flange at Beam 9.




SECTION



PLAN - TOP R_L




ELEVATION



PLAN - BOTTOM R_L

STEEL EXTENSION


Notes:
 Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.
 Steel extensions, shim plates, and connection bolts shall be paid for as Furnishing and Erecting Structural Steel.
 Side retainers and stainless steel plates provided for new Elastomeric Bearing Assemblies shall be included in the cost of Elastomeric Bearing Assembly, of the corresponding type. Where placed against exist. pier bearing assemblies, side retainers shall be paid for as Furnishing and Erecting Structural Steel.
 Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions.
 Anchor bolts and side retainers at all supports shall be installed as each member is erected unless an equivalent temporary means of lateral restraint is used.
 Provide two 1/8" adjusting shims for each bearing in addition to all other plates of the Bearing Assembly and placed as shown on the bearing details.
 See sheet 23 of 34 for Bill of Material.
 The Top Bearing Plates shall be shop painted with the inorganic zinc rich primer per AASHTO M300 Type I. Cost included with Elastomeric Bearing Assembly, Type I.



BEARING ASSEMBLY

FILL PLATE THICKNESS

S.N. 092-0012, E. Abut.	
Beam 10	1 3/4"
Beam 11	--
Beam 12	1/4"
Beam 13	--
Beam 14	--
Beam 15	1/2"
Beam 16	--
S.N. 092-0013, E. Abut.	
Beam 1	3/8"
Beam 2	1/4"
Beam 3	--
Beam 4	--
Beam 5	3/8"
Beam 6	1/2"
Beam 7	5/8"
Beam 8	1/4"
Beam 9	1/2"



SIDE RETAINER

(at E. Abut., Pier 1, & Pier 3)
 Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-025-Bearing Details (E Abut).dgn
 4/22/2022 11:51:13 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
CHECKED - BAS	REVISOR -	
PLOT SCALE =	DRAWN - BAS	REVISED -
PLOT DATE = 4/22/2022	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION




BEARING DETAILS - EAST ABUTMENTS
 STRUCTURE NO. 092-0012 & 092-0013

SHEET NO. 25 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	369
CONTRACT NO. 70A29				


ILLINOIS FED. AID PROJECT

LEGEND


	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal
	Epoxy Crack Injection (Length)

Notes:
 Repair areas shown are estimated from soundings on October 13, 2020.
 Actual size and locations of completed repairs shall be shown on this sheet and documented in the provide tables under "As Built".
 See sheet 27 of 34 for Bill of Material.
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened, and incorporated into the new construction as noted.
 Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system at no cost to the Department. Cost included with Concrte Removal.

GIRDER REACTION TABLE		
		W. Abutment
$R_{\bar{P}}$	(k)	20.6
$R_{\bar{L}}$	(k)	33.3
R_{IM}	(k)	9.5
R_{Total}	(k)	63.4



PLAN




ABUTMENT ELEVATION
(Looking West)

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.	SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.
1	2' x 1'	2			
2	8' x 2.5'	20			
3	1' x 1'	1			
4	3' x 2'	6			
5	4' x 2'	6			
6	1' x 1'	1			
7	7' x 2'	8			
8	3' x 2'	6			
9	3' x 2'	6			
10	4' x 2'	8			
11	3' x 1'	3			
12	2' x 1'	2			
13	3' x 2'	6			
14	2' x .5'	1			
15	4' x .5'	2			
16	3' x 3'	9			
17	2' x 1'	2			
Totals		89			


See Rdwy. Plans for approach slab removal
 See sheet 6 of 34 for bridge deck removal



SECTION A-A


MODEL: Default
 FILE NAME: S:\237\2019\12\3719020\00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-026-W. Abut. Removal -0012.dgn
 4/22/2022 11:51:14 PM

	USER NAME = baswanson	DESIGNED - LVM	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	WEST ABUTMENT REMOVAL STRUCTURE NO. 092-0012	F.A.I. RTE. = 74	SECTION = (92-10,11,12)R	COUNTY = VERMILION	TOTAL SHEETS = 698	SHEET NO. = 370	
	PLOT SCALE =	DRAWN - BAS	REVISED -			CONTRACT NO. 70A29					
	PLOT DATE = 4/22/2022	CHECKED - LVM	REVISED -			SHEET NO. 26 OF 34 SHEETS					
							ILLINOIS FED. AID PROJECT				




PLAN

** Prior to Diamond Grinding, Top surface of hatch block shall match the elevation and profile grade of the top of Latex Concrete Overlay




ELEVATION


* Clean and incorporate existing reinforcement bars extending into new hatch block and parapet. Vertical bars into the parapet greater than 2' above the removal line may be removed.




SECTION B-B



SECTION C-C



BAR s2(E)



BAR v10(E)

**STR. NO. 092-0012
WEST ABUTMENT
BILL OF MATERIAL**

Bar	No.	Size	Length	Shape
h(E)	4	#5	17'-11"	—
h1(E)	4	#5	23'-8"	—
s2(E)	43	#4	3'-3"	Π
v10(E)	4	#6	4'-2"	⌋
v11(E)	4	#6	4'-0"	—
Concrete Removal			Cu. Yd.	3.3
Concrete Superstructure			Cu. Yd.	3.5
Reinforcement Bars, Epoxy Coated			Pound	320
Structural Repair of Concrete (Depth ≤ 5 in.)			Sq. Ft.	89
Temporary Shoring and Cribbing			Each	3
Epoxy Crack Injection			Foot	15

MODEL: Default
FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-027-W. Abut -0012.dgn
4/22/2022 11:51:15 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -




**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**WEST ABUTMENT
STRUCTURE NO. 092-0012**

SHEET NO. 27 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	371
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal
	Epoxy Crack Injection (Length)




Notes:
 Repair areas shown are estimated from soundings on October 13, 2020. Actual size and locations of completed repairs shall be shown on this sheet and documented in the provide tables under "As Built". See sheet 29 of 34 for Bill of Material.
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened, and incorporated into the new construction as noted. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system at no cost to the Department. Cost included with Concrete Removal.

GIRDER REACTION TABLE

	W. Abutment
R_{ϕ} (k)	20.6
R_{\perp} (k)	33.3
R_{IM} (k)	9.5
R_{Total} (k)	63.4

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC $\leq 5"$ Sq. Ft.	SRC $> 5"$ Sq. Ft.	SRC $\leq 5"$ Sq. Ft.	SRC $> 5"$ Sq. Ft.
1	2' x 1'	2			
2	7' x 1'	7			
3	6' x 3'	13			
4	3' x 3'	9			
5	4' x 4'	16			
6	1' x 1'	1			
7	6' x 2'	12			
8	2' x 2'	4			
9	6' x .5'	3			
10	8' x .5'	4			
11	4' x .5'	2			
12	4' x .5'	2			
13	3' x 2'	6			
Totals		81			



See sheet 26 of 34
For WB Abutment

See Rdwy. Plans for
approach slab removal

See sheet 11 of 34
for bridge deck
removal

SECTION A-A

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-028-W. Abut. Removal -0013.dgn




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**WEST ABUTMENT REMOVAL
STRUCTURE NO. 092-0013**


SHEET NO. 28 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	372
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




** Prior to Diamond Grinding, Top surface of hatch block shall match the elevation and profile grade of the top of Latex Concrete Overlay

PLAN




* Clean and incorporate existing reinforcement bars extending into new hatch block and parapet. Vertical bars into the parapet greater than 2' above the removal line may be removed.


ELEVATION




SECTION B-B



SECTION C-C



BAR s2(E)



BAR v10(E)

STR. NO. 092-0013
WEST ABUTMENT
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h(E)	4	#5	17'-11"	—
h2(E)	4	#5	37'-4"	—
s2(E)	57	#4	3'-3"	Π
v10(E)	4	#6	4'-2"	⌋
v11(E)	4	#6	4'-0"	—
Concrete Removal			Cu. Yd.	4.7
Concrete Superstructure			Cu. Yd.	5.0
Reinforcement Bars, Epoxy Coated			Pound	400
Structural Repair of Concrete (Depth ≤ 5 in.)			Sq. Ft.	81
Temporary Shoring and Cribbing			Each	5
Epoxy Crack Injection			Foot	22

MODEL: Default
FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-029-W. Abut -0013.dgn
4/22/2022 11:51:16 PM


MAURER-STUTZ
ENGINEERS SURVEYORS

USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

WEST ABUTMENT
STRUCTURE NO. 092-0013
SHEET NO. 29 OF 34 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	373
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



PLAN




VIEW A-A




SECTION C-C

LEGEND


	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal



VIEW B-B



ELEVATION
(Looking East)



SECTION D-D

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.	SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.
1	1' x 1'	1			
Totals		1			

Notes:
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened, and incorporated into the new construction as noted. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system at no cost to the Department. Cost included with Concrete Removal.
 See Sheet 2 of 34 for limits of Structure Excavation.
 See Sheet 31 of 34 for Bill of Material.

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-030-E_Abut Removal -0012.dgn
 4/22/2022 11:51:17 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

EAST ABUTMENT REMOVAL
STRUCTURE NO. 092-0012

SHEET NO. 30 OF 34 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	374
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT





PLAN


* Top of back wall shall be ±6" above the highest beam bearing seat.




ELEVATION
(Looking East)



SECTION C-C



VIEW A-A



VIEW B-B

**STR. NO. 092-0012
EAST ABUTMENT
BILL OF MATERIAL**

Bar	No.	Size	Length	Shape
h10(E)	4	#5	19'-7"	—
h11(E)	4	#5	23'-7"	—
h12(E)	4	#5	10'-2"	—
h13(E)	8	#5	9'-11"	—
h14(E)	4	#5	8'-0"	—
h15(E)	4	#5	8'-0"	—
h16(E)	4	#5	9'-7"	—
v1(E)	42	#4	2'-11"	—
Structure Excavation			Cu. Yd.	43
Concrete Removal			Cu. Yd.	17.0
Concrete Structures			Cu. Yd.	5.1
Reinforcement Bars, Epoxy Coated			Pound	490
Structural Repair of Concrete (Depth ≤ 5 in.)			Sq. Ft.	1

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-031-E_Abut -0012.dgn
4/22/2022 11:51:18 PM



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**EAST ABUTMENT
STRUCTURE NO. 092-0012**


SHEET NO. 31 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	375
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT



PLAN




VIEW A-A


SECTION C-C

LEGEND


	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Concrete Removal



ELEVATION
(Looking East)



VIEW B-B



SECTION D-D

Notes:
Existing reinforcement bars that will be reused in the new construction shall not be cut or damaged. Damaged bars shall be replaced with new reinforcement bars drilled and epoxy grouted into existing concrete at no cost to the Department.
See Sheet 2 of 34 for limits of Structure Excavation.
See Sheet 33 of 34 for Bill of Material.

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.	SRC ≤5" Sq. Ft.	SRC >5" Sq. Ft.
1	2' x 1'	2			
2	2' x 2"	4			
Totals		6			

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-032-E_Abut Removal -0013.dgn



USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**EAST ABUTMENT REMOVAL
STRUCTURE NO. 092-0013**

SHEET NO. 32 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	376
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT




PLAN

Bar h13(E)

Bar h14(E)


Bar h15(E)




SECTION C-C

STR. NO. 092-0013
EAST ABUTMENT
BILL OF MATERIAL


Bar	No.	Size	Length	Shape
h12(E)	4	#5	10'-2"	—
h13(E)	8	#5	9'-11"	—
h14(E)	4	#5	8'-0"	∟
h15(E)	4	#5	8'-0"	∟
h16(E)	4	#5	9'-7"	—
h20(E)	4	#5	18'-0"	—
h21(E)	4	#5	35'-9"	—
v1(E)	42	#4	2'-11"	—
Structure Excavation			Cu. Yd.	58
Concrete Removal			Cu. Yd.	19.0
Concrete Structures			Cu. Yd.	5.5
Reinforcement Bars, Epoxy Coated			Pound	540
Structural Repair of Concrete (Depth ≤ 5 in.)			Sq. Ft.	6



ELEVATION
(Looking East)



VIEW A-A



VIEW B-B

MODEL: Default
FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920012-033-E_Abut -0013.dgn
4/22/2022 11:51:19 PM




USER NAME = baswanson	DESIGNED - LVM	REVISED -
PLOT SCALE =	CHECKED - BAS	REVISED -
PLOT DATE = 4/22/2022	DRAWN - BAS	REVISED -
	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

EAST ABUTMENT
STRUCTURE NO. 092-0013

SHEET NO. 33 OF 34 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	377
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



STANDARD BAR SPLICER ASSEMBLY PLAN
 (All components shall be provided from one supplier)

Threaded splicer bar length = min. lap length + 1 1/2" + thread length


* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

STR. NO. 092-0012

Location	Bar size	No. assemblies required	Minimum lap length
Bridge Deck	#5	24	3'-6"
Diaphragm	#6	5	4'-0"
Diaphragm	#4	2	2'-5"
Approach Slab	#5	90	3'-4"
Approach Slab	#8	118	4'-9"
Approach Footing	#5	80	3'-2"
Abutments	#5	8	3'-7"

STR. NO. 092-0013

Location	Bar size	No. assemblies required	Minimum lap length
Bridge Deck	#5	24	3'-6"
Diaphragm	#6	5	4'-0"
Diaphragm	#4	2	2'-5"
Approach Slab	#5	90	3'-4"
Approach Slab	#8	118	4'-9"
Approach Footing	#5	80	3'-2"
Abutments	#5	8	3'-7"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.


"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required



HEADED BAR SPLICER ASSEMBLY PLAN

Location	Bar size	No. assemblies required	A	B
Diaphragms -0012	#6	4	3'-0"	3'-1"
Diaphragms -0013	#6	4	3'-2"	2'-10"

Notes:

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars.

Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.


See approved list of bar splicer assemblies and mechanical splicers for alternatives.

MODEL: Default
 FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920012-034-4-Bar Splicers.dgn
 4/22/2022 11:51:19 PM

Existing structures 092-0014 & 092-0015 were built in 1963 as F.A.I. 74, Section 92-12B at Station 1992+54. Each structure consisted of five continuous spans of two steel plate girders with steel floorbeams and reinforced concrete deck superstructure with double column piers and vaulted abutments. Overall length is 583'-9 $\frac{1}{4}$ " and clear roadway width is 30'-0". In 1990 the structures were reconstructed as F.A.I. 74, Section (92-12B)BR. The superstructures and decks were removed and replaced with 45" Web \bar{r} Girders. Structure 092-0014 has 7 girders spaced for a clear roadway width of 41'-3 $\frac{3}{4}$ " at the West Abutment and 49'-1" at the East Abutment. Traffic to be maintained using staged construction. Salvage - None.

PROPOSED SCOPE OF WORK - S.N. 092-0014

1. Rehabilitate bridge deck and concrete approach pavement with scarification and latex concrete overlay
2. Remove and replace HLMR bearing assemblies at west abutment
3. Remove and replace deck joint at west abutment with preformed joint strip seal
4. Remove and replace deck joint at east abutment with modular expansion joint
5. Repair concrete delaminations on abutment wall and back walls
6. Repair sections of concrete slope wall
7. Repair steel beam ends at west abutment
8. Paint beam ends




LOADING HS20-44


DESIGN SPECIFICATIONS
2002 AASHTO Standard Specifications for Highway Bridges, 17th Edition (LFD)

DESIGN STRESSES


FIELD UNITS
New Construction:
 $f'_c = 3,500$ psi
 $f'_c = 4,000$ psi (deck)
 $f_y = 60,000$ psi (Reinforcement)
 $f_y = 50,000$ psi (Str. Steel)
Exist. Structure:
 $f'_c = 3,500$ psi
 $f_y = 60,000$ psi (deck reinf.)
 $f_y = 40,000$ psi (orig. substr. reinf.)
 $f_y = 36,000$ psi (structural steel)
 $f_y = 50,000$ psi (plate girder flanges)



PLAN
(Stations shown per original bridge plans)



LOCATION SKETCH



Bryan Swanson
 Date Signed: 4-22-22
 Exp. Date: 11/30/2022

GENERAL PLAN AND ELEVATION
I-74 OVER VERMILION RIVER
F.A.I. 74 - SEC. (92-10,11,12)R
VERMILION COUNTY
STATION 1992+54.00
STRUCTURE NO. 092-0014

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920014-001-GPE.dgn



USER NAME =	jdkoch	DESIGNED -	BAS	REVISED -	
CHECKED -	JDK	REVISIONS -			
PLOT SCALE =		DRAWN -	JDK	REVISED -	
PLOT DATE =	4/21/2022	CHECKED -	LVM	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET NO. 1 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	379
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT

TOTAL BILL OF MATERIAL

ITEM	UNIT	TOTAL
Stone Riprap, Class A4	Sq. Yd.	73
Filter Fabric	Sq. Yd.	73
Concrete Removal	Cu. Yd.	32.5
Concrete Superstructure	Cu. Yd.	36.4
* Protective Coat	Sq. Yd.	3534
Reinforcement Bars, Epoxy Coated	Pound	6310
Bar Splicers	Each	48
Mechanical Splicers	Each	253
Preformed Joint Strip Seal	Foot	50
Modular Expansion Joint, 6"	Foot	57
Anchor Bolts, 1"	Each	28
Slope Wall Crack Sealing	Foot	81
Inlet Boxes to be Adjusted (Special)	Each	1
Bridge Deck Grooving (Longitudinal)	Sq. Yd.	2482
High Load Multi-Rotational Bearings, Guided Expansion, 100K	Each	7
Jack and Remove Existing Bearings	Each	7
Structural Steel Repair	Pound	2200
Bridge Deck Latex Concrete Overlay 2 3/4"	Sq. Yd.	3443
Bridge Deck Scarification 3/4"	Sq. Yd.	3443
Cleaning and Painting Steel Bridge No. 5	L. Sum	1
Containment and Disposal of Non-Lead Paint Cleaning Residues No. 5	L. Sum	1
Structural Repair of Concrete (Depth Equal to or Less Than 5 Inches)	Sq. Ft.	96
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	7
Drainage Scuppers to be Adjusted	Each	6
Diamond Grinding (Bridge Section)	Sq. Yd.	3200
Polymer Concrete	Cu. Ft.	5
Relocating Name Plates	Each	2
Slope Wall Repair	Sq. Yd.	18
Slope Wall Slurry Pumping	Cu. Yd.	7

* On new concrete superstructure and latex concrete overlay.

GENERAL NOTES

All new fasteners shall be 3/4" Ø high-strength steel bolts, unless noted otherwise.

No field welding is permitted except as specified in the contract documents.

Reinforcement bars designated (E) shall be epoxy coated.

Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.

As directed by the Engineer, existing construction accessories welded to the top flange of beams and girders shall be removed. The weld areas shall be ground flush and inspected for cracks using magnetic particle testing (MT) or dye penetrant testing (PT) by qualified personnel approved by the Engineer. Any cracks that can not be removed by grinding 1/4 in. deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. The cost of removing welded accessories, grinding and inspecting weld areas, and grinding cracks will be paid for according to Article 109.04 of the Standard Specifications.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work; however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Existing Name Plates shall be removed, cleaned and incorporated into the new construction. Cost included with Relocating Name Plates.

Synthetic Fibers shall be included in the bridge deck concrete overlay specified. See Special Provisions.

Existing structure plans are available from the District upon request.

Cleaning and painting of the existing structural steel shall be as specified in the special provision for "Cleaning and Painting Existing Steel Structures". After removal of deck ends, but prior to new modular joint and bearing installation or structural steel repair, all beams, diaphragms, and other existing structural steel within 5 ft of the beam ends shall be cleaned per Near White Blast Cleaning (SSPC-SPI0).

The designated areas cleaned per Near White Blast Cleaning (SSPC-SPI0) shall be painted according to the requirements of Paint System 1 (OZ/E/U). The color of the final finish coat for all steel surfaces shall be Gray, Munsell No. 5B 7/1.

Existing structural steel that will be in contact with new structural steel shall be cleaned and painted prior to erection as required by the special provision "Cleaning and Painting Contact Surface Areas of Existing Steel Structures".

Containment of cleaning residue is required to control nuisance dust. See special provisions.

SSPC-QP1 Painting Contractor Certifications will be required for this contract.


All new structural steel shall be hot dip galvanized unless noted otherwise. See special provision for "Hot Dip Galvanizing for Structural Steel".

Expansion joints shall be fabricated and installed according to the manufacturer's recommendations and as approved by the Engineer.


Expansion joints shall be fabricated to conform to the existing cross slopes of the bridge.

Modular expansion joints shall be assembled in their final relative position with the ends in place for shop inspection and acceptance.

Joint openings shall be adjusted according to Article 503.10(c) of the Standard Specifications when the deck is poured at an ambient temperature other than 50°F.



STAGE I CONSTRUCTION
(Looking East)



STAGE II CONSTRUCTION
(Looking East)

INDEX OF SHEETS

1. General Plan and Elevation
2. General Data
3. Slope Wall Repairs
- 4-5. Deck Slab Repair Plan
- 6-7. Superstructure Details
- 8-9. West Abutment Joint Replacement
- 10-11. East Abutment Joint Replacement
12. Preformed Joint Strip Seal
13. Drainage Scupper Adjustment Details
14. Inlet Box to be Adjusted
15. Structural Steel Framing Plan
16. HLMR Bearing Replacement Details
17. West Abutment Repairs
18. East Abutment Repairs
19. Bar Splicer Assemblies

MODEL: Default
FILE NAME: S:\237\2019\12\31\19020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-002-Gen Data.dgn
4/21/2022 6:01:30 PM

MAURER-STUTZ ENGINEERS SURVEYORS	USER NAME = jdkoch	DESIGNED - BAS	REVISED -
	PLOT SCALE =	CHECKED - JDK	REVISED -
	PLOT DATE = 4/21/2022	DRAWN - JDK	REVISED -
		CHECKED - LVM	REVISED -



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

GENERAL DATA
STRUCTURE NO. 092-0014


SHEET NO. 2 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	380
CONTRACT NO. 70A29				
		ILLINOIS	FED. AID PROJECT	

MODEL: Default
 FILE NAME: S:\237\2019\23719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920014-003-Slope Wall Plan.dgn
 4/21/2022 6:01:37 PM



SLOPE WALL REPAIR PLAN



SECTION A-A

Notes:
 Slope wall shall be reinforced with welded wire fabric, 6 in. x 6 in. - W4.0 x W4.0, weighing 58 lbs. per 100 sq. ft.
 The quantities provided for Crack Wall Sealing are estimated. Open joints shall be sealed at the direction of the Engineer, and the locations documented on the As-Built drawings.
 Layout and limits of the slope wall removal and repairs may be varied to suit conditions in the field as directed by the Engineer.

LEGEND

	Remove and Replace Slope Wall (paid for as Slope Wall Repair)
	Slope Wall Slurry Pumping
	Slope Wall Crack Sealing (Length)

SLOPE WALL BILL OF MATERIAL

Item	Unit	Quantity
Slope Wall Repair	Sq. Yd.	18
Slope Wall Slurry Pumping	Cu. Yd.	7
Slope Wall Crack Sealing	Foot	81
Stone Riprap, Class A4	Sq. Yd.	73
Filter Fabric	Sq. Yd.	73




USER NAME =	jdkoch	DESIGNED -	BAS	REVISED -	
PLOT SCALE =		CHECKED -	JDK	REVISED -	
PLOT DATE =	4/21/2022	DRAWN -	JDK	REVISED -	
		CHECKED -	LVM	REVISED -	

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**SLOPE WALL REPAIRS
 STRUCTURE NO. 092-0014 & 092-0015**

SHEET NO. 3 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	381
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




LEGEND

	Deck Slab Repair (Partial Depth) (For Information Only)
	Deck Slab Repair (Full Depth)
	Bridge Deck Scarification, 3/4" and Bridge Deck Latex Concrete Overlay, 2 3/4"
	Concrete Removal and Concrete Superstructure, see sheets 8 thru 11 of 19

PLAN - DECK SLAB REPAIRS
(West End)

Notes:
See sheet 5 of 19 for callouts, Deck Repair Table, Section A-A, Bill of Material, and additional notes.



PLAN - DECK SLAB REPAIRS
(Spans 3 & 4)

(Sheet 1 of 2)

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-004-Deck Repair Plan.dgn



USER NAME =	jdkoch	DESIGNED -	BAS	REVISED -	
		CHECKED -	JDK	REVISED -	
PLOT SCALE =		DRAWN -	JDK	REVISED -	
PLOT DATE =	4/21/2022	CHECKED -	LVM	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


DECK SLAB REPAIR PLAN
STRUCTURE NO. 092-0014

SHEET NO. 4 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	382
CONTRACT NO. 70A29				


ILLINOIS FED. AID PROJECT

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD_Sheets\70A29-0920014-005-Deck Repair Plan.dgn



PLAN - DECK SLAB REPAIRS
(East End)

- Callouts:
- ① - Adjust elevation of frame and grate on inlet box to match overlay. See sheet 14 of 19 for details.
 - ② - Remove and reinstall drainage scupper and install adjusting ring to raise the grate elevation to match the overlay. See sheet 13 of 19 for details. Cost of removal and installing the existing scupper within the deck repair shall be included with Drainage Scuppers to be Adjusted.



SECTION A-A

DECK SLAB REPAIR TABLE

Label	Size	Plan Qty.			As Built	
		Deck Slab Repair (Part. Depth)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)	Deck Slab Repair (FD Type I)	Deck Slab Repair (FD Type II)
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
A	2' x 4' x 6 Loc.			48		
B	3' x 3'			9		
	W. Appr., Stage II	22				
	Span 2, Stage I	14				
	Span 2, Stage II	32				
	Span 3, Stage I	24				
	Span 3, Stage II	4				
	Span 4, Stage I	4				
	Span 4, Stage II	4				
	Span 5, Stage I	14				
	Span 5, Stage II	34				
	E. Appr., Stage I	7				
	E. Appr., Stage II	14				
Totals		173		57		

LEGEND


	Deck Slab Repair (Partial Depth) (For Information Only)
	Deck Slab Repair (Full Depth)
	Bridge Deck Scarification, 3/4" and Bridge Deck Latex Concrete Overlay, 2 3/4"
	Concrete Removal and Concrete Superstructure, see sheets 8 thru 11 of 19

Notes:
 See sheet 6 of 19 for cross section thru bridge deck.
 Deck survey performed on December 14, 2020. Locations and sizes shown in the plan view are approximate.
 Deck Slab Repair (Partial Depth) is an estimated quantity per the deck survey. This area shall not be paid for separately, but shall be addressed as stated in the Special Provision for Bridge Deck Latex Concrete Overlay.
 Actual size and locations of full-depth patches shall be shown on this sheet and documented in the Deck Slab Repair Table under "As Built".

**DECK SLAB
BILL OF MATERIAL**

ITEM	UNIT	TOTAL
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	7
Bridge Deck Scarification 3/4"	Sq. Yd.	3443
Bridge Deck Latex Concrete Overlay, 2 3/4 Inches	Sq. Yd.	3443



(Sheet 2 of 2)




* Cross slope varies from normal crown at Sta. 1993+42.56 to 2.0% superelevation at Sta. 1994+84.56.
 ** Prior to 1/4\"/>

CROSS SECTION - BRIDGE DECK
 (Looking East)


Notes:
 Actual bridge cross slopes and superelevation transition locations shall be measured and documented in the field prior to scarification.
 Stations shown for the superelevation transition are according to the original bridge plans. Stations per the existing alignment may be different.



MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-006-Deck Section.dgn
 4/21/2022 6:01:56 PM



ELEVATION - NORTH PARAPET
(West End, Looking North)




ELEVATION - NORTH PARAPET
(East End, Looking North)

LEGEND

	Structural Repair of Concrete (Depth ≤ 5")
	Removal and replacement of parapet, See sheets 8 thru 11 of 19

Callouts:
 (A) - Void at base of parapet, remove loose or damaged concrete and fill during placement of Latex Concrete Overlay, cost of concrete removal included with Bridge Deck Scarification.

Notes:
 See sheets 8 thru 11 of 19 for sections thru bridge deck and approach parapets.
 Parapets were sounded on December 14, 2020. Locations and sizes of the concrete repairs shown are approximate. Actual sizes of parapet repairs should be documented on the As Built drawings.



ELEVATION - SOUTH PARAPET
(East End, Looking South)

**PARAPETS
BILL OF MATERIAL**

ITEM	UNIT	TOTAL
Structural Repair of Concrete (Depth ≤ 5 Inches)	Sq. Ft.	83
Relocating Name Plates	Each	2



ELEVATION - SOUTH PARAPET
(West End, Looking South)

MODEL: Default
 FILE NAME: S:\237\2019\12\31\19\20\20\00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-007-Parapets.dgn
 4/21/2022 6:02:01 PM



USER NAME =	jdkoch	DESIGNED -	BAS	REVISED -	
		CHECKED -	JDK	REVISED -	
PLOT SCALE =		DRAWN -	JDK	REVISED -	
PLOT DATE =	4/21/2022	CHECKED -	LVM	REVISED -	


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**SUPERSTRUCTURE DETAILS
STRUCTURE NO. 092-0014**

SHEET NO. 7 OF 19 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	385
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-008-West Abut. Removal.dgn




CONCRETE REMOVAL AT WEST ABUTMENT


* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.



SECTION A-A
 (Near CL Roadway)
 (Dims. at Rt. L's to end of deck)



SECTION THRU SOUTH APPROACH PARAPET




SECTION THRU NORTH APPROACH PARAPET

Notes:
 Hatched areas indicate Concrete Removal.
 For Bridge Deck Parapet Dimensions and Details and Bill of Material, see sheet 9 of 19.

USER NAME = jdkoch	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - JDK	REVISED -
PLOT DATE = 4/21/2022	DRAWN - JDK	REVISED -
	CHECKED - LVM	REVISED -


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	386
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 D5 I-74 Danville)\CADD\CADD Sheets\70A29-0920014-009-West Abut.dgn




Note A:
 4-#5 d(E) bars at 11" cts. (i.f.)
 4-#5 d1(E) bars at 11" cts. (i.f.)
 4-#4 d2(E) bars at 11" cts. (o.f.)
 4-#4 d3(E) bars at 11" cts. (o.f.)
 (See Section thru Bridge Deck Parapet)

CONCRETE REPLACEMENT AT WEST ABUTMENT




SECTION THRU BRIDGE DECK PARAPET



SECTION B-B
 (Near Roadway)
 (Dims. at RT L's to end of deck)

Notes:
 Dimensions of joint opening are based on a Rolled Rail Strip Seal Joint. If the Contractor elects to use the Welded Rail Strip Seal Joint, deck dimensions may require adjustments to satisfy the details on sheet 12 of 19.
 See sheet 19 of 19 for details of Bar Splicers.
 See sheet 6 of 19 for bar details.

* Prior to 1/4" Diamond Grinding
 ** Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.



SECTION THRU SOUTH APPROACH PARAPET

SECTION THRU NORTH APPROACH PARAPET

WEST ABUTMENT JOINT BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a(E)	10	#5	23'-7"	—
a1(E)	10	#5	25'-0"	—
a2(E)	6	#6	6'-0"	—
d(E)	8	#5	3'-0"	┌┐
d1(E)	8	#5	2'-7"	┌┐
d2(E)	8	#4	3'-0"	┌┐
d3(E)	8	#4	3'-10"	┌┐
h(E)	4	#6	25'-2"	┌┐
h1(E)	4	#6	26'-8"	┌┐
Concrete Removal			Cu. Yd.	7.2
Concrete Superstructure			Cu. Yd.	8.2
Reinforcement Bars, Epoxy Coated			Pound	960



USER NAME =	jdkoch	DESIGNED -	BAS	REVISED -	
CHECKED -	JDK	REVISIONS -		REVISED -	
PLOT SCALE =		DRAWN -	JDK	REVISED -	
PLOT DATE =	4/21/2022	CHECKED -	LVM	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


WEST ABUTMENT JOINT REPLACEMENT DETAILS
STRUCTURE NO. 092-0014

SHEET NO. 9 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	387
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT


MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-010-East Abut. Removal.dgn




Notes:
 Hatched areas indicate Concrete Removal unless otherwise noted.
 For Bridge Deck Parapet Dimensions and Details and Bill of Material, see sheet 11 of 19.

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.


** Prior to 1/4" Diamond Grinding.



SECTION C-C
 (Near Roadway)
 (Dims. at Rt. L's to end of deck)



SECTION E-E
 Hatched area indicates Concrete Removal & Replacement.



SECTION THRU SOUTH APPROACH PARAPET
 Hatched area indicates Concrete Removal & Replacement.

SECTION THRU NORTH APPROACH PARAPET
 Hatched area indicates Concrete Removal & Replacement.

CONCRETE REMOVAL AT EAST ABUTMENT



USER NAME =	jdkoch	DESIGNED -	BAS	REVISED -	
CHECKED -	JDK	REVISED -		REVISED -	
PLOT SCALE =		DRAWN -	JDK	REVISED -	
PLOT DATE =	4/21/2022	CHECKED -	LVM	REVISED -	


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

EAST ABUTMENT JOINT REMOVAL DETAILS
 STRUCTURE NO. 092-0014

SHEET NO. 10 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	388
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 D5 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-011-East Abut.dgn



Note C:
 6-#5 d7(E) bars at 11" cts. (i.f.)
 6-#5 d8(E) bars at 11" cts. (i.f.)
 6-#4 d9(E) bars at 11" cts. (o.f.)
 (See Section thru Bridge Deck Parapet)

CONCRETE REPLACEMENT AT EAST ABUTMENT

Note A:
 Lower existing W12x40 diaphragm if required.
 Cost included with Modular Expansion Joint.

Note B:
 9-3/4" Ø Shear Studs at 6" cts. on exterior face of Beam 7.
 11-3/4" Ø Shear Studs at 6" cts. on exterior face of Beam 1.
 Cost included with Concrete Superstructure.

* Support Box spacing per manufacturer. Support Boxes to be rigidly attached to diaphragms, beams and abutment wall by adjustable brackets, stools, or shims as determined by manufacturer. Support Boxes to be spaced so they do not interfere with existing top flange of girders.


** Cut existing reinforcement 6" from removal line to facilitate installation of Mechanical Splicers.

*** Epoxy grout rods in 9" min. holes according to Article 584 of the Standard Specifications.


**** Prior to 1/4" Diamond Grinding.

Note:
 For bar details, see sheet 6 of 19.
 For Approach Parapet Dimensions & Details and Section E-E, see sheet 10 of 19.
 See sheet 19 of 19 for details of Bar Splicers and Mechanical Splicers.

**** 2 3/4" Latex Concrete Overlay




SECTION D-D
 (Modular Joint not shown for clarity.)



SECTION D-D
 (Reinforcement not shown for clarity.)

EAST ABUTMENT JOINT
BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a2(E)	10	#6	6'-0"	
a3(E)	18	#5	24'-4"	
a4(E)	18	#5	34'-10"	
a10(E)	16	#7	25'-3"	
a11(E)	16	#7	35'-9"	
b(E)	48	#5	4'-9"	
b1(E)	84	#7	3'-11"	
b2(E)	10	#5	5'-1"	
d4(E)	10	#5	4'-10"	
d5(E)	10	#4	6'-2"	
d6(E)	16	#4	2'-3"	
d7(E)	12	#5	4'-5"	
d8(E)	12	#5	4'-4"	
d9(E)	12	#4	4'-8"	
x(E)	55	#5	5'-3"	
x1(E)	66	#6	4'-6"	
z(E)	18	#6	6'-10"	
Concrete Removal			Cu. Yd.	25.3
Concrete Superstructure			Cu. Yd.	28.2
Reinforcement Bars, Epoxy Coated			Pound	5350
Modular Expansion Joint, 6"			Foot	57



SECTION THRU BRIDGE DECK PARAPET




USER NAME = jdkoch	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - JDK	REVISED -
PLOT DATE = 4/21/2022	DRAWN - JDK	REVISED -
	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


EAST ABUTMENT JOINT REPLACEMENT DETAILS
STRUCTURE NO. 092-0014

SHEET NO. 11 OF 19 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	389
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



FOR SKEWS $\leq 30^\circ$
PLAN AT PARAPET




SECTION AT PARAPET



DETAIL A

** Prior to Diamond Grinding




SHOWING ROLLED RAIL JOINT

* $\frac{5}{8}$ " \varnothing x 6" studs @ 6" cts. (alternate angled/bent studs with horizontal studs)




$\frac{3}{8}$ " \varnothing threaded rods in $\frac{7}{16}$ " \varnothing holes at ± 4 -0" cts. for holding the proper joint opening based on the temperature during the deck pour. Place to miss studs. All rods shall be burned or sawed off flush with the plates after concrete is set.

SECTION A-A

* Granular or solid Flux filled headed studs conforming to Article 1006.32 of the Std. Specs., automatically end welded.



SHOWING WELDED RAIL JOINT



LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue. Rolled rail shown, welded rail similar.

LOCKING EDGE RAILS

*** Back gouge not required if complete joint penetration is verified by mock-up.

BILL OF MATERIAL

Item	Unit	Total
Preformed Joint Strip Seal	Foot	50

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-012-PISS.dgn
 4/21/2022 6:02:30 PM

MAURER-STUTZ
 ENGINEERS SURVEYORS

USER NAME = jdkoch	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - JDK	REVISED -
PLOT DATE = 4/21/2022	DRAWN - JDK	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREFORMED JOINT STRIP SEAL
STRUCTURE NO. 092-0014


SHEET NO. 12 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	390
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				


Notes:
 All structural steel shall be AASHTO M270 Grade 36. The adjusting scupper ring and $\frac{3}{4}$ " \varnothing pipe sleeve spacers shall be galvanized.
 Bolts shall be $\frac{1}{2}$ " \varnothing AASHTO M164 Type 1, mechanically galvanized.
 Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished based at the unit price bid for the work.
 Shop plans for proposed adjusting scupper ring shall be submitted for approval prior to fabrication.
 Contractor shall ensure that no damage is done to existing grates to be reused.
 Cost of all labor and materials necessary to remove existing grates, clean existing scuppers, install adjusting scupper rings and reinstalling grates is included in the cost per unit Each for Drainage Scuppers to be Adjusted.




PLAN VIEW



SECTION A-A




SECTION C-C



ADJUSTING SCUPPER RING

BILL OF MATERIAL

Item	Unit	Total
Drainage Scuppers To Be Adjusted	Each	6



SECTION B-B

MODEL: Default
 FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920014-013-Drainage Scupper Adj.dgn
 4/21/2022 6:02:36 PM



USER NAME = jdkoch	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - JDK	REVISED -
PLOT DATE = 4/21/2022	DRAWN - JDK	REVISED -
	CHECKED - LVM	REVISED -


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

DRAINAGE SCUPPER ADJUSTMENT DETAILS
 STRUCTURE NO. 092-0014

SHEET NO. 13 OF 19 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	391
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT



DETAIL "A" - EXISTING


Concrete Removal




DETAIL "A" - PROPOSED

Class S.I. Concrete


* Prior to Diamond Grinding



**PLAN - PROPOSED
(GRATING OMITTED FOR CLARITY)**



**EXISTING TYPE D INLET BOX PROFILE
BRIDGE APPROACH SHOULDER PAVEMENT AND DRAIN**
(Existing Approach Shoulder Pavement Std. 2324-6)



**PROPOSED PROFILE
BRIDGE APPROACH SHOULDER PAVEMENT AND DRAIN**

Notes:
Expansion bolts shall extend a minimum of 4" into the proposed concrete.

All work and materials shall be in accordance with applicable portions of Section 602.

This work will be paid for at the Contract unit price each for "Inlet Boxes to be Adjusted (Special)" which shall include all labor, equipment and material necessary to complete the work.

ESTIMATED QUANTITIES
(for information only)

ITEM	UNIT	TOTAL
Concrete Removal	Cu Yd	0.13
Reinforcement Bars (Epoxy)	Pound	11.4
Class S.I. Concrete	Cu Yd	0.16
Expansion Bolts, 3/4"	Each	18

BILL OF MATERIALS

ITEM	UNIT	TOTAL
Inlet Boxes to be Adjusted (Special)	Each	1

MODEL: Default
FILE NAME: S:\237\2019\12\3719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-014-Inlet_Box_Adj.dgn
4/21/2022 6:02:42 PM

MAURER-STUTZ
ENGINEERS SURVEYORS


USER NAME = jdkoch	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - JDK	REVISED -
PLOT DATE = 4/21/2022	DRAWN - JDK	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**INLET BOX TO BE ADJUSTED
STRUCTURE NO. 092-0014**

SHEET NO. 14 OF 19 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	392
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




PARTIAL FRAMING PLAN - S.N. 092-0014

Callouts:


- (A) - Jack and remove existing bearing assembly, replace with new bearing assemblies as shown on sheet 16 of 19.
- (B) - Beam End Repair, see detail on this sheet



BEAM END REPAIR - ELEVATION



SECTION A-A



BEAM END REPAIR - PLAN

BOLT HOLE LEGEND

- Drill 1 1/4" Ø hole in Bent R using template to match ctr. of hole in bott. flange, 1" Ø threaded stud from Bearing Assembly
- 1 3/16" Ø hole in Bent R or End R and field drill 1 3/16" Ø hole in beam web, flange, or stiffener R to match, 3/4" Ø H.S. bolt

GIRDER REACTION TABLE (EXIST.)			
S.N. 092-00014 (WB)			
		W. Abut.	E. Abut.
R ₀	(k)	42.3	42.3
R ₁	(k)	44.8	44.8
R _{IM}	(k)	10.0	10.0
R _{Total}	(k)	97.1	97.1

Notes:

Cost of furnishing and erecting steel for beam end repairs shall be included with Structural Steel Repair. See Special Provision.
 All structural steel for the beam end repairs shall conform to the requirements of AASHTO M 270, Grade 50.
 Structural steel plates for the beam end repairs shall be hot dip galvanized. See Special Provisions for Hot Dip Galvanizing for Structural Steel.
 Removal of existing bearing assemblies shall be paid for as Jack and Remove Existing Bearings.
 Minimum jack capacity shall be 55 tons.
 The existing structural steel beams and diaphragms at each abutment shall be cleaned and painted prior to completing beam repairs or installing new modular expansion joint and bearing assemblies. See general notes on sheet 2 of 19.
 Abandoned holes in existing diaphragm at east abutment after removal of existing finger plate expansion joint shall be filled with galvanized H.S. bolts. Cost included with Concrete Removal.
 See sheet 16 of 19 for Bill of Material.

MODEL: Default
FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920014-015-Framing Plan.dgn




USER NAME = baswanson	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - JDK	REVISED -
PLOT DATE = 5/11/2022	DRAWN - JDK	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**STRUCTURAL STEEL FRAMING PLAN
SHEET NO. 092-0014**

SHEET NO. 15 OF 19 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	393
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



ELEVATION AT ABUTMENT
(at West Abutment only)




SECTION A-A



EXISTING BEARING REMOVAL DETAIL

HLMR EXPANSION BEARING ASSEMBLY




BELOW 50°F.
D=1/8" per each 100' of expansion for every 15° temp. change from the normal temp. of 50°F.


ABOVE 50°F.

EXPANSION BEARING ORIENTATION

The above diagrams are for informational purposes only to show the amount of expected offset "D" for the current temperature in the field.



SOLE \varnothing AND UPPER BEARING \varnothing



BOTTOM BEARING \varnothing AND DISK PLAN

BILL OF MATERIAL

Item	Unit	Total
Jack and Remove Existing Bearings	Each	7
High Load Multi-Rotational Bearings, Guided Expansion, 100k	Each	7
Anchor Bolts	Each	28
Structural Steel Repair	Pound	2200

Notes:

Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.

Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions.

Provide two 1/8" adjusting shims for each bearing in addition to all other plates of the Bearing Assembly and placed as shown on the bearing details.

The structural steel plates of the Bearing Assembly shall conform to the requirements of AASHTO M 270, Grade 50.

All new anchor bolts, nuts, and washers shall be hot dip galvanized. Steel plates of the Bearing Assembly shall be hot dip galvanized except where prohibited by the manufacturer. See Special Provisions for Hot Dip Galvanizing for Structural Steel.

Bearings shall be designed for a vertical load of 100 kips, a horizontal load of 5.2 kips, and a total required movement of 3". Reactions are given for service loads. See sheet 15 of 19 for bearing reactions.

MODEL: Default
FILE NAME: S:\237\2019\12\3719020\00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-0-16-Bearing Replacement.dgn




USER NAME = jdkoch	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - JDK	REVISED -
PLOT DATE = 4/21/2022	DRAWN - JDK	REVISED -
	CHECKED - LVM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**HLMR BEARING REPLACEMENT DETAILS
STRUCTURE NO. 092-0014**



SHEET NO. 16 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	394
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				



ELEVATION - WEST ABUTMENT
(Looking West)

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Structural Repair of Concrete (Depth Greater Than 5 inches)

Notes:
 Repair areas shown are estimated from soundings on October 13, 2020.
 Actual size and locations of completed repairs shall be shown on this sheet and documented in the provide tables under "As Built".

STRUCTURAL REPAIR OF CONCRETE TABLE

Label	Size	Plan Qty.		As Built	
		SRC ≤5"	SRC >5"	SRC ≤5"	SRC >5"
		Sq. Ft.	Sq. Ft.	Sq. Ft.	Sq. Ft.
A	1' x 1'	1			
B	1' x 1'	1			
C	1' x 1'	1			
D	2' x 1'	2			
E	1' x 1'	1			
F	1' x 1'	1			
G	2' x 2'	4			
<i>Totals</i>		11			

BILL OF MATERIAL

Item	Unit	Quantity
Structural Repair of Concrete (Depth ≤ 5 in.)	Sq. Ft.	11

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS I-74 Danville)\CADD\CADD Sheets\70A29-0920014-017-W. Abut. Repairs.dgn
 4/21/2022 6:02:59 PM




USER NAME = jdkoch	DESIGNED - BAS	REVISED -
PLOT SCALE =	CHECKED - JDK	REVISED -
PLOT DATE = 4/21/2022	DRAWN - JDK	REVISED -
	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

WEST ABUTMENT REPAIRS
STRUCTURE NO. 092-0014

SHEET NO. 17 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	395
CONTRACT NO. 70A29				
ILLINOIS FED. AID PROJECT				




STANDARD BAR SPLICER ASSEMBLY PLAN
 (All components shall be provided from one supplier)

Threaded splicer bar length = min. lap length + 1 1/2" + thread length


* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum lap length
West Abutment	#5	10	3'-6"
West Abutment	#6	4	3'-7"
East Abutment	#5	18	3'-6"
East Abutment	#7	16	4'-8"



INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.
 "B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.
 (E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required
East Abutment	#5	103
East Abutment	#6	66
East Abutment	#7	84

Notes:
 Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.
 All reinforcement shall be lapped and tied to the splicer bars.
 Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.
 See approved list of bar splicer assemblies and mechanical splicers for alternatives.

MODEL: Default
 FILE NAME: S:\237\2019\123719020.00 (193-026 DS 1-74 Danville)\CADD\CADD Sheets\70A29-0920014-019-Bar Splicers.dgn

BSD-1

1-1-2020



USER NAME = jdkoch	DESIGNED - BAS	REVISED -
	CHECKED - JDK	REVISED -
PLOT SCALE =	DRAWN - JDK	REVISED -
PLOT DATE = 4/21/2022	CHECKED - LVM	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS
 STRUCTURE NO. 092-0014

SHEET NO. 19 OF 19 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	397
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT

Existing Structure S.N. 092-0038 built in 1963, reconstructed in 1995. 6-Span Steel Beam R.C. Deck.
Total width out to out = 92'-6". Total length bk. to bk. abut. = 290'-8". R.C. Piers and Abuts.

No Salvage.

Traffic to be maintained during Stage Construction.



ELEVATION

INDEX OF SHEETS

1. General Plan & Elevation
2. General Data
- 3-4. Existing & Proposed Typical Cross Sections
- 5-6. Stage Construction Details - Bridge
7. Temporary Concrete Barrier for Construction
8. Deck Plan - Overlay
- 9-10. Abutment Joint Replacement Details
11. Preformed Joint Strip Seal Details
12. Approach Slab Repair Details
13. Framing Plan
14. Diaphragm Replacement & Beam End Repair
15. Parapet Repairs
16. Bearing Details - Abutments
17. Abutment and Slope Wall Repair Plan
- 18-22. Pier Repair Plans
23. Pier Repair Details
24. Bar Splicer Assembly and Mechanical Splicer Details
25. Drainage Scupper Adjustment Ring Detail
26. Inlet Box to be Adjusted

DESIGN STRESSES (EXIST.)

ORIGINAL STRUCTURES
 $f'_c = 1,400$ psi (allow.)
 $f_s = 20,000$ psi (Reinf.)
 $f_s = 20,000$ psi (Struct.)

1995 RECONSTRUCTION
 $f'_c = 3,500$ psi
 $f_y = 60,000$ psi (Reinf.)
 $f_y = 36,000$ psi (Struct. M270, GR. 36)

DESIGN STRESSES (PROP.)


FIELD UNITS
 $f'_c = 4,000$ psi
 $f_y = 60,000$ psi (Reinforcement)
 $f_y = 36,000$ psi (M270 Grade 36)

DESIGN SPECIFICATIONS

2002 AASHTO Standard Specifications, for Highway Bridge Design, 17th Edition

LOADING

HS20-44



LOCATION SKETCH

GENERAL PLAN AND ELEVATION

U.S. RTE. 150/IL. RTE. 1


OVER F.A.I. RT. 74

F.A.I. 74 SEC. (92-10,11,12)R

STA. 3054+61.03


VERMILION COUNTY

SN. 092-0038



PLAN

(Stations shown per original bridge plans)



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET 1 OF 26 SHEETS

MODEL: 2D Sheet H
FILE NAME: I:\jobs\2019\1901_PTB_193-026-1-74_Reconstruction\Drawings\CAD_Sheets\Rte_150_Bridge_092-0038\0920038-D570A29-001-GPE.dgn

4/25/2022 9:11:46 AM

Prairie Engineers, P.C.
 22484 Grossbach Road
 Washington, IL 61571
 (217) 605-0403
 www.prairieengineers.com
 Professional design firm no. 1644-005955
 ENGINEERS ARCHITECTS SCIENTISTS
 © Copyright Prairie Engineers, P.C. 2021

USER NAME = jmasset	DESIGNED - SMJ	REVISED -
PLOT SCALE = 0.166666" / in.	CHECKED - BAS	REVISED -
PLOT DATE = 4/25/2022	DRAWN - JLM	REVISED -
	CHECKED - SMJ	REVISED -

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10,11,12)R	VERMILION	698	398
CONTRACT NO. 70A29				
ILLINOIS		FED. AID PROJECT		

GENERAL NOTES

Fasteners shall be high strength bolts. Holes shall be 13/16" dia for 3/4" dia. bolts, unless otherwise noted.

No field welding is permitted except as specified in the contract documents.

Reinforcement bars designated (E) shall be epoxy coated.

Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.

As directed by the Engineer, existing construction accessories welded to the top flange of beams and girders shall be removed. The weld areas shall be ground flush and inspected for cracks using magnetic particle testing (MT) or dye penetrant testing (PT) by qualified personnel approved by the Engineer.

Any cracks that cannot be removed by grinding 1/4 inch deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. The cost of removing welded accessories, grinding and inspecting weld areas and grinding cracks will be paid for according to Article 109.04 of the Standard Specifications.

If the Contractor elects to use cantilever forming brackets on the exterior beams or girders, the brackets shall be placed at the same locations as required for the hardwood blocks in Article 503.06(b) of the Standard Specifications. If additional cantilever forming brackets are required, hardwood blocking shall be wedged between the exterior and first interior beam at each of these additional bracket locations.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Concrete Sealer shall be applied to the repaired areas of the piers.

Two 1/8 in. adjusting shims shall be provided for each bearing in addition to all other plates or shims and placed as shown on bearing details.

Areas of repairs shown are estimated. The engineer shall show actual locations of the repairs on as-built plans.

Protective coat shall be applied to new Concrete Superstructure surfaces only. Applicable areas include exposed new concrete deck ±6'-11" width along joints, new overlay, and interior and top surfaces of repaired parapet only.

All new structural steel shall be hot-dipped galvanized, except as noted. See Special Provisions for "Hot Dip Galvanizing For Structural Steel", see also notes on sheet 16.

Synthetic Fibers shall be included in the bridge deck concrete overlay specified. See special provisions.

Up to 1/4 inch may be ground off the bridge deck and the bridge approach slabs.

Joint openings shall be adjusted according to Article 503.10(c) of the Standard Specifications when the deck is poured at an ambient temperature other than 50°F.

Existing structural steel that will be in contact with new structural steel shall be cleaned and painted prior to erection as required by the Special Provision "Cleaning and Painting Contact Surface Areas of Existing Steel Structures".

The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to deal with the presence of lead on this project.

Existing structure plans are available from the District upon request.


SCOPE OF WORK:

1. Complete bridge scarification 3/4".
2. Complete deck patching, removal of deck ends and hatch blocks.
3. Complete structural repair of concrete on substructure.
4. Remove and replace approach slab Type B curb.
5. Perform epoxy injection on longitudinal cracks in approach slabs.
6. Complete steel beam repairs and end diaphragm replacements.
7. Replace bearings at abutments.
8. Install shear studs at beam ends.
9. Cast deck ends and hatch blocks.
10. Place preformed joint strip seal.
11. Adjust inlets in approaches and scuppers in deck.
12. Place bridge deck latex concrete overlay 2 3/4".
13. Fill gaps between deck and beams w/ epoxy injection.
14. Complete slope wall crack sealing.
15. Complete diamond grinding and bridge deck grooving.


TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB	TOTAL
Concrete Removal	Cu. Yd.	49.0	-	49.0
Concrete Superstructure	Cu. Yd.	57.0	-	57.0
Protective Shield	Sq. Yd.	2,148	-	2,148
Concrete Structures	Cu. Yd.	24.0	-	24.0
† Bridge Deck Grooving (Longitudinal)	Sq. Yd.	2,805	-	2,805
Protective Coat	Sq. Yd.	3,415	-	3,415
Furnishing and Erecting Structural Steel	Pound	12,840	-	12,840
Stud Shear Connectors	Each	448	-	448
Reinforcement Bars, Epoxy Coated	Pound	8,450	-	8,450
Bar Splicers	Each	88	-	88
Preformed Joint Strip Seal	Foot	183.0	-	183.0
Elastomeric Bearing Assembly Type II	Each	32	-	32
Concrete Sealer	Sq. Ft.	-	1,120.0	1,120.0
Epoxy Crack Injection	Foot	120	-	120
† Jack and Remove Existing Bearings	Each	32	-	32
† Structural Steel Removal	Pound	8,030	-	8,030
† Structural Steel Repair	Pound	5,940	-	5,940
† Bridge Deck Latex Concrete Overlay 2 3/4"	Sq. Yd.	3,258	-	3,258
† Bridge Deck Scarification 3/4"	Sq. Yd.	3,258	-	3,258
† Structural Repair of Concrete Depth <=5"	Sq. Ft.	-	135.0	135.0
† Deck Slab Repair (Full Depth, Type 1)	Sq. Yd.	17	-	17
† Drainage Scuppers to be Adjusted	Each	6	-	6
† Inlet Boxes to be Adjusted (Special)	Each	4	-	4
† Epoxy Injection	Foot	108	-	108
† Temporary Support System	L Sum	1	-	1
† Diamond Grinding (Bridge Section)	Sq. Yd.	2,958	-	2,958
† Slope Wall Crack Sealing	Foot	-	120.5	120.5
Anchor Bolts 1"	Each	64	-	64

† Special Provision



PROFILE GRADE F.A. RTE. 332
(From 1995 Reconstruction Plans)



PROFILE GRADE F.A.I.-74
(From 1995 Reconstruction Plans)

MODEL: 2D Sheet H
FILE NAME: I:\jobs\2019\1901.PTB 193-026 I-74 Reconstruction\Drawings\CAD_Sheets\Rte_150 Bridge_092-0038\0920038-D570A29-002 - GENERAL DATA.dgn

Prairie Engineers, P.C.
22484 Grossbach Road
Washington, IL 61571
(217) 605-0403
www.prairieengineers.com
Professional Design Firm No. 1644-005965
© Copyright Prairie Engineers, P.C. 2021


USER NAME = jmasset	DESIGNED - SMJ	REVISED -
PLOT SCALE = 0.166666" / in.	CHECKED - BAS	REVISED -
PLOT DATE = 4/25/2022	DRAWN - JLM	REVISED -
	CHECKED - SMJ	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**GENERAL DATA
S.N. 092-0038**

SHEET 2 OF 26 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	399
CONTRACT NO. 70A29				
		ILLINOIS	FED. AID PROJECT	



EXISTING DECK CROSS SECTION
(Looking North)



PROPOSED DECK CROSS SECTION
(Looking North)

*Prior to grinding

MODEL: 2D Sheet H
FILE NAME: I:\jobs\2019\19111901_PTB_193-026 I-74 Reconstruction\Drawings\CAD_Sheets\Ite_150_Bridge_092-0038\0920038-D570A29-003-Typicals.dgn

Prairie Engineers, P.C.
22484 Grossbach Road
Washington, IL 61571
(217) 605-0403
www.prairieengineers.com
professional design firm no. 1644-005955
© Copyright Prairie Engineers, P.C. 2021

USER NAME = jmasset
DESIGNED - SMJ
CHECKED - BAS
DRAWN - JLM
PLOT SCALE = 0.166666" / in.
PLOT DATE = 4/25/2022

DESIGNED - SMJ
CHECKED - BAS
DRAWN - JLM
CHECKED - SMJ

REVISED -
REVISED -
REVISED -
REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**EXISTING AND PROPOSED TYPICAL CROSS SECTIONS
S.N. 092-0038**

SHEET 3 OF 26 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	(92-10.11,12)R	VERMILION	698	400
CONTRACT NO. 70A29				

ILLINOIS FED. AID PROJECT