

| GUTTER OUTLET SCHEDULE | | |
|------------------------|--------|----------------------------|
| LOCATION | OFFSET | CLASS SI CONCRETE (OUTLET) |
| M.S. | RT/LT | CU YD |
| 0.276 | RT | 3.77 |
| 0.276 | LT | 3.77 |
| 0.994 | RT | 3.77 |
| 0.994 | LT | 3.77 |
| 1.532 | RT | 3.77 |
| 1.532 | LT | 3.77 |
| 4.579 | RT | 3.77 |
| 4.579 | LT | 3.77 |
| TOTAL | | 30.14 |

| GUTTER SCHEDULE | | | | | |
|-----------------|----------|--------|---------|-------------------------|--|
| LOCATION | | OFFSET | REMOVAL | CONCRETE GUTTER, TYPE B | |
| M.S. | TO M.S. | RT/LT | FOOT | FOOT | |
| 0.276 | TO 0.456 | RT | 950.4 | 950.4 | |
| 0.276 | TO 0.456 | LT | 950.4 | 950.4 | |
| 0.900 | TO 0.994 | RT | 496.3 | 496.3 | |
| 0.900 | TO 0.994 | LT | 496.3 | 496.3 | |
| 1.373 | TO 1.532 | RT | 839.5 | 839.5 | |
| 1.373 | TO 1.532 | LT | 839.5 | 839.5 | |
| 4.486 | TO 4.579 | RT | 491.0 | 491.0 | |
| 4.486 | TO 4.579 | LT | 491.0 | 491.0 | |
| TOTAL | | | 5554.6 | 5554.6 | |

| WIDENING SCHEDULE | | | | |
|-------------------|----------|--------|--------|--------------------------|
| LOCATION | | OFFSET | LENGTH | HMA BASE COURSE WIDENING |
| M.S. | TO M.S. | RT/LT | FOOT | SQ YD |
| 0.276 | TO 0.456 | RT | 950.4 | 316.8 |
| 0.276 | TO 0.456 | LT | 950.4 | 316.8 |
| 0.900 | TO 0.994 | RT | 496.3 | 165.4 |
| 0.900 | TO 0.994 | LT | 496.3 | 165.4 |
| 1.373 | TO 1.532 | RT | 839.5 | 279.8 |
| 1.373 | TO 1.532 | LT | 839.5 | 279.8 |
| 4.486 | TO 4.579 | RT | 491.0 | 163.7 |
| 4.486 | TO 4.579 | LT | 491.0 | 163.7 |
| TOTAL | | | 5554.6 | 1851.5 |

| SHOULDERS SCHEDULE | | | | | |
|------------------------------|--------|--------|------------------|-------------------|-----------------------|
| MILE STATION TO MILE STATION | OFFSET | LENGTH | EARTH EXCAVATION | HMA SHOULDERS, 8" | SHOULDER RUMBLE STRIP |
| | RT/LT | FOOT | CU YD | SQ YD | FOOT |
| 0.900 TO 0.980 | LT | 425 | 42 | 188.9 | 0 |
| 1.915 TO 1.952 | RT | 198 | 14.7 | 66 | 198 |
| 1.980 TO 2.053 | RT | 384 | 28.4 | 128 | 384 |
| 2.067 TO 2.123 | RT | 295 | 21.9 | 98.3 | 295 |
| 1.915 TO 2.123 | LT | 1100 | 81.5 | 366.7 | 1100 |
| TOTAL | | 2402 | 188.4 | 847.9 | 1977.0 |

| STONE RIPRAP SCHEDULE | | | | | | |
|-----------------------|----------|--------|--------|-------|------------|------------------------|
| LOCATION | | OFFSET | LEIGHT | WIDTH | EXCAVATION | STONE RIPRAP, CLASS A3 |
| M.S. | TO M.S. | RT/LT | FEET | FEET | CU YD | SQ YD |
| 0.405 | TO 0.435 | LT | 160 | 15 | 59.26 | 266.67 |
| 0.409 | TO 0.437 | RT | 150 | 20 | 74.07 | 333.33 |
| 0.919 | TO 0.978 | RT | 310 | 12 | 91.85 | 413.33 |
| 0.946 | TO 0.982 | LT | 190 | 16 | 75.06 | 337.78 |
| 1.526 | TO 1.537 | LT | 60 | 6 | 8.89 | 40.00 |
| 1.526 | TO 1.537 | LT | 60 | 10 | 14.81 | 66.67 |
| 1.526 | TO 1.537 | LT | 60 | 2 | 2.96 | 13.33 |
| TOTAL | | | | | 326.91 | 1471.11 |