

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	SIGNATURE SHEET
3	INDEX OF SHEETS, GENERAL NOTES, HIGHWAY STANDARDS
4	MIXTURE REQUIREMENTS, STRUCTURE INFORMATION
5	SUMMARY OF QUANTITIES
6 - 7	TYPICAL SECTION
8	SCHEDULE FOR MAINLINE RESURFACING - LOCATION 1 & 2
9	SCHEDULE SIDE ROADS AND ENTRANCES RESURFACING
10	SCHEDULE FOR SHOULDERS
11 - 12	SCHEDULE FOR PAVEMENT MARKING
13 - 19	PLAN LAYOUT FOR FAP 312 (IL 3) LOCATION 1 - STA. 396+14.34
20 - 23	PLAN LAYOUT FOR FAP 312 (IL 3) LOCATION 2 - STA. 195+00 TO STA. 434+55
24	DETAILS: LOCATON 1 BUTT JT AT BEGINNING WITH PAINTED MEDIAN TRANSITION
25	DETAIL: INLAY OF SN 039-2025 AT STA. 194+10
26 - 27	LOCATION 1 BUTT JOINTS AND TRANSITIONS DETAILS
28 - 30	LOCATION 2 BUTT JOINTS AND TRANSITIONS DETAILS
31 - 33	DETAILS: SIDE ROAD AND ENTRANCE DETAILS
34	STANDARD DETAILS - TEMP. HOT-MIX ASPHALT TRANSITIONS
35	STANDARD DETAILS - ROUGH GROOVED SURFACE SIGN; UNEVEN LANE SIGN

GENERAL NOTES

THE THICKNESS OF BITUMINOUS MIXTURE SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE BITUMINOUS MIXTURE IS PLACED.

FACTORS USED FOR ESTIMATING PLAN QUANTITIES ARE AS FOLLOWS AND SHALL NOT BE USED FOR THE BASIS OF FINAL QUANTITIES EXCEPT FOR OC/OA OF BITUMINOUS MIXTURES:

ALL HOT-MIX ASPHALT.....2.016 TONS/CU.YD.
 ALL AGGREGATE.....2.05 TONS/CU.YD.
 BITUMINOUS MATERIALS (PRIME COAT)
 ON PAVEMENT.....0.09 GALS./SQ. YD.
 ON AGG. SURFACE.....0.32 GALS./SQ. YD.
 AGGREGATE (PRIME COAT).....0.0015 TONS/SQ. YD.

THE QUANTITY OF SHORT TERM PAVEMENT MARKING SHOWN IN THE PLANS WAS BASED ON ONE APPLICATION EACH FOR THE PRIME COAT, SURFACE COURSE AND LEVELING BINDER.

PRIOR TO PLACEMENT OF THE FINAL PAVEMENT MARKINGS, THE RESIDENT ENGINEER SHOULD CONTACT THE BUREAU OF OPERATIONS AND ARRANGE FOR INSPECTION AND APPROVAL OF THE PAVEMENT MARKING LAYOUT.

THE CONTRACTOR SHALL STAMP STATIONING IN THE PROPOSED BITUMINOUS MATS AT 300 FT. INTERVALS ON ALTERNATING SIDES OF THE PAVEMENT AND AS DIRECTED BY THE ENGINEER. THE STATION SYMBOL STAMPS USED SHALL BE FURNISHED BY THE CONTRACTOR. THEY SHALL BE 5/2" TALL OF A DESIGN APPROVED BY THE ENGINEER AND SHALL REMAIN THE PROPERTY OF THE CONTRACTOR.

UNLESS OTHERWISE DIRECTED BY THE ENGINEER, HOT-MIX ASPHALT RESURFACING SHALL BE PLACED IN A SEQUENCE THAT WILL MINIMIZE THE TIME THAT A LANE EDGE IS EXPOSED TO TRAFFIC.

QUANTITIES SHOWN IN THE PLANS FOR PATCHING ARE ESTIMATES. THE ACTUAL AMOUNT OF PATCHING REQUIRED SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.

HIGHWAY STANDARDS

000001-05	701311-03
442101-07	701336-05
442201-03	701901-01
701301-03	780001-02
701306-02	781001-03

FILE NAME =	USER NAME = mccordkr	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	INDEX OF SHEETS AND GENERAL NOTES		F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
cover.dgn	cover.dgn	DRAWN -	REVISED -		SCALE: _____ SHEET NO. ____ OF ____ SHEETS STA. _____ TO STA. _____		312	12385-5h130.13185-4	JACKSON	35	3
PLOT SCALE = 1/8" = 1' / IN.		CHECKED -	REVISED -		CONTRACT NO. 78195						
PLOT DATE = 4/26/2018		DATE -	REVISED -		ILLINOIS FED. AID PROJECT						