


NOTES:

- ① WHITE BAR PAVEMENT MARKING LINE - 24" SOLID
- ② WHITE PAVEMENT MARKING LINE - 8" SOLID
- ③ WHITE PAVEMENT MARKING LINE - 8" SOLID, 2' LONG, 6' GAP
- ④ YELLOW PAVEMENT MARKING LINE - 6" SOLID, 10' LONG, 30' GAP
- ⑤ EXISTING DOUBLE YELLOW PAVEMENT MARKING LINE - 4" SOLID EACH
- ⑥ DOUBLE YELLOW PAVEMENT MARKING LINE - 4" SOLID EACH
- ⑦ YELLOW PAVEMENT MARKING LINE - 12" SOLID @ 20' CTS.
- ⑧ PAVEMENT MARKING SYMBOL, SEE STANDARD NO. 780001-01
- ⑨ WHITE PAVEMENT MARKING LINE - 4" SOLID

- 1) STOP LINES ARE SOLID WHITE 24" WIDE EXTENDING ACROSS ALL APPROACH LANES.
- 2) LINES SHALL NOT BE LAID DIRECTLY OVER A LONGITUDINAL CRACK OR JOINT NOR OVER A TAR OR ASPHALT PAINTED LINE THE EDGE OF CENTER LINE OR LANE LINE SHALL BE OFFSET A MINIMUM OF 2 INCHES FROM A LONGITUDINAL CRACK OR JOINT.
- 3) SEE DETAILS FOR PLACEMENT OF TURN LANE MARKINGS.
- 4) EXISTING CURB AND GUTTER NOT SHOWN FOR PURPOSES OF CLARITY.
- 5) PERMANENT PAVEMENT MARKING SHALL BE THERMOPLASTIC FROM STA. 566+59 TO STA. 577+39.

- ◆ RAISED REFLECTIVE PAVEMENT MARKER, TWO WAY AMBER
- ◆ RAISED REFLECTIVE PAVEMENT MARKER, ONE WAY AMBER
- ◆ RAISED REFLECTIVE PAVEMENT MARKER, ONE WAY CLEAR



FILE NAME =	USER NAME = duncenbd	DESIGNED -	REVISED - DIST 3 COMMENT	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	IL 47 & IL 165 PAVEMENT MARKING PLAN	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
cr\projects\ed82484\consult\cadd drawings\shamp02.dgn	PLOT SCALE = 50.0001' / IN.	DRAWN - MAP	REVISED - 5/27/04			326		FORD	22	19	
	PLOT DATE = Mar 11, 2009 - 09:21:26 AM	CHECKED - RRM	REVISED - BDD 01/28/08			SCALE: 1" = 50' SHEET NO. OF SHEETS STA. TO STA.		CONTRACT NO. 66423			
		DATE - 02/26/04	REVISED -					FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT			

• (125)RS-5, (126)RS-3 & (127)RS-2