

DETAIL 1

N\_T\_S\_

USER NAME = razeqam

PLOT DATE = 4/17/2014

LOT SCALE = 100.0000 '/ in.

:\pw\_work\pwidot\razegam\d0312623\D152**0**12-sht-plan.dgr


DESIGNED

CHECKED

R,K,F,

DRAWN

DATE



LEFT TURN LANES WITHOUT MEDIANS VOLUME DENSITY ("FAR OUT" DETECTION) ON SAME APPROACH (PROTECTED / PERMITTED LEFT TURN PHASING) # = (600 mm) (900 m (1.8 m) (3.6 STRAIGHT SAW CUT TO HEAVY DUTY HANDHOLE (TYP.) PLACE HEAVY DUTY HANDHOLE BETWEEN FIRST AND SECOND LOOP AS SHOWN, NOTE: DUAL LEFT TURNS NOT SHOWN REFER TO PLAN SHEET FOR DETECTOR LOOP REPLACEMENT

UNIT DUCT

DRIVEWAY

ARE LOCATED IN TAPER OF A RIGHT TURN LANE, DIMENSION THIS LOOP TO COVER

ARTERIAL-VOLUME DENSITY ("FAR OUT" DETECTION)

DETAIL 2

N.T.S.

CROSS STREET-NON VOLUME DENSITY ("UPTIGHT" PRESENCE DETECTION) CROSS STREET-VOLUME DENSITY ("FAR OUT" DETECTION) ARTERIAL OFFSET LOOPS BY -DO NOT INSTALL 1' (300mm) FOR STRAIGHT SAW CUTS CALLING LOOP IN ARTERIAL RIGHT TURN LANE THIS DIMENSION MAY BE ADJUSTED FOR DRIVEWAY OR OTHER OBSTRUCTIONS. WHEN ADJUSTMENT IS \* = (1.8m) REQUIRED, DETECTORS WILL NORMALLY BE MOVED CLOSER \*\* = (1.5m) TO THE INTERSECTION. CROSS STREET CROSS STREET DEPENDING ON DRIVE-WAY LOCATION. CALLING LOOPS -10'(3.0m) PREFERRED-| e.| a. | e.| a. | e.| [TYP.-12' (3.6m) LANES] LOOPS ARE SAW-CUT TO THE EDGE OF TYP.-ALL LEGS-VOLUME PAVEMENT, 1" (25 mm) UNIT DUCT IS RUN BETWEEN EDGE OF PAVEMENT SI + - THESE DIMENSIONS WILL BE VARIABLE STRAIGHT SAW CUTS TO HEAVY [6' (1.8m) MINIMUM. AND HANDHOLE. DUTY HANDHOLE 25' (7,6 m) MAX[MUM] INFF SET LOOPS BY IN PAVEMENT l' (300mm) FOR STRAIGHT SAW CUTS. 4 - THESE DIMENSIONS (TYP.) IN HANDHOLES SHALL BE 5' (1.5m) FOR 10' (3.0m) LANE WIDTHS OUTSIDE PAVEMENT) - IF "FAR OUT" LOOPS TAPER AREA. DO NOT COVER THE LEFT TURN

REVISED

REVISED

REVISED

REVISED

## NOTES

## VEHICLES LOOP DETECTORS

- \* ALL LEAD IN CABLE SHALL BE TWO CONDUCTOR NO. 14 TWISTED.
- \* EACH DETECTOR LOOP SHALL HAVE ITS OWN SAW CUT FROM THE LOOP TO THE EDGE OF PAVEMENT OR TO A HANDHOLE IN THE
- \* EACH DETECTOR LOOP SHALL HAVE ITS OWN ONE INCH (25 mm) UNIT DUCT BETWEEN THE EDGE OF PAVEMENT AND THE FIRST HANDHOLE OR JUNCTION BOX. EACH UNIT DUCT RUN SHALL BE SHOWN ON THE PLANS BY THE DESIGNER, BUT SHALL NOT BE PAID FOR SEPARATLY. THIS ITEM IS INCIDENTAL TO THE PAY ITEM FOR DETECTOR LOOPS.
- \* ONE DIMENSION OF ALL DETECTOR LOOPS SHALL BE SIX FEET (1.8 m)
- \* EACH LANE OF NON-LOCKING, PRESENCE DETECTION AND EACH LANE OF A DOUBLE LEFT TURN LANE REQUIRES A SEPARATE INDUCTIVE LOOP DETECTOR AND LEAD IN CABLE.
- \* WHEN NON-LOCKING, PRESENCE DETECTION IS USED, MORE THAN ONE LOOP PER LANE IS REQUIRED BEHIND THE STOP BAR (i.e. 1-1/2, 1-3/4, 2).
- \* WHEN SYSTEM LOOPS ARE REQUIRED ON AN APPROACH OF AN INTERSECTION, THE LOOPS USED FOR VOLUME DENSITY AND INTERSECTION TIMING SHALL ALSO BE USED AS SYSTEM DETECTORS. EACH ONE OF THESE TYPE OF LOOPS REQUIRES A SEPARATE TWO CONDUCTOR NO. 14 TWISTED SHIELDED CABLE AND A SEPARATE INDUCTIVE LOOP DETECTOR WHEN NEW CONTROLLERS ARE UTILIZED. THE DESIGNER SHALL LABEL THESE TYPES OF LOOPS AS "INTERSECTION AND SAMPLING (SYSTEM) DETECTORS" ON THE SIGNAL LAYOUT, THE INTERCONNECT PLAN AND THE SYSTEM CABLE PLAN, WHEN AN EXISTING CONTROLLER IS UTILIZED FOR THIS TYPE OF DETECTION, THE PAY ITEM "INDUCTIVE LOOP DETECTOR WITH SYSTEM OUTPUT" SHOULD BE USED.

## PLACEMENT OF DETECTORS

THE FOLLOWING FIGURES REPRESENT THE MOST COMMON DETECTOR LOOP LOCATIONS AND SIZES. ADJUSTMENTS WILL BE NECESSARY FOR SPECIFIC GEOMETRIC CONSIDERATIONS.

LOCATIONS AND DEMENSIONS OF DETECTOR LOOPS ARE REQUIRED ON ALL SIGNAL LAYOUT PLAN SHEETS.

"FAR OUT" DETECTION REFERS TO LOCKING, PRESENCE TYPE DETECTION LOCATED IN THRU LANES, RIGHT TURN LANES, AND RIGHT TURN LANE TAPER AREAS (IF APPLICABLE), USUALLY 250' (75 m) IN ADVANCE OF STOP BARS. "UPTIGHT" DETECTION REFERS TO NON-LOCKING PRESENCE TYPE DETECTION LOCATED IN ALL LANES AND 10'-15' (3.0 m-4.5 m) BEHIND THE CROSSING STREET'S EDGE OF PAVEMENT EXTENDED.

ALL DETAILS AND NOTES SHOWN ARE FROM THE I.D.O.T. DISTRICT 1 TRAFFIC SIGNAL DESIGN GUIDELINES DATED JANUARY 1995

THIS DRAWING HAS BEEN PREPARED TO ASSIST THE RESIDENT ENGINEER FOR ALL ROADWAY RESURFACING OR S.M.A.R.T. PROJECTS WHERE THE DIMENSIONS ARE NOT SHOWN ON THE PLANS AND THE FINAL LOCATIONS FOR CROSSWALKS OR STOP BARS ARE NOT DETERMINED.

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	DISTRICT 1 – DETECTOR LOOP INSTALLATION				F.A.P. RTÉ.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	DETAILS FOR ROADWAY RESURFACING				324	29R-RS-3	MCHENRY	25	24
						TS-07	CONTRACT	NO. E	50V13
	SCALE: NONE	SHEET NO. 1 OF 1 SHEETS	STA.	TO STA.	FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT				