

DRAINAGE STRUCTURE SCHEDULE

NO.	LOCATION		TYPE	RIM ELEV	INVERT ELEVATION			
	STATION	OFFSET			(IN)	(IN)	(IN)	(OUT)
100	491+40	36.0 RT	CB TC T24F&G	932.22				928.76
101	491+40	43.5 RT	MAN TA 4 DIA T1F CL	932.47		928.74		928.74
102	493+00	36.0 RT	CB TC T24F&G	931.41				927.95
103	493+00	43.5 RT	MAN TA 4 DIA T1F CL	931.66	926.94	927.93		926.94
104	494+30	36.0 RT	CB TC T24F&G	930.75				927.29
105	494+30	43.5 RT	MAN TA 4 DIA T1F CL	931.00	926.36	927.27		926.11
106	495+60	36.0 RT	CB TC T24F&G	930.09				926.63
107	495+60	43.5 RT	MAN TA 4 DIA T1F CL	930.34	925.48	926.61		925.48
108	496+75	36.0 RT	CB TC T24F&G	929.51				926.05
109	496+75	43.5 RT	MAN TA 4 DIA T1F CL	929.76	924.93	926.03		924.93
110	497+85	36.0 RT	CB TC T24F&G	928.95				925.49
111	497+85	43.5 RT	MAN TA 5 DIA T1F CL	929.20	924.44	925.46		924.44
112	498+47	36.0 RT	CB TC T24F&G	928.63				925.17
113	498+47	43.5 RT	MAN TA 5 DIA T1F CL	928.89	924.01	925.15		924.01
114	501+15	43.5 RT	CB TC T24F&G	927.12				923.66
115	501+15	51.0 RT	MAN TA 5 DIA T1F CL	927.37	922.89	923.63		922.89
116	502+25	39.2 RT	CB TC T24F&G	926.65				923.19
117	502+25	46.7 RT	MAN TA 5 DIA T1F CL	926.90	922.36	923.14		921.94
118	503+50	38.0 RT	CB TC T24F&G	926.04				922.58
119	503+50	45.5 RT	MAN TA 5 DIA T1F CL	926.29	921.34	922.54		921.34
120	504+78	38.0 RT	CB TC T24F&G	925.39				921.93
121	504+78	45.5 RT	MAN TA 5 DIA T1F CL	925.64	920.73	921.89		920.73
122	504+78	74.0 RT	PRCF END S EL EORS 24	-				920.61
123	9+32.00	64.3 LT	PRCF END S EL EORS 18	-				923.37
124	9+36.36	42.1 LT	MAN TA 5 DIA T24F&G	926.90	923.27			923.27
125	9+36.55	31.7 RT	CB TA 5 DIA T24F&G	927.27	922.86			922.86
126	9+30.47	56.6 RT	PRCF END S EL EORS 18	-				922.70
127	9+13	34.6 LT	INLETS TA T24F&G	927.19				923.30
128	9+13	22.2 RT	INLETS TB T11F&G	927.85	923.06			923.06
129	8+00	22.0 LT	INLETS TB T11F&G	928.33	924.45			924.45
130	8+00	22.0 RT	INLETS TB T11F&G	928.33	924.27			924.27
131	7+00	20.6 RT	INLETS TA T11F&G	929.21				924.88

DRAINAGE SEWER SCHEDULE

SEWER NO.	TYPE	SIZE (INCH)	LENGTH (FEET)	SLOPE (%)
				(%)
100	STORM SEW CL A 2	12	4.5	0.44%
101	STORM SEW CL A 2	12	156.0	1.15%
102	STORM SEW CL A 2	12	4.5	0.44%
103	STORM SEW CL A 2	12	126.0	0.46%
104	STORM SEW CL A 2	12	4.5	0.44%
105	STORM SEW CL A 2	15	126.0	0.50%
106	STORM SEW CL A 2	12	4.5	0.44%
107	STORM SEW CL A 2	15	111.0	0.50%
108	STORM SEW CL A 2	12	4.5	0.44%
109	STORM SEW CL A 2	15	105.5	0.46%
110	STORM SEW CL A 2	12	4.0	0.75%
111	SS CL A 2 EORS 18	23X14	57.0	0.75%
112	STORM SEW CL A 1	12	4.0	0.50%
113	SS CL A 2 EORS 18	23X14	263.1	0.43%
114	STORM SEW CL A 2	12	4.0	0.75%
115	SS CL A 2 EORS 18	23X14	105.1	0.50%
116	STORM SEW CL A 2	12	4.0	1.25%
117	SS CL A 2 EORS 24	30X19	120.0	0.50%
118	STORM SEW CL A 2	12	4.0	1.00%
119	SS CL A 2 EORS 24	30X19	123.0	0.50%
120	STORM SEW CL A 2	12	4.0	1.00%
121	SS CL A 2 EORS 24	30X19	10.5	0.86%
122	SS CL A 2 EORS 18	23X14	15.0	0.67%
123	SS CL A 2 EORS 18	23X14	70.8	0.58%
124	SS CL A 2 EORS 18	23X14	17.4	0.75%
125	STORM SEW CL A 2	12	20.3	1.00%
126	STORM SEW CL A 2	12	54.6	0.44%
127	STORM SEW CL A 2	12	110.0	1.10%
128	STORM SEW CL A 1	12	40.6	0.45%
129	STORM SEW CL A 1	12	97.0	0.44%

DRAINAGE STRUCTURE SCHEDULE

NO.	LOCATION		TYPE	RIM ELEV	INVERT ELEVATION			
	STATION	OFFSET			(IN)	(IN)	(IN)	(OUT)
200	491+40	36.0 LT	CB TC T24F&G	932.22				928.76
201	491+40	52.6 LT	MAN TA 4 DIA T1F CL	932.30		928.70		928.18
202	493+00	36.0 LT	CB TC T24F&G	931.41				927.95
203	493+00	52.6 LT	MAN TA 4 DIA T1F CL	931.49	927.40	927.89		927.40
204	494+30	36.0 LT	CB TC T24F&G	930.75				927.29
205	494+30	52.6 LT	MAN TA 4 DIA T1F CL	930.83	926.77	927.23		926.77
206	495+60	36.0 LT	CB TC T24F&G	930.09				926.63
207	495+60	52.6 LT	MAN TA 4 DIA T1F CL	930.17	926.14	926.57		925.87
208	496+75	39.1 LT	CB TC T24F&G	929.46				926.00
209	496+75	55.7 LT	MAN TA 4 DIA T1F CL	929.53	925.31	925.94		925.31
210	497+90	44.0 LT	CB TC T24F&G	928.76				925.30
211	497+90	60.6 LT	MAN TA 4 DIA T1F CL	928.84	924.76	925.24		924.76
212	498+58	44.0 LT	CB TC T24F&G	928.42				924.96
213	498+58	60.6 LT	MAN TA 4 DIA T1F CL	928.50	924.35	924.90		924.08
214	500+50	48.0 LT	CB TC T24F&G	927.30				923.84
215	500+50	64.6 LT	MAN TA 4 DIA T1F CL	927.38	923.10	923.78		923.10
216	501+55	48.0 LT	CB TC T24F&G	926.77				923.31
217	501+55	64.6 LT	MAN TA 4 DIA T1F CL	926.85	922.43	923.25		922.43
218	502+60	45.7 LT	CB TC T24F&G	926.29				922.83
219	502+60	64.0 LT	MAN TA 5 DIA T1F CL	926.33	921.88	922.76		921.78
220	503+70	39.7 LT	CB TA 4 DIA T24F&G	925.88				922.42
221	503+70	55.8 LT	MAN TA 5 DIA T1F CL	925.97	921.12	922.36		921.12
222	504+70	36.0 LT	CB TC T24F&G	925.47				922.01
223	504+70	52.1 LT	MAN TA 5 DIA T1F CL	925.56	920.42	921.95		920.42
224	505+60	36.0 LT	CB TC T24F&G	925.01				921.55
225	505+60	52.1 LT	MAN TA 5 DIA T1F CL	925.10	919.97	921.49		919.97
226	506+50	36.0 LT	CB TC T24F&G	924.55				921.09
227	506+50	52.1 LT	MAN TA 5 DIA T1F CL	924.64	919.52	921.03	919.00	919.00
228	507+60	36.0 LT	CB TC T24F&G	923.99				920.53
229	507+60	52.6 LT	MAN TA 4 DIA T1F CL	924.07		920.47		919.57
230	506+50	70.0 LT	PRCF END S EL EORS 24	-				918.63
231	11+64	24.0 LT	INLETS TA T24F&G	927.93				924.66
232	11+64	26.2 RT	INLETS TB T24F&G	928.05		924.45		924.45
233	11+05	32.6 LT	INLETS TA T8G	927.40				923.53
234	10+97	24.0 LT	INLETS TB T24F&G	927.22		923.48		923.48
235	10+97	38.2 RT	INLETS TB T24F&G	927.15		924.16		923.21
236	10+69.18	53.3 LT	PRCF END S EL EORS 18	-				923.48
237	10+68.80	29.9 LT	MAN TA 5 DIA T24F&G	927.10	923.40			923.40
238	10+70.12	48.7 RT	CB TA 5 DIA T24F&G	927.00	923.10			923.10
239	503+00	75.7 LT	PRCF END S EL EORS 18	-				921.67

DRAINAGE SEWER SCHEDULE

SEWER NO.	TYPE	SIZE (INCH)	LENGTH (FEET)	SLOPE (%)
				(%)
200	STORM SEW CL A 1	12	13.6	0.44%
201	STORM SEW CL A 2	12	156.0	0.50%
202	STORM SEW CL A 1	12	13.6	0.44%
203	STORM SEW CL A 2	12	126.0	0.50%
204	STORM SEW CL A 1	12	13.6	0.44%
205	STORM SEW CL A 2	12	126.0	0.50%
206	STORM SEW CL A 1	12	13.6	0.44%
207	STORM SEW CL A 1	15	111.0	0.50%
208	STORM SEW CL A 1	12	13.6	0.44%
209	STORM SEW CL A 1	15	111.0	0.50%
210	STORM SEW CL A 1	12	13.6	0.44%
211	STORM SEW CL A 1	15	64.0	0.64%
212	STORM SEW CL A 1	12	13.6	0.44%
213	STORM SEW CL A 1	18	188.0	0.52%
214	STORM SEW CL A 1	12	13.6	0.44%
215	STORM SEW CL A 1	18	101.0	0.66%
216	STORM SEW CL A 1	12	13.6	0.44%
217	STORM SEW CL A 1	18	100.5	0.55%
218	STORM SEW CL A 1	12	14.9	0.44%
219	SS CL A 1 EORS 24	30X19	105.3	0.63%
220	STORM SEW CL A 1	12	12.6	0.44%
221	SS CL A 2 EORS 24	30X19	95.1	0.74%
222	STORM SEW CL A 1	12	12.6	0.44%
223	SS CL A 2 EORS 24	30X19	85.0	0.53%
224	STORM SEW CL A 1	12	12.6	0.44%
225	SS CL A 2 EORS 24	30X19	85.0	0.53%
226	STORM SEW CL A 1	12	12.6	0.44%
227	STORM SEW CL A 2	12	105.5	0.54%
228	STORM SEW CL A 1	12	13.6	0.44%
229	SS CL A 1 EORS 24	30X19	12.4	2.98%
230	STORM SEW CL A 1	12	47.7	0.44%
231	STORM SEW CL A 1	12	65.0	0.45%
232	STORM SEW CL A 1	12	8.9	0.56%
233	STORM SEW CL A 1	12	59.8	0.45%
234	STORM SEW CL A 1	12	25.0	0.44%
235	SS CL A 1 EORS 18	23X14	13.0	0.62%
236	SS CL A 1 EORS 18	23X14	75.0	0.40%
237	SS CL A 1 EORS 18	23X14	308.0	0.46%