

MAINLINE SCHEDULE													
	STA.	TO	STA.	WIDTH	LENGTH	AREA	LEVEL BINDER (M.M.), 3/4 "	HMA SURF. CSE. MIX. "C" 1 1/2 "	BIT. MAT'LS. (PRIME COAT)	MIX CRACKS JOINTS & FLWY	LEVEL BINDER (H.M.),	HMA SURF. REM 1 1/2"	TEMP RAMP
				FEET	FEET	SQ YD	TON	TON	POUND	TON	TON	SQ YD	SQ YD
<b>URBAN</b>													
BRIDGE OMISSION - S.N. 053-0159	15+85.00	TO	21+20.00	26	535.00	1546	65	130	1044	0.5	0.8	1546	29
	29+05.00	TO	53+96.00	26	2491.00	7196	303	605	4858	2.2	3.6	7196	14
	53+96.00	TO	56+35.00	27	239.00	717	31	61	484	0.3	0.4	717	14
BRIDGE OMISSION - S.N. 053-0070	60+60.00	TO	62+75.82	27	215.82	647	28	55	438	0.2	0.4	647	14
STA. EQUATION 62+75.82 (BK) = 64+90.00 (AH)	62+75.82	TO	65+74.00	27	298.18	895	38	77	604	0.3	0.5	895	
<b>SUBTOTALS</b>						<b>11001</b>	<b>465</b>	<b>928</b>	<b>7428</b>	<b>4</b>	<b>6</b>	<b>11001</b>	<b>72</b>
<b>RURAL</b>													
	65+74.00	TO	79+25.95	26	1351.95	3906	165	329	2637	1.2	2.0	3906	
	79+25.95	TO	89+89.97	27 & VARIES	1064.02	3192	135	269	2155	1.0	1.6	3192	
STA. EQUATION 89+89.97 (BK) = 92+45.38 (AH)	92+45.38	TO	93+62.05	27 & VARIES	116.67	350	15	30	237	0.2	0.2	350	
	93+62.05	TO	423+94.50	26	33,032.45	95,427	4008	8016	64414	28.7	47.8	95427	14
STRUCTURE OMISSION - S.N. 053-2557	424+05.50	TO	436+17.00	26	1,211.50	3,500	147	294	2363	1.1	1.8	3500	14
BRIDGE OMISSION - S.N. 053-0075	437+33.00	TO	583+00.00	26	14,567.00	42,082.44	1768	3535	28406	12.7	21.1	42082	29
<b>SUBTOTALS</b>						<b>148,457</b>	<b>6,238</b>	<b>12,473</b>	<b>100,212</b>	<b>44.9</b>	<b>74.5</b>	<b>148,457</b>	<b>58</b>
<b>TOTALS</b>						<b>159,458</b>	<b>6,703</b>	<b>13,401</b>	<b>107,640</b>	<b>48.4</b>	<b>80.2</b>	<b>159,458</b>	<b>130</b>

HOT MIX ASPHALT SHOULDERS										
LOCATION	SIDE	LENGTH	WIDTH	AREA	HMA SURF REM 1 1/2"	BIT MATLS PR CT	LEVEL BINDER (M.M.) 3/4"	HMA SURFACE MIX "C"		
				SQ YD	SQ YD	POUND	TON	TON		
<b>RURAL</b>										
79+40.00 TO 92+95.30*	RT	1099.89	6	733	733	495	31	62		
79+40.00 TO 92+95.30*	LT	1099.89	6	733	733	495	31	62		
432+20.00 TO 435+87.67	RT	367.67	5	204	204	138	9	18		
432+20.00 TO 435+87.67	LT	367.67	5	204	204	138	9	18		
437+62.33 TO 441+15.00	RT	352.67	5	196	196	133	9	17		
437+62.33 TO 441+15.00	LT	352.67	5	196	196	133	9	17		
<b>TOTALS</b>				<b>2267</b>	<b>2267</b>	<b>1532</b>	<b>98</b>	<b>194</b>		

\* STA. EQUATION 89+89.97 BK = 92+45.38 AH

PAVEMENT PATCHING	
LOCATION	CLASS D PATCHES TYPE II, 16 INCH SQ YD.
BETWEEN N. 2300 E. ROAD AND S.N. 053-2557	25
BETWEEN S.N. 053-0075 AND N. 2500 E. ROAD	25
BETWEEN N. 2500 E. ROAD AND N. 2600 E. ROAD	25
<b>TOTAL</b>	<b>75</b>