



TYPICAL SECTION

STA. 1296+00 TO STA. 1308+56

MIX DESIGN					
MIX	PG GRADE ••	DESIGN AIR VOIDS	MIX COMPOSITION	FRICTION AGG	DENSITY CONTROL
HMA SURFACE	PG 64-22	4.0% @N50	IL 9.5	MIXTURE D	CORRELATION
LEVELING BINDER	PG 64-22	4.0% @N50	IL 9.5 FG		

•• WHEN RAP/RAS ABR EXCEEDS 20%, THE HIGH AND LOW VIRGIN ASPHALT BINDER GRADES SHALL EACH BE REDUCED BY ONE GRADE (EXAMPLE: 25% ABR WOULD REQUIRE A VIRGIN ASPHALT BINDER GRADE OF PG 64-22 TO BE REDUCED TO PG 58-28).

FILE NAME =	USER NAME = carpenterdj	DESIGNED -	REVISED -
ct:\pwork\pwork\carpenterdj\d0122637\366930-shd-details.DGN		DRAWN -	REVISED -
	PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -
	PLOT DATE = 6/6/2014	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

TYPICAL SECTIONS	
SCALE: _____	SHEET NO. ___ OF ___ SHEETS
STA. _____ TO STA. _____	

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
41	11RS-4 & 12RS-5	KANKAKEE	14	7
CONTRACT NO. 66930			ILLINOIS FED. AID PROJECT	