

TYPICAL SECTION 5

STA. 1182+29 TO STA. 1184+82

MIXTURES TABLE									
	HMA SURFACE								
PG GRADE**	PG 64-22	PG 64-22 PG 64-22							
DESIGN AIR	4.0% @	4.0% @	4.0% @						
VOIDS	N50	N50	N50						
MIXTURE	IL 9 . 5	IL 9.5 FG	IL 9.5						
COMPOSITION									
FRICTION	MIXTURE		MIXTURE						
AGGREGATE	С		С						
DENSITY CONTROL METHOD	CORRELATION	CORRELATION	SATISFACTION OF ENGINEER						

** WHEN RAP/RAS ABR EXCEEDS 20 PERCENT, THE HIGH AND LOW VIRGIN ASPHAL BINDER GRADES SHALL EACH BE REDUCED BY ONE GRADE (I.E. 25% ABR WOULD REQUIRE A VIRGIN ASPHALT BINDER GRADE OF PG 64-22 TO BE REDUCED TO PG 58-28)

FILE NAME =	USER NAME = duncanbd	DESIGNED -	REVISED -		TYPICAL SECTIONS						F.A.P.	SECTION	COUNTY	CHEETE	SHEET
c:\pw_work\pwidot\duncanbd\d0304146\D36	C34-sht-typical.dgn	DRAWN -	REVISED -	STATE OF ILLINOIS							646	(103.104)RS-6	BUREAU	28	7
	PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION									CONTRACT		6C34
	PLOT DATE = 6/6/2014	DATE -	REVISED -		SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT				