



## MICRO-SURFACING DETAIL

\* FIBER-MODIFIED ASPHALT CRACK SEALING

## TYPICAL SECTION F. A. I. 55

STA 406+64.73 TO STA 655+49.51

OMISSION: SN 053-0139 & 053-0140 STA 561+69.71 TO STA 562+61.13

STATION EQUATIONS: 552+08.35BK = 121+28.60AH 477+82.67BK = 470+23.55AH

## NOTES

- 1) MICRO-SURFACING SHALL BE LOCATED AT THE CENTERLINE OF PAVEMENT JOINT. ACTUAL LOCATIONS SHALL BE FIELD DETERMINED BY THE ENGINEER PRIOR TO THE CONTRACTOR BEGINNING HIS/HER CONSTRUCTION OPERATIONS.
- 2) THE TEMPORARY STRIPING SHALL BE OFFSET 3' FROM THE CENTERLINE, IN THE DRIVING LANE.
- 3) OFFSET OF THE PERMANENT CENTERLINE PAVEMENT STRIPING SHALL BE FIELD DETERMINED BY THE ENGINEER.

FILE NAME =	USER NAME = carpenterdy	DESIGNED	REVISED			F.A.I. RTF.	SECTION	COUNTY	TOTAL SHEET
c:\pw_work\pwidot\carpenterdj\d0374121\[	366D48-sht-details.dgn	DRAWN	REVISED	STATE OF ILLINOIS	TYPICALS		(53-4,4(1),3(1),3,2)I-4	LIVINGSTON	8 5
	PLOT SCALE = 100.0000 ' / in.	CHECKED	REVISED	DEPARTMENT OF TRANSPORTATION				CONTRACT	NO. 66D48
	PLOT DATE = 5/9/2014	DATE	REVISED		SCALE:   SHEET OF SHEETS   STA TO STA	ILLINOIS FED. AID PROJECT			