

ENTRANCE IMPROVEMENT SCHEDULE FOR RURAL / URBAN "PPP" PROJECTS															
LOCATION	TYPE OF ENTRANCE	EX MATERIAL TYPE	WIDTH 1	WIDTH 2	WIDTH 3	WIDTH 4	LENGTH A	LENGTH B	PR HMA CONC. THICKNESS	HMA SURF. REMOVAL - BUTT JOINT	PREP OF BASE	AGGREGATE SURFACE COURSE TY - B	BIT (P.C.)	AGG (P.C.)	INCIDENTAL HMA SURF.
(LT / RT) (STA) (+)	(FE / PE / CE / MB) - (RURAL / URBAN)	(EARTH / AGG. / HMA / P.C.C.)	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	INCH	SO. YD.	SO. YD.	TON	TON	TON	TON
RT 527+75	PE	AGG	12.0	15.0	39.0		8.0	7.0	3.50		24.0	1.2	0.01	0.0	4.7
LT 566+67	TR 500	O&C		23.0	51.0		10.0		8.00		41.1		0.02	0.1	18.4
RT 566+75	TR 500	O&C		19.0	44.0		10.0		8.00		35.0		0.01	0.1	15.7
LT 620+62	TR 600	O&C		56.0	94.0		10.0		8.00		83.3		0.03	0.2	37.3
RT 620+62	TR 600	HMA		68.0	155.0		10.0		2.00	123.9			0.05	0.2	13.9
LT 622+67	CE	HMA		40.0	58.0		10.0		2.00	54.4			0.02	0.1	6.1
RT 622+71	CE	AGG	35.0	37.0	57.0		10.0	5.0	8.00		52.2	2.3	0.02	0.1	23.4
RT 628+06	CE	AGG	24.0	25.0	50.0		10.0	5.0	8.00		41.7	1.6	0.02	0.1	18.7
RT 629+24	CE	AGG	24.0	24.0	50.0		10.0	5.0	8.00		41.1	1.5	0.02	0.1	18.4
RT 631+19	CE	AGG	24.0	26.0	52.0		10.0	5.0	8.00		43.3	1.6	0.02	0.1	19.4
RT 632+29	CE	AGG	24.0	27.0	44.0		10.0	5.0	8.00		39.4	1.6	0.01	0.1	17.7
RT 639+18	CE	AGG	24.0	24.0	46.0		10.0	5.0	8.00		38.9	1.5	0.01	0.1	17.4
LT 686+46	TR 700	O&C		28.0	48.0		10.0		8.00		42.2		0.02	0.1	18.9
RT 686+67	TR 700	HMA		90.0	157.0		10.0		2.00	137.2			0.05	0.3	15.4
RT 707+64	TR 1700	HMA		90.0	137.0		10.0		2.00	126.1			0.05	0.3	14.1
LT 713+03	PE	HMA		13.0	32.0		8.0		2.00	20.0			0.01	0.0	2.2
RT 713+61	PE	AGG	24.0	43.0	68.0		8.0	7.0	3.50		49.3	3.0	0.02	0.1	9.7
RT 719+43	PE	HMA		33.0	40.0		8.0		2.00	32.4			0.01	0.1	3.6
LT 726+82	TR 1700	HMA		55.0	102.0		10.0		2.00	87.2			0.03	0.2	9.8
RT 726+85	PE	HMA		26.0	36.0		8.0		2.00	27.6			0.01	0.1	3.1
LT 741+86	PE	HMA		20.0	63.0	26.0	8.0		2.00	48.4			0.02	0.1	5.4
LT 747+50	PE	HMA		30.0	64.0	22.0	8.0		2.00	51.6			0.02	0.1	5.8
LT 748+28	PE	HMA		10.0	23.0		8.0		2.00	14.7			0.01	0.0	1.6
LT 750+83	PE	HMA		27.0	69.0	24.0	8.0		2.00	53.3			0.02	0.1	6.0
LT 753+60	TR 825	O&C		30.0	63.0		10.0		8.00		51.7		0.02	0.1	23.1
RT 753+70	TR 825	O&C		25.0	45.0		10.0		8.00		38.9		0.01	0.1	17.4
LT 756+51	PE	HMA		30.0	63.0	21.0	8.0		2.00	50.7			0.02	0.1	5.7
LT 758+60	PE	AGG	24.0	25.0	56.0	20.0	8.0	7.0	3.50		36.0	2.2	0.01	0.1	7.1
LT 760+03	PE	AGG	24.0	42.0	65.0	29.0	8.0	7.0	3.50		47.6	2.9	0.02	0.1	9.3
LT 760+91	PE	HMA		15.0	57.0	17.0	8.0		2.00	39.6			0.02	0.1	4.4
LT 761+88	PE	HMA		42.0	69.0	22.0	8.0		2.00	59.1			0.02	0.1	6.6
RT 761+80	TR 840	HMA		50.0	83.0		10.0		2.00	73.9			0.03	0.1	8.3
TOKEN QUANTITY TO BE USED AT THE DISCRETION OF THE ENGINEER										50.0	50.0	3.0	0.04	0.2	11.2
TOTAL =										1050.1	756	22	0.7	3.6	400