

GENERAL NOTES

THIS SECTION SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE PLANS, THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION; ADOPTED JANUARY 1, 2012; THE "SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS" INDICATED ON THE CHECK SHEET, AND "THE SPECIAL PROVISIONS" INCLUDED IN THE PROPOSAL. THE WORK INCLUDED IN THE SECTION 07 HMA RESURF 2015-2 CONSISTS OF HMA RESURFACING AND ANY OTHER WORK NECESSARY TO COMPLETE THE SECTION.

THE CONTRACTOR SHALL PROVIDE INTERNET ACCESS TO THE BITUMINOUS PLANT QUALITY CONTROL LAB SO THAT BITUMINOUS PLANT REPORTS CAN BE E-MAILED TO THE DISTRICT HEADQUARTERS. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE UNIT PRICES FOR OTHER ITEMS IN THE CONTRACT.

PAVEMENT MARKING SHALL BE APPLIED IN ACCORDANCE WITH SECTION 780 OF THE STANDARD SPECIFICATIONS. SHORT TERM PAVEMENT MARKING SHALL BE APPLIED TO THE MILLED SURFACE AND HOT-MIX ASPHALT SURFACE COURSE AS SPECIFIED IN SECTION 703 OF THE STANDARD SPECIFICATIONS. TEMPORARY TAPE SHALL BE USED ON THE SURFACE COURSE AND PAINT SHALL BE USED ON MILLED SURFACE.

IN ADDITION TO THE REQUIREMENTS IN ARTICLE 701.15(J), A LAPTOP COMPUTER SHALL BE SUPPLIED BY THE CONTRACTOR.

REFER TO ARTICLE 701.07 FOR THE DROP-OFF POLICY.

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT:

MIXTURE USE: LEVEL BINDER (1")
 APPLICATION: Levelling Binder (Machine Method) N90
 PG GRADE: PG 64-22
 DESIGN AIR VOIDS: 4.0% @ Ndesign = 90
 MIXTURE COMPOSITION: IL-9.5
 FRICTION AGGREGATE: N/A

MIXTURE USE: SURFACE COURSE (1 1/2")
 APPLICATION: Polymerized Hot-Mix Asphalt Surface Course, Mix "D", N90
 PG GRADE: SBS PG 70-22
 DESIGN AIR VOIDS: 4.0% @ Ndesign = 90
 MIXTURE COMPOSITION: IL-9.5
 FRICTION AGGREGATE: Mixture D

MIXTURE USE: 2-1/2" Shoulders
 APPLICATION: Hot Mix Asphalt Surface Course, IL-9.5L, N30
 PG GRADE: PG 64-22
 DESIGN AIR VOIDS: 4.0% @ Ndesign = 30
 MIXTURE COMPOSITION: IL-9.5L
 FRICTION AGGREGATE: N/A

INDEX OF SHEETS

SHEET NO.	TITLE
1	COVER SHEET
2	INDEX OF SHEETS & GENERAL NOTES
3-4	SUMMARY OF QUANTITIES
5-6	TYPICAL SECTIONS
7	SCHEDULES
8	DETAILS
9-10	PLAN SHEETS
11-14	TYPICAL APPLICATIONS OF PAVEMENT MARKING
15	TYPICAL APPLICATIONS OF DETECTOR LOOPS

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED AFTER SHEET NO. :

000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001001-02	AREAS OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND A FOOT
442101-07	CLASS B PATCHES
482001-02	HMA SHOULDER ADJACENT TO FLEXIBLE PAVEMENT
701101-04	OFF-RD OPERATIONS, MULTILANE, 15' TO 24" FROM PAVEMENT EDGE.
701421-06	URBAN LANE CLOSURE, MULTILANE, MULTILANE, DAY OPERATIONS ONLY, FOR SPEEDS >= 45 MPH TO 55 MPH
701426-06	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPER., FOR SPEEDS >= 45 MPH
701701-09	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701901-03	TRAFFIC CONTROL DEVICES

FILE NAME =	USER NAME = teesleyok	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	GENERAL NOTES & INDEX OF SHEETS	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
c:\pwork\pwork\teesleyok\20384072\074668-ht-index.dgn	DRAWN -	REVISED -	323			07 HMA RESURF 2015-2	MACON	15	2	
PLOT SCALE = 100.0000' / 1"	CHECKED -	REVISED -	CONTRACT NO. 74668							
Default	PLOT DATE = 5/28/2014	DATE -	REVISED -			SCALE:	SHEET OF SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT	