

RESURFACING SCHEDULE

STATION TO STATION	LENGTH FOOT	HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2" SQ YD	BITUMINOUS MATERIALS (PRIME COAT) POUND	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N90 TON	TEMPORARY RAMP SQ YD
IL 15 EB					
81+67.00 TO 120+50.00	3883.0	14487.2	6519.3	1216.9	114.4
IL 15 WB					
81+50.00 TO 115+02.87	3352.9	10113.9	4551.3	849.6	71.1
US 45 & CURVE C					
97+92.42 TO 111+87.35	1394.9	4322.4	1945.1	363.1	77.8
CURVE F					
1+15.00 TO 9+77.00	862.0	1797.2	808.8	151.0	0.0
CURVE D					
3+78.53 TO 11+77.16	798.6	1552.6	698.7	130.4	43.3
CURVE B					
96+18.00 TO 106+12.19	994.2	3422.6	1540.2	287.5	27.8
TOTALS		35696.0	16063.0	2999.0	334.0

PATCHING SCHEDULE

	CLASS D PATCHES, TYPE I, 11 INCH	CLASS D PATCHES, TYPE II, 11 INCH	CLASS D PATCHES, TYPE III, 11 INCH	CLASS D PATCHES, TYPE IV, 11 INCH
	SQ YD	SQ YD	SQ YD	SQ YD
TOTALS	5.0	354.0	71.0	279.0