



ADJUST OUTLET SLOPES TO CONFORM TO SITE CONDITIONS

QUANTITIES

For Section A-A to E-E and curtain wall =
 1.82 m³ (2.38 cu. yds.) concrete for (225 (9) pav't.)
 1.84 m³ (2.41 cu. yds.) concrete for (250 (10) pav't.)
 For Section F-F =
 .17 m³ (0.069 cu. yds.) concrete per m (ft.)

CLASS SI CONCRETE (OUTLET), SPECIAL

GENERAL NOTES

Tie bars shall be No. 19 (No. 6) at 600 mm (24") centers unless otherwise shown.
 Gutter outlet shall be tied to the pavement in accordance with details for longitudinal construction joint shown on Standard 420001.
 If the average grade of pavement for the distance from Section A-A to D-D exceeds 2%, this distance shall be increased 1.8 m (6 feet) for each 1% increase in grade.
 All dimensions are in millimeters (inches) unless otherwise shown.

LAST SAVED = 5/23/2013
 PEN TABLE = V8-HA-1F-1A3
 PLOT DRIVER = TR-18pdf-Block-Half.plt

FILE NAME =	USER NAME = jepettibone	DESIGNED -	REVISED -
\\06103\cad\l\plans\029.D672789-Sht-Details-Misc.dgn		DRAWN -	REVISED -
PLOT SCALE = 100.0000' / IN.		CHECKED -	REVISED -
PLOT DATE = 5/23/2013 10:41:04 AM		DATE -	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

MISCELLANEOUS DETAILS	
CLASS SI CONCRETE (OUTLET), SPECIAL	
SCALE: NONE	SHEET NO. 4 OF 8 SHEETS STA. TO STA.

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
7706	23(B-1)	LOGAN	179	140
BUS. LOOP 55 OVER SALT CREEK			CONTRACT NO. 72789	
FED. ROAD DIST. NO.			ILLINOIS FED. AID PROJECT	