

RESURFACING SCHEDULE

| LOCATION | LENGTH | BITUMINOUS MATERIALS (PRIME COAT) | | | AGGREGATE (PRIME COAT) | | | POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, STONE MATRIX ASPHALT, N80 | POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, STONE MATRIX ASPHALT, N80 | SHOULDER RUMBLE STRIPS, 16 INCH | AGGREGATE SHOULDER, TYPE B | | HOT-MIX ASPHALT SHOULDERS | | HOT-MIX ASPHALT SHOULDERS, 15" | | PAVED SHOULDER REMOVAL | | EARTH EXCAVATION | | | | |
|--------------------|--------|--------------------------------------|------|-----------|------------------------|------------|-----------|---|--|--|-------------------------------|------------|------------------------------|-------|---|-------|------------------------------|-------|---------------------|-------|-------|-------|-------|
| | | STATION TO STATION | LANE | LEFT SHLD | MAIN | RIGHT SHLD | LEFT SHLD | | | | MAIN | RIGHT SHLD | FOOT | LEFT | RIGHT | LEFT | RIGHT | LEFT | RIGHT | LEFT | RIGHT | LEFT | RIGHT |
| | | | | TON | TON | TON | TON | | | | TON | TON | | TON | TON | TON | TON | SO YD | SO YD | SO YD | SO YD | CU YD | CU YD |
| 1350+60 TO 1350+96 | NB | 36.0 | 0.01 | 0.03 | 0.01 | 0.05 | 0.14 | 0.06 | 16.13 | | 72 | 1.33 | 4.35 | 6.72 | | | | | | | | | |
| 1350+96 TO 1351+12 | NB | 16.0 | 0.00 | 0.01 | | 0.02 | 0.06 | | 4.78 | 4.78 | 32 | 0.79 | 2.27 | | | 17.8 | 17.8 | | | | | | |
| 1351+12 TO 1352+00 | NB | 88.0 | 0.02 | | | 0.12 | | | 26.28 | 26.28 | 176 | 4.35 | 12.48 | | | 97.8 | 97.8 | | | | | | |
| 1352+00 TO 1355+00 | NB | 300.0 | 0.08 | | | 0.40 | | | 89.60 | 89.60 | 600 | 14.81 | 42.56 | | | 333.3 | 200.0 | | 55.6 | | | | |
| 1355+00 TO 1355+12 | NB | 12.0 | 0.00 | | | 0.02 | | | 3.58 | 3.58 | 24 | 0.59 | 1.70 | | | 13.3 | 13.3 | | | | | | |
| 1355+12 TO 1355+24 | NB | 12.0 | 0.00 | 0.01 | | 0.02 | 0.05 | | 3.58 | 3.58 | 24 | 0.59 | 1.70 | | | 13.3 | 13.3 | | | | | | |
| 1355+24 TO 1355+60 | NB | 36.0 | 0.01 | 0.03 | 0.01 | 0.05 | 0.14 | 0.06 | 16.13 | | 72 | 1.33 | 4.35 | 6.72 | | | | | | | | | |
| 1350+87 TO 1351+23 | SB | 36.0 | 0.01 | 0.03 | 0.01 | 0.06 | 0.14 | 0.04 | 16.13 | | 72 | 1.33 | 2.67 | 6.72 | 4.03 | | | | | | | | |
| 1351+23 TO 1351+33 | SB | 10.0 | | 0.01 | 0.00 | | 0.04 | 0.01 | 2.99 | 2.99 | 20 | 0.49 | 0.99 | | 1.49 | 11.1 | 11.1 | | | | | | |
| 1351+33 TO 1351+50 | SB | 17.0 | | | 0.00 | | | 0.02 | 5.08 | 5.08 | 34 | 0.84 | 1.68 | | 2.54 | 18.9 | 18.9 | | | | | | |
| 1351+50 TO 1354+50 | SB | 300.0 | | | 0.06 | | | 0.30 | 89.60 | 89.60 | 600 | 14.81 | 29.63 | | 44.80 | 333.3 | 200.0 | | 55.6 | | | | |
| 1354+50 TO 1355+30 | SB | 80.0 | | | 0.02 | | | 0.08 | 23.89 | 23.89 | 160 | 3.95 | 7.90 | | 11.95 | 88.9 | 88.9 | | | | | | |
| 1355+30 TO 1355+40 | SB | 10.0 | | 0.01 | 0.00 | | 0.04 | 0.01 | 2.99 | 2.99 | 20 | 0.49 | 0.99 | | 1.49 | 11.1 | 11.1 | | | | | | |
| 1355+40 TO 1355+76 | SB | 36.0 | 0.01 | 0.03 | 0.01 | 0.06 | 0.14 | 0.04 | 16.13 | | 72 | 1.33 | 2.67 | 6.72 | 4.03 | | | | | | | | |
| SUBTOTAL | | | | 0.16 | 0.16 | 0.13 | 0.79 | 0.77 | 0.61 | 316.89 | 252.37 | 1978 | 23.26 | 70.31 | 82.87 | 83.78 | 463.3 | 475.6 | 330.0 | 342.2 | 55.6 | 55.6 | |
| TOTAL | | | | 0.5 | | | 3 | | | 316.9 | 252.4 | 1978 | 94 | | 167 | | 939 | | 672 | | 115 | | |

NOTE: LEFT/RIGHT (LT/RT) IS DEFINED LOOKING UPSTATION.

HMA SURFACE REMOVAL, VARIABLE DEPTH

| STATION TO STATION | LANE | LENGTH (FT.) | WIDTH (FT.) | AREA (SQ YD.) |
|--------------------------|------|--------------|-------------|---------------|
| 1350+60.00 TO 1351+00.00 | NB | 40.0 | 42 | 186.7 |
| 1350+87.00 TO 1351+27.00 | SB | 40.0 | 40 | 177.8 |
| 1355+20.00 TO 1355+60.00 | NB | 40.0 | 42 | 186.7 |
| 1355+36.00 TO 1355+76.00 | SB | 40.0 | 40 | 177.8 |
| SUBTOTAL | | | | 728.9 |
| TOTAL | | | | 729 |

PATCHING SCHEDULE

| LOCATION | | | | LANES | | | | AREA (SQ YD.) | CLASS D, TYPE II, 15" (SQ YD.) | CLASS D, TYPE II, 15" (SQ YD.) |
|--------------------------|----------------|----|----|-------------|-------------|-------|-------|---------------|--------------------------------|--------------------------------|
| STATION TO STATION | DISTANCE (FT.) | NB | SB | WIDTH (FT.) | DEPTH (FT.) | | | | | |
| 1350+96.00 TO 1351+12.00 | 16.0 | 2 | | 12 | 0.17 | 21.33 | | 42.67 | | |
| 1355+12.00 TO 1355+24.00 | 12.0 | 2 | | 12 | 0.17 | 16.00 | | 32.00 | | |
| 1351+23.00 TO 1351+33.00 | 10.0 | | 2 | 12 | 0.17 | 13.33 | 26.67 | | | |
| 1355+30.00 TO 1355+40.00 | 10.0 | | 2 | 12 | 0.17 | 13.33 | 26.67 | | | |
| SUBTOTAL | | | | | | | | 53.33 | 74.67 | |
| TOTAL | | | | | | | | 54 | 75 | |