

TABULATION OF QUANTITIES

40600100 BITUMINOUS MATERIALS (PRIME COAT)

LOCATION	WIDTH	QUANTITY REQUIRED
STA. 36+90 TO 141+80	21.0	2447.6 GAL
RATE OF APPL. = 0.1 GAL/ S.Y.	TOTAL	2447.6 (USE 2448 GAL)

40600982 HOT-MIX ASPHALT SURFACE REMOVAL BUTT JOINT

LOCATION	WIDTH	QUANTITY REQUIRED
STA. 36+90 (MAIN LANES)	21.0	59.0 SQ YD
	TOTAL	59.0 (USE 59 SQ YD)

48101200 AGGREGATE SHOULDERS, TYP B

LOCATION	WIDTH	QUANTITY REQUIRED
STA. 36+90 - 141+80 (MAIN LANE)	21.0	1000.0 TON
RATE OF APPL. = 2.08 TON/S.Y.	TOTAL	1000.0 USE (1000.0 TON)

78001110 PAINT PAVEMENT MARKING - LINE 4"

LOCATION	WIDTH	QUANTITY REQUIRED
STA. 36+90 - 141+80 (EDGE LINES)	4"	20980 FT
STA. 36+90 - 141+80 (CENTERLINE)	4"	2622 FT.
ENTIRE SECTION (NO PASSING ZONES)	4"	<u>6700 FT</u>
		30302 FT
	TOTAL	30302.0 (USE 30302 FT)

40603080 HOT-MIX ASPHALT BINDER COURSE IL 19.0 N50

LOCATION	WIDTH	QUANTITY REQUIRED
STA. 36+90 - 141+80 (MAIN LANES)	21.0'	3084.00 TON
ENTIRE SECTION (ENTRANCES)	VAR.	63.93 TON
ENTIRE SECTION (INTERSECTIONS)	VAR.	<u>20.97 TON</u>
		3169.90 TON
RATE OF APPL. = 112 LB./S.Y./IN.	TOTAL	3168.90 (USE 3169 TON)