

F.A.P. RTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
869	104B-1, 104B-2	FRANKLIN	56	2
STA.		TO STA.		
FED. ROAD DIST. NO. -		ILLINOIS	FED. AID PROJECT	

GENERAL NOTES

THE THICKNESS OF BITUMINOUS MIXTURE SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE BITUMINOUS MIXTURE IS PLACED.

FACTORS USED FOR QUANTITY CALCULATIONS ARE AS FOLLOWS:

ALL ASPHALT:	2.016 TONS/CU. YD.
ALL AGGREGATE:	2.05 TONS/CU. YD.
RIPRAP (A4 & A5)	1.50 TONS/CU YD
RIPRAP (A1)	1.85 TONS/CU YD

PLAN DIMENSIONS AND DETAILS RELATIVE TO THE EXISTING STRUCTURE HAVE BEEN TAKEN FROM EXISTING PLANS AND ARE SUBJECT TO NOMINAL CONSTRUCTION VARIATIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY SUCH DIMENSIONS AND DETAILS IN THE FIELD AND MAKE NECESSARY APPROVED ADJUSTMENTS PRIOR TO CONSTRUCTION OR ORDERING OF MATERIALS. SUCH VARIATIONS SHALL NOT BE A CAUSE FOR ADDITIONAL COMPENSATION FOR A CHANGE IN THE SCOPE OF THE WORK. THE CONTRACTOR, HOWEVER, WILL BE PAID FOR THE ACTUAL QUANTITY FURNISHED AT THE UNIT PRICE BID FOR THE WORK. CONSTRUCTION PLANS ARE AVAILABLE FOR REVIEW AT THE DISTRICT 9 OFFICE.

IN ADDITION TO THE REQUIREMENTS OF ARTICLE 107.16 THE CONTRACTOR SHALL PROTECT THE SURFACE OF ALL BRIDGE DECK AND BRIDGE APPROACH PAVEMENTS IN A MANNER SATISFACTORY TO THE ENGINEER BEFORE ANY EQUIPMENT IS ALLOWED TO CROSS THE STRUCTURE. PROTECTION SHALL BE PROVIDED FOR ALL EQUIPMENT AS DEFINED IN ARTICLE 101.17 REGARDLESS IF TRACK MOUNTED OR WHEELED.

AT ALL LOCATIONS WHERE BITUMINOUS OR CONCRETE PAVEMENT JOINS AN EXISTING BITUMINOUS OR CONCRETE PAVEMENT, A SAWED JOINT SHALL BE CONSTRUCTED. THE COST OF THIS JOINT SHALL BE INCLUDED IN THE TYPE OF PAVEMENT BEING CONSTRUCTED.

QUANTITIES SHOWN IN THE PLANS FOR BRIDGE DECK GROOVING AND PROTECTIVE COAT INCLUDE THE BRIDGE, THE BRIDGE APPROACH PAVEMENTS, AND THE BRIDGE APPROACH PAVEMENT CONNECTORS (PCC).

PROTECTIVE COAT SHALL BE APPLIED TO THE BRIDGE, THE BRIDGE APPROACH PAVEMENTS, AND THE BRIDGE APPROACH PAVEMENT CONNECTORS (PCC) IN ACCORDANCE WITH ARTICLE 503.19 OF THE STANDARD SPECIFICATIONS. THE PROTECTIVE COAT SHALL BE APPLIED REGARDLESS OF THE CURING METHOD USED. THE RATE OF APPLICATION FOR EACH COAT ON SAW CUT GROOVED AREAS SHALL BE 25 SQUARE YARDS PER GALLON OF MIXTURE.

REMOVAL OF EXISTING 10.5" TO 16.5" THICK BRIDGE APPROACH PAVEMENTS IS INCLUDED IN THE QUANTITY FOR PAVEMENT REMOVAL - 390 SQ YD.

ALL OBSTRUCTIONS WHICH ARE WITHIN THE CLEAR ZONE SHOWN ON THE TYPICAL SECTION, AND ARE NOT SHIELDED BY THE PROPOSED GUARDRAIL, SHALL BE REMOVED BETWEEN STATIONS 576+50 - 581+70 AND STATIONS 600+42 - 606+80. TYPICAL OBSTRUCTIONS ARE HEADWALLS, FOUNDATIONS, EXT. WHICH PROJECT 100 mm (4 IN.) OR MORE ABOVE THE GROUNDLINE; AND TREES WHICH WILL MATURE TO A DIAMETER OF 100 mm (4 IN.) OR GREATER.

TREES SHALL BE PRESERVED THROUGHOUT THIS SECTION AS SHOWN ON THE PLANS AND AS DIRECTED BY THE ENGINEER. GENERALLY, TREES OUTSIDE THE CLEAR ZONE, AND WHICH DO NOT INTERFERE WITH CONSTRUCTION, SHALL NOT BE DISTURBED.

ALL TEMPORARY EROSION CONTROL MEASURES SHALL BE LEFT IN PLACE UNTIL REMOVAL IS REQUIRED TO CONSTRUCT FINAL GRADE LINES.

THE QUANTITY OF SHORT TERM PAVEMENT MARKING SHOWN IN THE PLANS IS BASED ON ONE APPLICATION.

THE QUANTITY OF TEMPORARY PAVEMENT MARKING SHOWN IN THE PLANS IS BASED ON ONE APPLICATION FOR STAGE I AND STAGE II CONSTRUCTION OF BOTH STRUCTURES.

THE DISTRICT BUREAU OF OPERATIONS SHALL BE NOTIFIED AT LEAST 10 DAYS PRIOR TO PLACEMENT OF THE FINAL PAVEMENT MARKINGS. THE BUREAU OF OPERATIONS WILL THEN DETERMINE THE ACTUAL LIMITS TO BE STRIPED AS "NO PASSING" ZONES.

COST OF REMOVING "HOT-MIX ASPHALT BASE COURSE WIDENING, 10'" USED FOR STAGE I TRAFFIC IS INCLUDED IN "PAVED SHOULDER REMOVAL-SO YD."

THE "HOT-MIX ASPHALT BASE COURSE WIDENING, 10'" CONSTRUCTED IN PRE-STAGE I ON PROPOSED STRUCTURE 028-2016 MAY BE INCORPORATED INTO THE FINAL "HOT-MIX ASPHALT SHOULDERS, 8'" DURING STAGE II CONSTRUCTION IF APPROVED BY THE ENGINEER. SUCH CHANGE WILL NOT BE A CAUSE FOR ADDITIONAL COMPENSATION, BUT THE CONTRACTOR WILL BE PAID FOR THE ACTUAL QUANTITY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.

THE ADVANCE DETECTOR LOOPS ARE TYPICALLY LOCATED 300 FEET IN ADVANCE OF THE STOP BAR. THE BUREAU OF OPERATIONS SHOULD APPROVE THE LOOP LOCATIONS PRIOR TO INSTALLATION.

THE CENTERLINE PAVEMENT MARKING SHOULD BE REMOVED FROM THE STOP BAR TO THE SAND ATTENUATORS OR DRUMS. EDGE LINE PAVEMENT MARKING SHOULD BE REMOVED IF A 10 FOOT LANE WIDTH CANNOT BE MAINTAINED. TEMPORARY EDGE LINES SHOULD BE INSTALLED WHEN THE EDGE LINES ARE REMOVED.

VERTICAL PANELS SHOWN ON STANDARD 701321 WILL NOT BE REQUIRED ON THE STAGE II NEW BRIDGE PARAPET. THE BARRIER WALL REFLECTORS SHALL BE INSTALLED PRIOR TO OPENING TO TRAFFIC.

ANY TIME THE CONCRETE BARRIER IS NOT IN THE PROPER POSITION, FLAGGERS SHALL BE IN PLACE TO CONTROL TRAFFIC. THE TEMPORARY TRAFFIC SIGNALS SHALL BE SET TO FLASH ALL RED.

THE ALGEBRAIC DIFFERENCE BETWEEN THE PAVEMENT AND SHOULDER SLOPES SHALL NOT EXCEED 8%. THE SHOULDER ON THE OUTSIDE OF SUPERELEVATED CURVES SHALL BE FLATTENED ACCORDINGLY.

ON ALL SUPERELEVATED CURVES, THE PROPOSED BASE COURSE WIDENING SHALL BE CONSTRUCTED WITH A SLOPE CONFORMING TO THE RATE OF SUPERELEVATION OF THE EXISTING PAVEMENT.

TRIM EDGES OF EXISTING BITUMINOUS CONCRETE SURFACE FLUSH WITH EXISTING PAVEMENT PRIOR TO CONSTRUCTING NEW BASE COURSE WIDENING.

THE "HOT-MIX ASPHALT BASE COURSE WIDENING, 10'" CONSTRUCTED IN PRE-STAGE I ON PROPOSED STRUCTURE 028-2016 MAY BE INCORPORATED INTO THE FINAL "HOT-MIX ASPHALT SHOULDERS, 8'" DURING STAGE II CONSTRUCTION IF APPROVED BY THE ENGINEER. SUCH CHANGE WILL NOT BE A CAUSE FOR ADDITIONAL COMPENSATION, BUT THE CONTRACTOR WILL BE PAID FOR THE ACTUAL QUANTITY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.

COMMITMENTS: NONE AS OF MAY 11, 2007, REFER TO COMMITMENT FILE FOR ANY COMMITMENTS AFTER THIS DATE.

STANDARDS

000001-04	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
280001-03	TEMPORARY EROSION CONTROL SYSTEMS
420001-06	PAVEMENT JOINTS
420101-03	7.2 M (24') JOINTED PCC PAVEMENT
420401-05	BRIDGE APPROACH PAVEMENT
421001-01	REINFORCEMENT FOR CONTINUOUSLY REINFORCED PCC PAVEMENT
482006-02	BITUMINOUS SHOULDER ADJACENT TO RIGID PAVEMENT
515001-02	NAME PLATE FOR BRIDGES
630001-07	STEEL PLATE BEAM GUARDRAIL
630201-04	PCC/HMA STABILIZATION AT STEEL PLATE BEAM GUARDRAIL
630301-04	SHOULDER WIDENING FOR TYPE 1, (SPECIAL) GUARDRAIL TERMINALS
631031-06	TRAFFIC BARRIER TERMINAL, TYPE 6
631032-03	TRAFFIC BARRIER TERMINAL, TYPE 6 A
635011-01	REFLECTOR MARKER & MOUNTING DETAILS
701006-02	OFF-ROAD OPERATIONS, 2L 2W, 4.5 m (15') TO PAVEMENT EDGE
701201-02	LANE CLOSURE, 2L 2W, DAY ONLY, ON-ROAD TO 600 mm (24") OFF-ROAD, FOR SPEEDS ≥ 45 MPH
701301-02	LANE CLOSURE, 2L 2W, SHORT TIME OPERATIONS
701321-08	LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER
701326-02	LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS ≥ 45 MPH
702001-06	TRAFFIC CONTROL DEVICES
704001-03	TEMPORARY CONCRETE BARRIER
780001-01	TYPICAL PAVEMENT MARKINGS

542401
609000-03

INDEX OF SHEETS

1	COVER SHEET
2	INDEX OF SHEETS; GENERAL NOTES; STANDARDS
3-4	SUMMARY OF QUANTITIES
SN 028-2016 REPLACEMENT	
5	TYPICAL SECTIONS
6-7	SCHEDULES OF QUANTITIES
8	PLAN-PROFILE
9	STAGE CONSTRUCTION PLAN
10	BITUMINOUS SHOULDER AND GUARDRAIL PLAN
11	EROSION CONTROL PLAN
12-17	CROSS SECTIONS
18-25	STRUCTURE PLANS - SN 028-2016
SN 028-0076 REPLACEMENT	
26	TYPICAL SECTIONS
27-28	SCHEDULES OF QUANTITIES
29	PLAN-PROFILE
30	STAGE CONSTRUCTION PLAN
31	HOT-MIX ASPHALT SHOULDER AND GUARDRAIL PLAN
32	EROSION CONTROL PLAN
33-37	CROSS SECTIONS
38	DETAILS - SEEDING AND MULCHING; BITUMINOUS SHOULDERS AT TERMINAL
39	DETAILS - POROUS GR. BACKFILL; STEP CONST. ON EX. FILL & BUTT JOINT
40	DETAILS - REFLECTOR AND TERMINAL MARKER PLACEMENT
41-56	STRUCTURE PLANS - SN 028-0076
54A-56B DETAILS	

Rev. 7-17-07

Prepared By:	<i>James Travis Emons</i> DISTRICT STUDIES & PLANS ENGINEER
Examined By:	<i>James Travis Emons</i> DISTRICT LAND ACQUISITION ENGINEER
Examined By:	<i>Carrie Nelson</i> DISTRICT PROGRAM DEVELOPMENT ENGINEER
Examined By:	<i>Nicholas Hammer</i> DISTRICT OPERATIONS ENGINEER
Examined By:	<i>Joseph L...</i> DISTRICT CONSTRUCTION ENGINEER
Examined By:	<i>Bruce ...</i> DISTRICT MATERIALS ENGINEER
Examined By:	<i>Shirley ...</i> DISTRICT PROJECT IMPLEMENTATION ENGINEER
Examined By:	<i>...</i> ASSISTANT REGIONAL ENGINEER
Approved By:	<i>Neil ...</i> DEPUTY DIRECTOR OF HIGHWAYS, REGION ENGINEER
DATE	May 8 2007

**GENERAL NOTES, INDEX OF SHEETS, STANDARDS - SN 028-2016 & SN 028-0076
IL 14 OVER ANDY CREEK AND TRIBUTARY TO ANDY CREEK**