



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

July 18, 2012

SUBJECT: FAS 815 (CH 20)
Project RS-0815(103)
Section 09-00075-01-RS
White County
Contract No. 99478
Item 022
August 3, 2012 Letting
Addendum (A)

NOTICE TO PROSPECTIVE BIDDERS:

Due to clarify information necessary to revise the following:

1. Revised page 3 of the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

John Baranzelli, P.E.
Acting Engineer of Design and Environment

A handwritten signature in cursive script, reading "Ted B. Walschleger P.E.", with a small "P.E." to the right.

By: Ted B. Walschleger, P.E.
Engineer of Project Management

After removal of the base and surface, the area shall be filled with a LEV BIND MM N70. This area shall be compacted as per Article 442.08 of the Standard Specifications and to a density of not less than 90 percent of the maximum theoretical density.

HOT-MIX ASPHALT MIXTURES

The rate of Prime Coat application shall be 0.25 Gal/Sq. Yd. Payment will be made at the Contract Unit Price per Gal. for **Bituminous Materials (Prime Coat)**.

Locations	Hot-Mix Asphalt Surface Course
Mixture Use:	Hot-Mix Asphalt Surface Course, Mix "C" N70
AC/PG	PG64-22
Friction Aggregate	C Surface
Locations	Hot-Mix Asphalt Binder Course
Mixture Use:	Hot-Mix Asphalt Binder Course, IL -19.0, N70
AC/PG	PG64-22
Friction Aggregate	C Surface

AGGREGATE SHOULDERS, TYPE B

This work shall be constructed in accordance with the applicable portions of Section 481 of the Standard Specifications. These shoulders shall be constructed, as shown on the Shoulders detail located on Sheet 5 of the Plans, of Aggregate Shoulders, Type B. These Aggregate Shoulders, Type B shall have a minimum I.B.R. of 80, in addition to conforming with the applicable portions of Section 481 of the Standard Specifications.

UTILITIES

It shall be the Contractor's responsibility to contact all the utilities, affecting the Project, prior to construction.

PRECAUTION FOR UTILITIES

The Contractor shall take whatever precautions which may be necessary to protect the property of the various public utilities, which may be located underground or above ground, at or adjacent to the site of this improvement. He will be required to repair or replace at his own expense, or bear the cost, to repair or replace, any public utility property which has been damaged through his efforts. The procedure and specifications of repair will be in accordance with the regulations and/or policy of the utility.