

P. A. D. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
1225	(11 & 12) RS-6	LAKE	36	2
STA.	TO STA.			
FED. ROAD DIST. NO. 1	RLINGS	FED. AID PROJECT		
60819				

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)

3 METER (10') TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURBS AND GUTTER AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE CITY OF WAUKEGAN

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 40 MM (1 1/2 INCHES) WHERE THE SPEED LIMIT IS 80 KM/H (45 MPH) OR LESS AND 25 MM (1 INCH) WHERE THE SPEED LIMIT IS GREATER THAN 80 KM/H (45 MPH). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 75 MM (3 INCHES) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND BITUMINOUS TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT DEBBIE HANLON AREA TRAFFIC FIELD TECHNICIAN AT (847) 705-4413 A MINIMUM OF 72 HOURS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

PAVEMENT PATCHING SHALL BE COMPLETED PRIOR TO BITUMINOUS SURFACE REMOVAL OPERATIONS.

LIST OF STANDARDS

- 000001-04 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
- 442201-01 CLASS C AND D PATCHES
- 604001-02 FRAME AND LIDS, TYPE 1
- 606001-02 CONCRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER
- 701601-04 URBAN LANE CLOSURE, MULTILANE 1W OR 2W WITH NONTRAVERSABLE MEDIAN
- 701606-04 URBAN LANE CLOSURE, MULTILANE, 2W, WITH MOUNTABLE MEDIAN
- 701701-04 URBAN LANE CLOSURE, MULTILANE INTERSECTION
- 702001-05 TRAFIC CONTROL DEVICE
- 780001-01 TYPICAL PAVEMENT MARKINGS

INDEX OF SHEET

SHEET NO.	
1	TITLE SHEET
2	INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES
3-4	SUMMARY OF QUANTITIES
5-6	TYPICAL SECTIONS
7-9	ROADWAY PLAN
10-12	PAVEMENT MARKING PLAN
13-22	DETECTOR LOOP REPLACEMENT PLANS
23	DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS
24	MEDIAN NOSE DETAIL
25	DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING
26	FRAMES AND LIDS ADJUSTMENT WITH MILLING
27	PAVEMENT PATCHING BITUMINOUS SURFACED PAVEMENT
28	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
29	BUTT JOINT AND BITUMINOUS TAPER DETAILS
30	TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS AND DRIVEWAYS
31	RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
32	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
33	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
34	SIGNING FOR FLAGGING OPERATIONS AT WORK ZONE OPENING
35	TEMPORARY INFORMATION SIGNING
36	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

BELVIDERE ROAD
INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES

SCALE: VERT. 1"=50'
HORIZ. 1"=50'

DATE 7/16/2005

DRAWN BY _____
CHECKED BY _____

7/16/2005
c:\p\c\obj\ref\81487000\m32
REF
REF

VI=