


**LEGEND**

① 4" WHITE (10' DASH, 30' SKIP)	⑥ 24" WHITE
② 2-4" YELLOW (11" C-C)	⑦ 4" YELLOW
③ 12" YELLOW DIAGONALS @ 45° SPACING PER TC-13.	⑧ WHITE LETTERS AND SYMBOLS
④ 4" YELLOW, (10' DASH, 30' SKIP)	⑩ 6" WHITE
⑤ WHITE LEFT ARROWS	

- NOTES:**
- TWO WEEKS PRIOR TO PLACING THE PERMANENT PAVEMENT MARKINGS, CONTACT THE AREA TRAFFIC FIELD ENGINEER CORY JUCCIUS AT (815) 485-6475.
  - PERMANENT PAVEMENT MARKINGS SHALL BE APPLIED IN ACCORDANCE WITH THE DISTRICT ONE DETAIL FOR "TYPICAL PAVEMENT MARKINGS" TC-13.
  - RAISED REFLECTIVE PAVEMENT MARKINGS SHALL BE APPLIED IN ACCORDANCE WITH THE DISTRICT ONE DETAIL FOR "RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT)" TC-11.
  - FINAL PAVEMENT MARKING ON BITUMINOUS SURFACES SHALL BE THERMOPLASTIC PAVEMENT MARKINGS.



**K&E** KAM ENGINEERING, INC.  
CONSULTING ENGINEERS  
7074 Davis Road, Suite 205  
Evanston, Illinois 60223-1969

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

**PAVEMENT MARKING PLAN**  
US ROUTE 30  
SHEET 3 OF 3

SCALE: 1"=50'  
DATE: MARCH 2005

DRAWN BY: MD  
CHECKED BY: JS/MSA

\$FILES  
\$DATES