



POINT	STATION	OFFSET	ELEVATION
A	101+34.64	18.37' RT	EL. 11.39
B	101+39.66	38.37' RT	EL. 11.69
C	101+44.66	28.39' RT	EL. 11.45
D	101+14.93	38.38' RT	EL. 11.44
E	101+15.43	54.38' RT	EL. 11.12
F	101+61.23	38.35' RT	EL. 11.92
G	101+61.27	54.35' RT	EL. 11.59
I	102+30.48	53.90' RT	EL. 10.90
K	102+30.31	37.90' RT	EL. 11.22
L	101+88.78	38.24' RT	EL. 11.63
M	101+78.69	28.30' RT	EL. 12.41
N	101+88.67	18.24' RT	EL. 13.20
O	101+14.93	28.37' RT	EL. 11.19
P	100+63.93	28.37' RT	EL. 9.97
R	100+63.93	64.96' RT	EL. 9.24
S	100+79.94	64.96' RT	EL. 9.51
T	100+79.93	53.37' RT	EL. 9.74
U	100+83.18	34.37' RT	EL. 10.61
V	100+83.18	44.87' RT	EL. 10.40
W	101+44.66	33.37' RT	EL. 11.35

- ① HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50, 2"
- ② HOT-MIX ASPHALT BASE COURSE, 8"
- ③ SUB-BASE GRANULAR MATERIAL, TYPE B 6"
- ④ AGGREGATE SHOULDERS, TYPE A 12"

NOTES:

1. DURING CONSTRUCTION, THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION AS NOT TO DAMAGE EXISTING TREES THAT ARE NOT INDICATED TO BE REMOVED. THE APPROPRIATE TREE PROTECTION MEASURES SHALL BE ADHERED TO DURING THIS WORK.
2. TREES NOT TO BE REMOVED SHALL BE PROTECTED FROM ALL CONSTRUCTION ACTIVITIES AND PAID FOR AT THE CONTRACT UNIT PRICE PER EACH AS "TREE TRUNK PROTECTION".