

MATCHLINE STA. 452+00

MATCHLINE STA. 467+00

MATCHLINE STA. 467+00

MATCHLINE STA. 482+00

PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"  
 PROP. POLYMERIZED LEVELING BINDER  
 (MACHINE METHOD), IL-4.75, N50, 3/4"  
 PROP. HOT-MIX ASPHALT SURFACE COURSE,  
 MIX "D", N70, 1 1/2"

IL. 68 (DUNDEE RD.)



PAVEMENT MARKING KEY NOTE LEGEND:

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>(A) PROP. THERMO. PVT. MARKING (YELLOW) - 4" SOLID CENTERLINE (2 LINES @ 11" C-C) - (TYP.)</li> <li>(B) PROP. THERMO. PVT. MARKING (YELLOW) - 4" SOLID EDGELINE - (TYP.)</li> <li>(C) PROP. THERMO. PVT. MARKING (YELLOW) - 4" SKIP-DASH CENTERLINE (10' LINE - 30' SPACE) - (TYP.)</li> <li>(D) PROP. THERMO. PVT. MARKING (YELLOW) - 4" SOLID NO PASSING ZONE LINE (5-1/2" C-C FROM SKIP-DASH) - (TYP.)</li> <li>(E) PROP. THERMO. PVT. MARKING (WHITE) - 4" SOLID EDGELINE - (TYP.)</li> <li>(F) PROP. THERMO. PVT. MARKING (WHITE) - 4" SKIP-DASH LANE LINE (10' LINE - 30' SPACE) - (TYP.)</li> <li>(G) PROP. THERMO. PVT. MARKING (YELLOW) - 4" TWO-WAY LEFT TURN LANE LINE (2 LINES @ 5-1/2" C-C) - (TYP.)</li> <li>(H) PROP. THERMO. PVT. MARKING (WHITE) - 6" SOLID TURN LANE LINE - (TYP.)</li> <li>(I) PROP. THERMO. PVT. MARKING (WHITE) - 6" SKIP-DASH TURN LANE LINE (2' LINE - 6' SPACE) - (TYP.)</li> <li>(J) PROP. THERMO. PVT. MARKING (WHITE) - 6" SOLID PEDESTRIAN CROSSWALK - (TYP.)</li> <li>(K) PROP. THERMO. PVT. MARKING (WHITE) - 8" SOLID CHANNELIZATION LINE - (TYP.)</li> </ul> | <ul style="list-style-type: none"> <li>(L) PROP. THERMO. PVT. MARKING (YELLOW) - 12" SOLID PAINTED MEDIAN DIAGONAL LINE - RT. 45° DIAGONAL @ 75' C-C - (TYP.)</li> <li>(LI) PROP. THERMO. PVT. MARKING (WHITE) - 12" SOLID SHOULDER DIAGONAL LINE - RT. 45° DIAGONAL @ 75' C-C - (TYP.)</li> <li>(M) PROP. THERMO. PVT. MARKING (YELLOW) - 12" SOLID PAINTED MEDIAN DIAGONAL LINE - RT. 45° DIAGONAL @ 150' C-C - (TYP.)</li> <li>(MI) PROP. THERMO. PVT. MARKING (WHITE) - 12" SOLID SHOULDER DIAGONAL LINE - RT. 45° DIAGONAL @ 150' C-C - (TYP.)</li> <li>(N) PROP. THERMO. PVT. MARKING (WHITE) - 12" SOLID CHANNELIZATION LINE - RT. 45° CHEVRON @ 20' C-C - (TYP.)</li> <li>(O) PROP. THERMO. PVT. MARKING (YELLOW) - 12" SOLID PAINTED MEDIAN DIAGONAL LINE - RT. 45° DIAGONAL 5 EQUALLY SPACED</li> <li>(P) PROP. THERMO. PVT. MARKING (WHITE) - 24" SOLID STOP BAR - (TYP.)</li> <li>(Q) PROP. THERMO. PVT. MARKING (WHITE) LETTERS AND SYMBOLS - (TYP.)</li> </ul> |
|---|--|

IL. 68 (DUNDEE RD.)

LAKEVIEW LN.

PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"  
 PROP. POLYMERIZED LEVELING BINDER  
 (MACHINE METHOD), IL-4.75, N50, 3/4"  
 PROP. HOT-MIX ASPHALT SURFACE COURSE,  
 MIX "D", N70, 1 1/2"

FILE NAME =	USER NAME = steedpe	DESIGNED -	REVISED -	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	<b>ROADWAY AND PAVEMENT MARKING PLANS</b>			F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
c:\pwork\pwork\stedpe\d0293334\0127	12-sht-plan.dgn	DRAWN -	REVISED -		F.A.P. 343/ IL 68 (DUNDEE RD.)-IL 59 (HAWTHORNE RD.) TO US 12	343	(70 & 3045)RS-2	COOK	57	17		
	PLOT SCALE = 100.0000 / in.	CHECKED -	REVISED -		SCALE: 1"=50'	SHEET	OF	SHEETS	STA. 452+00	TO STA. 482+00	CONTRACT NO. 60T02	
	PLOT DATE = 6/13/2014	DATE -	REVISED -		ILLINOIS FED. AID PROJECT							