

SCHEDULE OF QUANTITIES

DITCH PROTECTION						
STATION	TO	STATION	SIDE	WIDTH (FEET)	28100107	28200200
					STONE RIPRAP CLASS A4 (SQ YD)	FILTER FABRIC FOR USE W/ RIPRAP (SQ YD)
250+22	TO	250+31	LT	9.0	9.0	9.0
152+28	TO	152+53	RT	20.0	75.7	75.7
152+28	TO	152+53	LT	25.0	69.4	69.4
166+47	TO	166+72	RT	20.0	33.3	33.3
166+47	TO	166+72	LT	25.0	69.4	69.4
190+44	TO	190+62	LT	13.0	26.0	26.0
TOTAL=					282.8	282.8
ROUNDED TOTAL=					283.0	283.0

60300305 FRAMES AND LIDS TO BE ADJUSTED		
STATION	OFFSET	EACH
243+71.00	2' LT	1.0
179+20.00	21' RT	1.0
183+03.00	21' RT	1.0
TOTAL =		3.0

60266600 VALVE BOXES TO BE ADJUSTED			
LOCATION	STATION	OFFSET	EACH
FAP 693	231+51.30	3' RT	1.0
FAP 693	240+73.80	2' RT	1.0
FAP 693	244+00.00	5' RT	1.0
CH 22	80+45.00	51' RT	1.0
TRINITY LN	65+10.00	38' LT	1.0
TOTAL =			5.0

XZ193400 SURVEY MARKER, TYPE 2 (SPECIAL)			
DESCRIPTION	STATION	EXISTING TYPE	EACH
PC	239+70.25	MAG NAIL	1.0
PI	243+69.94	MAG NAIL	1.0
POT	250+50.00	I.P. W/ CAP	1.0
POT	150+56.32	MAG NAIL	1.0
KINK	174+49.00	DISK	1.0
KINK	183+99.97	MAG NAIL	1.0
KINK	204+00.00	VAULT	1.0
POT	241+99.80	MAG NAIL	1.0
TOTAL =			8.0

Z0070100 SURVEY MONUMENT COVER ASSEMBLY			
DESCRIPTION	STATION	OFFSET	EACH
SECTION CORNER	244+23.27	21.8278' LT	1.0
SECTION CORNER	204+02.93	7.3217' LT	1.0
SECTION CORNER	177+71.48	7.7404' LT	1.0
SECTION CORNER	177+34.06	7.7457' LT	1.0
TOTAL =			4.0

WORK ZONE PAVEMENT MARKING							
LOCATION	STATION	TO	STATION	# OF LINES	LENGTH (FOOT)	70301000	70301000
						SHORT-TERM PAVEMENT MARKING (3-APPS) (FOOT)	WORKZONE PAVEMENT MARKING REMOVAL AREA (SQ FT)
MAINLINE - 4" SKIP-DASH LINES (WHITE)							
E.B.	229+63	TO	230+44	1.0	8	24	3
E.B.	231+69	TO	243+76	1.0	121	362	40
E.B.	244+83	TO	250+50	1.0	57	170	19
STATION EQUATION	250+50 (BK)	=	150+56 (AH)				
E.B.	150+56	TO	157+00	1.0	64	193	21
E.B.	158+20	TO	183+11	1.0	249	747	83
E.B.	184+22	TO	198+64	1.0	144	433	48
W.B.	229+23	TO	230+44	1.0	12	36	4
W.B.	231+69	TO	243+76	1.0	121	362	40
W.B.	244+83	TO	250+50	1.0	57	170	19
STATION EQUATION	250+50 (BK)	=	150+56 (AH)				
W.B.	150+56	TO	156+84	1.0	63	188	21
W.B.	158+13	TO	183+11	1.0	250	749	83
W.B.	184+22	TO	203+15	1.0	189	568	63
W.B.	204+77	TO	209+55	1.0	48	143	16
SUBTOTAL=						4,147	460
MAINLINE - 4" SOLID (WHITE)							
E.B.	229+63	TO	230+15	1.0	5	16	2
E.B.	239+18	TO	243+75	1.0	46	137	15
E.B.	153+34	TO	157+00	1.0	37	110	12
E.B.	153+34	TO	156+70	1.0	34	101	11
E.B.	178+00	TO	183+08	1.0	51	152	17
E.B.	198+64	TO	203+14	1.0	45	135	15
E.B.	198+64	TO	202+93	1.0	43	129	14
W.B.	231+67	TO	233+50	1.0	18	55	6
W.B.	245+19	TO	247+19	1.0	20	60	7
W.B.	158+15	TO	160+22	1.0	21	62	7
W.B.	158+15	TO	160+31	1.0	22	65	7
W.B.	184+23	TO	186+27	1.0	20	61	7
W.B.	184+23	TO	186+27	1.0	20	61	7
W.B.	204+55	TO	207+80	1.0	32	97	11
E.B. SHOULDER	231+47	TO	250+50	1.0	76	228	25
STATION EQUATION	250+50 (BK)	=	150+56 (AH)				
E.B. SHOULDER	150+56	TO	156+26	1.0	23	68	8
E.B. SHOULDER	158+17	TO	182+40	1.0	97	291	32
E.B. SHOULDER	184+30	TO	202+43	1.0	73	218	24
W.B. SHOULDER	229+63	TO	243+14	2.0	108	324	36
W.B. SHOULDER	245+53	TO	250+50	1.0	20	60	7
STATION EQUATION	250+50 (BK)	=	150+56 (AH)				
W.B. SHOULDER	150+56	TO	156+80	1.0	45	134	15
W.B. SHOULDER	158+50	TO	182+86	1.0	97	292	32
W.B. SHOULDER	184+63	TO	202+15	1.0	70	210	23
SUBTOTAL=						3,067	340

CONTINUED ON NEXT PAGE