

INDEX OF SHEETS

| SHEET NO. | DESCRIPTION |
|-----------|---|
| 1 | COVER SHEET |
| 2 | SIGNATURE SHEET |
| 3 | INDEX OF SHEETS, HIGHWAY STANDARDS, & MIXTURE REQUIREMENTS |
| 4 | GENERAL NOTES & COMMITMENTS |
| 5-6 | SUMMARY OF QUANTITIES |
| 7-8 | TYPICAL SECTIONS |
| 9 | RESURFACING SCHEDULE |
| 10 | PAVEMENT MARKING SCHEDULE |
| 11 | STANDARD DETAIL - UNEVEN LANES SIGN |
| 12 | STANDARD DETAIL - ROUGH GROOVED SURFACE SIGN |
| 13 | STANDARD DETAIL - TEMP HOT-MIX ASPHALT TRANSITIONS HIGHWAY STANDARDS |

HIGHWAY STANDARDS

| | |
|-----------|-----------|
| 000001-06 | 701301-04 |
| 001006 | 701306-03 |
| 442201-03 | 701311-03 |
| 642006 | 701336-06 |
| 701001-02 | 701901-03 |
| 701006-05 | 780001-04 |
| 701011-04 | 781001-03 |

MIXTURE REQUIREMENTS

| | |
|---|--|
| LOCATIONS | HOT-MIX ASPHALT SURFACE COURSE |
| MIXTURE USE(S): | HOT-MIX ASPHALT SURFACE COURSE, MIX C, N90 |
| AC/PG: | PG64-22 |
| ABR % (MAX): | SEE SPECIAL PROVISION |
| DESIGN AIR VOIDS: | 4.0 %, 90 GYRATION DESIGN |
| MIXTURE COMPOSITION: (GRADATION MIXTURE) | IL-9.5 MM |
| FRICTION AGGREGATE: | C SURFACE |
| QUALITY MANAGEMENT PROGRAM: | OCP |

| | |
|---|---|
| LOCATIONS | HOT-MIX ASPHALT LEVELING BINDER COURSE |
| MIXTURE USE(S): | HOT-MIX ASPHALT LEVELING BINDER, N90, IL-9.5MM FINE GRADE |
| AC/PG: | PG64-22 |
| ABR % (MAX): | SEE SPECIAL PROVISION |
| DESIGN AIR VOIDS: | 4.0 %, 90 GYRATION DESIGN |
| MIXTURE COMPOSITION: (GRADATION MIXTURE) | IL-9.5MM FINE GRADE |
| FRICTION AGGREGATE: | NONE |
| QUALITY MANAGEMENT PROGRAM: | OCP |

| | |
|---|--|
| LOCATIONS | PAVEMENT PATCHING |
| MIXTURE USE(S): | HOT-MIX ASPHALT BINDER COURSE, N90, IL-19.0MM FINE GRADE |
| AC/PG: | PG64-22 |
| ABR % (MAX): | SEE SPECIAL PROVISION |
| DESIGN AIR VOIDS: | 4.0 %, 90 GYRATION DESIGN |
| MIXTURE COMPOSITION: (GRADATION MIXTURE) | IL-19.0MM FINE GRADE |
| FRICTION AGGREGATE: | NONE |
| QUALITY MANAGEMENT PROGRAM: | OC/OA |

| | |
|---|--|
| LOCATIONS | HOT-MIX ASPHALT SHOULDERS |
| MIXTURE USE(S): | HOT-MIX ASPHALT SURFACE COURSE, MIX C, N90 |
| AC/PG: | PG64-22 |
| ABR % (MAX): | SEE SPECIAL PROVISION |
| DESIGN AIR VOIDS: | 4.0 %, 90 GYRATION DESIGN |
| MIXTURE COMPOSITION: (GRADATION MIXTURE) | IL-9.5 MM |
| FRICTION AGGREGATE: | C SURFACE |
| QUALITY MANAGEMENT PROGRAM: | OC/OA |

| | | | | | | | | | | | | |
|--------------------------------------|-------------------------|------------|-----------|---|---|---------------------------------|--------------------------|---|-------------|-----------------------|-------------------|--|
| FILE NAME * | USER NAME * Stoverpg | DESIGNED - | REVISED - | STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION | INDEX OF SHEETS, HIGHWAY STANDARDS, & MIXTURE REQUIREMENTS | | F.A.P. RTE. 881 | SECTION 34RS-6 | COUNTY * | TOTAL SHEETS 13 | SHEET NO. 3 | |
| c:\pwork\pndot\stoverpg\d8383763\784 | 7-shh-plen.dgn | DRAWN - | REVISED - | | SCALE: _____ | SHEET NO. _____ OF _____ SHEETS | STA. _____ TO STA. _____ | ILLINOIS FED. AID PROJECT CONTRACT NO. 7B417 | | | | |
| | PLDT SCALE * 1/8"=1'-0" | CHECKED - | REVISED - | | | | | | | | | |
| | PLDT DATE * 6/12/2014 | DATE - | REVISED - | | | | | | | | | |