



PROPOSED DRAINAGE IMPROVEMENTS

STRUCT NUMBER	STATION	OFFSET	EXIST. RIM ELEV.	PROP. RIM ELEV.	INVERT ELEV.	PROPOSED TREATMENT
1	98+06.78	17.3' RT.	699.20	699.15	691.50 E; 691.60 W	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
2	98+07.03	17.7' LT.	699.20	699.15	691.50 E; 691.60 W	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
3	98+14.43	0.4' RT.	699.44	699.55	693.44 S	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
4	98+56.72	33.4' RT.	698.87	699.23	UNKNOWN	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
5	98+69.22	47.3' RT.	698.75	699.05	685.65 S; 684.35 E; 684.35 W	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
6	98+79.22	32.6' LT.	698.83	699.48	692.53 S	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
7	99+33.96	19.1' RT.	699.54	700.39	691.04 E; 691.14 W	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
8	99+38.03	18.5' LT.	699.54	700.45	691.04 E; 691.14 W	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
9	100+64.19	34.0' RT.	699.75	700.48	695.35 N; 695.35 S	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
10	100+68.39	0.5' RT.	700.18	701.13	695.98 S	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
11	100+69.00	34.8' LT.	699.59	700.44	693.59 N	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
12	101+93.43	33.4' LT.	699.73	700.03	693.33 N; 693.63 S	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
13	101+94.45	33.5' RT.	699.83	700.02	695.93 N	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)
14	102+07.33	37.8' LT.	699.68	700.35	691.65 E; 691.35 W	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)

NOTE:

RIM ELEVATIONS & OFFSETS FOR DRAINAGE STRUCTURES CONSTRUCTED IN CONJUNCTION WITH GUTTER OR CURB & GUTTER ARE CALLED OUT TO THE EDGE OF THE GUTTER PAN. ALL OTHER DRAINAGE STRUCTURES ARE CALLED OUT TO THE CENTER OF THE STRUCTURE.

PROPOSED STORM SEWER FROM [8] TO EXISTING OUTLET
 CLASS A TYPE 2 - 24" DIA.
 U.S. INV. = 691.04; D.S. INV. = SET TO EXISTING OUTLET

