



- DEVELOPMENT PLAN NOTES:**
- 5' CONCRETE PAD. SCORE WALK IN 5' MODULES OR AS SHOWN AND PROVIDE 1/2" EXPANSION JOINTS AS SHOWN. BACKFILL WALK WHERE APPLICABLE WITH TOPSOIL BY AN APPROVED METHOD.
 - MEET EXISTING PAVEMENT ELEVATION WITH NEW BITUMINOUS CONCRETE PAVEMENT AND RELOCATED PAVERS. ALL PAVEMENT TRANSITIONS SHALL BE SMOOTH AND SUBTLE. ANY ABRUPT OR NOTICEABLE ELEVATION CHANGES SHALL BE REMOVED OR REPAIRED AT NO ADDITIONAL EXPENSE TO THE PARK DISTRICT.
 - CONCRETE CURB AND PAD. EXCAVATE TO SUBGRADES INDICATED AND INSTALL NEW CONC. PITCH WALKWAY AT A MIN. 1% IN THE DIRECTION OF THE DRAINAGE PATTERN SHOWN. BACKFILL WALK WITH TOPSOIL & BLEND INTO SURROUNDING GRADE.
 - EXCAVATE TO SUBGRADES SHOWN AND INSTALL EXISTING PAVERS, PAVING PATTERN & ALIGNMENT, AND CORNER TREATMENT TO MATCH EXISTING CONDITIONS. CONTRACTOR IS RESPONSIBLE TO VERIFY ALL DIMENSIONS AND LAYOUT OF EXISTING PAVERS. CONTRACTOR TO SUPPLEMENT ADDITIONAL PAVERS AS NECESSARY.
 - REINSTALL EXISTING BENCH IN NEW PAVEMENT AREA AS SHOWN. MATCH EXISTING ATTACHMENT METHODS.
 - ALL ITEMS TO BE REUSED ARE TO BE STORED ON-SITE, WITHIN THE CONSTRUCTION FENCING LIMITS.
 - EXISTING PAVEMENT TO BE PROTECTED DURING CONSTRUCTION WITH ANY DAMAGE TO BE REPAIRED BY CONTRACTOR AT HIS EXPENSE. PEDESTRIAN WALKS TO REMAIN OPEN AND FREE OF CONSTRUCTION DEBRIS AT ALL TIMES WITHIN REASON. DURING SUCH TIMES THAT PEDESTRIAN WALKS NEED TO BE CLOSED, THE CONTRACTOR SHALL PROVIDE CONSTRUCTION FENCING TO PROTECT THE SAFETY OF THE RESIDENTS AND TO MAINTAIN THE TRAFFIC FLOW.

DEVELOPMENT PLAN	REVISIONS
	DATE:
SUBMITTAL	

FIREMEN'S MEMORIAL
Naperville, Illinois

REVIEWED BY:	APPROVED BY:	DESIGNED/DRAWN BY:	PROJECT NO.:
		BCL	F20164-01

PLANNING RESOURCES, INC.
Date: 10.06.05

Drawing
SD3.0
Development Plan

SD3.0

DEVELOPMENT PLAN

Scale: 1"=5'-0"

