TRAFFIC SIGNAL LEGEND

ITEM	DEMONIA	EVICTIVA	DDODOGEO	ITCH	DEMON	EVICTION	DDAGGGG	1754	DEMON	PUICETIO	DDODGGG
<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL R≪	EXISTING	PROPOSED	ITEM ELECTRIC CABLE IN CONDUIT, TRACER,	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	\bowtie^R	\boxtimes		EMERGENCY VEHICLE LIGHT DETECTOR		≪	◄	NO. 14 1/C, UNLESS NOTED OTHERWISE			—1)—
RAILROAD CONTROL CABINET	R		▶-€	CONFIRMATION BEACON	Ro-Q	0 −0	н	COAXIAL CABLE		−© −	—©—
COMMUNICATIONS CABINET MASTER CONTROLLER	CC	E C C	СС	HANDHOLE	R _□			Absolutions State of Capus of Suit		,	O
MASTER MASTER CONTROLLER		EMC EMMC	MC	HEAVY DUTY HANDHOLE	R	H	H	VENDOR CABLE FOR CAMERA		_ V	
UNINTERRUPTABLE POWER SUPPLY	UPS R	EUPS	UPS]	DOUBLE HANDHOLE	R		N.	COPPER INTERCONNECT CABLE,		<u> </u>	-6-
SERVICE INSTALLATION.		-o-º	- = P	JUNCTION BOX	R		0	NO. 18 3 PAIR TWISTED, SHIELDED		~	
P) POLE OR (G) GROUND MOUNT	-□ ^R	-11-	-	UNDERGROUND CONDUIT,				FIBER OPTIC CABLE NO. 62.5/125, MM12F		— <u>(12F</u>)—	
FELEPHONE CONNECTION P) POLE OR (G) GROUND MOUNT	R	P	P	GALVANIZED STEEL (UC) TEMPORARY SPAN WIRE, TETHER WIRE,	P			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		- <u>24</u> F-	—24F—
STEEL MAST ARM ASSEMBLY AND POLE	R _O	0	•	AND CABLE			S 	NO. 62.37123, MM12F SM12F		×	
LUMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			ст	FIBER OPTIC CABLE NO. 62.5/125, MM12F SM24F		— <u>36F</u> —	—(36F)—
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH LUMINAIRE	^R o-≭—	0-32	• ×	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	GROUND ROD AT (C) CONTROLLER.			
STEEL COMBINATION MAST ARM	R	0	•	SYSTEM ITEM		S	S	(H) HANDHOLE, (P) POST, (M) MAST ARM,		C	c _i l →
SSEMBLY AND POLE WITH PTZ CAMERA	門立	配	PU	INTERSECTION ITEM	55	I	IP	OR (S) SERVICE CONTROLLER CABINET AND	RCF		
IGNAL POST	RO	0	•	REMOVE ITEM RELOCATE ITEM	R			FOUNDATION TO BE REMOVED			
EMPORARY WOOD POLE (CLASS 5 OR ETTER) 45 FOOT (13.7m) MINIMUM	$\stackrel{R}{\otimes}$	8	•	ABANDON ITEM	A			STEEL MAST ARM POLE AND	RMF		
UY WIRE	>R	>	\succ	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	FOUNDATION TO BE REMOVED	0		
GNAL HEAD	R	>	-			R	_	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
IGNAL HEAD CONSTRUCTION STAGES NUMBERS INDICATE THE CONSTRUCTION STAGE)			→ ²	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF O-X		
IGNAL HEAD WITH BACKPLATE	+C ^R	+1>	+-			R	R	FOUNDATION TO BE REMOVED			
IGNAL HEAD OPTICALLY PROGRAMMED	R →⊃"P"	—⊳′′p′′	→ "P"	SIGNAL FACE			G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RPF		
ASHER INSTALLATION DENOTES SOLAR POWER)	R O-D″F″	O- ⊳ ″F″	• > "F"			* Y Y Y Y Y Y Y Y Y Y	∢Υ ∢G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR			IS
EDESTRIAN SIGNAL HEAD	R -	-0	4			R	R	SAMPLING (SYSTEM) DETECTOR		[s]	S
EDESTRIAN PUSHBUTTON DETECTOR	R _©	©	©	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			Y G	QUEUE DETECTOR		[0]	
CCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R aps	@APS	@ APS	"RB" INDICATES REFLECTIVE BACKPLATE			← Y ← G				٥
LUMINATED SIGN	R S	8	•			"P"	"P"	PREFORMED QUEUE DETECTOR		[PO]	PO
NO LEFT TURN"	<u> </u>	Cy.	<u>V</u>	12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		(W)		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
LUMINATED SIGN NO RIGHT TURN"	R	8	®	12" (300mm) PEDESTRIAN SIGNAL HEAD				PREFORMED SAMPLING (SYSTEM) DETECTOR		PS]	PS
ETECTOR LOOP, TYPE I		[7]		INTERNATIONAL SYMBOL, OUTLINED			p to that to be	The string strin		1, 7	11
REFORMED DETECTOR LOOP		1-P	P	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID			*	RAILROAD	SVMRO	210	
	R	7		PEDESTRIAN SIGNAL HEAD, INTERNATIONAL		55-25C		MAILIIVAL	, GIIVIDO	LU	
ICROWAVE VEHICLE SENSOR	R MD	M	M	SYMBOL, WITH COUNTDOWN TIMER		● C ★ D	₽ C ★ D			EXISTING	PROPOSED
IDEO DETECTION CAMERA	R [√b	(V)	(RADIO INTERCONNECT	##*O			RAILROAD CONTROL CABINET			
IDEO DETECTION ZONE				DANIO DEDEATED	100	-	**************************************	RAILROAD CANTILEVER MAST ARM	2	XOX X	IOI I
N. TV.T. 700V 0	R			RADIO REPEATER	RERR	ERR	RR	FLASHING SIGNAL		X0X	X-X
AN, TILT, ZOOM CAMERA	配	PIZ	PTZ#	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,		-5-	_ 5 <u></u> -	CROSSING GATE		X0X>	XOX-
IRELESS DETECTOR SENSOR	RW	(W)	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED							
IRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)			(1)	CROSSBUCK		≥ ≤	*
E NAME = USER NAME = footemj		SIGNED - DAG/BCK		- DAG 1-1-14	OF 111115	•		DISTRICT ONE	F.A RTE.	SECTION	COUNTY TOTAL SHEETS
w_work\pwidot\footemj\d0108315\ts05.dgn PLOT SCALE = 50.0000 '/	DR		- BCK REVISED - DAD REVISED	STATE	OF ILLINOIS	5		STANDARD TRAFFIC SIGNAL DESIGN DETAILS		2014-044TS	COOK 65