

| SHOULDER IMPROVEMENTS  |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
|--|-----------|----|-----|-----------|-----------------------------|--------------------------|---------------|---------------|---------------|---------------|------|--|--|--|--|--|--|--|---|-------------------------------------|---|--|--|--|---------------|
| BITUMINOUS MATERIAL (PRIME COAT) RATE - 0.05 LB / SQ FT<br>BITUMINOUS SURFACE / BINDER (112 LBS) RATE - 0.056 T / SY • IN<br>AGGREGATE (SURFACE, BASE, SUBBASE) RATE - 2.05 T / CY |           |    |     |           |                             |                          |               |               |               |               |      | 20200600<br>EXC &<br>GRAD EX<br>SHOULDER | 40600285<br>POLY BIT<br>MATERIALS<br>(PRIME<br>COAT) | 48203100<br>HMA<br>SHOULDERS<br>MIX "C", N50<br>d = 2" | 44000152<br>HMA<br>SURFACE<br>REMOVAL,<br>3/4" | 44000155<br>HMA<br>SURFACE<br>REMOVAL,<br>1 1/2" | 44000157<br>HMA<br>SURFACE<br>REMOVAL,<br>2" | 44004250<br>PAVED<br>SHOULDER<br>REMOVAL | 48102100<br>AGG<br>WEDGE<br>SHLD<br>TY, B | 48203029<br>HMA<br>SHOULDERS,<br>8" | 64200116<br>SHLD<br>RUMB<br>STRIP,<br>16 INCH | X0320157<br>CLEAN<br>UNDER-<br>DRAIN<br>OUTLETS<br>(THEOR) | X0322279<br>OUTLET<br>MARKERS<br>(THEOR) | X4820110<br>HMA SHLD<br>REM & REPL<br>(SPECIAL)<br>(ANTICIPATED) |               |
| LOCATION   |           |    |     |           | LENGTH                      | HMA                      |               | HMA REM       | AGGREGATE     |               | UNIT | POUND                                    | TON  | SQ YD  | SQ YD  | SQ YD  | SQ YD  | TON                                      | SQ YD                                     | FOOT                                | EACH  | EACH   | SQ YD                                    |  |               |
| STATION TO STATION   |           |    |     |           | FOOT                        | WIDTH<br>FOOT            | AREA<br>SQ YD | DEPTH<br>INCH | WIDTH<br>FOOT | DEPTH<br>INCH |      |  |  |  |  |  |  |  |   |                                     |   |  |  | WIDTH<br>FOOT  | DEPTH<br>INCH |
| I-55 NB (R001)   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 380+57.30 | TO | STA | 445+62.78 | OUTSIDE STATION BREAK       | 6,505.48                 | 10.0          | 7,228.31      | 1.5           | 3.0           | 3.0  | -  | 3,252.74   | 809.57   | -  | 7,228.31   | -  | -  | 370.45                                    | -                                   | 6,505.48                                      | 13   | 13                                       |  |               |
| STA  | 380+57.30 | TO | STA | 398+93.27 | MEDIAN                      | 1,835.97                 | 10.0          | 2,039.97      | 1.5           | 3.0           | 3.0  | -  | 917.98   | 228.48   | -  | 2,039.97   | -  | -  | 104.55                                    | -                                   | 1,835.97                                      | 4  | 4  |  |               |
| STA  | 398+95.73 | TO | STA | 426+04.36 | MEDIAN                      | 2,708.63                 | 6.0           | 1,805.75      | 1.5           | 3.0           | 3.0  | -  | 812.59   | 202.24   | -  | 1,805.75   | -  | -  | 154.24                                    | -                                   | 2,708.63                                      | 5  | 5  |  |               |
| GORE   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| I-55 NB TO I-155 NB (R002, R002A)  |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 01+15.00  | TO | STA | 15+23.48  | MEDIAN OMIT SN 054-0051     | 1,408.48                 | 6.0           | 938.99        | 1.5           | 3.0           | 3.0  | -  | 422.54   | 105.17   | -  | 938.99   | -  | -  | 80.21                                     | -                                   | 1,408.48                                      | 3  | 3  |  |               |
| STA  | 01+15.00  | TO | STA | 15+72.28  | OUTSIDE OMIT SN 054-0051    | 1,457.28                 | 10.0          | 1,619.20      | 1.5           | 3.0           | 3.0  | -  | 728.64   | 181.35   | -  | 1,619.20   | -  | -  | 82.98                                     | -                                   | 1,457.28                                      | 3  | 3  |  |               |
| I-55 SB TO I-155 NB (R005)   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| ON RAMP (NO STATION)   |           |    |     |           | OUTSIDE                     | 606.49                   | 6.0           | 404.33        | 1.5           | 3.0           | 3.0  | -  | 181.95   | 45.28  | -  | 404.33   | -  | -  | 34.54                                     | -                                   | 606.49  | 1  | 1  |  |               |
| GORE   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| I-55 SB (A003, A004, R003)   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 379+87.59 | TO | STA | 387+92.82 | MEDIAN                      | 805.23                   | 10.0          | 894.70        | 1.5           | 3.0           | 3.0  | -  | 402.62   | 100.21   | -  | 894.70   | -  | -  | 45.85                                     | -                                   | 805.23  | 2  | 2  |  |               |
| STA  | 379+87.59 | TO | STA | 385+77.02 | OUTSIDE                     | 589.43                   | 10.0          | 654.92        | 1.5           | 3.0           | 3.0  | -  | 294.72   | 73.35  | -  | 654.92   | -  | -  | 33.56                                     | -                                   | 589.43  | 1  | 1  |  |               |
| STA  | 387+92.82 | TO | STA | 395+84.52 | MEDIAN CHAIN BREAK          | 791.70                   | 6.0           | 527.80        | 1.5           | 3.0           | 3.0  | -  | 237.51   | 59.11  | -  | 527.80   | -  | -  | 45.08                                     | -                                   | 791.70  | 2  | 2  |  |               |
| STA  | 45+25.71  | TO | STA | 00+00.00  | MEDIAN CHAIN BREAK          | 4,525.71                 | 6.0           | 3,017.14      | 1.5           | 3.0           | 3.0  | -  | 1,357.71   | 337.92   | -  | 3,017.14   | -  | -  | 257.71                                    | -                                   | 4,525.71                                      | 9  | 9  |  |               |
| STA  | 452+88.81 | TO | STA | 465+56.26 | MEDIAN                      | 1,267.45                 | 6.0           | 844.97        | 1.5           | 3.0           | 3.0  | -  | 380.24   | 94.64  | -  | 844.97   | -  | -  | 72.17                                     | -                                   | 1,267.45                                      | 3  | 3  |  |               |
| STA  | 460+30.85 | TO | STA | 460+84.56 | OUTSIDE STATION BREAK       | 53.71                    | 6.0 TO 10.0   | 47.74         | 1.5           | 3.0           | 3.0  | -  | 21.48  | 5.35   | -  | 47.74  | -  | -  | 3.06                                      | -                                   | 53.71   | -  | -  |  |               |
| STA  | 460+84.56 | TO | STA | 465+56.26 | OUTSIDE STATION BREAK       | 471.70                   | 10.0          | 524.11        | 1.5           | 3.0           | 3.0  | -  | 235.85   | 58.70  | -  | 524.11   | -  | -  | 26.86                                     | -                                   | 471.70  | 1  | 1  |  |               |
| STA  | 43+41.63  | TO | STA | 00+00.00  | OUTSIDE CHAIN BREAK         | 4,341.63                 | 10.0          | 4,824.03      | 1.5           | 3.0           | 3.0  | -  | 2,170.82   | 540.29   | -  | 4,824.03   | -  | -  | 247.23                                    | -                                   | 4,341.63                                      | 9  | 9  |  |               |
| STA  | 452+88.81 | TO | STA | 454+27.46 | OUTSIDE                     | 138.65                   | 10.0          | 154.06        | 1.5           | 3.0           | 3.0  | -  | 69.33  | 17.25  | -  | 154.06   | -  | -  | 7.90                                      | -                                   | 138.65  | -  | -  |  |               |
| GORE   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| I-155 SB TO I-55 NB (R004, R006)   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 18+28.12  | TO | STA | 34+44.61  | OUTSIDE                     | 1,616.49                 | 4.0           | 718.44        | 1.5           | 3.0           | 3.0  | -  | 323.30   | 80.47  | -  | 718.44   | -  | -  | 92.05                                     | -                                   | 1,616.49                                      | 3  | 3  |  |               |
| STA  | 18+43.80  | TO | STA | 37+35.58  | MEDIAN CHAIN BREAK          | 1,891.78                 | 6.0           | 1,261.19      | 1.5           | 3.0           | 3.0  | -  | 567.53   | 141.25   | -  | 1,261.19   | -  | -  | 107.73                                    | -                                   | 1,891.78                                      | 4  | 4  |  |               |
| STA  | 428+92.88 | TO | STA | 445+62.78 | MEDIAN STATION BREAK        | 1,669.90                 | 6.0           | 1,113.27      | 1.5           | 3.0           | 3.0  | -  | 500.97   | 124.69   | -  | 1,113.27   | -  | -  | 95.09                                     | -                                   | 1,669.90                                      | 3  | 3  |  |               |
| GORE   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| I-55 NB (I55, A004)  |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 465+56.26 | TO | STA | 533+29.96 | MEDIAN OMIT SN 054-0053     | 6,773.70                 | 6.0           | 4,515.80      | 1.5           | 3.0           | 3.0  | -  | 2,032.11   | 505.77   | -  | 4,515.80   | -  | -  | 385.72                                    | -                                   | 6,773.70                                      | 14   | 14                                       |  |               |
| STA  | 465+56.26 | TO | STA | 532+97.99 | OUTSIDE OMIT SN 054-0053    | 6,741.73                 | 10.0          | 7,490.81      | 1.5           | 3.0           | 3.0  | -  | 3,370.87   | 838.97   | -  | 7,490.81   | -  | -  | 383.90                                    | -                                   | 6,741.73                                      | 13   | 13                                       |  |               |
| STA  | 540+35.82 | TO | STA | 554+83.64 | MEDIAN OMIT SN 054-0055     | 1,447.82                 | 6.0           | 965.21        | 1.5           | 3.0           | 3.0  | -  | 434.35   | 108.10   | -  | 965.21   | -  | -  | 82.45                                     | -                                   | 1,447.82                                      | 3  | 3  |  |               |
| STA  | 540+35.82 | TO | STA | 554+83.64 | OUTSIDE OMIT SN 054-0055    | 1,447.82                 | 10.0          | 1,608.69      | 1.5           | 3.0           | 3.0  | -  | 723.91   | 180.17   | -  | 1,608.69   | -  | -  | 82.45                                     | -                                   | 1,447.82                                      | 3  | 3  |  |               |
| STA  | 562+33.86 | TO | STA | 575+70.23 | MEDIAN OMIT SN 054-0057     | 1,336.37                 | 6.0           | 890.91        | 1.5           | 3.0           | 3.0  | -  | 400.91   | 99.78  | -  | 890.91   | -  | -  | 76.10                                     | -                                   | 1,336.37                                      | 3  | 3  |  |               |
| STA  | 562+33.86 | TO | STA | 575+70.23 | OUTSIDE OMIT SN 054-0057    | 1,336.37                 | 10.0          | 1,484.86      | 1.5           | 3.0           | 3.0  | -  | 668.19   | 166.30   | -  | 1,484.86   | -  | -  | 76.10                                     | -                                   | 1,336.37                                      | 3  | 3  |  |               |
| STA  | 577+98.08 | TO | STA | 696+51.35 | MEDIAN OMIT SN 054-0061     | 11,853.27                | 6.0           | 7,902.18      | 1.5           | 3.0           | 3.0  | -  | 3,555.98   | 885.04   | -  | 7,902.18   | -  | -  | 674.98                                    | -                                   | 11,853.27                                     | 24   | 24                                       |  |               |
| STA  | 577+98.08 | TO | STA | 696+51.35 | OUTSIDE OMIT SN 054-0061    | 11,853.27                | 10.0          | 13,170.30     | 1.5           | 3.0           | 3.0  | -  | 5,926.64   | 1,475.07   | -  | 13,170.30  | -  | -  | 674.98                                    | -                                   | 11,853.27                                     | 24   | 24                                       |  |               |
| STA  | 702+43.49 | TO | STA | 790+97.21 | BK MEDIAN                   | 8,853.72                 | 6.0           | 5,902.48      | 1.5           | 3.0           | 3.0  | -  | 2,656.12   | 661.08   | -  | 5,902.48   | -  | -  | 504.17                                    | -                                   | 8,853.72                                      | 18   | 18                                       |  |               |
| GORE STA 705+19.55   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 706+29.71 | TO | STA | 716+48.41 | OUTSIDE                     | 1,018.70                 | 10.0          | 1,131.89      | 1.5           | 3.0           | 3.0  | -  | 509.35   | 126.77   | -  | 1,131.89   | -  | -  | 58.01                                     | -                                   | 1,018.70                                      | 2  | 2  |  |               |
| GORE STA 716+46.71   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 727+57.24 | TO | STA | 790+97.21 | BK OUTSIDE                  | 6,339.97                 | 10.0          | 7,044.41      | 1.5           | 3.0           | 3.0  | -  | 3,169.99   | 788.97   | -  | 7,044.41   | -  | -  | 361.03                                    | -                                   | 6,339.97                                      | 13   | 13                                       |  |               |
| STA  | 184+93.0  | AH | TO  | STA       | 280+98.86                   | MEDIAN OMIT SN 054-0063  | 9,605.86      | 6.0           | 6,403.91      | 1.5           | 3.0  | 3.0                                      | -  | 2,881.76   | 717.24   | -  | 6,403.91                                     | -  | -   | 547.00                              | -   | 9,605.86   | 19                                       | 19   |               |
| STA  | 184+93.0  | AH | TO  | STA       | 281+08.56                   | OUTSIDE OMIT SN 054-0063 | 9,615.56      | 10.0          | 10,683.96     | 1.5           | 3.0  | 3.0                                      | -  | 4,807.78   | 1,196.60                                       | -  | 10,683.96                                    | -  | -   | 547.55                              | -   | 9,615.56   | -  | -  |               |
| STA  | 284+15.35 | TO | STA | 456+40.33 | MEDIAN OMIT SN 054-0065     | 17,224.98                | 6.0           | 11,483.32     | 1.5           | 3.0           | 3.0  | -  | 5,167.49   | 1,286.13   | -  | 11,483.32  | -  | -  | 980.87                                    | -                                   | 17,224.98                                     | -  | -  |  |               |
| STA  | 284+25.05 | TO | STA | 456+38.97 | OUTSIDE OMIT SN 054-0065    | 17,213.92                | 10.0          | 19,126.58     | 1.5           | 3.0           | 3.0  | -  | 8,606.96   | 2,142.18   | -  | 19,126.58  | -  | -  | 980.24                                    | -                                   | 17,213.92                                     | -  | -  |  |               |
| STA  | 457+60.45 | TO | STA | 590+00.00 | MEDIAN                      | 13,239.55                | 6.0           | 8,826.37      | 1.5           | 3.0           | 3.0  | -  | 3,971.87   | 988.55   | -  | 8,826.37   | -  | -  | 753.92                                    | -                                   | 13,239.55                                     | -  | -  |  |               |
| STA  | 457+58.34 | TO | STA | 478+95.07 | OUTSIDE ATLANTA INTERCHANGE | 2,136.73                 | 10.0          | 2,374.14      | 1.5           | 3.0           | 3.0  | -  | 1,068.37   | 265.90   | -  | 2,374.14   | -  | -  | 121.67                                    | -                                   | 2,136.73                                      | -  | -  |  |               |
| GORE   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 485+24.89 | TO | STA | 508+30.51 | OUTSIDE                     | 2,305.62                 | 10.0          | 2,561.80      | 1.5           | 3.0           | 3.0  | -  | 1,152.81   | 286.92   | -  | 2,561.80   | -  | -  | 131.29                                    | -                                   | 2,305.62                                      | -  | -  |  |               |
| GORE   |           |    |     |           |                             |                          |               |               |               |               |      |  |  |  |  |  |  |  |   |                                     |   |  |  |  |               |
| STA  | 519+65.42 | TO | STA | 590+00.00 | OUTSIDE                     | 7,034.58                 | 10.0          | 7,816.20      | 1.5           | 3.0           | 3.0  | -  | 3,517.29   | 875.41   | -  | 7,816.20   | -  | -  | 400.58                                    | -                                   | 7,034.58                                      | -  | -  |  |               |

SCHEDULE CONTINUED ON NEXT 3 SHEETS