

63500105 DELINEATORS (EACH)										
LOCATION STATION TO STATION	STANDARD 635001	LENGTH FOOT	CURVE RADIUS FOOT	SPACING FOOT	CRYSTAL		AMBER			
					SINGLE EACH	DOUBLE EACH	SINGLE EACH	DOUBLE EACH	TRIPLE EACH	
I-55 SB (R003, A004)										
STA 45+25.71 TO STA 0+00.00	OUTSIDE	4525.71	2864.75	150.00	30					
STA 622+14.86 TO STA 639+48.18	OUTSIDE	1733.32	7635.91	400.00	4					
STA 675+43.92 TO STA 692+77.24	OUTSIDE	1733.32	7636.63	400.00	4					
STA 708+43.0 TO STA 743+07.77	OUTSIDE	3464.77	2863.92	150.00	23					
STA 761+00.55 TO STA 789+63.83	OUTSIDE	2863.28	7634.43	400.00	7					
STATION EQUATION: 790+97.12 BK = STA 184+93.00 AH										
STA 403+38.86 TO STA 429+92.22	OUTSIDE	2653.36	4582.89	400.00	7					
STA 453+88.01 TO STA 477+74.85	OUTSIDE	2386.84	3819.92	175.00	14					
STA 513+89.55 TO STA 539+22.87	OUTSIDE	2533.32	3819.25	175.00	14					
STA 549+92.23 TO STA 577+01.85	OUTSIDE	2709.62	3818.67	175.00	15					
I-55 NB (R001, A004)										
STA 380+57.30 TO STA 397+79.40	OUTSIDE	1722.1	7632.03	400.00	4					
STA 397+79.40 TO STA 445+62.78	OUTSIDE	4783.38	3821.10	175.00	27					
STA 622+14.86 TO STA 639+48.18	OUTSIDE	1733.32	7635.91	400.00	4					
STA 675+43.92 TO STA 692+77.24	OUTSIDE	1733.32	7636.63	400.00	4					
STA 708+43.0 TO STA 743+07.77	OUTSIDE	3464.77	2863.92	150.00	23					
STA 761+00.55 TO STA 789+63.83	OUTSIDE	2863.28	7634.43	400.00	7					
STATION EQUATION: 790+97.12 BK = STA 184+93.00 AH										
STA 403+38.86 TO STA 429+92.22	OUTSIDE	2653.36	4582.89	400.00	7					
STA 453+88.01 TO STA 477+74.85	OUTSIDE	2386.84	3819.92	175.00	14					
STA 513+89.55 TO STA 539+22.87	OUTSIDE	2533.32	3819.25	175.00	14					
STA 549+92.23 TO STA 577+01.85	OUTSIDE	2709.62	3818.67	175.00	15					
I-55 NB TO I-155 NB (R002)										
STA 2+75.00 TO STA 18+23.90	OUTSIDE	1548.9	2883.85	150.00	10					
I-155 SB TO I-55 NB (R004)										
STA 6+20.60 TO STA 23+18.46	OUTSIDE	1697.86	881.63	85.00	20					
BUSINESS 55 INTERCHANGE										
RAMP A										
STA 0+00.00 TO STA 10+08.22	RT	1008.22	-	100.00	10					
STA 10+08.22 TO STA 18+99.36	RT	891.14	504.48	65.00	14					
STA 18+99.36 TO STA 21+36.96	RT	237.6	-	100.00	2					
STA 21+36.96 TO STA 28+43.59	RT	706.63	768.27	80.00	9					
STA 28+43.59 TO STA 38+95.57	RT	1051.98	-	100.00		11				
STA 21+36.96 TO STA 27+59.81	LT	622.85	-	100.00			6			
RAMP B										
STA 2+31.21 TO STA 6+63.99	RT	432.78	-	100.00		4				
STA 6+63.99 TO STA 22+54.11	RT	1590.12	422.838	55.00	29					
STA 6+63.99 TO STA 22+54.11	LT	1590.12	422.838	55.00			29			
STA 22+54.11 TO STA 0+00.00	LT	2254.11	-	100.00			23			
RAMP C										
STA 0+00.00 TO STA 2+81.55	LT	281.55	-	100.00			3			
STA 2+81.55 TO STA 5+56.61	LT	275.06	265.49	40.00			7			
STA 5+56.61 TO STA 7+56.66	LT	200.05	397.83	55.00			4			
STA 7+56.66 TO STA 14+31.87	LT	675.21	774.21	80.00			8			
STA 8+11.69 TO STA 14+31.87	RT	620.18	774.21	80.00	8					
STA 14+31.87 TO STA 18+72.87	RT	441	-	100.00		4				
RAMP D										
STA 0+00.00 TO STA 6+57.57	RT	657.57	-	100.00			7			
STA 6+57.57 TO STA 15+14.38	RT	856.81	763.05	80.00	11					
STA 6+57.57 TO STA 15+14.38	LT	856.81	763.05	80.00			11			
STA 15+14.38 TO STA 23+61.23	LT	846.85	-	100.00			8			

SCHEDULE CONTINUED ->

SCHEDULE CONTINUED

63500105 DELINEATORS (EACH)											
LOCATION STATION TO STATION	STANDARD 635001	LENGTH FOOT	CURVE RADIUS FOOT	SPACING FOOT	CRYSTAL		AMBER				
					SINGLE EACH	DOUBLE EACH	SINGLE EACH	DOUBLE EACH	TRIPLE EACH		
ATLANTA INTERCHANGE											
RAMP A											
STA 0+00.00 TO STA 6+64.61	RT	664.61	-	100.00			7				
STA 6+64.61 TO STA 12+94.69	RT	630.08	765.07	80.00	8						
STA 6+43.73 TO STA 12+94.69	LT	650.96	765.07	80.00			8				
STA 12+94.69 TO STA 15+34.55	LT	239.86	-	100.00			2				
STA 15+34.55 TO STA 21+62.30	LT	627.75	462.85	65.00			10				
STA 21+62.30 TO STA 24+19.00	RT	256.7	-	100.00			3				
RAMP B											
STA 0+00.00 TO STA 2+07.32	LT	207.32	-	100.00			2				
STA 2+07.32 TO STA 8+00.56	LT	593.24	779.78	80.00			7				
STA 2+07.32 TO STA 8+00.56	RT	593.24	779.78	80.00	7						
STA 8+00.56 TO STA 19+73.26	RT	1172.7	-	100.00			12				
RAMP C											
STA 0+00.00 TO STA 6+57.28	RT	657.28	-	100.00			7				
STA 6+57.28 TO STA 13+09.06	RT	651.78	763.68	80.00	8						
STA 6+21.57 TO STA 13+09.06	LT	687.49	763.68	80.00			9				
STA 13+09.06 TO STA 15+49.54	LT	240.48	-	100.00			2				
STA 15+49.54 TO STA 22+32.24	LT	682.7	462.21	65.00			11				
STA 22+32.24 TO STA 24+86.90	LT	254.66	-	100.00			3				
RAMP D											
STA 0+00.00 TO STA 4+61.84	LT	461.84	-	100.00			5				
STA 4+61.84 TO STA 8+88.00	LT	426.16	765	80.00			5				
STA 4+61.84 TO STA 9+80.83	RT	518.99	765	80.00	6						
STA 9+80.83 TO STA 20+32.06	RT	1051.23	-	100.00			11				
MEDIAN CROSS OVERS - NB & SB APPROACH											
STA 486+90.80				500.00			2	2	2		
STA 619+83.13				500.00			2	2	2		
STA 671+25.53				500.00			2	2	2		
STA 762+72.61				500.00			2	2	2		
STATION EQUATION											
STA 250+68.45				500.00			2	2	2		
STA 435+46.20				500.00			2	2	2		
OBSTRUCTIONS - DRAINAGE STRUCTURES											
LOCATION TO BE DETERMINED BY ENGINEER ON THE FIELD											
SUBTOTAL:							383	61	177	132	12
TOTAL:							765				

X6350120 DELINEATOR REMOVAL (EACH)	
LOCATION	QUANTITY
STATION	EACH
I-55 MAINLINE & RAMPS	
JOBSITE	400
TOTAL:	400