

PAVEMENT AND SHOULDER SCHEDULE

LOCATION					LENGTH	WIDTH	AREA	HMA SURFACE REMOVAL 2 1/4"	HMA SURF CSE MIX "D", N90	HMA LEVELING BINDER, N90, IL-9.5MM FG	BIT MAT PRIME COAT	HMA SHLDRS	STRIP REFLECTIVE CRACK CONTROL	TEMPORARY RAMP
					FOOT	FOOT	SQ FT	SQ YD	TON	TON	POUND	TON	FOOT	SQ YD
IL 148														
121+03.	N	TO	120+24.65	N	78.35	30	2350.5	261.2	17.6	8.8	176.3	6.6	156.7	25.0
120+24.65	BK	=	120+36.29	AH										
120+36.29	N	TO	44+00.	N	7636.29	30	229088.7	25454.3	1719.4	861.9	17181.7	641.4	15272.6	
44+00.	N	TO	17+81.	N	2619.00	30	78570.0	8730.0	589.7	295.6	5892.8	220.0	5238.0	
17+81.	N	TO	4+56.	N	1325.00	26	34450.0	3827.8	323.1	161.9	2583.8		2650.0	
4+56.	N	TO	2+76.	N	180.00	32	5760.0	640.0	54.0	27.0	432.0		360.0	
2+76.	N	TO	0+00	N	276.00	36	9936.0	1104.0	93.1	46.6	745.2		552.0	
0+00	N	=	0+00	S										
0+00	S	TO	2+76.	S	276.00	36	9936.0	1104.0	93.1	46.6	745.2		552.0	
2+76.	S	TO	4+56.	S	180.00	31	5580.0	620.0	52.3	26.2	418.5		360.0	
4+56.	S	TO	30+66.	S	2610.00	24	62640.0	6960.0	587.7	294.6	4698.0		5220.0	
30+66.	S	TO	33+06.	S	240.00	31	7440.0	826.7	69.7	34.9	558.0		480.0	
33+06.	S	TO	38+00.	S	494.00	36	17784.0	1976.0	166.6	83.4	1333.8		988.0	
38+00.	S	TO	39+38.	S	138.00	42	5796.0	644.0	46.5	23.3	434.7	11.6	276.0	
39+38.	S	TO	41+78.	S	240.00	36	8640.0	960.0	67.5	33.8	648.0	20.2	480.0	
41+78.	S	TO	91+43.	S	4965.00	30	148950.0	16550.0	1118.0	560.4	11171.3	417.1	9930.0	25.0
TOTAL					21257.64			69658	4998	2505	47019	1317	42515	50