



SCI ENGINEERING, INC.
650 Pierce Boulevard
O'Fallon, Illinois 62269
618-624-6969
www.sciengineering.com

Structure Geotechnical Report

**BRIDGE CONSTRUCTION
PTB 195 ITEM 57
IL - ROUTE 157 (FAP ROUTE 592) OVER JUDY'S BRANCH
MADISON COUNTY, ILLINOIS
SECTION: 51-R
STRUCTURE NO. SN 060-0087 (EXISTING)
STRUCTURE NO. SN 060-0229 (PROPOSED)**


Thomas J. Casey, P.E.
TCasey@SCIEngineering.com
(618) 624-6969
March 27, 2023

**Prepared for:
FUHRMANN ENGINEERING
1022 EASTPORT PLAZA DRIVE
COLLINSVILLE, ILLINOIS 62234
(618) 855-8000**

DocuSigned by:
SCI No. 2020-0531.10

Thomas Casey

E358897B1C3F458





SCI ENGINEERING, INC.

EARTH • SCIENCE • SOLUTIONS

GEOTECHNICAL
ENVIRONMENTAL
NATURAL RESOURCES
CULTURAL RESOURCES
CONSTRUCTION SERVICES

March 23, 2023

Eric M. Lagemann, P.E., S.E.
Fuhrmann Engineering
1022 Eastport Plaza Drive
Collinsville, Illinois 62234

RE: Structure Geotechnical Report
Bridge Construction
IL - Route 157 (FAP Route 592) over Judy's Branch
Madison County, Illinois
Section: 51-R
Structure No. SN 060-0087 (Existing)
Structure No. SN 060-0229 (Proposed)
SCI No.: 2020-0531.10

Dear Eric M. Lagemann:

Enclosed is our *Final Structure Geotechnical Report (SGR)*, dated March 2023. This report should be read in its entirety, and our recommendations considered in the design and construction of the proposed bridge. Please call if you have any questions.

Respectfully,

SCI ENGINEERING, INC.

A handwritten signature in black ink, appearing to read 'Prakash Paudel'.

Prakash Paudel, E.I.
Staff Engineer

A handwritten signature in black ink, appearing to read 'Thomas J. Casey'.

Thomas J. Casey, P.E.
Chief Geotechnical Engineer

PP/TJC/snp

Enclosure

Structural Geotechnical Report

N:\Projects\2020\2020-0531 PTB 195, Item 57 Realignment of IL 162 at 157\Report\SN 060-0087 (E) 0229 (P) - IL-157 over Judy's Branch\20-0531.10 IL-157 over Judy's Branch (SN060-0229) - Final.docx

TABLE OF CONTENTS

1.0	PROJECT DESCRIPTION	1
2.0	SUBSURFACE EXPLORATION	1
2.1	Area Geology	1
2.2	Exploration Procedures	2
2.3	Subsurface Conditions	2
2.4	Groundwater Conditions	3
3.0	GEOTECHNICAL EVALUATIONS	4
3.1	Seismic Considerations	4
	3.1.1 Design Earthquake	4
	3.1.2 Site Class Determination	4
	3.1.3 Liquefaction Potential Analysis	5
3.2	Abutment and Pier Settlement	6
3.3	Bridge Approach Slabs	6
3.4	Slope Stability	6
3.5	Scour	7
3.6	Bridge Foundations	7
	3.6.1 Driven Steel Piles	8
3.7	Lateral Pile Response	10
4.0	CONSTRUCTION CONSIDERATIONS	10
5.0	LIMITATIONS	11

TABLES

Table 2.1 – Summary of Bedrock Elevations	3
Table 2.2 – Summary of Approximate Groundwater Levels	3
Table 3.1 – Seismic Design Parameters	5
Table 3.2 – Summary of Estimated Global Slope Stability Factors of Safety	7
Table 3.3 – Summary of Design Scour Elevations	7
Table 3.4 – Maximum Nominal Required Bearing for Steel H-Piles	9

FIGURES

Figure 1 – Vicinity and Topographic Map
 Figure 2 – Aerial Photograph
 Figure 3 – Site Plan
 Figure 4 – Subsurface Profile

APPENDICES

Appendix A – Boring Logs and Laboratory Test Results
 Appendix B – Liquefaction Potential Analyses
 Appendix C – Driven Pile Capacity Sheets (H-Piles)
 Appendix D – L-PILE Table Inputs
 Appendix E – Slope Stability Analyses
 Appendix F – TS&L Plans

Structure Geotechnical Report

BRIDGE CONSTRUCTION

PTB 195 ITEM 57

IL - ROUTE 157 (FAP ROUTE 592) OVER JUDY'S BRANCH

MADISON COUNTY, ILLINOIS

SECTION: 51-R

STRUCTURE NO. SN 060-0087 (EXISTING)

STRUCTURE NO. SN 060-0229 (PROPOSED)

1.0 PROJECT DESCRIPTION

The geotechnical study summarized in this report was performed for the proposed construction of the bridge that carries Illinois Route 157 over the Judy's Branch in Madison County, Illinois. Based on the TS&L provided by Fuhrmann Engineering (Fuhrmann) on August 15, 2022, the proposed structure will be a four-lane, three-span structure with a back-to-back abutment length of approximately 133 feet and an out-to-out deck width that will vary in between 213 to 247 feet. According to the provided profiles and cross sections, a maximum fill of approximately 8 to 10 feet is planned near the south approach embankment whereas minimal cuts and fills (<5 feet) is planned near the north approach embankment. The end slopes will have maximum inclination of 2 horizontal to 1 vertical (2H:1V) and the streambed of the creek will be capped with approximately 24 inches of stone riprap used for scour protection. The location of the site is shown on the *Vicinity and Topographic Map*, Figure 1.

2.0 SUBSURFACE EXPLORATION

2.1 Area Geology

The project is located approximately 7.5 miles east of the Mississippi River in the floodplain known locally as the American Bottoms. According to *Surficial Geology of Monks Mound Quadrangle, Madison and St. Clair Counties, Illinois 2007*, the near-surface soils are of the Cahokia Formation that mainly consist of silt loam with occasional thin sand and diamicton beds. The near-surface soils are soft and weakly stratified and up to 15 feet thick. These alluviums were deposited by distributary channels in fans including redeposited loess and some mud flows.

According to *Bedrock Geologic Map, Monks Mound Quadrangle, Madison and St. Clair Counties, Illinois 2001*, the bedrock at this site belongs to Carbondale and Tradewater formations. The Carbondale formation is dominated by dark gray carbonaceous and pyritic shales with siltstone intervals while the Tradewater formation is dominated by shale or claystone and commonly shows rooting.

SCI Engineering, Inc.
Fuhrmann Engineering

IL - Route 157 (FAP Route 592) over Judy's Branch
SCI No. 2020-0531.10

2.2 Exploration Procedures

Two standard penetration test (SPT) borings, designated B-7 and B-19 were drilled near the proposed abutment locations, as shown on the *Aerial Photograph*, Figure-2, and *Site Plan*, Figure 3. The boring locations were selected and staked in the field by SCI personnel; however the elevations were estimated from publicly available LIDAR data. The stations and offsets were estimated from the TS&L plans provided and included in Appendix F. The field exploration was performed in general accordance with procedures outlined in the *2020 IDOT Geotechnical Manual*.

Personnel from SCI were with the drill rig to supervise drilling, log the borings, and perform field unconfined compressive strength tests of the borings. A CME 550X all-terrain-mounted drill rig equipped with both hollow stem augers and mud-rotary was used to advance the borings. SPTs were performed with a split-spoon sampler at 2½-foot intervals to 30 feet, and at 5-foot intervals thereafter to the termination depth of the borings. The unconfined compressive strength of the cohesive soils was determined with a Rimac test apparatus. A pocket penetrometer was used to measure the compressive strength if the soils were not conducive to Rimac testing. While auger refusal did not occur in any of the borings, split spoon sampler refusal did occur within the shale bedrock in both soil test borings to the depths of 87.5 to 89 feet, as detailed on the appended boring logs. Split-spoon sampler refusal is a designation applied to any material that results in SPT N-values in excess of 100 blows per foot (bpf) or 50 blows over the advancement depth of less than 6 inches.

2.3 Subsurface Conditions

Detailed information regarding the nature and thickness of the soils and rock encountered, and the results of the field sampling and laboratory testing are shown on the Boring Logs and Lab Test Results in Appendix A. The generalized soil profile is included on the *Subsurface Profile*, Figure 4.

The boring B-7 encountered 6 feet of existing fill consisting of couple feet of cinders (A-1) at the top followed by dark brown to brown silty clay loam (A-4) while no fill was encountered in boring B-19. Standard Penetration Test (SPT) N-values (the sum of the second and third blow count numbers in each sampling interval from the SPT) in the existing fill ranged from 13 to 15 blows per foot (bpf) with an average of 14 bpf and Rimac unconfined compressive strength of the loamy soil was 0.9 tons per square foot (tsf), overall classifying the fill as medium stiff to stiff in consistency and medium dense in relative density. Moisture contents in the existing fill ranged from 16 to 18 percent with an average of 17 percent.

SCI Engineering, Inc.
Fuhrmann Engineering

IL - Route 157 (FAP Route 592) over Judy's Branch
SCI No. 2020-0531.10

Underlying the fill, the natural soils generally consisted of silty to sandy loam (A-4) and silty clay (A-6) to clay (A-7), with occasional layers of sand (A-3) to a nominal depth of 32 feet (El. 406) followed by clay (A-7) to silty clay loam (A-6) to the termination depth of the boring. As an exception, a gray weathered layer of clayey shale was encountered in boring B-7 at 79.5 feet (El. 358.5) that extended all the way down to 86 feet (El. 352).

In general, the natural soils were very soft to stiff in consistency and loose to medium dense in relative density, with a majority of the N-values ranging between 0 and 31 blows per foot (bpf) with an average of 10 bpf. Unconfined compressive strengths obtained from Rimac test ranged between 0.1 to 3 tons per square foot (tsf), with an average of 1.1 tsf. Moisture contents in the native soil samples ranged from 17 to 51 percent, with an average of approximately 27 percent. Table 2.1 presents a summary of the depth and elevation of the top of bedrock that was first encountered in each of the borings.

Table 2.1 – Summary of Bedrock Elevations

Boring	Ground Surface Elevation (feet)	Depth to Bedrock (feet)	Top of Bedrock Elevation (feet)
B-7	438±	86.0	352.0
B-19	438±	88.5	349.5

2.4 Groundwater Conditions

Groundwater levels observed at the time of drilling are summarized in Table 2.2. It should be noted that the groundwater level is subject to seasonal and climatic variations, the water level in the existing Judy's Branch, and other factors; and may be present at different depths in the future. In addition, without extended periods of observation, measurement of the true groundwater levels may not be possible.

Table 2.2 – Summary of Approximate Groundwater Levels

Boring	Ground Surface Elevation (feet)	Depth to Groundwater during Drilling (feet)	Groundwater Elevation during Drilling (feet)
B-7	438±	13.0	425.0
B-19	438±	16.0	422.0

SCI Engineering, Inc.
Fuhrmann Engineering

IL - Route 157 (FAP Route 592) over Judy's Branch
SCI No. 2020-0531.10

3.0 GEOTECHNICAL EVALUATIONS

In order to provide design recommendations for founding the structure, we performed the following evaluations based on all available data collected and reviewed at the time of this report. This information includes subsurface explorations performed by SCI, existing plans, and communications with Fuhrmann personnel familiar with the project.

3.1 Seismic Considerations

3.1.1 Design Earthquake

Ground shaking at the foundation of structures and liquefaction of the soil under the foundation are the principle seismic hazards to be considered in design of earthquake-resistant structures. Soil liquefaction is possible within loose sand and low plastic silt deposits below the groundwater table. Liquefaction occurs when a rapid development in water pressure, caused by the ground motion, pushes sand particles apart, resulting in a loss of strength and later densification as the water pressure dissipates. This loss of strength can cause bearing capacity failure while the densification can cause excessive settlement. Potential earthquake damage can be mitigated by structural and/or geotechnical measures or procedures common to earthquake resistant design.

For the purposes of seismic design the bridge has been classified as *Regular* and *Essential*. According to the Illinois Department of Transportation Bridge Manual 2012 edition, the structure should be designed to a design earthquake with a 7 percent Probability of Exceedance (PE) over a 75-year exposure period (i.e. a 1,000-year design earthquake). The design earthquake has a Moment Magnitude (M_w) of 4.9 and a site coefficient (A_s) of 0.25g, as determined from data provided by the United States Geological Survey (USGS) National Seismic Hazard Mapping Project and procedures outlined in the All Geotechnical Manual Users (AGMU) 10.1, *Liquefaction Analysis Procedure*.

3.1.2 Site Class Determination

The seismic site soil classification for the bridge site was determined from the design earthquake data, the subsurface data, and the procedures described in AGMU Memo 09.1, *Seismic Site Class Definition*, of the IDOT Bridge Manual Design Guides. The global site Class was evaluated using methods defined as B and C, which include evaluating the SPT N-values and undrained shear strength, S_u . The following results were calculated:

- Method B using N : 8 bpf (Site Class E)
- Method C using N_{ch} : 8 bpf (Site Class E)
- Method C using S_u : 1,120 psf (Site Class D)

Based on the span and overall bridge lengths and the guidelines in the AGMU, we recommend that Site Class D be used for the project. Based on Table 3.15.2-1 the Seismic Performance Zone is 2. Seismic design parameters for the site are summarized in Table 3.1.

Table 3.1 – Seismic Design Parameters

Site Class	D
PGA	0.17
Spectral Acceleration at 0.2 sec. (S_s)	0.35g
Spectral Acceleration at 1.0 sec. (S_1)	0.10g
F_{pga}	1.46
F_a	1.52
F_v	2.40
Site Coefficient (A_s)	0.25
Design Spectral Acceleration at 0.2 sec. (S_{DS})	0.53g
Design Spectral Acceleration at 1.0 sec. (S_{D1})	0.23g
Seismic Design Category	B
Seismic Performance Zone	2

3.1.3 Liquefaction Potential Analysis

The liquefaction potential analysis for the site was conducted using field and laboratory data and the techniques outlined in AGMU 10.1. For the seismic hazard evaluation, it is generally not prescribed to assume that earthquakes would coincide with other extreme loading events, (i.e., reoccurring flood events) unless the structure is considered critical, for which, engineering judgement may be used to provide additional conservatism to the analysis, if necessary. The average seasonal groundwater elevation used in the analysis was estimated from the end of boring conditions and the seasonal weather conditions. Sands located above the water table are not susceptible to liquefaction.

Based on our analyses, a majority of the soils observed have sufficient strength and/or a plasticity index that make the threat of liquefaction minimal during the design earthquake. However, isolated relatively thin (<5 feet) layers of very loose silty sands encountered at approximate elevation of 425.5 in boring B-7

and 423 in boring B-19 may be susceptible to liquefaction. It is anticipated that all the piles will extend through the potentially liquefiable soils and bear on or in the underlying shale bedrock. Additionally, the unbraced length of the piles during liquefaction should not be a concern as the potentially liquefiable layers are relatively thin and do not occur uniformly across the site. The detailed input parameters and results of the Liquefaction Analyses are provided in Appendix B. While the amount of seismically induced settlement is dependent on the magnitude and distance from the seismic event, SCI estimates that the impacts from the design earthquake will be negligible.

3.2 Abutment and Pier Settlement

Based on the maximum fill of 10 feet near the south abutment, settlement of approximately 2 inches is anticipated which requires the effects of down drag be considered on the determination of axial pile capacity. Minimal cuts and fills (< 5 feet) are planned near the interior pier locations and north abutment. Therefore, settlement is not anticipated to be of concern and hence the effects of down drag on axial pile capacities can be neglected at these locations.

3.3 Bridge Approach Slabs

Based on the available information, the bridge approach slabs will likely bear on newly placed, low plastic structural fill and existing fills. In evaluating the bearing resistance of the slabs, we recommend using a modulus of subgrade reaction of 100 pounds per square inch per inch of deflection (pci).

3.4 Slope Stability

The global slope stability of both end-slopes was analyzed for end-of-construction (short-term), long-term, and seismic (pseudo-static) loading conditions. The analyses were conducted using limit equilibrium slope stability methods and the commercially available software program Slide 2018 (developed by Rocscience, Inc.). The analyses considered soil properties from the subsurface exploration data and the given slope geometries. To account for traffic loading, a surcharge load of 250 pounds per square foot (psf) was applied to the analyses. For the seismic evaluation, the peak ground acceleration (PGA) from the design earthquake along with procedures for seismic slope stability outlined in Federal Highway Administration (FHWA) publication FHWA-HI-99-012 *Geotechnical Earthquake Engineering* were utilized. Soil parameters used in the analyses and the results of the analyses are shown on the output plots in Appendix-E.

SCI Engineering, Inc.
Fuhrmann Engineering

IL - Route 157 (FAP Route 592) over Judy's Branch
SCI No. 2020-0531.10

The Bishop method, as recommended by IDOT, with a circular mode of failure, was used to search for the critical factor of safety (FS). The required minimum factors of safety were obtained from Section 6.10.4 of the 2020 IDOT Geotechnical Manual for the global slope stability. The results of the global slope stability analyses are presented in Table 3.2 below. The analysis results indicate that the calculated factor of safety meets the required minimum factor of safety. Therefore, the end slopes will perform satisfactorily under short term, long term, and seismic conditions.

Table 3.2 – Summary of Estimated Global Slope Stability Factors of Safety

Analyzed End Slope	Short-Term Static Condition		Long-Term Static Condition		Seismic Condition	
	Required FOS	Estimated FOS	Required FOS	Estimated FOS	Required FOS	Estimated FOS
North Abutment	1.50	1.54	1.50	1.53	1.00	1.24
South Abutment	1.50	1.79	1.50	2.14	1.00	1.42

3.5 Scour

The pile capacity is dependent on the scour elevation and suitable protection should be provided to the foundation elements. Based on the provided TS&L, the design scour elevations for the 100-year and 200-year events for the abutment and interior bents are shown in Table 3.3 below.

Table 3.3 – Summary of Design Scour Elevations

Event/Limit State	Design Scour Elevation (ft)				Item 113
	South Abutment	Interior South Pier (Pier-1)	Interior North Pier (Pier-2)	North Abutment	
Q100	439.00	414.80	414.80	438.92	5
Q200	439.00	413.93	413.93	438.92	
Design	439.00	414.80	414.80	438.92	
Check	439.00	413.93	413.93	438.92	

3.6 Bridge Foundations

The foundation supporting the proposed bridge must provide sufficient support to resist dead and live loads, including seismic loads. As per the TS&L, integral abutments are planned for this bridge. Per the IDOT Bridge Manual, this type of abutment requires either H-Piles or metal shell piles to accommodate the deflection needs of the superstructure. The piles must be configured in a single non-battered row and

SCI Engineering, Inc.
Fuhrmann Engineering

IL - Route 157 (FAP Route 592) over Judy's Branch
SCI No. 2020-0531.10

oriented with their weak axis of bending placed at 90 degrees to the centerline of the bridge. The piles must also extend 2 feet into the abutment to create a fixed condition, which helps the pile withstand the lateral forces and resulting moment while at the same time carrying axial loads.

For the interior piers, several potential foundation options were considered for supporting the new bridge structure that included driven steel H-Piles, metal shell piles, drilled shafts, and shallow foundations. Shallow foundations are not recommended due to the relatively soft consistency of the shallow subsurface conditions encountered. Drilled shaft foundations were determined to be too costly, given the size of the proposed structure. SCI should be contacted for additional recommendations if drilled shafts will be considered. Driven steel H-piles and metal shell piles are feasible for both the abutments and the piers for the bridge. However, as per the latest TS&L provided on March 22, 2023, steel H-piles are planned for the bridge and hence the design information for only steel H-piles is included in Appendix C. No structure loads were provided at the time of writing this report. Therefore, a preliminary load of 1700 kips was assumed for both abutments and the interior piers.

For the driven steel foundation options, we recommend a minimum of one index pile be installed to verify the length of the piles. The index pile can be installed at either side of the creek in the general area of the abutment to help verify the pile length.

3.6.1 Driven Steel Piles

The structural capacity of driven piles depends on the allowable stress and cross-sectional areas of steel and concrete. The pile recommendations in this report assume that Steel H-piles will conform to ASHTO M270 Grade 50 (ASTM 709 Gr 50) or equivalent with a minimum yield stress of 50 kips per square inch (ksi). While metal shell piles are not anticipated, if they are used, they should conform to ASTM A252 grade 3 (or equivalent) with a minimum yield stress of 45 ksi.

Based on the most current IDOT Bridge Manual, All Geotechnical Manual User Memorandums (AGMUs), and Guide Bridge Special Provisions (GBSP), a geotechnical resistance factor (ϕ_G) of 0.55 was used for the design of the driven pile foundations. Geotechnical losses due to down drag was considered for the south abutment as mentioned above. Similarly, geotechnical losses associated with scour were not calculated as the scour elevations at the pier locations were not determined yet. During the seismic event the Bridge Manual allows the use of a Geotechnical Resistance Factor (ϕ_G) of 1.0.

SCI Engineering, Inc.
Fuhrmann Engineering

IL - Route 157 (FAP Route 592) over Judy's Branch
SCI No. 2020-0531.10

All estimates of capacity were calculated using the "Modified IDOT Static Method" spreadsheet associated with the IDOT Bridge Manual, and appropriate AGMUs and GMSPs, and assume construction verification will follow the "WSDOT" formula outlined in Section 512 of the most current IDOT Standard Specifications for Road and Bridge construction. The tip elevations were calculated from the Modified IDOT Static Method spreadsheets based on the available factored resistance. It should be noted that the Static Pile Tables for Pier 1 (Interior South Pier) and Pier 2 (Interior North Pier) were the compilation of data from the nearby borings to provide the best engineering estimate for the design.

A summary of the design capacities, or factored resistance available (R_F), seismic factored resistance (R_{Fseis}), and nominal required bearing (R_N) as well as estimated pile lengths, is presented in Appendix C for additional H-pile sizes. It should be noted that H-piles driven into shale may run shorter than the IDOT spreadsheet predicts. The estimated pile lengths should be adjusted based on the index pile results. The maximum nominal required bearing and the available maximum factored resistance for typical steel H-piles for the abutments and the interior piers are shown in Table 3.4.

Table 3.4 – Maximum Nominal Required Bearing for Steel H-Piles

Abutment/ Pier	Pile Size	Maximum Nominal Required Bearing, R_{Nmax} (kips)	Maximum Factored Resistance Available (kips)	Maximum Factored Resistance Available Considering Geotechnical Losses [DD/Scour] (kips)	Estimated Length of Pile at Refusal (feet)
South Abutment	HP 12X74	589	324	298	94
	HP 12X84	664	365	339	94
	HP 14X89	705	388	357	94
	HP 14X117	929	511	479	95
Pier 1	HP 12X74	589	324	320	96
	HP 12X84	664	365	361	96
	HP 14X89	705	388	383	96
	HP 14X117	929	511	506	96
Pier 2	HP 12X74	589	324	316	98
	HP 12X84	664	365	357	98
	HP 14X89	705	388	379	98
	HP 14X117	929	511	502	100
North Abutment	HP 12X74	589	324	--	97
	HP 12X84	664	365	--	98
	HP 14X89	705	388	--	97
	HP 14X117	929	511	--	100

SCI Engineering, Inc.
Fuhrmann Engineering

IL - Route 157 (FAP Route 592) over Judy's Branch
SCI No. 2020-0531.10

We recommend a minimum driven pile center to center spacing of three pile diameters, as recommended by the IDOT Bridge Manual. The maximum spacing shall be limited to 3.5 times the effective footing thickness plus 1 foot, but not to exceed 8 feet. Once the final spacing is determined, the piles should be evaluated for group effects.

3.7 Lateral Pile Response

A representation of the pile response under lateral loading exceeding 3 kips per pile is required for design of the bridge superstructure per Section 3.10.1.10 of the 2012 Bridge Manual. The lateral response can be developed by modeling the soil/shaft interaction with the computer program LPILE. Discrete elements are used in LPILE to represent the shaft and non-linear soil using springs. The non-linear soil springs are commonly referred to as P-Y curves. Tables for the pier and abutment locations summarizing approximate soil and rock parameters for the LPILE analyses are included in Appendix D (Reference: LPILE User's Manual, Ensoft, Inc., 2019).

4.0 CONSTRUCTION CONSIDERATIONS

The construction activities should be performed in accordance with the current *IDOT Standard Specifications for Road and Bridge Construction* and any pertinent Special Provisions or policies.

4.1 Temporary Sheet Pile

According to the conversations with Fuhrmann Engineering, IDOT has directed to perform staged construction of this bridge. However, due to the presence of very loose silts and loams down to an estimated depth of 15 feet from underneath the excavation line, temporary sheet piling will not be feasible for this site. Therefore, a temporary soil retention system will be needed for the proposed construction.

4.2 Dewatering

Based on the loamy/silty nature of the near surface soils, dewatering of the site should be anticipated. Depending on conditions at the time of construction, dewatering may consist of sumps and pumps for controlling water flow into the excavation or more aggressive dewatering using well points may be required. The fine grained loamy and silty soils may be subject to piping during dewatering and should be considered when evaluating groundwater control methods. Piping or transport of the finer materials could result in settlement of adjacent roadways or other features.


SCI Engineering, Inc.
Fuhrmann Engineering

IL - Route 157 (FAP Route 592) over Judy's Branch
SCI No. 2020-0531.10


Additionally, the interior piers are planned to be above the estimated water surface elevation of 426.5 in the creek as shown on the *TS&L* in Appendix F. If construction work is planned during periods of highwater (typically March through August) and the methods discussed above do not control the flow of groundwater into the excavations, coffer dams may be required.

5.0 LIMITATIONS

The recommendations provided herein are for the exclusive use of Fuhrmann Engineering and IDOT. They are specific only to the project described and are based on subsurface information obtained at two boring locations within the bridge area, our understanding of the project as described herein, and geotechnical engineering practice consistent with the standard of care. No other warranty is expressed or implied. SCI should be contacted if conditions encountered during construction are not consistent with those described.



	PROJECT NAME PTB 195 ITEM 57 IL – ROUTE 157 OVER JUDY’S BRANCH MADISON COUNTY, ILLINOIS			GENERAL NOTES/LEGEND USGS TOPOGRAPHIC MAPS WOOD RIVER, ILLINOIS QUADRANGLE DATED 1994 10’ CONTOURS EDWARDSVILLE, ILLINOIS QUADRANGLE DATED 1991 10’ CONTOURS		 FIGURE 1	
	VICINITY AND TOPOGRAPHIC MAP			MONKS MOUND, ILLINOIS QUADRANGLE DATED 1954, REVISED 1993 10’ CONTOURS COLLINSVILLE, ILLINOIS QUADRANGLE DATED 1991 10’ CONTOURS			
	DRAWN BY	JTM	DATE	03/2023	JOB NUMBER		2020-0531.10
	CHECKED BY	pp					



PROJECT NAME
PTB 195 ITEM 57
IL – ROUTE 157 OVER JUDY'S BRANCH
MADISON COUNTY, ILLINOIS

AERIAL PHOTOGRAPH

DRAWN BY JTM
CHECKED BY pp

DATE
03/2023

JOB NUMBER
2020-0531.10

GENERAL NOTES/LEGEND




APPROXIMATE STB LOCATIONS

AERIAL PHOTOGRAPH OBTAINED FROM ARCGIS ONLINE, WORLD IMAGERY.

DIMENSIONS AND LOCATIONS ARE APPROXIMATE; ACTUAL MAY VARY.
DRAWING SHALL NOT BE USED OUTSIDE THE CONTEXT OF THE REPORT FOR WHICH IT WAS GENERATED.




FIGURE
2



PTB 195 ITEM 57
IL - ROUTE 157 OVER JUDY'S BRANCH
MADISON COUNTY, ILLINOIS

STILL LIFE





DB NUMBER	2020-0531.10
DATE	03/2023
DRAWN BY	JTM
CHECKED BY	PP
SIGNATURE	

3



APPROXIMATE STB LOCATIONS





Appendix A



SCI ENGINEERING, INC.

**130 Point West Boulevard
St. Charles, Missouri 63301
636-949-8200
www.sciengineering.com**

BORING LOG LEGEND AND NOMENCLATURE

Depth is in feet below ground surface. **Elevation** is in feet mean sea level, site datum, or as otherwise noted.

Sample Type

- SS** Split-spoon sample, disturbed, obtained by driving a 2-inch-O.D. split-spoon sampler (ASTM D 1586).
- NX** Diamond core bit, nominal 2-inch-diameter rock sample (ASTM D 2113).
- ST** Thin-walled (Shelby) tube sample, relatively undisturbed, obtained by pushing a 3-inch-diameter, tube (ASTM D 1587).
- CS** Continuous sample tube system, relatively undisturbed, obtained by split-barrel sampler in conjunction with auger advancement.
- SV** Shear vane, field test to determine strength of cohesive soil by pushing or driving a 2-inch-diameter vane, and then shearing by torquing soil in existing and remolded states (ASTM D 2573).
- BS** Bag sample, disturbed, obtained from cuttings.

Recovery is expressed as a ratio of the length recovered to the total length pushed, driven, cored.

Blows Numbers indicate blows per 6 inches of split-spoon sampler penetration when driven with a 140-pound hammer falling freely 30 inches. The number of total blows obtained for the second and third 6-inch increments is the N value (Standard Penetration Test or SPT) in blows per foot (ASTM D 1586). Practical refusal is considered to be 50 or more blows without achieving 6 inches of penetration, and is expressed as a ratio of 50 to actual penetration, e.g., 50/2 (50 blows for 2 inches).

For analysis, the N value is used when obtained by a cathead and rope system. When obtained by an automatic hammer, the N value may be increased by a factor of 1.3.

Vane Shear Strength is expressed as the peak strength (existing state) / the residual strength (remolded state).

Description indicates soil constituents and other classification characteristics (ASTM D 2488) and the Unified Soil Classification (ASTM D 2487). Secondary soil constituents (expressed as a percentage) are described as follows:

Trace	<5
Few	5-15
With	>15-30

Stratigraphic Breaks may be observed or interpreted, and are indicated by a dashed line. Transition between described materials may be gradual.

Laboratory Test Results

- Natural moisture content (ASTM D 2216) in percent.
- Dry density in pounds per cubic foot (pcf).
- Hand penetrometer value of apparently intact cohesive sample in kips per square foot (ksf).
- Unconfined compressive strength (ASTM D 2166) in kips per square foot (ksf).
- Liquid and Plastic Limits (ASTM D 4318) in percent.

RQD (Rock Quality Designation) is the ratio between the total length of core segments 4 inches or more in length and the total length of core drilled. RQD (expressed as a percentage) indicates insitu rock quality as follows:

Excellent	90 to 100
Good	75 to 90
Fair	50 to 75
Poor	25 to 50
Very Poor	0 to 25



Illinois Department of Transportation

Division of Highways
SCI Engineering, Inc.

SOIL BORING LOG

Page 1 of 3

Date 3/1,2/2022

ROUTE Route 157/162 DESCRIPTION IL - Route 157 over Judy's Branch LOGGED BY SCI

SECTION 51-1R LOCATION Madison County, Illinois, SEC. 4, TWP. 3N, RNG. 8W
Lat 38.740837 Long -90.002113

COUNTY Madison DRILLING METHOD CME 550 w/HSA and Mud Rotary HAMMER TYPE Automatic

SN 060-0229/ SN
STRUCT. NO. 060-7003
Station 584+70.00 and 11+32.26

BORING NO. B-7
Station 17+86
Offset 50 ft LT
Ground Surface Elev. 438.0 ft

D E P T H (ft)	B L O W S (/6")	U C S Qu (tsf)	M O I S T (%)	Surface Water Elev. <u>N/A</u> ft	Stream Bed Elev. <u>N/A</u> ft	D E P T H (ft)	B L O W S (/6")	U C S Qu (tsf)	M O I S T (%)
				Groundwater Elev.:					
				First Encounter <u>425.0</u> ft ▼					
				Upon Completion <u>N/A</u> ft					
				After <u>N/A</u> Hrs. <u>N/A</u> ft					
FILL: CINDERS (A-1)				Gray fine SAND (A-3), wet, medium dense					
436.5	5	3.0 P	16				4	NC	23
FILL: Dark brown to brown SILTY LOAM (A-4), stiff	6						7		
	9						9		
	4	0.9 S/10%	18	Gray SILTY LOAM (A-4), moist, stiff	414.0		5	1.5 P	21
	6						5		
	-5						-25		
432.5				Gray fine SAND (A-3), wet, medium dense	412.5				
Brown SILTY LOAM (A-4), very moist, very soft									
Percentage finer than #200 test performed (21.6% passing)	WOH	<0.25 P	29				8	NC	NC
	WOH						12		
	WOH						13		
Percentage finer than #200 test performed (19.9% passing)	WOH	NC	26				6	NC	24
	WOH						6		
Brown to reddish brown SANDY LOAM (A-3) w/ silt, very moist, very loose	-10						-30		
Percentage finer than #200 test performed (19.2% passing)	WOH	NC	23						
	WOH								
	1								
Percentage finer than #200 test performed (20.3% passing)		<0.25 P	31	Gray CLAY (A-7), moist, stiff	406.0				
	1						5		
	1						4	2.0 B/20%	23
423.0	-15						-35		
Gray and Brown SILTY CLAY (A-6), moist, very soft									
	WOH	0.5 S/15%	30						
	1								
	2								
420.0									
Gray CLAY (A-7), moist, soft									
Atterberg Limits test performed (LL=34, PI=18)									
	1	0.6 B/20%	23				4		
	1						4	2.5 B/20%	21
	2						7		
418.0	-20						-40		

Division of Highways
SCI Engineering, Inc.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
AASHTO Classifications are based on visual classifications unless otherwise noted BBS, form 137 (Rev. 8-99)

Division of Highways
SCI Engineering, Inc.

ROUTE	Route 157/162	DESCRIPTION	IL - Route 157 over Judy's Branch	LOGGED BY	SCI
-------	---------------	-------------	-----------------------------------	-----------	-----

COUNTY	Madison	DRILLING METHOD	CME 550 w/HSA and Mud Rotary	HAMMER TYPE	Automatic
---------------	---------	------------------------	------------------------------	--------------------	-----------

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)	(/6")	(tsf)	(%)

Surface Water Elev.	<u>N/A</u>	ft
Stream Bed Elev.	<u>N/A</u>	ft
Groundwater Elev.:		
First Encounter	<u>425.0</u>	ft ▼
Upon Completion	<u>N/A</u>	ft
After N/A Hrs.	<u>N/A</u>	ft

Gray weathered CLAYEY SHALE,
hard (continued)

**Sampler Refusal at 87.5 feet.
Borehole grouted upon
completion.**

350.5

-90

-95

-100



Illinois Department of Transportation

Division of Highways
SCI Engineering, Inc.

SOIL BORING LOG

Page 1 of 3

Date 3/14, 15/2022

ROUTE Route 157/162 DESCRIPTION IL - Route 157 over Judy's Branch LOGGED BY SCI

SECTION 51-1R LOCATION Madison County, Illinois, SEC. 4, TWP. 3N, RNG. 8W
Lat 38.741338 Long -90.001838

COUNTY Madison DRILLING METHOD CME 550 w/HSA and Mud Rotary HAMMER TYPE Automatic

STRUCT. NO. SN 060-0229
Station 584+70.00

BORING NO. B-19
Station 585+41
Offset 46 ft RT
Ground Surface Elev. 438.0 ft

D E P T H (ft)	B L O W S (/6")	U C S Qu (tsf)	M O I S T (%)
-------------------------------	--------------------------------	----------------------------	------------------------------

Surface Water Elev.	N/A	ft
Stream Bed Elev.	N/A	ft
Groundwater Elev.:		
First Encounter	422.0	ft ▼
Upon Completion	N/A	ft
After N/A Hrs.	N/A	ft

D E P T H (ft)	B L O W S (/6")	U C S Qu (tsf)	M O I S T (%)
-------------------------------	--------------------------------	----------------------------	------------------------------

Brown SILTY CLAY (A-6), very soft			
	WOH	0.3	26
	1 1 1	S/20%	
435.5			
Gray CLAY (A-7), some fine to medium sand, clay is loose to medium stiff			
	1 1 -5	0.5 P	24
	2 2 2	0.5 P	28
430.0			
Tan and gray CLAY (A-7), soft			
	2 2 -10	0.3 S/20%	50
CLAYEY SAND (A-2), sand is fine to coarse, very loose			
	WOH	0.3	51
	2 3	S/5%	
425.0			
Gray CLAY (A-6), soft			
	1 1 -15	NC	25
422.0 ▼			
	2 2 2	0.2 S/5%	36
	WOH	0.1	34
	2 2 -20	S/5%	

Gray CLAY (A-6), soft (continued)			
	Becomes silty		
		1 2 3	2.0 P 28
415.0			
Gray SAND and CLAY (A-3, A-6), sand is loose to medium dense, clay is medium stiff			
		2 2 -25	1.0 P 20
		2 3 8	0.5 P 24
		4 14 -30	0.5 P 23
406.0			
Light brown CLAY (A-7), medium stiff			
		3 2 -35	0.3 P 26
		3 4 -40	0.6 B/20% 21

Division of Highways
SCI Engineering, Inc.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
AASHTO Classifications are based on visual classifications unless otherwise noted BBS, form 137 (Rev. 8-99)



Illinois Department of Transportation

Division of Highways
SCI Engineering, Inc.

SOIL BORING LOG

Page 3 of 3

Date 3/14, 15/2022

ROUTE Route 157/162 DESCRIPTION IL - Route 157 over Judy's Branch LOGGED BY SCI

SECTION 51-1R LOCATION Madison County, Illinois, SEC. 4, TWP. 3N, RNG. 8W
Lat 38.741338 Long -90.001838

COUNTY Madison DRILLING METHOD CME 550 w/HSA and Mud Rotary HAMMER TYPE Automatic

STRUCT. NO. SN 060-0229
Station 584+70.00

BORING NO. B-19
Station 585+41
Offset 46 ft RT
Ground Surface Elev. 438.0 ft

D E P T H	B L O W S	U C S	M O I S T
(ft)	(/6")	(tsf)	(%)

Surface Water Elev.	<u>N/A</u>	ft
Stream Bed Elev.	<u>N/A</u>	ft
Groundwater Elev.:		
First Encounter	<u>422.0</u>	ft ▼
Upon Completion	<u>N/A</u>	ft
After <u>N/A</u> Hrs.	<u>N/A</u>	ft

Gray CLAY (A-7), medium stiff
(continued)

some weathered limestone

6			
8	2.0		22
16	P		

349.5

Gray SHALE, hard

349.0

50/5"

Sampler Refusal at 89 feet.
Borehole grouted upon
completion.

-90

-95

-100

Appendix B



LIQUEFACTION ANALYSIS

REFERENCE BORING NUMBER ===== B-7 S Abut
ELEVATION OF BORING GROUND SURFACE ===== 438.00 FT.
DEPTH TO GROUNDWATER - DURING DRILLING ===== 13.00 FT. (Below Boring Ground Surface)
DEPTH TO GROUNDWATER - DURING EARTHQUAKE ===== 13.00 FT. (Below Finished Grade Cut or Fill Surface)
PEAK HORIZ. GROUND SURFACE ACCELERATION COEFFICIENT (As) ===== 0.433
EARTHQUAKE MOMENT MAGNITUDE ===== 5.1
FINISHED GRADE FILL OR CUT FROM BORING SURFACE ===== 2.44 FT. (Fill Height)
HAMMER EFFICIENCY===== 73 %
BOREHOLE DIAMETER===== 6 IN.
SAMPLING METHOD===== Sampler w/out Liners

EQ MAGNITUDE SCALING FACTOR
(MSF) = 2.362

AVG. SHEAR WAVE VELOCITY (top 40')
V_{s,40'} = 359 FT./SEC.

PGA CALCULATOR
Earthquake Moment Magnitude = 5.1
Source-To-Site Distance, R (km) = 10
Ground Motion Prediction Equations = CEUS
PGA = 0.297

ELEV. OF SAMPLE	BORING DATA							CONDITIONS DURING DRILLING				CONDITIONS DURING EARTHQUAKE							
	BORING SAMPLE	SPT N	UNCONF. COMPR.	% FINES	PLAST. INDEX	LIQUID LIMIT	MOIST. CONTENT	EFFECTIVE UNIT	VERT.	CORR. SPT N	EQUIV. CLN. SAND SPT	CRR	EFFECTIVE UNIT	VERT.	TOTAL VERT.	OVER- BURDEN	CORR. RESIST.	SOIL MASS PART.	EQ
	DEPTH (FT.)	VALUE (BLOWS)	STR., Q _u (TSF.)	< #200 (%)	PI	LL	w _c (%)	WT. (KCF.)	STRESS (KSF.)	VALUE (N ₁) ₆₀	N VALUE (N ₁) _{60cs}	MAG 7.5 CRR _{7.5}	WT. (KCF.)	STRESS (KSF.)	STRESS (KSF.)	CORR. FACT. (Ks)	CRR _{7.5} CRR	FACTOR (r _d)	INDUCED CSR
435.5	2.5	15	2					0.130	0.325	29.061	29.061	0.413	0.130	0.618	0.618	1.500	1.464	0.889	0.250
433	5	13	0.9					0.120	0.625	21.839	21.839	0.240	0.120	0.918	0.918	1.291	0.731	0.826	0.233
430.5	7.5	1		21.6				0.095	0.863	1.452	5.452	0.075	0.095	1.155	1.155	1.131	0.202	0.759	0.214
428	10	1		19.9		26	26	0.095	1.100	1.466	5.179	0.073	0.095	1.393	1.393	1.088	0.189	0.692	0.195
425.5	12.5	1		19.2		23	23	0.095	1.338	1.452	5.031	0.072	0.033	1.475	1.596	1.075	0.184	0.626	0.191
423	15	2		20.3				0.048	1.458	2.926	6.829	0.086	0.048	1.595	1.872	1.062	0.216	0.564	0.186
420.5	17.5	3	0.5	50	12	30	30	0.051	1.585	4.368	10.241	0.115	0.051	1.723	2.156	1.050	0.286	0.507	0.178
418	20	3	0.6		18	34	23	0.053	1.718	4.312	4.312	0.067	0.053	1.855	2.444	1.027	0.163	0.455	0.169
415.5	22.5	16						0.065	1.880	23.850	23.850	0.271	0.065	2.018	2.763	1.016	0.650	0.411	0.158
413	25	10	1		5	21	21	0.059	2.028	13.731	13.731	0.148	0.059	2.165	3.066	0.995	0.347	0.373	0.149
410.5	27.5	25						0.069	2.200	37.650	37.650	0.000	0.069	2.338	3.395	0.962	0.000	0.342	0.140
408	30	13						0.063	2.358	17.181	17.181	0.183	0.063	2.495	3.708	0.956	0.413	0.316	0.132
403	35	10	2		12	23	23	0.067	2.693	12.204	12.204	0.133	0.067	2.830	4.355	0.932	0.293	0.278	0.120
398	40	11	2.5		12	21	21	0.070	3.043	12.662	12.662	0.137	0.070	3.180	5.017	0.904	0.293	0.254	0.113
393	45	11	2		12	18	18	0.067	3.378	12.013	12.013	0.131	0.067	3.515	5.664	0.884	0.274	0.239	0.109
388	50	10	1.6		12	17	17	0.065	3.703	10.402	10.402	0.117	0.065	3.840	6.301	0.870	0.240	0.230	0.106
383	55	14	2.8		12	22	22	0.072	4.063	13.817	13.817	0.148	0.072	4.200	6.973	0.840	0.294	0.225	0.105
378	60	8	1.4		12	28	28	0.063	4.378	7.550	7.550	0.092	0.063	4.515	7.600	0.849	0.185	0.221	0.105
373	65	15	3		12	22	22	0.072	4.738	13.466	13.466	0.145	0.072	4.875	8.272	0.810	0.277	0.213	0.102
368	70	9	2.7		12	32	32	0.071	5.093	7.705	7.705	0.093	0.071	5.230	8.939	0.822	0.181	0.206	0.099
363	75	16	2.1		12	28	28	0.068	5.433	13.121	13.121	0.142	0.068	5.570	9.591	0.785	0.263	0.199	0.097
358	80	12	1.4		12	28	28	0.063	5.748	9.484	9.484	0.109	0.063	5.885	10.218	0.792	0.203	0.192	0.094
353	85	31	1.7					0.065	6.073	25.033	25.033	0.293	0.065	6.210	10.855	0.705	0.487	0.185	0.091

* FACTOR OF SAFETY DESCRIPTIONS
N.L. (1) = NOT LIQUEFIABLE, ABOVE EQ GROUND WATER ELEVATION
N.L. (2) = NOT LIQUEFIABLE, PI ≥ 12 OR w_c/LL ≤ 0.85
N.L. (3) = NOT LIQUEFIABLE, (N₁)₆₀ > 25
(C) = CONTRACTIVE SOIL TYPES
(D) = DILATIVE SOIL TYPES



LIQUEFACTION ANALYSIS

REFERENCE BORING NUMBER ===== B-19 N Abut
ELEVATION OF BORING GROUND SURFACE ===== 438.00 FT.
DEPTH TO GROUNDWATER - DURING DRILLING ===== 16.00 FT. (Below Boring Ground Surface)
DEPTH TO GROUNDWATER - DURING EARTHQUAKE ===== 16.00 FT. (Below Finished Grade Cut or Fill Surface)
PEAK HORIZ. GROUND SURFACE ACCELERATION COEFFICIENT (As) ===== 0.433
EARTHQUAKE MOMENT MAGNITUDE ===== 5.1
FINISHED GRADE FILL OR CUT FROM BORING SURFACE ===== 3.13 FT. (Fill Height)
HAMMER EFFICIENCY===== 73 %
BOREHOLE DIAMETER===== 6 IN.
SAMPLING METHOD===== Sampler w/out Liners

EQ MAGNITUDE SCALING FACTOR
(MSF) = 2.362

AVG. SHEAR WAVE VELOCITY (top 40')
V_{s,40'} = 381 FT./SEC.

PGA CALCULATOR
Earthquake Moment Magnitude = 5.1
Source-To-Site Distance, R (km) = 10
Ground Motion Prediction Equations = CEUS
PGA = 0.297

ELEV. OF SAMPLE	BORING DATA							CONDITIONS DURING DRILLING				CONDITIONS DURING EARTHQUAKE							
	BORING SAMPLE	SPT N	UNCONF. COMPR.	% FINES	PLAST. INDEX	LIQUID LIMIT	MOIST. CONTENT	EFFECTIVE UNIT	VERT.	CORR. SPT N	EQUIV. CLN. SAND SPT	CRR	EFFECTIVE UNIT	VERT.	TOTAL VERT.	OVER- BURDEN	CORR. RESIST.	SOIL MASS PART.	EQ
	DEPTH (FT.)	VALUE (BLOWS)	STR., Q _u (TSF.)	< #200 (%)	PI	LL	w _c (%)	WT. (KCF.)	STRESS (KSF.)	VALUE (N ₁) ₆₀	N VALUE (N ₁) _{60cs}	MAG 7.5 CRR _{7.5}	WT. (KCF.)	STRESS (KSF.)	STRESS (KSF.)	CORR. FACT. (Ks)	CRR _{7.5} CRR	FACTOR (r _d)	INDUCED CSR
435.5	2.5	2	0.3					0.108	0.270	3.494	3.494	0.061	0.108	0.646	0.646	1.268	0.184	0.889	0.250
433	5	3	0.5					0.114	0.555	4.759	4.759	0.070	0.114	0.931	0.931	1.179	0.196	0.831	0.234
430.5	7.5	4	0.5					0.114	0.840	5.848	5.848	0.079	0.114	1.216	1.216	1.121	0.208	0.769	0.217
428	10	4	0.3					0.108	1.110	5.847	5.847	0.079	0.108	1.486	1.486	1.076	0.199	0.706	0.199
425.5	12.5	5	0.3					0.108	1.380	7.182	7.182	0.089	0.108	1.756	1.756	1.041	0.219	0.643	0.181
423	15	3						0.105	1.643	4.195	4.195	0.066	0.043	1.863	1.996	1.026	0.161	0.583	0.176
420.5	17.5	4	0.2		12	36	36	0.042	1.748	5.603	5.603	0.077	0.042	1.968	2.257	1.015	0.184	0.527	0.170
418	20	4	0.1		12	34	34	0.035	1.835	5.595	5.595	0.077	0.035	2.056	2.501	1.006	0.182	0.477	0.163
415.5	22.5	5	1.5		12	28	28	0.064	1.995	6.837	6.837	0.086	0.064	2.216	2.817	0.991	0.202	0.433	0.155
413	25	4	1	50	12	20	20	0.059	2.143	5.348	11.417	0.126	0.059	2.363	3.120	0.974	0.290	0.395	0.147
410.5	27.5	11	0.5	50	12	24	24	0.051	2.270	14.501	22.401	0.248	0.051	2.491	3.404	0.951	0.557	0.363	0.140
408	30	27	0.5	50				0.051	2.398	39.525	52.430	0.329	0.051	2.618	3.687	0.919	0.715	0.337	0.133
403	35	5	0.3		12	26	26	0.046	2.628	6.179	6.179	0.081	0.046	2.848	4.229	0.941	0.180	0.298	0.125
398	40	8	0.2		12	21	21	0.042	2.838	9.560	9.560	0.109	0.042	3.058	4.751	0.920	0.237	0.273	0.119
393	45	9	0.6		12	21	21	0.053	3.103	10.308	10.308	0.116	0.053	3.323	5.328	0.900	0.246	0.258	0.116
388	50	15	0.4		12	21	21	0.049	3.348	16.825	16.825	0.179	0.049	3.568	5.885	0.867	0.366	0.248	0.115
383	55	11	0.4		12	50	50	0.049	3.593	11.688	11.688	0.128	0.049	3.813	6.442	0.868	0.263	0.243	0.115
378	60	9	0.3		12	23	23	0.046	3.823	9.235	9.235	0.106	0.046	4.043	6.984	0.864	0.217	0.239	0.116
373	65	11	0.3		12	19	19	0.046	4.053	10.901	10.901	0.121	0.046	4.273	7.526	0.847	0.242	0.230	0.114
368	70	12	0.8		12	22	22	0.057	4.338	11.400	11.400	0.126	0.057	4.558	8.123	0.832	0.247	0.223	0.112
363	75	8	0.6		12	26	26	0.053	4.603	7.323	7.323	0.090	0.053	4.823	8.700	0.838	0.179	0.216	0.110
358	80	13	0.6		12	25	25	0.053	4.868	11.494	11.494	0.127	0.053	5.088	9.277	0.810	0.242	0.209	0.107
353	85	24	1.5		12	22	22	0.064	5.188	21.173	21.173	0.231	0.064	5.408	9.909	0.754	0.411	0.202	0.104

* FACTOR OF SAFETY DESCRIPTIONS
N.L. (1) = NOT LIQUEFIABLE, ABOVE EQ GROUND WATER ELEVATION
N.L. (2) = NOT LIQUEFIABLE, PI ≥ 12 OR w_c/LL ≤ 0.85
N.L. (3) = NOT LIQUEFIABLE, (N₁)₆₀ > 25
(C) = CONTRACTIVE SOIL TYPES
(D) = DILATIVE SOIL TYPES

Appendix C



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE===== N Abutment (SN060-0229)
REFERENCE BORING ===== B-19
LRFD or ASD or SEISMIC ===== LRFD
PILE CUTOFF ELEV. ===== 439.92 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 438.92 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) ===== None
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD ===== ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) ===== ft

TOTAL FACTORED SUBSTRUCTURE LOAD ===== 1700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)===== 96.53 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE ===== 1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 140.89 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 52.83 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of Pile	Maximum Nominal Req'd Bearing of Boring	Maximum Factored Resistance Available in Boring	Maximum Pile Driveable Length in Boring
929 KIPS	929 KIPS	511 KIPS	100 FT.

PILE TYPE AND SIZE ===== Steel HP 14 X 117
Pile Perimeter===== 4.850 FT. Unplugged Pile Perimeter===== 7.117 FT.
Pile End Bearing Area===== 1.469 SQFT. Unplugged Pile End Bearing Area===== 0.239 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
435.50	3.42	0.30	2		4.0		9.6	5.9		6.8	7	0	0	4	4
433.00	2.50		3	Fine Sand	0.6	5.6	15.2	0.9	0.9	8.5	9	0	0	5	7
430.50	2.50		4	Fine Sand	0.8	10.6	11.6	1.2	1.7	9.0	9	0	0	5	9
428.00	2.50	0.30	4		2.9	6.2	14.6	4.3	1.0	13.3	13	0	0	7	12
425.50	2.50	0.30	5		2.9	6.2	15.5	4.3	1.0	17.3	15	0	0	9	14
423.00	2.50	0.20	3		2.0	4.1	15.4	2.9	0.7	19.9	15	0	0	8	17
420.50	2.50	0.10	4		1.0	2.1	18.5	1.5	0.3	21.7	18	0	0	10	19
418.00	2.50	0.20	4		2.0	4.1	30.1	2.9	0.7	26.2	26	0	0	14	22
415.50	2.50		5	Very Fine Silty Sand	0.9	13.7	31.9	1.4	2.2	27.7	28	0	0	15	24
413.00	2.50		4	Clean Coarse Sand	1.0	14.6	58.5	1.4	2.4	33.3	33	0	0	18	27
410.50	2.50		11	Clean Coarse Sand	2.7	40.3	119.7	3.9	6.5	46.7	47	0	0	26	29
408.00	2.50		27	Medium Sand	6.0	98.8	45.2	8.8	16.1	42.5	43	0	0	23	32
403.00	5.00		5	Medium Sand	2.2	18.3	33.3	3.2	3.0	43.4	33	0	0	18	37
398.00	5.00	0.20	8		4.0	4.1	45.5	5.8	0.7	50.6	45	0	0	25	42
393.00	5.00	0.60	9		11.1	12.4	52.5	16.4	2.0	66.3	53	0	0	29	47
388.00	5.00	0.40	15		7.7	8.2	60.2	11.3	1.3	77.6	60	0	0	33	52
383.00	5.00	0.40	11		7.7	8.2	65.8	11.3	1.3	88.6	66	0	0	36	57
378.00	5.00	0.30	9		5.9	6.2	71.7	8.6	1.0	97.2	72	0	0	39	62
373.00	5.00	0.30	11		5.9	6.2	87.9	8.6	1.0	107.5	88	0	0	48	67
368.00	5.00	0.80	12		14.3	16.5	106.3	21.0	2.7	129.1	106	0	0	58	72
363.00	5.00	1.00	8		17.2	20.6	123.6	25.3	3.3	154.4	124	0	0	68	77
358.00	5.00	1.00	13		17.2	20.6	161.4	25.3	3.3	183.1	161	0	0	89	82
349.50	8.50	2.00	24		48.0	41.2	351.2	70.4	6.7	276.5	277	0	0	152	90
348.50	1.00			Shale	60.4	183.0	411.6	88.7	29.8	365.2	365	0	0	201	91.4
347.50	1.00			Shale	60.4	183.0	472.0	88.7	29.8	453.8	454	0	0	250	92.4
346.50	1.00			Shale	60.4	183.0	532.5	88.7	29.8	542.5	532	0	0	293	93.4
345.50	1.00			Shale	60.4	183.0	592.9	88.7	29.8	631.1	593	0	0	326	94.4
344.50	1.00			Shale	60.4	183.0	653.3	88.7	29.8	719.8	653	0	0	359	95.4
343.50	1.00			Shale	60.4	183.0	713.7	88.7	29.8	808.5	714	0	0	393	96.4
342.50	1.00			Shale	60.4	183.0	774.1	88.7	29.8	897.1	774	0	0	426	97.4
341.50	1.00			Shale	60.4	183.0	834.5	88.7	29.8	985.8	835	0	0	459	98.4
340.50	1.00			Shale	60.4	183.0	895.0	88.7	29.8	1074.4	895	0	0	492	99.4
339.50	1.00			Shale	60.4	183.0	955.4	88.7	29.8	1163.1	955	0	0	525	100.4
338.50	1.00			Shale	60.4	183.0	1015.8	88.7	29.8	1251.7	1016	0	0	559	101.4
337.50	1.00			Shale	60.4	183.0	1076.2	88.7	29.8	1340.4	1076	0	0	592	102.4
336.50	1.00			Shale	60.4	183.0	1136.6	88.7	29.8	1429.0	1137	0	0	625	103.4
335.50	1.00			Shale	60.4	183.0	1197.0	88.7	29.8	1517.7	1197	0	0	658	104.4
334.50	1.00			Shale		183.0			29.8						

Pile Design Table for N Abutment (SN060-0229) utilizing Boring #B-19

	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)		Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)		Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	
				Steel HP 10 X 42	80	44	77		Steel HP 12 X 84	87	48	72
					101	55	82			102	56	77
					179	99	90			131	72	82
					335	184	94			227	125	90
					335	184	96			664	365	98
				Steel HP 10 X 57					Steel HP 14 X 73			
					81	45	77			85	47	67
					103	57	82			102	56	72
					184	101	90			119	66	77
					454	250	96			155	85	82
				Steel HP 12 X 53						260	143	90
					84	46	72			578	318	95
					98	54	77			578	318	96
					126	69	82		Steel HP 14 X 89			
					215	118	90			86	47	67
					418	230	94			104	57	72
					418	230	96			121	66	77
				Steel HP 12 X 63						157	86	82
					85	47	72			266	147	90
					99	54	77			705	388	97
					127	70	82		Steel HP 14 X 102			
					220	121	90			87	48	67
					497	273	95			105	58	72
					497	273	96			122	67	77
				Steel HP 12 X 74						159	88	82
					86	47	72			271	149	90
					100	55	77			810	445	98
					129	71	82		Steel HP 14 X 117			
					224	123	90			88	48	67
					589	324	97			106	58	72
										124	68	77
										161	89	82
										277	152	90
										929	511	100



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====Int N Pier est. (SN060-0229)
REFERENCE BORING =====B-19
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====439.92 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 432.58 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of Pile	Maximum Nominal Req'd Bearing of Boring	Maximum Factored Resistance Available in Boring	Maximum Pile Driveable Length in Boring
929 KIPS	929 KIPS	511 KIPS	100 FT.

TOTAL FACTORED SUBSTRUCTURE LOAD =====1700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====96.53 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====140.89 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====52.83 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 117
Pile Perimeter=====4.850 FT. Unplugged Pile Perimeter=====7.117 FT.
Pile End Bearing Area=====1.469 SQFT. Unplugged Pile End Bearing Area=====0.239 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
430.00	2.58	0.50	4		4.9		11.1	7.2		8.2	8	0	0	4	10
427.50	2.50	0.30	4		2.9	6.2	14.0	4.3	1.0	12.5	12	0	0	7	12
425.00	2.50	0.30	5		2.9	6.2	14.9	4.3	1.0	16.4	15	0	0	8	15
422.50	2.50	0.20	3		2.0	4.1	14.8	2.9	0.7	19.0	15	0	0	8	17
420.00	2.50	0.10	4		1.0	2.1	17.9	1.5	0.3	20.9	18	0	0	10	20
417.50	2.50	0.20	4		2.0	4.1	29.5	2.9	0.7	25.3	25	0	0	14	22
415.00	2.50		5	Very Fine Silty Sand	0.9	13.7	31.3	1.4	2.2	26.9	27	0	0	15	25
412.50	2.50		4	Clean Coarse Sand	1.0	14.6	57.9	1.4	2.4	32.5	32	0	0	18	27
410.00	2.50		11	Clean Coarse Sand	2.7	40.3	119.2	3.9	6.5	45.9	46	0	0	25	30
407.50	2.50		27	Medium Sand	6.0	98.8	44.6	8.8	16.1	41.6	42	0	0	23	32
402.50	5.00		5	Medium Sand	2.2	18.3	32.7	3.2	3.0	42.6	33	0	0	18	37
397.50	5.00	0.20	8		4.0	4.1	44.9	5.8	0.7	49.7	45	0	0	25	42
392.50	5.00	0.60	9		11.1	12.4	51.9	16.4	2.0	65.4	52	0	0	29	47
387.50	5.00	0.40	15		7.7	8.2	59.6	11.3	1.3	76.7	60	0	0	33	52
382.50	5.00	0.40	11		7.7	8.2	65.2	11.3	1.3	87.7	65	0	0	36	57
377.50	5.00	0.30	9		5.9	6.2	71.1	8.6	1.0	96.3	71	0	0	39	62
372.50	5.00	0.30	11		5.9	6.2	87.3	8.6	1.0	106.6	87	0	0	48	67
367.50	5.00	0.80	12		14.3	16.5	105.7	21.0	2.7	128.3	106	0	0	58	72
362.50	5.00	1.00	8		17.2	20.6	123.0	25.3	3.3	153.6	123	0	0	68	77
357.50	5.00	1.00	13		17.2	20.6	160.8	25.3	3.3	182.2	161	0	0	88	82
349.50	8.00	2.00	24		45.2	41.2	347.8	66.3	6.7	271.5	272	0	0	149	90
348.50	1.00			Shale	60.4	183.0	408.2	88.7	29.8	360.2	360	0	0	198	91.4
347.50	1.00			Shale	60.4	183.0	468.6	88.7	29.8	448.8	449	0	0	247	92.4
346.50	1.00			Shale	60.4	183.0	529.0	88.7	29.8	537.5	529	0	0	291	93.4
345.50	1.00			Shale	60.4	183.0	589.5	88.7	29.8	626.1	589	0	0	324	94.4
344.50	1.00			Shale	60.4	183.0	649.9	88.7	29.8	714.8	650	0	0	357	95.4
343.50	1.00			Shale	60.4	183.0	710.3	88.7	29.8	803.4	710	0	0	391	96.4
342.50	1.00			Shale	60.4	183.0	770.7	88.7	29.8	892.1	771	0	0	424	97.4
341.50	1.00			Shale	60.4	183.0	831.1	88.7	29.8	980.7	831	0	0	457	98.4
340.50	1.00			Shale	60.4	183.0	891.5	88.7	29.8	1069.4	892	0	0	490	99.4
339.50	1.00			Shale	60.4	183.0	952.0	88.7	29.8	1158.1	952	0	0	524	100.4
338.50	1.00			Shale	60.4	183.0	1012.4	88.7	29.8	1246.7	1012	0	0	557	101.4
337.50	1.00			Shale	60.4	183.0	1072.8	88.7	29.8	1335.4	1073	0	0	590	102.4
336.50	1.00			Shale	60.4	183.0	1133.2	88.7	29.8	1424.0	1133	0	0	623	103.4
335.50	1.00			Shale	60.4	183.0	1193.6	88.7	29.8	1512.7	1194	0	0	656	104.4
334.50	1.00			Shale		183.0			29.8						

Pile Design Table for Int N Pier est. (SN060-0229) utilizing Boring #B-19

Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)
			Steel HP 10 X 42			Steel HP 12 X 84		
			79	44	77	87	48	72
			100	55	82	101	56	77
			176	97	90	131	72	82
			335	184	94	223	123	90
			335	184	98	664	365	98
			Steel HP 10 X 57			Steel HP 14 X 73		
			81	45	77	84	46	67
			103	57	82	102	56	72
			180	99	90	119	65	77
			454	250	96	155	85	82
			454	250	98	255	141	90
			Steel HP 12 X 53			578	318	95
			83	46	72	578	318	98
			98	54	77	Steel HP 14 X 89		
			125	69	82	85	47	67
			210	116	90	103	57	72
			418	230	94	120	66	77
			418	230	98	157	86	82
			Steel HP 12 X 63			262	144	90
			84	46	72	705	388	97
			98	54	77	705	388	98
			127	70	82	Steel HP 14 X 102		
			216	119	90	86	47	67
			497	273	95	104	57	72
			497	273	98	121	67	77
			Steel HP 12 X 74			159	87	82
			85	47	72	266	146	90
			100	55	77	810	445	98
			129	71	82	Steel HP 14 X 117		
			220	121	90	87	48	67
			589	324	97	106	58	72
			589	324	98	123	68	77
						161	88	82
						272	149	90
						929	511	100
Steel HP 8 X 36								
79	44	82						
141	78	90						
286	157	95						
286	157	98						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====Int N Pier est. (SN060-0229)
REFERENCE BORING =====B-19
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====439.92 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 432.58 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====414.80 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of Pile	Maximum Nominal Req'd Bearing of Boring	Maximum Factored Resistance Available in Boring	Maximum Pile Driveable Length in Boring
929 KIPS	929 KIPS	502 KIPS	100 FT.

TOTAL FACTORED SUBSTRUCTURE LOAD =====1700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====96.53 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====140.89 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====52.83 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 117
Pile Perimeter=====4.850 FT. Unplugged Pile Perimeter=====7.117 FT.
Pile End Bearing Area=====1.469 SQFT. Unplugged Pile End Bearing Area=====0.239 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
430.00	2.58	0.50	4		4.9		11.1	7.2		8.2	8	3	0	2	10
427.50	2.50	0.30	4		2.9	6.2	14.0	4.3	1.0	12.5	12	4	0	3	12
425.00	2.50	0.30	5		2.9	6.2	14.9	4.3	1.0	16.4	15	6	0	2	15
422.50	2.50	0.20	3		2.0	4.1	14.8	2.9	0.7	19.0	15	7	0	1	17
420.00	2.50	0.10	4		1.0	2.1	17.9	1.5	0.3	20.9	18	8	0	2	20
417.50	2.50	0.20	4		2.0	4.1	29.5	2.9	0.7	25.3	25	9	0	5	22
415.00	2.50		5	Very Fine Silty Sand	0.9	13.7	31.3	1.4	2.2	26.9	27	9	0	6	25
412.50	2.50		4	Clean Coarse Sand	1.0	14.6	57.9	1.4	2.4	32.5	32	9	0	9	27
410.00	2.50		11	Clean Coarse Sand	2.7	40.3	119.2	3.9	6.5	45.9	46	9	0	16	30
407.50	2.50		27	Medium Sand	6.0	98.8	44.6	8.8	16.1	41.6	42	9	0	14	32
402.50	5.00		5	Medium Sand	2.2	18.3	32.7	3.2	3.0	42.6	33	9	0	9	37
397.50	5.00	0.20	8		4.0	4.1	44.9	5.8	0.7	49.7	45	9	0	16	42
392.50	5.00	0.60	9		11.1	12.4	51.9	16.4	2.0	65.4	52	9	0	19	47
387.50	5.00	0.40	15		7.7	8.2	59.6	11.3	1.3	76.7	60	9	0	24	52
382.50	5.00	0.40	11		7.7	8.2	65.2	11.3	1.3	87.7	65	9	0	27	57
377.50	5.00	0.30	9		5.9	6.2	71.1	8.6	1.0	96.3	71	9	0	30	62
372.50	5.00	0.30	11		5.9	6.2	87.3	8.6	1.0	106.6	87	9	0	39	67
367.50	5.00	0.80	12		14.3	16.5	105.7	21.0	2.7	128.3	106	9	0	49	72
362.50	5.00	1.00	8		17.2	20.6	123.0	25.3	3.3	153.6	123	9	0	58	77
357.50	5.00	1.00	13		17.2	20.6	160.8	25.3	3.3	182.2	161	9	0	79	82
349.50	8.00	2.00	24		45.2	41.2	347.8	66.3	6.7	271.5	272	9	0	140	90
348.50	1.00			Shale	60.4	183.0	408.2	88.7	29.8	360.2	360	9	0	189	91.4
347.50	1.00			Shale	60.4	183.0	468.6	88.7	29.8	448.8	449	9	0	238	92.4
346.50	1.00			Shale	60.4	183.0	529.0	88.7	29.8	537.5	529	9	0	282	93.4
345.50	1.00			Shale	60.4	183.0	589.5	88.7	29.8	626.1	589	9	0	315	94.4
344.50	1.00			Shale	60.4	183.0	649.9	88.7	29.8	714.8	650	9	0	348	95.4
343.50	1.00			Shale	60.4	183.0	710.3	88.7	29.8	803.4	710	9	0	381	96.4
342.50	1.00			Shale	60.4	183.0	770.7	88.7	29.8	892.1	771	9	0	415	97.4
341.50	1.00			Shale	60.4	183.0	831.1	88.7	29.8	980.7	831	9	0	448	98.4
340.50	1.00			Shale	60.4	183.0	891.5	88.7	29.8	1069.4	892	9	0	481	99.4
339.50	1.00			Shale	60.4	183.0	952.0	88.7	29.8	1158.1	952	9	0	514	100.4
338.50	1.00			Shale	60.4	183.0	1012.4	88.7	29.8	1246.7	1012	9	0	548	101.4
337.50	1.00			Shale	60.4	183.0	1072.8	88.7	29.8	1335.4	1073	9	0	581	102.4
336.50	1.00			Shale	60.4	183.0	1133.2	88.7	29.8	1424.0	1133	9	0	614	103.4
335.50	1.00			Shale	60.4	183.0	1193.6	88.7	29.8	1512.7	1194	9	0	647	104.4
334.50	1.00			Shale		183.0			29.8						

Pile Design Table for Int N Pier est. (SN060-0229) utilizing Boring #B-19

	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)		Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)		Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	
				Steel HP 10 X 42	100	49	82		Steel HP 12 X 84	101	48	77
					176	90	90		131	64	82	
					335	178	94		223	115	90	
					335	178	98		664	357	98	
				Steel HP 10 X 57					Steel HP 14 X 73			
					103	50	82		102	47	72	
					180	93	90		119	56	77	
					454	243	96		155	76	82	
					454	243	98		255	132	90	
				Steel HP 12 X 53					578	309	95	
					98	46	77		578	309	98	
					125	61	82		Steel HP 14 X 89			
					210	108	90		103	48	72	
					418	223	94		120	57	77	
					418	223	98		157	77	82	
				Steel HP 12 X 63					262	135	90	
					98	47	77		705	379	97	
					127	62	82		705	379	98	
					216	111	90		Steel HP 14 X 102			
					497	266	95		104	48	72	
					497	266	98		121	58	77	
				Steel HP 12 X 74					159	78	82	
					100	47	77		266	137	90	
					129	63	82		810	436	98	
					220	113	90		Steel HP 14 X 117			
					589	316	97		106	49	72	
					589	316	98		123	58	77	
									161	79	82	
									272	140	90	
									929	502	100	



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====Int S Pier est. (SN060-0229)
REFERENCE BORING =====B-7
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====440.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 432.58 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====1700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====96.53 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 140.89 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 52.83 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of Pile	Maximum Nominal Req'd Bearing of Boring	Maximum Factored Resistance Available in Boring	Maximum Pile Driveable Length in Boring
929 KIPS	929 KIPS	511 KIPS	95 FT.

PILE TYPE AND SIZE =====Steel HP 14 X 117
Pile Perimeter===== 4.850 FT. Unplugged Pile Perimeter===== 7.117 FT.
Pile End Bearing Area===== 1.469 SQFT. Unplugged Pile End Bearing Area===== 0.239 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
430.00	2.58		0	Very Fine Silty Sand	0.0		1.6	0.0		0.3	0	0	0	0	10
427.50	2.50		1	Very Fine Silty Sand	0.2	1.6	2.6	0.3	0.3	0.7	1	0	0	0	13
425.00	2.50		1	Very Fine Silty Sand	0.2	2.4	5.9	0.3	0.4	1.4	1	0	0	1	15
422.50	2.50		2	Very Fine Silty Sand	0.4	5.5	10.6	0.6	0.9	2.7	3	0	0	1	18
420.00	2.50	0.48	3		4.6	9.9	13.5	6.7	1.6	9.1	9	0	0	5	20
417.50	2.50		3	Very Fine Silty Sand	0.6	8.2	64.4	0.8	1.3	18.1	18	0	0	10	23
415.00	2.50		16	Fine Sand	3.3	58.6	36.7	4.9	9.5	18.0	18	0	0	10	25
412.50	2.50		10	Very Fine Silty Sand	1.9	27.5	102.6	2.8	4.5	31.1	31	0	0	17	28
410.00	2.50		25	Medium Sand	5.5	91.5	64.2	8.1	14.9	32.1	32	0	0	18	30
407.50	2.50		13	Medium Sand	2.9	47.6	60.5	4.2	7.7	35.2	35	0	0	19	33
402.50	5.00	1.99	10		28.2	41.0	98.7	41.3	6.7	78.2	78	0	0	43	38
397.50	5.00	2.48	11		32.5	51.1	121.1	47.7	8.3	124.2	121	0	0	67	43
392.50	5.00	1.99	11		28.2	41.0	141.2	41.3	6.7	164.2	141	0	0	78	48
387.50	5.00	1.60	10		24.4	32.9	190.3	35.8	5.4	204.0	190	0	0	105	53
382.50	5.00	2.80	14		35.3	57.7	196.2	51.8	9.4	251.1	196	0	0	108	58
377.50	5.00	1.37	8		21.9	28.2	252.3	32.1	4.6	288.8	252	0	0	139	63
372.50	5.00	3.03	15		37.4	62.4	283.7	54.8	10.1	342.6	284	0	0	156	68
367.50	5.00	2.74	9		34.8	56.4	305.1	51.1	9.2	391.5	305	0	0	168	73
362.50	5.00	2.09	16		29.0	43.0	320.5	42.6	7.0	431.9	321	0	0	176	78
357.50	5.00	1.43	12		22.6	29.4	347.6	33.1	4.8	465.7	348	0	0	191	83
352.00	5.50	1.65	31		27.4	34.0	524.0	40.2	5.5	530.2	524	0	0	288	88
351.00	1.00			Shale	60.4	183.0	584.5	88.7	29.8	618.8	584	0	0	321	89
350.00	1.00			Shale	60.4	183.0	644.9	88.7	29.8	707.5	645	0	0	355	90
349.00	1.00			Shale	60.4	183.0	705.3	88.7	29.8	796.1	705	0	0	388	91
348.00	1.00			Shale	60.4	183.0	765.7	88.7	29.8	884.8	766	0	0	421	92
347.00	1.00			Shale	60.4	183.0	826.1	88.7	29.8	973.4	826	0	0	454	93
346.00	1.00			Shale	60.4	183.0	886.6	88.7	29.8	1062.1	887	0	0	488	94
345.00	1.00			Shale	60.4	183.0	947.0	88.7	29.8	1150.7	947	0	0	521	95
344.00	1.00			Shale	60.4	183.0	1007.4	88.7	29.8	1239.4	1007	0	0	554	96
343.00	1.00			Shale	60.4	183.0	1067.8	88.7	29.8	1328.0	1068	0	0	587	97
342.00	1.00			Shale	60.4	183.0	1128.2	88.7	29.8	1416.7	1128	0	0	621	98
341.00	1.00			Shale	60.4	183.0	1188.6	88.7	29.8	1505.3	1189	0	0	654	99
340.00	1.00			Shale	60.4	183.0	1249.1	88.7	29.8	1594.0	1249	0	0	687	100
339.00	1.00			Shale	60.4	183.0	1309.5	88.7	29.8	1682.6	1309	0	0	720	101
338.00	1.00			Shale	60.4	183.0	1369.9	88.7	29.8	1771.3	1370	0	0	753	102
337.00	1.00			Shale	60.4	183.0	1430.3	88.7	29.8	1860.0	1430	0	0	787	103
336.00	1.00			Shale		183.0			29.8						

Pile Design Table for Int S Pier est. (SN060-0229) utilizing Boring #B-7

Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)
			Steel HP 10 X 42			Steel HP 12 X 84		
			89	49	48	64	35	38
			117	64	53	97	53	43
			127	70	58	115	63	48
			158	87	63	153	84	53
			181	99	68	162	89	58
			198	109	73	205	113	63
			212	116	78	232	128	68
			229	126	83	252	139	73
			317	174	88	267	147	78
			335	184	89	289	159	83
			Steel HP 10 X 57			419	231	88
			91	50	48	664	365	93
			120	66	53	664	365	96
			130	72	58	Steel HP 14 X 73		
			162	89	63	74	41	38
			185	102	68	116	64	43
			203	111	73	136	75	48
			216	119	78	183	100	53
			234	129	83	189	104	58
			325	179	88	243	133	63
			454	250	92	273	150	68
			454	250	96	294	162	73
			Steel HP 12 X 53			310	170	78
			93	51	43	336	185	83
			111	61	48	502	276	88
			147	81	53	578	318	90
			156	86	58	Steel HP 14 X 89		
			197	108	63	75	41	38
			224	123	68	118	65	43
			243	134	73	138	76	48
			258	142	78	185	102	53
			279	154	83	192	105	58
			401	221	88	246	135	63
			418	230	89	277	152	68
			Steel HP 12 X 63			298	164	73
			94	52	43	313	172	78
			112	61	48	340	187	83
			149	82	53	509	280	88
			158	87	58	705	388	92
			199	109	63	705	388	96
			226	124	68	Steel HP 14 X 102		
			245	135	73	77	42	38
			260	143	78	119	66	43
			282	155	83	139	77	48
			406	223	88	188	103	53
			497	273	90	194	107	58
			Steel HP 12 X 74			249	137	63
			95	53	43	280	154	68
			113	62	48	301	166	73
			151	83	53	317	174	78
			160	88	58	344	189	83
			202	111	63	517	284	88
			229	126	68	810	445	93
			249	137	73	810	445	96
			264	145	78	Steel HP 14 X 117		
			286	157	83	78	43	38
			412	227	88	121	67	43
			589	324	92	141	78	48
			589	324	96	190	105	53
						196	108	58
						252	139	63
						284	156	68
						305	168	73
						321	176	78
						348	191	83
						524	288	88
						929	511	95
						929	511	96
Steel HP 8 X 36								
92	50	53						
102	56	58						
125	69	63						
144	79	68						
159	87	73						
171	94	78						
185	102	83						
246	135	88						
286	157	90						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====Int S Pier est. (SN060-0229)
REFERENCE BORING =====B-7
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====440.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 432.58 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====414.80 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of Pile	Maximum Nominal Req'd Bearing of Boring	Maximum Factored Resistance Available in Boring	Maximum Pile Driveable Length in Boring
929 KIPS	929 KIPS	506 KIPS	95 FT.

TOTAL FACTORED SUBSTRUCTURE LOAD =====1700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====96.53 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====140.89 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====52.83 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 117
Pile Perimeter=====4.850 FT. Unplugged Pile Perimeter=====7.117 FT.
Pile End Bearing Area=====1.469 SQFT. Unplugged Pile End Bearing Area=====0.239 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
430.00	2.58		0	Very Fine Silty Sand	0.0		1.6	0.0		0.3	0	0	0	0	10
427.50	2.50		1	Very Fine Silty Sand	0.2	1.6	2.6	0.3	0.3	0.7	1	0	0	0	13
425.00	2.50		1	Very Fine Silty Sand	0.2	2.4	5.9	0.3	0.4	1.4	1	0	0	1	15
422.50	2.50		2	Very Fine Silty Sand	0.4	5.5	10.6	0.6	0.9	2.7	3	0	0	1	18
420.00	2.50	0.48	3		4.6	9.9	13.5	6.7	1.6	9.1	9	3	0	2	20
417.50	2.50		3	Very Fine Silty Sand	0.6	8.2	64.4	0.8	1.3	18.1	18	3	0	7	23
415.00	2.50		16	Fine Sand	3.3	58.6	36.7	4.9	9.5	18.0	18	5	0	5	25
412.50	2.50		10	Very Fine Silty Sand	1.9	27.5	102.6	2.8	4.5	31.1	31	5	0	12	28
410.00	2.50		25	Medium Sand	5.5	91.5	64.2	8.1	14.9	32.1	32	5	0	13	30
407.50	2.50		13	Medium Sand	2.9	47.6	60.5	4.2	7.7	35.2	35	5	0	14	33
402.50	5.00	1.99	10		28.2	41.0	98.7	41.3	6.7	78.2	78	5	0	38	38
397.50	5.00	2.48	11		32.5	51.1	121.1	47.7	8.3	124.2	121	5	0	62	43
392.50	5.00	1.99	11		28.2	41.0	141.2	41.3	6.7	164.2	141	5	0	73	48
387.50	5.00	1.60	10		24.4	32.9	190.3	35.8	5.4	204.0	190	5	0	100	53
382.50	5.00	2.80	14		35.3	57.7	196.2	51.8	9.4	251.1	196	5	0	103	58
377.50	5.00	1.37	8		21.9	28.2	252.3	32.1	4.6	288.8	252	5	0	134	63
372.50	5.00	3.03	15		37.4	62.4	283.7	54.8	10.1	342.6	284	5	0	151	68
367.50	5.00	2.74	9		34.8	56.4	305.1	51.1	9.2	391.5	305	5	0	163	73
362.50	5.00	2.09	16		29.0	43.0	320.5	42.6	7.0	431.9	321	5	0	171	78
357.50	5.00	1.43	12		22.6	29.4	347.6	33.1	4.8	465.7	348	5	0	186	83
352.00	5.50	1.65	31		27.4	34.0	524.0	40.2	5.5	530.2	524	5	0	283	88
351.00	1.00			Shale	60.4	183.0	584.5	88.7	29.8	618.8	584	5	0	316	89
350.00	1.00			Shale	60.4	183.0	644.9	88.7	29.8	707.5	645	5	0	350	90
349.00	1.00			Shale	60.4	183.0	705.3	88.7	29.8	796.1	705	5	0	383	91
348.00	1.00			Shale	60.4	183.0	765.7	88.7	29.8	884.8	766	5	0	416	92
347.00	1.00			Shale	60.4	183.0	826.1	88.7	29.8	973.4	826	5	0	449	93
346.00	1.00			Shale	60.4	183.0	886.6	88.7	29.8	1062.1	887	5	0	483	94
345.00	1.00			Shale	60.4	183.0	947.0	88.7	29.8	1150.7	947	5	0	516	95
344.00	1.00			Shale	60.4	183.0	1007.4	88.7	29.8	1239.4	1007	5	0	549	96
343.00	1.00			Shale	60.4	183.0	1067.8	88.7	29.8	1328.0	1068	5	0	582	97
342.00	1.00			Shale	60.4	183.0	1128.2	88.7	29.8	1416.7	1128	5	0	615	98
341.00	1.00			Shale	60.4	183.0	1188.6	88.7	29.8	1505.3	1189	5	0	649	99
340.00	1.00			Shale	60.4	183.0	1249.1	88.7	29.8	1594.0	1249	5	0	682	100
339.00	1.00			Shale	60.4	183.0	1309.5	88.7	29.8	1682.6	1309	5	0	715	101
338.00	1.00			Shale	60.4	183.0	1369.9	88.7	29.8	1771.3	1370	5	0	748	102
337.00	1.00			Shale	60.4	183.0	1430.3	88.7	29.8	1860.0	1430	5	0	782	103
336.00	1.00			Shale		183.0			29.8						

Pile Design Table for Int S Pier est. (SN060-0229) utilizing Boring #B-7

Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)
			Steel HP 10 X 42			Steel HP 12 X 84		
			89	45	48	97	49	43
			117	61	53	115	59	48
			127	67	58	153	80	53
			158	84	63	162	85	58
			181	96	68	205	109	63
			198	106	73	232	124	68
			212	113	78	252	134	73
			229	123	83	267	143	78
			317	171	88	289	155	83
			335	181	89	419	226	88
			Steel HP 10 X 57			664	361	93
			91	47	48	664	361	96
			120	62	53	Steel HP 14 X 73		
			130	68	58	74	36	38
			162	85	63	116	59	43
			185	98	68	136	70	48
			203	108	73	183	96	53
			216	115	78	189	99	58
			234	125	83	243	129	63
			325	175	88	273	145	68
			454	246	92	294	157	73
			454	246	96	310	165	78
			Steel HP 12 X 53			336	180	83
			93	47	43	502	271	88
			111	57	48	578	313	90
			147	77	53	Steel HP 14 X 89		
			156	82	58	75	37	38
			197	104	63	118	60	43
			224	119	68	138	71	48
			243	130	73	185	97	53
			258	138	78	192	100	58
			279	149	83	246	130	63
			401	217	88	277	147	68
			418	226	89	298	159	73
			Steel HP 12 X 63			313	167	78
			94	48	43	340	182	83
			112	57	48	509	275	88
			149	78	53	705	383	92
			158	83	58	705	383	96
			199	105	63	Steel HP 14 X 102		
			226	120	68	77	37	38
			245	131	73	119	61	43
			260	139	78	139	72	48
			282	151	83	188	98	53
			406	219	88	194	102	58
			497	269	90	249	132	63
			Steel HP 12 X 74			280	149	68
			95	48	43	301	161	73
			113	58	48	317	169	78
			151	79	53	344	184	83
			160	84	58	517	279	88
			202	107	63	810	440	93
			229	122	68	810	440	96
			249	133	73	Steel HP 14 X 117		
			264	141	78	78	38	38
			286	153	83	121	62	43
			412	223	88	141	73	48
			589	320	92	190	100	53
			589	320	96	196	103	58
			Steel HP 8 X 36			252	134	63
			92	48	53	284	151	68
			102	53	58	305	163	73
			125	66	63	321	171	78
			144	76	68	348	186	83
			159	85	73	524	283	88
			171	91	78	929	506	95
			185	99	83	929	506	96
			246	133	88			
			286	155	90			



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE===== S Abutment (SN060-0229)
REFERENCE BORING ===== B-7
LRFD or ASD or SEISMIC ===== LRFD
PILE CUTOFF ELEV. ===== 440.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 439.00 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) ===== None
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD ===== ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) ===== ft

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of Pile	Maximum Nominal Req'd Bearing of Boring	Maximum Factored Resistance Available in Boring	Maximum Pile Driveable Length in Boring
929 KIPS	929 KIPS	511 KIPS	95 FT.

TOTAL FACTORED SUBSTRUCTURE LOAD ===== 1700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)===== 96.53 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE ===== 1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 140.89 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 52.83 KIPS

PILE TYPE AND SIZE ===== Steel HP 14 X 117
Pile Perimeter===== 4.850 FT. Unplugged Pile Perimeter===== 7.117 FT.
Pile End Bearing Area===== 1.469 SQFT. Unplugged Pile End Bearing Area===== 0.239 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
435.50	3.50		15	Clean Coarse Sand	5.1		24.0	7.4		10.5	11	0	0	6	5
433.00	2.50	0.92	13		8.0	18.9	13.1	11.8	3.1	19.3	13	0	0	7	7
430.50	2.50		0	Very Fine Silty Sand	0.0	0.0	15.9	0.0	0.0	19.7	16	0	0	9	10
428.00	2.50		1	Very Fine Silty Sand	0.2	2.7	16.1	0.3	0.4	20.0	16	0	0	9	12
425.50	2.50		1	Very Fine Silty Sand	0.2	2.7	19.0	0.3	0.4	20.7	19	0	0	10	15
423.00	2.50		2	Very Fine Silty Sand	0.4	5.5	23.8	0.6	0.9	22.0	22	0	0	12	17
420.50	2.50	0.48	3		4.6	9.9	26.7	6.7	1.6	28.4	27	0	0	15	20
418.00	2.50		3	Very Fine Silty Sand	0.6	8.2	77.6	0.8	1.3	37.4	37	0	0	21	22
415.50	2.50		16	Fine Sand	3.3	58.6	49.8	4.9	9.5	37.2	37	0	0	20	25
413.00	2.50		10	Very Fine Silty Sand	1.9	27.5	115.7	2.8	4.5	50.4	50	0	0	28	27
410.50	2.50		25	Medium Sand	5.5	91.5	77.3	8.1	14.9	51.4	51	0	0	28	30
408.00	2.50		13	Medium Sand	2.9	47.6	73.6	4.2	7.7	54.5	55	0	0	30	32
403.00	5.00	1.99	10		28.2	41.0	111.8	41.3	6.7	97.5	97	0	0	54	37
398.00	5.00	2.48	11		32.5	51.1	134.2	47.7	8.3	143.5	134	0	0	74	42
393.00	5.00	1.99	11		28.2	41.0	154.3	41.3	6.7	183.5	154	0	0	85	47
388.00	5.00	1.60	10		24.4	32.9	203.4	35.8	5.4	223.3	203	0	0	112	52
383.00	5.00	2.80	14		35.3	57.7	209.3	51.8	9.4	270.3	209	0	0	115	57
378.00	5.00	1.37	8		21.9	28.2	265.4	32.1	4.6	308.0	265	0	0	146	62
373.00	5.00	3.03	15		37.4	62.4	296.8	54.8	10.1	361.9	297	0	0	163	67
368.00	5.00	2.74	9		34.8	56.4	318.2	51.1	9.2	410.8	318	0	0	175	72
363.00	5.00	2.09	16		29.0	43.0	333.6	42.6	7.0	451.1	334	0	0	183	77
358.00	5.00	1.43	12		22.6	29.4	360.7	33.1	4.8	485.0	361	0	0	198	82
352.00	6.00	1.65	31		29.9	34.0	539.7	43.8	5.5	553.1	540	0	0	297	88
351.00	1.00			Shale	60.4	183.0	600.1	88.7	29.8	641.7	600	0	0	330	89
350.00	1.00			Shale	60.4	183.0	660.5	88.7	29.8	730.4	660	0	0	363	90
349.00	1.00			Shale	60.4	183.0	720.9	88.7	29.8	819.0	721	0	0	397	91
348.00	1.00			Shale	60.4	183.0	781.3	88.7	29.8	907.7	781	0	0	430	92
347.00	1.00			Shale	60.4	183.0	841.7	88.7	29.8	996.3	842	0	0	463	93
346.00	1.00			Shale	60.4	183.0	902.2	88.7	29.8	1085.0	902	0	0	496	94
345.00	1.00			Shale	60.4	183.0	962.6	88.7	29.8	1173.6	963	0	0	529	95
344.00	1.00			Shale	60.4	183.0	1023.0	88.7	29.8	1262.3	1023	0	0	563	96
343.00	1.00			Shale	60.4	183.0	1083.4	88.7	29.8	1350.9	1083	0	0	596	97
342.00	1.00			Shale	60.4	183.0	1143.8	88.7	29.8	1439.6	1144	0	0	629	98
341.00	1.00			Shale		183.0			29.8						

Pile Design Table for S Abutment (SN060-0229) utilizing Boring #B-7

Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)
			Steel HP 10 X 42			Steel HP 12 X 84		
			82	45	42	80	44	37
			98	54	47	108	59	42
			126	69	52	126	69	47
			136	75	57	164	90	52
			167	92	62	173	95	57
			190	104	67	216	119	62
			207	114	72	244	134	67
			221	121	77	263	145	72
			238	131	82	278	153	77
			327	180	88	301	165	82
			335	184	89	432	238	88
			335	184	94	664	365	93
			Steel HP 10 X 57			664	365	94
			84	46	42	Steel HP 14 X 73		
			100	55	47	93	51	37
			129	71	52	129	71	42
			139	77	57	149	82	47
			171	94	62	195	107	52
			194	107	67	202	111	57
			212	116	72	255	140	62
			225	124	77	286	157	67
			243	134	82	307	169	72
			336	185	88	322	177	77
			454	250	91	349	192	82
			454	250	94	517	285	88
			Steel HP 12 X 53			578	318	90
			76	42	37	578	318	94
			104	57	42	Steel HP 14 X 89		
			121	67	47	94	52	37
			158	87	52	131	72	42
			167	92	57	150	83	47
			208	114	62	198	109	52
			234	129	67	204	112	57
			254	140	72	259	142	62
			268	148	77	290	159	67
			290	159	82	311	171	72
			414	228	88	326	179	77
			418	230	89	353	194	82
			418	230	94	525	289	88
			Steel HP 12 X 63			705	388	92
			78	43	37	705	388	94
			105	58	42	Steel HP 14 X 102		
			123	67	47	96	53	37
			159	88	52	132	73	42
			169	93	57	152	84	47
			210	115	62	201	110	52
			237	130	67	207	114	57
			256	141	72	262	144	62
			271	149	77	293	161	67
			293	161	82	314	173	72
			419	230	88	330	181	77
			497	273	90	357	196	82
			497	273	94	532	293	88
			Steel HP 12 X 74			810	445	93
			79	44	37	810	445	94
			106	59	42	Steel HP 14 X 117		
			124	68	47	55	30	32
			162	89	52	97	54	37
			171	94	57	134	74	42
			213	117	62	154	85	47
			240	132	67	203	112	52
			260	143	72	209	115	57
			275	151	77	265	146	62
			297	163	82	297	163	67
			426	234	88	318	175	72
			589	324	92	334	183	77
			589	324	94	361	198	82
			Steel HP 8 X 36			540	297	88
			78	43	47	929	511	95
			99	54	52			
			109	60	57			
			132	73	62			
			151	83	67			
			166	91	72			
			178	98	77			
			192	106	82			
			255	140	88			
			286	157	89			
			286	157	94			



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE===== S Abutment (SN060-0229)
REFERENCE BORING ===== B-7
LRFD or ASD or SEISMIC ===== LRFD
PILE CUTOFF ELEV. ===== 440.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 439.00 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) ===== DD
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD ===== 418.00 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) ===== ft

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of Pile	Maximum Nominal Req'd Bearing of Boring	Maximum Factored Resistance Available in Boring	Maximum Pile Driveable Length in Boring
929 KIPS	929 KIPS	479 KIPS	95 FT.

TOTAL FACTORED SUBSTRUCTURE LOAD ===== 1700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)===== 96.53 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE ===== 1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 140.89 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 52.83 KIPS

PILE TYPE AND SIZE ===== Steel HP 14 X 117
Pile Perimeter===== 4.850 FT. Unplugged Pile Perimeter===== 7.117 FT.
Pile End Bearing Area===== 1.469 SQFT. Unplugged Pile End Bearing Area===== 0.239 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
435.50	3.50		15	Clean Coarse Sand	5.1		24.0	7.4		10.5	11	3	6	-3	5
433.00	2.50	0.92	13		8.0	18.9	13.1	11.8	3.1	19.3	13	7	14	-14	7
430.50	2.50		0	Very Fine Silty Sand	0.0	0.0	15.9	0.0	0.0	19.7	16	7	14	-13	10
428.00	2.50		1	Very Fine Silty Sand	0.2	2.7	16.1	0.3	0.4	20.0	16	7	15	-13	12
425.50	2.50		1	Very Fine Silty Sand	0.2	2.7	19.0	0.3	0.4	20.7	19	7	15	-12	15
423.00	2.50		2	Very Fine Silty Sand	0.4	5.5	23.8	0.6	0.9	22.0	22	8	15	-11	17
420.50	2.50	0.48	3		4.6	9.9	26.7	6.7	1.6	28.4	27	10	20	-16	20
418.00	2.50		3	Very Fine Silty Sand	0.6	8.2	77.6	0.8	1.3	37.4	37	10	21	-11	22
415.50	2.50		16	Fine Sand	3.3	58.6	49.8	4.9	9.5	37.2	37	10	21	-11	25
413.00	2.50		10	Very Fine Silty Sand	1.9	27.5	115.7	2.8	4.5	50.4	50	10	21	-4	27
410.50	2.50		25	Medium Sand	5.5	91.5	77.3	8.1	14.9	51.4	51	10	21	-3	30
408.00	2.50		13	Medium Sand	2.9	47.6	73.6	4.2	7.7	54.5	55	10	21	-1	32
403.00	5.00	1.99	10		28.2	41.0	111.8	41.3	6.7	97.5	97	10	21	22	37
398.00	5.00	2.48	11		32.5	51.1	134.2	47.7	8.3	143.5	134	10	21	42	42
393.00	5.00	1.99	11		28.2	41.0	154.3	41.3	6.7	183.5	154	10	21	53	47
388.00	5.00	1.60	10		24.4	32.9	203.4	35.8	5.4	223.3	203	10	21	80	52
383.00	5.00	2.80	14		35.3	57.7	209.3	51.8	9.4	270.3	209	10	21	84	57
378.00	5.00	1.37	8		21.9	28.2	265.4	32.1	4.6	308.0	265	10	21	115	62
373.00	5.00	3.03	15		37.4	62.4	296.8	54.8	10.1	361.9	297	10	21	132	67
368.00	5.00	2.74	9		34.8	56.4	318.2	51.1	9.2	410.8	318	10	21	144	72
363.00	5.00	2.09	16		29.0	43.0	333.6	42.6	7.0	451.1	334	10	21	152	77
358.00	5.00	1.43	12		22.6	29.4	360.7	33.1	4.8	485.0	361	10	21	167	82
352.00	6.00	1.65	31		29.9	34.0	539.7	43.8	5.5	553.1	540	10	21	265	88
351.00	1.00			Shale	60.4	183.0	600.1	88.7	29.8	641.7	600	10	21	299	89
350.00	1.00			Shale	60.4	183.0	660.5	88.7	29.8	730.4	660	10	21	332	90
349.00	1.00			Shale	60.4	183.0	720.9	88.7	29.8	819.0	721	10	21	365	91
348.00	1.00			Shale	60.4	183.0	781.3	88.7	29.8	907.7	781	10	21	398	92
347.00	1.00			Shale	60.4	183.0	841.7	88.7	29.8	996.3	842	10	21	432	93
346.00	1.00			Shale	60.4	183.0	902.2	88.7	29.8	1085.0	902	10	21	465	94
345.00	1.00			Shale	60.4	183.0	962.6	88.7	29.8	1173.6	963	40	24	498	95
344.00	1.00			Shale	60.4	183.0	1023.0	88.7	29.8	1262.3	1023	40	24	534	96
343.00	1.00			Shale	60.4	183.0	1083.4	88.7	29.8	1350.9	1083	40	24	564	97
342.00	1.00			Shale	60.4	183.0	1143.8	88.7	29.8	1439.6	1144	40	24	598	98
341.00	1.00			Shale		183.0			29.8						

Pile Design Table for S Abutment (SN060-0229) utilizing Boring #B-7

	Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)		Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)		Nominal Required Bearing (Kips)	Factored Resistance Available (Kips)	Estimated Pile Length (Ft.)
Steel HP 8 X 36				Steel HP 10 X 42				Steel HP 12 X 84			
				126	48	52		126	43	47	
				136	54	57		164	64	52	
				167	70	62		173	69	57	
				190	83	67		216	92	62	
				207	93	72		244	107	67	
				221	100	77		263	118	72	
				238	110	82		278	126	77	
				327	159	88		301	139	82	
				335	163	89		432	211	88	
				335	163	94		664	339	93	
				Steel HP 10 X 57				664	339	94	
				129	49	52	Steel HP 14 X 73				
				139	55	57	149	51	47		
				171	72	62	195	77	52		
				194	85	67	202	81	57		
				212	95	72	255	110	62		
				225	102	77	286	127	67		
				243	112	82	307	138	72		
				336	163	88	322	147	77		
				454	228	91	349	161	82		
				454	228	94	517	254	88		
				Steel HP 12 X 53				578	287	90	
				121	41	47	578	287	94		
				158	61	52	Steel HP 14 X 89				
				167	66	57	150	52	47		
				208	89	62	198	78	52		
				234	103	67	204	82	57		
				254	114	72	259	112	62		
				268	122	77	290	128	67		
				290	134	82	311	140	72		
				414	202	88	326	149	77		
				418	204	89	353	163	82		
				418	204	94	525	258	88		
				Steel HP 12 X 63				705	357	92	
				123	42	47	705	357	94		
				159	62	52	Steel HP 14 X 102				
				169	67	57	152	53	47		
				210	90	62	201	79	52		
				237	104	67	207	83	57		
				256	115	72	262	113	62		
				271	123	77	293	130	67		
				293	135	82	314	142	72		
				419	204	88	330	150	77		
				497	247	90	357	165	82		
			497	247	94	532	262	88			
			Steel HP 12 X 74				810	414	93		
			124	42	47	810	414	94			
			162	63	52	Steel HP 14 X 117					
			171	68	57	134	42	42			
			213	91	62	154	53	47			
			240	106	67	203	80	52			
			260	117	72	209	84	57			
			275	125	77	265	115	62			
			297	137	82	297	132	67			
			426	208	88	318	144	72			
			589	298	92	334	152	77			
			589	298	94	361	167	82			
						540	265	88			
						929	479	95			

Appendix D

Appendix D - L-Pile Parameters (SN060-0229)


North Abutment B-19	Depth (ft)	Elevation (ft)	Abbreviated Soil Description	Effective Unit Weight (pcf)	Cohesion (psf)	Phi (degrees)	Soil Modulus Parameter (pci)	E ₅₀
	0 to 17.6	439.6 to 422	Soft Sandy Clay (without free water)	120	250	--	30	0.02
	17.6 to 29	422 to 410.6	Soft Sandy Clay (with free water)	55	250	--	30	0.02
	29 to 74	410.6 to 365.6	Medium Stiff Clay (with free water)	55	500	--	80	0.01
	74 to 90.1	365.6 to 349.5	Stiff Clay (with free water)	55	1500	--	500	0.007
	90.1+	< 349.5	Shale	130	5000	44	2000	0.004

Int. North Pier B-19	Depth (ft)	Elevation (ft)	Abbreviated Soil Description	Effective Unit Weight (pcf)	Cohesion (psf)	Phi (degrees)	Soil Modulus Parameter (pci)	E ₅₀
	0 to 10.6	432.6 to 422	Soft Sandy Clay (without free water)	120	250	--	30	0.02
	10.6 to 22	422 to 410.6	Soft Sandy Clay (with free water)	55	250	--	30	0.02
	22 to 67	410.6 to 365.6	Medium Stiff Clay (with free water)	55	500	--	80	0.01
	67 to 83.1	365.6 to 349.5	Stiff Clay (with free water)	55	1500	--	500	0.007
	83.1+	< 349.5	Shale	130	5000	44	2000	0.004


Int. South Pier B-7	Depth (ft)	Elevation (ft)	Abbreviated Soil Description	Effective Unit Weight (pcf)	Cohesion (psf)	Phi (degrees)	Soil Modulus Parameter (pci)	E ₅₀
	0 to 14.6	432.6 to 418	Submerged Loose Loam	50	--	26	20	--
	14.6 to 26.6	418 to 406	Submerged Medium Dense Sand	45	--	30	60	--
	26.6 to 80.6	406 to 352	Medium Stiff Clay (with free water)	55	2000	--	700	0.007
	80.6+	< 352	Shale	130	5000	44	2000	0.004

South Abutment B-7	Depth (ft)	Elevation (ft)	Abbreviated Soil Description	Effective Unit Weight (pcf)	Cohesion (psf)	Phi (degrees)	Soil Modulus Parameter (pci)	E ₅₀
	0 to 7.6	439.6 to 432	Medium Stiff Silty Loam (without free water)	115	1000	--	100	0.01
	7.6 to 21.6	432 to 418	Submerged Loose Loam	50	--	26	20	--
	21.6 to 33.6	418 to 406	Submerged Medium Dense Sand	45	--	30	60	--
	33.6 to 87.6	406 to 352	Medium Stiff Clay (with free water)	55	2000	--	700	0.007
	87.6+	< 352	Shale	130	5000	44	2000	0.004

Appendix E




Material Name	Color	Unit Weight (lbs/ft3)	Cohesion (psf)	Phi (deg)
New Clay Fill (A-6) - LT		125	50	28
Stone Riprap A6		110	0	42
Stiff Loam Fill		110	1800	0
Loose Silty Loam (A-4)		115	0	26
Medium Dense Sand (A-3)		110	0	30
Soft Sandy Clay (A-6) - LT		120	25	27
Medium Stiff Clay (A-7) - LT		120	50	27
Clayey Shale		125	2500	12



Project						PTB 195 Item 57 IL-157 over Judy's Branch (SN 060-0229)											
Analysis Description				End Slope North Abut (Long Term)				Location				Madison County, Illinois					
Drawn By		PP		Reviewed By:		TJC		Scale		1:123		Company		SCI Engineering, Inc.			
Date		5/23/2022				Project #		2020-0531.10				File Name		Slope Stability Analysis.slmd			

Material Name	Color	Unit Weight (lbs/ft3)	Cohesion (psf)	Phi (deg)
New Clay Fill (A-6)- Seismic		125	800	10
Stone Riprap A6		110	0	42
Stiff Loam Fill		110	1800	0
Loose Silty Loam (A-4)		115	0	26
Medium Dense Sand (A-3)		110	0	30
Soft Sandy Clay (A-6) - Seismic		120	400	6
Medium Stiff Clay (A-7) - Seismic		120	640	8
Clayey Shale		125	2500	12



Project

PTB 195 Item 57 IL-157 over Judy's Branch (SN 060-0229)

Analysis Description

End Slope North Abut (Seismic)

Location

Madison County, Illinois

Drawn By

PP

Reviewed By:

TJC

Scale

1:152

Company

SCI Engineering, Inc.

Date


5/23/2022

Project #

2020-0531.10


File Name

Slope Stability Analysis.slmd




FS = 2.14

Material Name	Color	Unit Weight (lbs/ft ³)	Cohesion (psf)	Phi (deg)
New Clay Fill (A-6) - LT		125	50	28
Stone Riprap A6		110	0	42
Stiff Loam Fill		110	1800	0
Loose Silty Loam (A-4)		115	0	26
Medium Dense Sand (A-3)		110	0	30
Soft Sandy Clay (A-6) - LT		120	25	27
Medium Stiff Clay (A-7) - LT		120	50	27
Clayey Shale		125	2500	12



	Project					
	PTB 195 Item 57 IL-157 over Judy's Branch (SN 060-0229)					
	Analysis Description				Location	
	End Slope South Abut (Long Term)				Madison County, Illinois	
	Drawn By		Reviewed By:		Scale	
PP		TJC		1:286		
Date		Project #		File Name		
5/23/2022		2020-0531.10		Slope Stability Analysis.slmd		
Company		SCI Engineering, Inc.				



Appendix F

Benchmark: Cut "□", with +, on top of parapet wall at Northwest corner of IL-157 Bridge over Judys Branch (S.N. 060-0087). Elev. 449.226.

Existing Structure: S.N. 060-0087 was originally built in 1933 under Section 117-B to carry F.A.P. Rte. 592 over Judys Branch. A deck replacement was completed in 1982 under Section 117BR-2 to replace the original deck, in addition to also replacing the expansion joints and deck drains. The existing superstructure consists of a 7½" thick composite reinforced concrete deck supported by steel W-shape beams. The substructure consists of reinforced concrete abutments supported by concrete piles and reinforced concrete pier bents, supported by concrete piles. Fixed bearings are located at the abutments and expansion bearings are located at the piers. The existing slopewalls consist of bare earth. The existing structure has a total length of 121'-2¾" bk. to bk. of abutments and a total width of 47'-6" out to out of deck. The bridge will be closed during construction.


No Salvage

TABLE OF ROADWAY STATIONS AND OFFSETS

Point	Station	Offset
A	583+72.33	61.03' Lt.
B	583+77.70	61.03' Lt.
C	583+84.65	61.03' Lt.
D	583+89.28	61.03' Lt.
E	583+91.70	61.03' Lt.
F	584+02.33	61.03' Lt.
G	584+02.33	56.94' Lt.
H	584+45.00	39.00' Lt.
I	583+99.85	51.50' Lt.
J	584+30.97	39.00' Lt.
K	583+82.12	56.69' Lt.
L	584+34.33	32.00' Lt.
M	584+43.42	32.00' Lt.
N	583+53.44	53.52' Lt.
O	583+65.92	40.83' Lt.
P	583+70.85	37.36' Lt.
Q	583+72.33	36.32' Lt.
R	583+82.07	27.00' Lt.
S	583+45.20	20.00' Lt.
T	583+72.33	25.00' Lt.
U	584+18.02	20.00' Lt.
V	583+88.86	4.00' Rt.
W	583+83.66	5.14' Rt.
X	583+98.38	8.00' Rt.
Y	583+55.28	41.92' Rt.
Z	583+77.55	35.52' Rt.
AA	583+56.66	45.87' Rt.
AB	583+72.33	45.37' Rt.
AC	584+02.33	36.43' Rt.
AD	584+87.90	20.00' Rt.
AE	585+37.67	27.03' Rt.
AF	585+67.67	39.00' Lt.
AG	585+67.67	4.00' Rt.
AH	585+67.67	8.00' Rt.
AI	585+67.67	27.03' Rt.

TABLE OF ELEVATIONS

Elev. A	±441.89
Elev. B	±436.93
Elev. C	±436.00
Elev. D	±432.58
Elev. E	±432.58
Elev. F	±436.00
Elev. G	±436.93
Elev. H	±441.89



LOCATION SKETCH

GENERAL PLAN & ELEVATION
IL RTE. 157 OVER JUDYS BRANCH

F.A.P. ROUTE 586


SECTION 51-1R

MADISON COUNTY

STATION 584+70.00

STRUCTURE NO. 060-0229

Note:
For Sections A-A and B-B, see sheet 2 of 2.



DESIGN SPECIFICATIONS
2020 AASHTO LRFD Bridge
Design Specifications, 9th Edition

$f'_c = 3,500 \text{ psi}$
 $f'_c = 4,000 \text{ psi (Superstructure)}$
 $f_y = 60,000 \text{ psi (Reinforcement)}$
 $f_y = 50,000 \text{ psi (M270 Grade 50)}$

Seismic Performance Zone (SPZ) = 2
Design Spectral Acceleration at 1.0 sec. (SD1) = 0.23g
Design Spectral Acceleration at 0.2 sec. (SDS) = 0.53g
Soil Site Class = D





Diagram illustrating the structure and dimensions of a stone riprap structure:

- Stone Riprap, Class A6:** The top layer of stones.
- Bedding:** The layer of stones directly beneath the riprap.
- Filter fabric:** The layer beneath the bedding.
- Dimensions:**
 - Height of the riprap layer: 2'-2"
 - Height of the bedding layer: 10"
 - Width of the structure: 6'-6"
 - Width of the filter fabric layer: 4'-4"



Note:
For Location of Sections A-A and B-B, see sheet 1 of 2.

DETAILS
IL RTE. 157 OVER JUDYS BRANCH
F.A.P. ROUTE 586
SECTION 51-1R
MADISON COUNTY
STATION 584+70.00
STRUCTURE NO. 060-0229

 FUHRMANN ENGINEERING WWW.FUHRMANN-ENG.COM	USER NAME = _____	DESIGNED - T.S. Friederich	REVISED - _____	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	SHEET 2 OF 2 SHEETS	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	PLOT SCALE = _____	CHECKED - E.M. Lagemann	REVISED - _____			586	51-1R	MADISON	—	—
	PLOT DATE = _____	DRAWN - T.S. Friederich	REVISED - _____			CONTRACT NO. 76A46				
		CHECKED - E.M. Lagemann	REVISED - _____			ILLINOIS FED. AID PROJECT				

Important Information about Your Geotechnical Engineering Report

Subsurface problems are a principal cause of construction delays, cost overruns, claims, and disputes.

While you cannot eliminate all such risks, you can manage them. The following information is provided to help.

Geotechnical Services Are Performed for Specific Purposes, Persons, and Projects

Geotechnical engineers structure their services to meet the specific needs of their clients. A geotechnical engineering study conducted for a civil engineer may not fulfill the needs of a construction contractor or even another civil engineer. Because each geotechnical engineering study is unique, each geotechnical engineering report is unique, prepared *solely* for the client. No one except you should rely on your geotechnical engineering report without first conferring with the geotechnical engineer who prepared it. *And no one — not even you — should apply the report for any purpose or project except the one originally contemplated.*

Read the Full Report

Serious problems have occurred because those relying on a geotechnical engineering report did not read it all. Do not rely on an executive summary. Do not read selected elements only.

A Geotechnical Engineering Report Is Based on A Unique Set of Project-Specific Factors

Geotechnical engineers consider a number of unique, project-specific factors when establishing the scope of a study. Typical factors include: the client's goals, objectives, and risk management preferences; the general nature of the structure involved, its size, and configuration; the location of the structure on the site; and other planned or existing site improvements, such as access roads, parking lots, and underground utilities. Unless the geotechnical engineer who conducted the study specifically indicates otherwise, do not rely on a geotechnical engineering report that was:

- not prepared for you,
- not prepared for your project,
- not prepared for the specific site explored, or
- completed before important project changes were made.

Typical changes that can erode the reliability of an existing geotechnical engineering report include those that affect:

- the function of the proposed structure, as when it's changed from a parking garage to an office building, or from a light industrial plant to a refrigerated warehouse,

- elevation, configuration, location, orientation, or weight of the proposed structure,
- composition of the design team, or
- project ownership.

As a general rule, *always* inform your geotechnical engineer of project changes—even minor ones—and request an assessment of their impact. *Geotechnical engineers cannot accept responsibility or liability for problems that occur because their reports do not consider developments of which they were not informed.*

Subsurface Conditions Can Change

A geotechnical engineering report is based on conditions that existed at the time the study was performed. *Do not rely on a geotechnical engineering report* whose adequacy may have been affected by: the passage of time; by man-made events, such as construction on or adjacent to the site; or by natural events, such as floods, earthquakes, or groundwater fluctuations. *Always* contact the geotechnical engineer before applying the report to determine if it is still reliable. A minor amount of additional testing or analysis could prevent major problems.

Most Geotechnical Findings Are Professional Opinions

Site exploration identifies subsurface conditions only at those points where subsurface tests are conducted or samples are taken. Geotechnical engineers review field and laboratory data and then apply their professional judgment to render an opinion about subsurface conditions throughout the site. Actual subsurface conditions may differ—sometimes significantly—from those indicated in your report. Retaining the geotechnical engineer who developed your report to provide construction observation is the most effective method of managing the risks associated with unanticipated conditions.

A Report's Recommendations Are *Not* Final

Do not overrely on the construction recommendations included in your report. *Those recommendations are not final*, because geotechnical engineers develop them principally from judgment and opinion. Geotechnical engineers can finalize their recommendations only by observing actual

subsurface conditions revealed during construction. *The geotechnical engineer who developed your report cannot assume responsibility or liability for the report's recommendations if that engineer does not perform construction observation.*

A Geotechnical Engineering Report Is Subject to Misinterpretation

Other design team members' misinterpretation of geotechnical engineering reports has resulted in costly problems. Lower that risk by having your geotechnical engineer confer with appropriate members of the design team after submitting the report. Also retain your geotechnical engineer to review pertinent elements of the design team's plans and specifications. Contractors can also misinterpret a geotechnical engineering report. Reduce that risk by having your geotechnical engineer participate in prebid and preconstruction conferences, and by providing construction observation.

Do Not Redraw the Engineer's Logs

Geotechnical engineers prepare final boring and testing logs based upon their interpretation of field logs and laboratory data. To prevent errors or omissions, the logs included in a geotechnical engineering report should *never* be redrawn for inclusion in architectural or other design drawings. Only photographic or electronic reproduction is acceptable, *but recognize that separating logs from the report can elevate risk.*

Give Contractors a Complete Report and Guidance

Some owners and design professionals mistakenly believe they can make contractors liable for unanticipated subsurface conditions by limiting what they provide for bid preparation. To help prevent costly problems, give contractors the complete geotechnical engineering report, *but* preface it with a clearly written letter of transmittal. In that letter, advise contractors that the report was not prepared for purposes of bid development and that the report's accuracy is limited; encourage them to confer with the geotechnical engineer who prepared the report (a modest fee may be required) and/or to conduct additional study to obtain the specific types of information they need or prefer. A prebid conference can also be valuable. *Be sure contractors have sufficient time to perform additional study.* Only then might you be in a position to give contractors the best information available to you, while requiring them to at least share some of the financial responsibilities stemming from unanticipated conditions.

Read Responsibility Provisions Closely

Some clients, design professionals, and contractors do not recognize that geotechnical engineering is far less exact than other engineering disciplines. This lack of understanding has created unrealistic expectations that

have led to disappointments, claims, and disputes. To help reduce the risk of such outcomes, geotechnical engineers commonly include a variety of explanatory provisions in their reports. Sometimes labeled "limitations" many of these provisions indicate where geotechnical engineers' responsibilities begin and end, to help others recognize their own responsibilities and risks. *Read these provisions closely.* Ask questions. Your geotechnical engineer should respond fully and frankly.

Geoenvironmental Concerns Are Not Covered

The equipment, techniques, and personnel used to perform a *geoenvironmental* study differ significantly from those used to perform a *geotechnical* study. For that reason, a geotechnical engineering report does not usually relate any geoenvironmental findings, conclusions, or recommendations; e.g., about the likelihood of encountering underground storage tanks or regulated contaminants. *Unanticipated environmental problems have led to numerous project failures.* If you have not yet obtained your own geoenvironmental information, ask your geotechnical consultant for risk management guidance. *Do not rely on an environmental report prepared for someone else.*

Obtain Professional Assistance To Deal with Mold

Diverse strategies can be applied during building design, construction, operation, and maintenance to prevent significant amounts of mold from growing on indoor surfaces. To be effective, all such strategies should be devised for the *express purpose* of mold prevention, integrated into a comprehensive plan, and executed with diligent oversight by a professional mold prevention consultant. Because just a small amount of water or moisture can lead to the development of severe mold infestations, a number of mold prevention strategies focus on keeping building surfaces dry. While groundwater, water infiltration, and similar issues may have been addressed as part of the geotechnical engineering study whose findings are conveyed in this report, the geotechnical engineer in charge of this project is not a mold prevention consultant; *none of the services performed in connection with the geotechnical engineer's study were designed or conducted for the purpose of mold prevention. Proper implementation of the recommendations conveyed in this report will not of itself be sufficient to prevent mold from growing in or on the structure involved.*

Rely on Your ASFE-Member Geotechnical Engineer for Additional Assistance

Membership in ASFE/THE BEST PEOPLE ON EARTH exposes geotechnical engineers to a wide array of risk management techniques that can be of genuine benefit for everyone involved with a construction project. Confer with your ASFE-member geotechnical engineer for more information.



8811 Colesville Road/Suite G106, Silver Spring, MD 20910

Telephone: 301/565-2733 Facsimile: 301/589-2017

e-mail: info@asfe.org www.asfe.org

Copyright 2004 by ASFE, Inc. Duplication, reproduction, or copying of this document, in whole or in part, by any means whatsoever, is strictly prohibited, except with ASFE's specific written permission. Excerpting, quoting, or otherwise extracting wording from this document is permitted only with the express written permission of ASFE, and only for purposes of scholarly research or book review. Only members of ASFE may use this document as a complement to or as an element of a geotechnical engineering report. Any other firm, individual, or other entity that so uses this document without being an ASFE member could be committing negligent or intentional (fraudulent) misrepresentation.