

STRUCTURE GEOTECHNICAL REPORT

IL-169 Pulaski County Bridge Replacement (IL-169 over Kitchel Slough)

Existing S.N. 077-0023
Proposed S.N. 077-0042

F.A.S. RTE. 2937
PULASKI COUNTY, ILLINOIS
JOB NO. D-99-044-20
PTB 193-032
KEG NO. 19-1143.03



A handwritten signature in black ink that reads "Christoph Opperman".

12/27/2023
Exp. 11/30/2025

Authored By:
Christoph Opperman, P.E. &
Michael Harden, E.I.
copperman@kaskaskiaeng.com
(618) 233-5877

Prepared For:
Crawford, Murphy & Tilly, Inc.
2750 West Washington Street
Springfield, IL 62702-3465

December 27, 2023



TABLE OF CONTENTS

1.0	PROJECT DESCRIPTION AND SCOPE.....	1
1.1	Introduction	1
1.2	Project Description	1
1.3	Proposed Structure Information.....	1
2.0	FIELD EXPLORATION	1
2.1	Subsurface Exploration and Testing.....	1
2.2	Subsurface Conditions	1
	Table 2.2.1 - Boring Information Summary	2
	Table 2.2.2 – Subsurface Profile Summary	2
2.3	Groundwater	2
3.0	GEOTECHNICAL EVALUATIONS.....	2
3.1	Settlement	2
3.2	Slope Stability.....	2
	Table 3.2.1 – Slope Stability Critical FOS.....	3
3.3	Seismic Considerations	3
	Table 3.3.1 - Summary of Seismic Parameters	3
4.0	FOUNDATION EVALUATIONS AND DESIGN RECOMMENDATIONS.....	4
4.1	Driven Piles	4
	Table 4.1.1 - Preliminary Design Loads.....	4
	Table 4.1.2 - Estimated Pile Lengths for Metal Shell 12" ϕ w/.25" walls	4
	Table 4.1.3 - Estimated Pile Lengths for Metal Shell 14" ϕ w/.25" walls	5
	Table 4.1.4 - Estimated Pile Lengths for Metal Shell 14" ϕ w/.312" walls	6
	Table 4.1.5 - Estimated Pile Lengths for Metal Shell 16" ϕ w/.312" walls	7
	Table 4.1.6 - Estimated Pile Lengths for HP 10x42 Steel H-Piles	8
	Table 4.1.7 - Estimated Pile Lengths for HP 12x53 Steel H-Piles	8
	Table 4.1.8 - Estimated Pile Lengths for HP 12x63 Steel H-Piles	9
	Table 4.1.9 - Estimated Pile Lengths for HP 14x73 Steel H-Piles	9
	Table 4.1.10 – Estimated Pile Lengths for HP 14x89 Steel H-Piles	10
	Table 4.1.11 - Estimated Pile Lengths for HP 14x117 Steel H-Piles	10
4.2	Lateral Pile Response	10
	Table 4.2.1 - Soil Parameters for Lateral Pile Load Analysis	11
	Table 4.2.2 - Rock Parameters for Lateral Pile Load Analysis	12
5.0	CONSTRUCTION CONSIDERATIONS.....	12

5.1	Construction Activities	12
5.2	Temporary Sheet piling and Soil Retention.....	12
5.3	Cofferdams/Seal Coats	13
5.4	Site and Soil Conditions	13
6.0	COMPUTATIONS	13
7.0	GEOTECHNICAL DATA	13
8.0	LIMITATIONS.....	13

EXHIBITS

- Exhibit A - Location Map
- Exhibit B - Boring Plan
- Exhibit C - Type, Size, and Location Plan (TS&L)
- Exhibit D - Boring Logs
- Exhibit E – Subsurface Profile
- Exhibit F - Slope/W Slope Stability Analysis
- Exhibit G - Pile Length/Pile Type

1.0 PROJECT DESCRIPTION AND SCOPE

1.1 Introduction

The geotechnical study summarized in this report was performed by Kaskaskia Engineering Group, LLC (KEG) for a proposed bridge replacement carrying IL-169 over Kitchel Slough. The project is located in Pulaski County, Illinois. The purpose of this report is to document subsurface geotechnical conditions, provide analyses of anticipated site conditions as they pertain to the project described herein, and to present design and construction recommendations for the proposed structure.

1.2 Project Description

The project consists of the removal and replacement of a single-span bridge (Ex. SN 077-0023) carrying IL-169 over Kitchel Slough. The existing structure was built in 1933. It has a total length of 59'-6" from back-to-back of abutments and a width of 32'. The general location of the proposed structure is shown on a Location Map, Exhibit A. The project is located around 0.4 miles west of Karnak, IL.

1.3 Proposed Structure Information

The proposed structure will consist of a three-span bridge. It will provide two 12 ft. wide driving lanes and two 4 ft. wide shoulders. The bridge will measure 85'-7" back-to-back of abutments and 32'-0" out to out deck. A Type, Size, and Location Plan (TS&L) is included in Exhibit C.

Further substructure details will be based on the findings of this SGR.

2.0 FIELD EXPLORATION

2.1 Subsurface Exploration and Testing

Two standard penetration test (SPT) borings designated 1-S and 2-S were drilled on April 23 and May 7, 2023. The boring locations are shown on the Boring Plan, Exhibit B. Detailed information regarding the nature and thickness of the soils encountered and the results of the field sampling and laboratory testing are shown on the Boring Logs, Exhibit D. A Soil Profile is included as Subsurface Profile, Exhibit E.

2.2 Subsurface Conditions

The profiles at the two (2) boring locations exhibited layers of asphalt, concrete, clay, silty clay, clay loam, sandy loam, gravelly sand, and limestone. Boring 1-S was advanced to 120.5' in depth, while 2-S was advanced to 136' in depth. The bedrock found in 2-S was limestone. Table 2.2.1 shows a summary of the pavement structure(s), depth of drilling, the top of rock, and ground surface elevation (GSE) of the borings. A summary of the general condition of the subsurface is described in Table 2.2.2.

Table 2.2.1 - Boring Information Summary

Designation	Asphalt	Concrete	Depth (ft)	Top of Rock (ft.)	GSE (ft.)
1-S	7"	7"	120.5	-	343.1
2-S	7"	7"	135.9	212.2	343.0

Table 2.2.2 – Subsurface Profile Summary

Soil Type	N-Values (bpf)	Q _u (tsf)	WC (%)	Boring
Clay	0 - 12	0.3 - 3.7	18 - 40	1-S, 2-S
Silty Clay	0 - 8	0.5 – 1.4	22 - 31	2-S
Clay Loam	2 - 24	0.3 – 2.3	16 - 37	1-S, 2-S
Sandy Loam	4	0.6	-	1-S
Gravelly Sand	0 - 20	-	39 - 79	1-S, 2-S

2.3 Groundwater

Boring 1-S first encountered groundwater at an elevation of 293.1 ft. Upon completion of drilling the groundwater was measured at an elevation of 323.1 ft. Boring 2-S first encountered groundwater at an elevation of 324.5 ft and encountered groundwater at an elevation of 323.0 ft after the drilling was completed. It should be noted that the groundwater level is subject to seasonal and climatic variations. In addition, without extended periods of observation, measurement of true groundwater levels may not be possible.

3.0 GEOTECHNICAL EVALUATIONS

3.1 Settlement

Since no significant grading or changes to the existing embankments are expected at the proposed structure, it is estimated that the existing embankments will experience no settlement. Therefore, no settlement calculations were performed for the proposed structure.

3.2 Slope Stability

Stability analysis using SLOPE/W was performed using the proposed structure geometry on the TS&L. Three conditions were modeled for each scenario: end-of-construction, long-term, and seismic stability. A critical factor of safety (FOS) was calculated for each condition. According to the current standard of practice, the target FOS is 1.5 for end-of-construction and long-term slope stability.

To model the end-of-construction condition, undrained soil parameters were used. Full cohesion and a friction angle of 0 degrees were assumed for cohesive soils. Drained soil parameters with nominal cohesion and full friction angle values were used to model the long-term condition and

analyze the theoretical condition where pore water pressure dissipated. The drained strength parameters for cohesive materials included a nominal cohesion value between 50 and 100 psf, with friction angles between 26 and 30 degrees.

The Bishop Circular Method, which generates circular-shaped failure surfaces, was used to calculate the critical failure surfaces and FOS for the proposed conditions. The FOS obtained in the analysis is shown in Table 3.2.1. SLOPE/W program output from this analysis can be found in SLOPE/W Slope Stability Analysis, Exhibit F. As provided in Table 3.2.1, the analysis results indicate that an acceptable FOS will exist under the analyzed conditions.

Table 3.2.1 – Slope Stability Critical FOS

Location (1V:2H Slope)	Critical FOS		
	End-of Construction	Long Term	Seismic
North Abutment (1-S)	6.7	2.0	2.6
South Abutment (2-S)	5.1	2.0	1.7

3.3 Seismic Considerations

The determination of Seismic Site Class was based on the method described by IDOT AGMU Memo 09.1 - Seismic Site Class Definition and the IDOT provided spreadsheet titled: '*Seismic Site Class Determination*.' Using these resources, the controlling global site class for this project is Soil Site Class E.

Additional seismic parameters were calculated for use in the design of the structure. Published information and mapping from the USGS, including software directly applicable to the AASHTO Guide Specifications for LRFD Seismic Bridge Design, was used to develop the parameters for the bridge location. The values, based on Soil Site Class E, are summarized below.

Table 3.3.1 - Summary of Seismic Parameters

Parameter	Value
Soil Site Class	E
Spectral Response Acceleration, 0.2 Sec, S_{DS}	1.370 g (Site Class E)
Spectral Response Acceleration, 1.0 Sec, S_{D1}	0.951 g (Site Class E)
Seismic Performance Zone	4

As indicated in the table above, the Seismic Performance Zone is 4, based on S_{D1} and Table 3.15.2-1 in the IDOT Bridge Manual, the Soil Site Class E, and Figure 2.3.10-4 in the IDOT Bridge Manual.

Based on the soils encountered in the two borings, which were primarily clays with Plasticity Indices of 12 or higher, liquefaction is not a concern at this site.

4.0 FOUNDATION EVALUATIONS AND DESIGN RECOMMENDATIONS

4.1 Driven Piles

The foundations supporting the proposed bridge must provide sufficient support to resist dead and live loads. The IDOT Static Method uses the LRFD Pile Design Guide Procedure to estimate the pile lengths (Pile Length/Pile Type, Exhibit G).

The factored reactions and the preliminary design loads, as provided by Crawford, Murphy & Tilly (CM&T) are provided in Table 4.1.1.

Table 4.1.1 - Preliminary Design Loads

Substructure Unit	Factored Reactions (kips)
North Abutment	531.7
Pier 1	914.5
Pier 2	914.5
South Abutment	531.7

The estimated pile lengths for applicable Metal Shell and H-Pile types are shown in Tables 4.1.2 through 4.1.11 below. The Nominal Required Bearing (R_N) represents the resistance the pile will experience during driving and will assist the contractor in selecting a proper hammer size. The Factored Resistance Available (R_F) documents the net long-term axial factored pile capacity available at the top of the pile to support factored substructure loadings.

Generally, piles for the North Abutment and Pier 1 will need to be driven deeper due to the soils found in nearby Boring 1-S. Bedrock was not encountered in Boring 1-S due to an obstruction in the lead auger at El. 222.6, leading to the boring being abandoned at that depth. Therefore, the elevation of bedrock for Boring 1-S was estimated to be the same as found in Boring 2-S, El. 212.2. Liquefaction is not be a problem at this site due to the cohesive soils encountered in the borings, so the Metal Shell piles are applicable, though H-Piles are considered optimal in regions of moderate to high seismicity according to the 2023 IDOT Bridge Manual.

Table 4.1.2 - Estimated Pile Lengths for Metal Shell 12" ϕ w/.25" walls

Substructure Unit	R_N Nominal Required Bearing (kips)	R_F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	294	161	56	341.54
	316	174	61	341.54
	338	186	66	341.54

Substructure Unit	R _n Nominal Required Bearing (kips)	R _F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
	369	203	71	341.54
Pier 1 (1-S)	280	154	66	339.54
	310	170	71	339.54
	333	183	76	339.54
	371	204	86	339.54
Pier 2 (2-S)	199	110	46	339.00
	207	114	51	339.00
	268	147	56	339.00
	301	166	61	339.00
South Abutment (2-S)	258	142	48	340.47
	266	146	53	340.47
	326	179	58	340.47
	360	198	63	340.47

Table 4.1.3 - Estimated Pile Lengths for Metal Shell 14" ϕ w/.25" walls

Substructure Unit	R _n Nominal Required Bearing (kips)	R _F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	346	190	56	341.54
	371	204	61	341.54
	397	218	66	341.54
	434	239	71	341.54
Pier 1 (1-S)	328	181	66	339.54
	365	201	71	339.54
	391	215	76	339.54
	433	238	86	339.54
Pier 2	241	132	46	339.54

Substructure Unit	R _n Nominal Required Bearing (kips)	R _F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
(2-S)	242	133	51	339.54
	324	178	56	339.54
	360	198	61	339.54
South Abutment (2-S)	309	170	48	340.47
	310	171	53	340.47
	392	216	58	340.47
	428	236	63	340.47

Table 4.1.4 - Estimated Pile Lengths for Metal Shell 14" ϕ w/.312" walls

Substructure Unit	R _n Nominal Required Bearing (kips)	R _F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	460	253	76	341.54
	502	276	86	341.54
	530	292	96	341.54
	566	312	106	341.54
Pier 1 (1-S)	433	238	86	339.54
	462	254	96	339.54
	498	274	106	339.54
	517	284	116	339.54
Pier 2 (2-S)	242	133	51	339.54
	324	178	56	339.54
	360	198	61	339.54
	502	276	66	339.54
South Abutment (2-S)	310	171	53	340.47
	392	216	58	340.47
	428	236	63	340.47

Substructure Unit	R _n Nominal Required Bearing (kips)	R _F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
	570	314	68	340.47

Table 4.1.5 - Estimated Pile Lengths for Metal Shell 16" ϕ w/.312" walls

Substructure Unit	R _n Nominal Required Bearing (kips)	R _F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	529	291	76	341.54
	575	316	86	341.54
	608	334	96	341.54
	649	357	106	341.54
Pier 1 (1-S)	496	273	86	339.54
	529	291	96	339.54
	570	313	106	339.54
	591	325	116	339.54
Pier 2 (2-S)	276	152	51	339.54
	384	211	56	339.54
	421	232	61	339.54
	596	328	66	339.54
South Abutment (2-S)	207	114	37	340.47
	355	195	53	340.47
	462	254	58	340.47
	499	275	63	340.47

Table 4.1.6 - Estimated Pile Lengths for HP 10x42 Steel H-Piles

Substructure Unit	R_n Nominal Required Bearing (kips)	R_F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	335	184	108	341.54
Pier 1 (1-S)	335	184	116	339.54
Pier 2 (2-S)	335	184	67	339.54
South Abutment (2-S)	335	184	65	340.47

Table 4.1.7 - Estimated Pile Lengths for HP 12x53 Steel H-Piles

Substructure Unit	R_n Nominal Required Bearing (kips)	R_F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	418	230	111	341.54
Pier 1 (1-S)	418	230	117	339.54
Pier 2 (2-S)	418	230	68	339.54
South Abutment (2-S)	418	230	64	340.47

Table 4.1.8 - Estimated Pile Lengths for HP 12x63 Steel H-Piles

Substructure Unit	R_n Nominal Required Bearing (kips)	R_F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	497	273	119	341.54
Pier 1 (1-S)	497	273	122	339.54
Pier 2 (2-S)	497	273	74	339.54
South Abutment (2-S)	497	273	68	340.47

Table 4.1.9 - Estimated Pile Lengths for HP 14x73 Steel H-Piles

Substructure Unit	R_n Nominal Required Bearing (kips)	R_F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	578	318	119	341.54
Pier 1 (1-S)	578	318	121	339.54
Pier 2 (2-S)	578	318	72	339.54
South Abutment (2-S)	578	318	68	340.47

Table 4.1.10 – Estimated Pile Lengths for HP 14x89 Steel H-Piles

Substructure Unit	R_n Nominal Required Bearing (kips)	R_F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	705	388	124	341.54
Pier 1 (1-S)	705	388	127	339.54
Pier 2 (2-S)	705	388	85	339.54
South Abutment (2-S)	705	388	78	340.47

Table 4.1.11 - Estimated Pile Lengths for HP 14x117 Steel H-Piles

Substructure Unit	R_n Nominal Required Bearing (kips)	R_F Factored Resistance Available (LRFD) (kips)	Estimated Pile Length (ft.)	Assumed Pile Cut-off Elevation (ft.)
North Abutment (1-S)	929	511	130	341.54
Pier 1 (1-S)	929	511	129	339.54
Pier 2 (2-S)	929	511	127	339.54
South Abutment (2-S)	929	511	127	340.47

KEG recommends one test pile be performed, at a minimum. A test pile is performed prior to production driving so that actual, on-site field data can be gathered to determine pile driving requirements for the project. This is also the way the contractor's proposed equipment and methodologies identified in their Pile Installation Plan can be assessed.

4.2 Lateral Pile Response

Generally, the geotechnical engineer provides soil parameters to the structural engineer so that an L-Pile program, or other approved software, can be used for the lateral or displacement analysis of the foundations. Table 4.2.1 and Table 4.2.2 are included for the structural engineer's use in determining lateral pile response.

Table 4.2.1 - Soil Parameters for Lateral Pile Load Analysis

Boring	Soil Type	Depth at Bot. of Layer (Ft.)	γ (pcf)	Undrained (Short Term)		Drained (Long Term)		N Value (Avg)	Assumed % Fines < #200	K (pci)	ε ₅₀
				c (psf)	Φ (deg)	c (psf)	Φ (deg)				
1-S	Clay	28.5	120	2000	0	100	26	6	85	500	0.007
	Clay Loam	31	120	1300	0	100	26	5	65	500	0.007
	Clay	54	120	1850	0	100	26	5	85	500	0.007
	Sandy Loam	59	120	600	0	0	30	4	0	-	-
	Clay Loam	64	120	2300	0	100	26	5	65	1000	0.005
	Clay	69	120	1300	0	100	26	9	85	500	0.007
	Clay Loam	119	120	1300	0	100	26	8	65	500	0.007
	Sandy Gravel	120.5	120	0	38	0	38	20	3	-	-
2-S	Silty Clay	3.5	120	800	0	50	26	3	65	100	0.01
	Clay	18.5	120	1450	0	100	26	5	85	500	0.007
	Silty Clay	28.5	120	1250	0	100	26	5	65	500	0.007
	Clay	38.5	120	1250	0	100	26	7	85	500	0.007
	Silty Clay	44	120	1400	0	100	26	5	65	500	0.007
	Clay	49	120	2900	0	100	26	10	85	1000	0.005

Boring	Soil Type	Depth at Bot. of Layer (Ft.)	γ (pcf)	Undrained (Short Term)		Drained (Long Term)		N Value (Avg)	Assumed % Fines < #200	K (pci)	ε ₅₀
				c (psf)	φ (deg)	c (psf)	φ (deg)				
	Silty Clay	59+	120	600	0	50	26	2.5	65	100	0.01
	Clay	74	120	1333	0	100	26	6	85	500	0.007
	Clay Loam	119	120	900	0	100	26	10	65	100	0.01
	Sandy Gravel	130.9	120	0	38	0	38	4	3	-	-

Table 4.2.2 - Rock Parameters for Lateral Pile Load Analysis

Rock Type	Strong Rock	
	γ (psf)	Qu (tsf)
Limestone	149	200.0

5.0 CONSTRUCTION CONSIDERATIONS

5.1 Construction Activities

Construction activities should be performed in accordance with the current IDOT Standard Specifications for Road and Bridge Construction and any pertinent Special Provisions or Policies.

Should any design considerations assumed by KEG change, KEG should be contacted to determine if the recommendations stated in this report still apply.

5.2 Temporary Sheet piling and Soil Retention

Temporary shoring may be required at various stages of this project due to the proposed staged-construction layout shown in the TS&L.

Temporary Soil Retention Systems may be required versus Temporary Shoring, depending upon the surcharge loading, and retained heights required to be supported during construction. An Illinois-licensed Structural Engineer is required to seal the design of Temporary Soil Retention Systems, if deemed necessary.

5.3 Cofferdams/Seal Coats

Cofferdams will be required at the proposed pier locations. The estimated water surface elevation (E.W.S.E.), is listed as El. 330.00, which would put the E.W.S.E less than six feet above the top of piers, calling for a Type I Cofferdam. All cofferdams are required to be dewatered. The borings show mostly cohesive material present at the site, so a seal coat will not be required.

5.4 Site and Soil Conditions

Provisions of the Standard Specifications should adequately address site and soil conditions.

6.0 COMPUTATIONS

Computations and analyses for specific circumstances, if any, are included as exhibits. Please refer to each section of the report for reference to the exhibit containing any such calculations or analysis used.



7.0 GEOTECHNICAL DATA

Soil boring logs and subsurface profiles can be found in Exhibit D. Pile Design Tables can be found in Exhibit G.

8.0 LIMITATIONS

The recommendations provided herein are for the exclusive use of CM&T and the Illinois Department of Transportation (IDOT) District 9. They are specific only to the project described and are based on the subsurface information obtained by KEG at two boring locations within the structure area, KEG's understanding of the project as described herein, and geotechnical engineering practice consistent with the standard of care. No other warranty is expressed or implied. KEG should be contacted if conditions encountered during construction are not consistent with those described.

EXHIBIT A
LOCATION MAP



LOCATION MAP


**IL-169 Bridge
Replacement
Pulaski County,
Illinois**

Exhibit No.

A

KEG JOB #19-1143.03

EXHIBIT B
BORING PLAN



BORING LOCATION MAP

**IL-169 Bridge
Replacement
Pulaski County,
Illinois**

Exhibit No.

B

KEG JOB #19-1143.03

EXHBIT C

TYPE, SIZE, AND LOCATION PLAN (TS&L)

Existing Structure: SN 077-0023 was originally built in 1933 under Section E116. The structure is a single span bridge with closed abutments on untreated timber piles with an overall length of 59'-6" from back to back of abutments. The superstructure was originally a steel truss and in 1984 under Section 116BR-1 the superstructure was replaced with PPC deck beams and a 1¾" bituminous concrete overlay. The width of the structure is 33'-0" out-to-out deck. The structure is to be removed and replaced utilizing staged construction.

LOADING HL-93
Allow 50 #/sq. ft. for future wearing surface

2020 AASHTO LRFD Bridge Design
Specifications 9th Edition

FIELD UNITS

$f_c = 4,000 \text{ psi}$ (superstructure)
 $f_c = 3,500 \text{ psi}$ (substructure)
 $f_y = 60,000 \text{ psi}$ (reinforcement)

Seismic Performance Zone (SPZ) = 4

Design Spectral Acceleration at 1.0 sec. (SD1) = 0.951 g
Design Spectral Acceleration at 0.2 sec. (SDS) = 1.370 g
Soil Site Class = E

F.A.S. 2937 - IL Rt. 169

Functional Class: Major Collector



ADT: 1,850 (2020); 2,260 (2040)

ADTT: 185 (2020); 225 (2040)


DHV: 205 (2040)

Speed: 55 mph (posted); 60 mph (design)

Two-Way Traffic: Directional Dist. 50-50



Along $\mathbb{C}$ IL 169



LEGEND

-  Soil Boring
 Stone Riprap Class A4
 Edge of Channel

Note:
See Sheet 2 of 2 for Waterway Information
Table, Design Scour Elevation Table, and
Section A-A.

IL 169 OVER KITCHEL SLOUGH

F.A.S. RTE. 2937 - SEC. 116B-1

PULASKI COUNTY

STATION 78+93.00

STRUCTURE NO. 077-0042



License No. 184-000613 Copyright © 2013

USER NAME = dcochran	DESIGNED - DAC
	DRAWN - VT
PLOT SCALE = N/A	CHECKED - DAC/DH
PLOT DATE = 3/15/2024	DATE - 3/15/2024

REVISED	-
REVISED	-
REVISED	-
REVISED	-

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

SCALE:	SHEET 1	OF 2	SHEETS	STA.	TO STA.
--------	---------	------	--------	------	---------

F.A.S. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
2937	116B-1	PULASKI		
		CONTRACT NO. 78793		
ILLINOIS		FED. AID PROJECT		

EXHIBIT D
BORING LOGS

Page 1 of 4

Date 4/23/19

COUNTY Pulaski **DRILLING METHOD** Hollow stem auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lb

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

Cored Pavement, 7" HMA over 7" CONCRETE					V. Stiff Brown and Grey, Moist CLAY (Note 1) (continued)				
341.90							1		
M. Stiff Grey, Moist CLAY with ORGANICS							5	2.3	27
							5	B	
							1		
	1						2	2.1	25
	2	1.0	25				4	B	
-5	2	B				-25			
	WOH				317.10		1		
	WOH	0.5	28		Stiff Brown and Grey, Moist CLAY (Note 1)		2	1.2	26
	WOH	B					3	B	
334.60					314.60		1		
V. Stiff Grey, Moist CLAY	1				Stiff Browish Grey, Moist CLAY LOAM with pockets of Wet CLAY LOAM (Note 1)		2	1.3	24
	2	2.1	23				3	B	
-10	3	B				-30			
332.10					312.10		1		
Stiff Grey, Moist CLAY	1				V. Stiff Brownish Grey, V. Moist CLAY (Note 1)		3	2.7	26
	3	1.2	24				3	B	
	4	B							
329.60					309.60		1		
V. Stiff Brown and Grey, Moist CLAY (Note 1)	2				Stiff Grey, V. Moist CLAY (Note 1)		3	1.8	27
	4	3.5	25				3	B	
-15	6	S				-35			
					307.10		WOH		
	1				V. Stiff Grey, V. Moist CLAY with pockets of Wet CLAY (Note 1)		WOH	3.1	26
	5	3.5	26				2	B	
	5	B							
					304.60		1		
	1				Stiff Grey, V. Moist CLAY (Note 1)		1	1.2	30
	4	3.7	23				3	B	
-20	6	B				-40			

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)

Page 2 of 4

Date 4/23/19

COUNTY Pulaski **DRILLING METHOD** Hollow stem auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lb

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

3	B	
---	---	--

1		
4	1.3	29
5	B	

	3		
-70	4	1.4	18
	7	B	

	1		
-75	4	2.3	23
	4	B	

	3		
-80	4	1.4	17

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS. from 137 (Rev. 8-99)

Page 3 of 4

Date 4/23/19

COUNTY Pulaski **DRILLING METHOD** Hollow stem auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lb

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

	2		
-110	7	0.6	36
	2	B	

224.10	7		
-120	14	0.0	79

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE IL 169 DESCRIPTION Structure over stream LOGGED BY L. Estel

SECTION _____ LOCATION 0.4 mi West of Karnak (East Abut.), SEC. 16, TWP. 14S, RNG. 2E, PM

COUNTY Pulaski DRILLING METHOD Hollow stem auger (8" O.D., 3.25" I.D.) HAMMER TYPE Auto SPT 140 lb

STRUCT. NO. 077-0023
Station 78+93

BORING NO. 1-S
Station 79+50
Offset 7.0ft RT
Ground Surface Elev. 343.1 ft

D E P T H (ft)	B L O W S (tsf)	U C S Qu (%)	M O I S T (%)
-------------------------------	--------------------------------	--------------------------	------------------------------

Surface Water Elev. 330.4 ft
Stream Bed Elev. 329.0 ft

Groundwater Elev.:
▽ First Encounter 293.1 ft
▽ Upon Completion 323.1 ft
▽ After _____ Hrs. _____ ft

M. Dense Coarse SAND and Fine GRAVEL with V. Soft Reddish Brown, Wet CLAY Slurry 15% Fine SAND, 9% SILT, 15% CLAY, 61% Coarse SAND and Fine GRAVEL (Est. from visual ID & Lab 29 from Boring 2-S)
(continued)

222.60

6

E

(End of boring. Bore hole abandoned due to obstruction in lead auger that damaged two split spoon samplers.)

-125

Note 1: Not Liquefiable, PI >= 12 based on visual ID and historical data

Bottom of hole @ 120.5 ft

Elevation referenced to PSM 75, IDOT Mon. @ Sta 75+00, 72 ft RT; EL. 341.54

-130

To convert "N" values to "N60", multiply by 1.5

-135

-140

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE IL 169 DESCRIPTION Structure over stream LOGGED BY L. Estel

SECTION _____ LOCATION 0.4 mi West of Karnak (West Abut.), SEC. 16, TWP. 14S, RNG. 2E, PM

COUNTY Pulaski DRILLING METHOD Hollow stem auger (8" O.D., 3.25" I.D.) HAMMER TYPE Auto SPT 140 lb

STRUCT. NO. 077-0023
Station 78+93

BORING NO. 2-S
Station 78+35
Offset 6.0ft LT
Ground Surface Elev. 343.0 ft

D E P T H (ft)	B L O W S (tsf)	U C S Qu (tsf)	M O I S T (%)	Surface Water Elev. <u>330.4</u> ft Stream Bed Elev. <u>329.0</u> ft Groundwater Elev.: ▽ First Encounter <u>324.5</u> ft ▽ Upon Completion <u>323.0</u> ft ▽ After _____ Hrs. _____ ft	D E P T H (ft)	B L O W S (tsf)	U C S Qu (tsf)	M O I S T (%)
				Stiff Brown, Moist SILTY CLAY (Note 1) (continued) <u>322.00</u>				
				Stiff Brown, Moist SILTY CLAY with Fine PEBBLES (Note 1) <u>319.50</u>		1 3 5	1.2 B	22
				Stiff Grey, Moist SILTY CLAY (Note 1) <u>314.50</u>		WOH 1 3	1.2 B	27
				Stiff Grey, Moist CLAY (Note 1) <u>309.50</u>		WOH 2	1.3 B	31
				Stiff Grey, Moist CLAY (Note 1) <u>304.50</u>		1 3 5	1.8 B	24
				M. Stiff Grey, Moist CLAY with pockets of Stiff Grey, SILT (Note 1) <u>307.00</u>		1 1 3	0.7 B	40
				M. Stiff Grey, Moist SILTY CLAY (Note 1) <u>304.50</u>		1 2 3	1.4 B	27

Cored Pavement, 7" HMA over 7" CONCRETE <u>341.80</u>			
M. Stiff Grey, Moist SILTY CLAY <u>339.50</u>	1 2	0.8 B	31
Soft Grey, V. Moist CLAY with GRAVEL and ORGANICS <u>337.00</u>	WOH 1 2	0.3 B	34
M. Stiff Grey, V. Moist CLAY <u>334.50</u>	WOH 1	0.9 B	35
V. Stiff Grey and Brown, Moist CLAY <u>329.50</u>	WOH 3 4	2.7 B	30
Stiff Grey and Brown, Moist CLAY <u>327.00</u>	1 2 4	2.5 B	27
M. Stiff Grey and Brown, Moist CLAY <u>324.50</u>	1 1 3	1.3 B	26

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE IL 169 DESCRIPTION Structure over stream LOGGED BY L. Estel

SECTION _____ LOCATION 0.4 mi West of Karnak (West Abut.), SEC. 16, TWP. 14S, RNG. 2E, PM

COUNTY Pulaski DRILLING METHOD Hollow stem auger (8" O.D., 3.25" I.D.) HAMMER TYPE Auto SPT 140 lb

STRUCT. NO. 077-0023
Station 78+93

BORING NO. 2-S
Station 78+35
Offset 6.0ft LT
Ground Surface Elev. 343.0 ft

D E P T H (ft)	B L O W S (tsf)	U C S Qu (tsf)	M O I S T (%)	Surface Water Elev. <u>330.4</u> ft Stream Bed Elev. <u>329.0</u> ft Groundwater Elev.: ▽ First Encounter <u>324.5</u> ft ▽ Upon Completion <u>323.0</u> ft ▽ After _____ Hrs. _____ ft	D E P T H (ft)	B L O W S (tsf)	U C S Qu (tsf)	M O I S T (%)
						5	B	
299.00								
	1			Moist		WOH		
-45	3	2.9	23		-65	1	1.5	24
	7	B				4	B	
294.00								
	1			Stiff Grey, Moist CLAY with Fine GRAVEL		1		
-50	3	0.5	25		-70	5	1.1	19
	2	B				7	S	
289.00								
	WOH			M. Stiff Brown, Moist CLAY LOAM with Fine GRAVEL		3		
-55	WOH	0.7	22		-75	12	0.7	16
	WOH	B				12	S	
284.00								
	1					3		
-60	2	1.4	37		-80	5	1.0	20

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated)
Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)

Page 3 of 4

Date 5/7/19

COUNTY Pulaski **DRILLING METHOD** Hollow stem auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lb

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

WOH	
-----	--

1

-1

WOH

-1

0	WOH
---	-----

0.0

File Name S:\MATERIALS GEOTECHNICAL UNIT\BORING LOGS USING GINT\STATE STRUCTURES\PULASKI\077-0023.GPJ Data Template D6TEMPLT.GDT Date Printed 8/12/19
latitude 37.2891194 Longitude -88.9956083 Datum NAD83 Job Number

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS. from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE IL 169 DESCRIPTION Structure over stream LOGGED BY L. Estel

SECTION _____ LOCATION 0.4 mi West of Karnak (West Abut.), SEC. 16, TWP. 14S, RNG. 2E, PM

COUNTY Pulaski DRILLING METHOD Hollow stem auger (8" O.D., 3.25" I.D.) HAMMER TYPE Auto SPT 140 lb

STRUCT. NO. 077-0023
Station 78+93

BORING NO. 2-S
Station 78+35
Offset 6.0ft LT
Ground Surface Elev. 343.0 ft

D E P T H (ft)	B L O W S (tsf)	U C S Qu	M O I S T (%)
-------------------------------	--------------------------------	-------------------	------------------------------

Surface Water Elev. 330.4 ft
Stream Bed Elev. 329.0 ft

Groundwater Elev.:
▽ First Encounter 324.5 ft
▽ Upon Completion 323.0 ft
▼ After _____ Hrs. _____ ft

V. Loose Coarse Sand and Fine Angular GRAVEL with V. Soft Brown, Wet CLAY Slurry
15% Fine SAND, 9% SILT, 15% CLAY, 61% Coarse SAND and Fine GRAVEL (Lab 29)

(continued)

	WOH	E	
-125			
214.00	WOH		

Loose Coarse Sand and Fine Angular GRAVEL with V. Soft Brown, Wet CLAY Slurry
31% Fine SAND, 21% SILT, 26% CLAY, 22% Coarse SAND and Fine GRAVEL (Lab 30)
212.20
212.10

-130	3	0.0	42
	5	E	
	100/1		

Light Grey LIMESTONE, Dry, V. Fine Grained, Thickly Bedded, Hard Field Hardness

(Borehole continued with rock coring.)

-135			
------	--	--	--

Note 1: Not Liquefiable, PI >= 12 based on visual ID and historical data

Bottom of hole @ 135.9 ft

Elevation referenced to PSM 75, IDOT Mon. @ Sta 75+00, 72 ft RT; EL. 341.54

To convert "N" values to "N60", multiply by 1.5

-140			
------	--	--	--

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation
District Nine Materials
Unconfined Compressive Strength


Route IL 169
Structure 077-0023 (Boring 2-S)
Pulaski County



Boring #	Specimen#	Depth	Unconfined Compression
2-S	1	131.7'	6194 psi
2-S	2	132.7'	5925 psi
2-S	3	133.0'	12,819 psi
2-S	4	133.5'	13,231 psi
2-S	5	134.8'	11,797 psi
2-S	6	135.8'	11,832 psi

EXHIBIT E
SUBSURFACE PROFILE

PRINTERMOD2 11x17 19-1143.03 WO 3 PULASKI CO.GPJ IL_DOT.GDT 12/8/23



208 E. Main St., Suite 100
Belleville, Illinois 62220
618.233.5877 phone
618.233.5977 fax
www.kaskaskiaeng.com

PROFESSIONAL REGISTRATIONS
Illinois Professional Design Firm
Professional Engineering Group

LICENSE NO.
184.004773
20-5080586

NOT TO HORIZONTAL SCALE


SUBSURFACE PROFILE

Route: F.A.S. RTE. 2937 (IL 169)
County: Pulaski

EXHIBIT F


SLOPE/W SLOPE STABILITY ANALYSIS

IL-169, Pulaski Co. Bridge Replacement - North Abutment
Boring 1-S
End of Construction (Undrained Analysis)




Color	Name	Slope Stability Material Model	Unit Weight (pcf)	Effective Cohesion (psf)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Line
	1 Clay I (EOC)	Mohr-Coulomb	120	2,000	0	0	1
	2 Clay Loam (EOC)	Mohr-Coulomb	120	1,300	0	0	1
	3 Clay II (EOC)	Mohr-Coulomb	120	1,850	0	0	1
	4 Sandy Loam (EOC)	Mohr-Coulomb	120	600	0	0	1
	Riprap	Mohr-Coulomb	145	0	45	0	1

IL-169, Pulaski Co. Bridge Replacement - North Abutment
Boring 1-S
Long Term (Drained Analysis)




Color	Name	Slope Stability Material Model	Unit Weight (pcf)	Effective Cohesion (psf)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Line
	1 Clay I (LT)	Mohr-Coulomb	120	100	26	0	1
	2 Clay Loam (LT)	Mohr-Coulomb	120	100	26	0	1
	3 Clay II (LT)	Mohr-Coulomb	120	100	26	0	1
	4 Sandy Loam (LT)	Mohr-Coulomb	120	0	30	0	1
	Riprap	Mohr-Coulomb	145	0	45	0	1

IL-169, Pulaski Co. Bridge Replacement - North Abutment
Boring 1-S
End of Construction (Undrained Analysis)
Seismic Analysis, Ks = 0.3613




Color	Name	Slope Stability Material Model	Unit Weight (pcf)	Effective Cohesion (psf)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Line
■	1 Clay I (EOC)	Mohr-Coulomb	120	2,000	0	0	1
■	2 Clay Loam (EOC)	Mohr-Coulomb	120	1,300	0	0	1
■	3 Clay II (EOC)	Mohr-Coulomb	120	1,850	0	0	1
■	4 Sandy Loam (EOC)	Mohr-Coulomb	120	600	0	0	1
■	Riprap	Mohr-Coulomb	145	0	45	0	1

IL-169, Pulaski Co. Bridge Replacement - South Abutment
Boring 2-S
End of Construction (Undrained Analysis)




Color	Name	Slope Stability Material Model	Unit Weight (pcf)	Effective Cohesion (psf)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Line
	1 Silty Clay I (EOC)	Mohr-Coulomb	120	800	0	0	1
	2 Clay I (EOC)	Mohr-Coulomb	120	1,450	0	0	1
	3 Silty Clay II (EOC)	Mohr-Coulomb	120	1,250	0	0	1
	4 Clay II (EOC)	Mohr-Coulomb	120	1,250	0	0	1
	5 Silty Clay III (EOC)	Mohr-Coulomb	120	1,400	0	0	1
	6 Clay III (EOC)	Mohr-Coulomb	120	2,900	0	0	1
	7 Silty Clay IV (EOC)	Mohr-Coulomb	120	600	0	0	1
	Riprap	Mohr-Coulomb	145	0	45	0	1

IL-169, Pulaski Co. Bridge Replacement - South Abutment Boring 2-S Long Term (Drained Analysis)



Color	Name	Slope Stability Material Model	Unit Weight (pcf)	Effective Cohesion (psf)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Line
	1 Silty Clay I (LT)	Mohr-Coulomb	120	100	26	0	1
	2 Clay I (LT)	Mohr-Coulomb	120	100	26	0	1
	3 Silty Clay II (LT)	Mohr-Coulomb	120	100	26	0	1
	4 Clay II (LT)	Mohr-Coulomb	120	100	26	0	1
	5 Silty Clay III (LT)	Mohr-Coulomb	120	100	26	0	1
	6 Clay III (LT)	Mohr-Coulomb	120	100	26	0	1
	7 Silty Clay IV (LT)	Mohr-Coulomb	120	50	26	0	1
	Riprap	Mohr-Coulomb	145	0	45	0	1

IL-169, Pulaski Co. Bridge Replacement - South Abutment
Boring 2-S
End of Construction (Undrained Analysis)
Seismic Analysis, $K_s = 0.3613$



Color	Name	Slope Stability Material Model	Unit Weight (pcf)	Effective Cohesion (psf)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Line
	1 Silty Clay I (EOC)	Mohr-Coulomb	120	800	0	0	1
	2 Clay I (EOC)	Mohr-Coulomb	120	1,450	0	0	1
	3 Silty Clay II (EOC)	Mohr-Coulomb	120	1,250	0	0	1
	4 Clay II (EOC)	Mohr-Coulomb	120	1,250	0	0	1
	5 Silty Clay III (EOC)	Mohr-Coulomb	120	1,400	0	0	1
	6 Clay III (EOC)	Mohr-Coulomb	120	2,900	0	0	1
	7 Silty Clay IV (EOC)	Mohr-Coulomb	120	600	0	0	1
	Riprap	Mohr-Coulomb	145	0	45	0	1

EXHIBIT G

PILE LENGTH/PILE TYPE



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====North Abutment

REFERENCE BORING =====1-S

LRFD or ASD or SEISMIC =====LRFD

PILE CUTOFF ELEV. =====341.54 ft

GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING =339.54 ft

GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None

BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft

TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====532 kips

TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====32.00 ft

NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1

Approx. Factored Loading Applied per pile at 8 ft. Cts =====132.93 KIPS

Approx. Factored Loading Applied per pile at 3 ft. Cts =====49.85 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req.d Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
392 KIPS	372 KIPS	205 KIPS	72 FT.

PILE TYPE AND SIZE =====Metal Shell 12"Φ w/.25" walls

Pile Perimeter=====3.142 FT.

Pile End Bearing Area=====0.785 SQFT.

BOT. OF LAYER ELEV. (FT.)															
	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL						NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)								
337.14	2.40	1.00	10		8.4		12.7				13	0	0	7	4
334.64	2.50	0.50			4.8	4.3	31.3				31	0	0	17	7
332.14	2.50	2.10			14.8	18.1	38.3				38	0	0	21	9
329.64	2.50	1.20			10.1	10.3	68.2				68	0	0	37	12
327.14	2.50	3.50			21.1	30.2	89.2				89	0	0	49	14
324.64	2.50	3.50			21.1	30.2	112.0				112	0	0	62	17
322.14	2.50	3.70			22.0	31.9	121.9				122	0	0	67	19
319.64	2.50	2.30			15.7	19.8	135.8				136	0	0	75	22
317.14	2.50	2.10			14.8	18.1	142.8				143	0	0	79	24
314.64	2.50	1.20			10.1	10.3	153.8				154	0	0	85	27
312.14	2.50	1.30	10.7	11.2	176.5				177	0	0	97	29		
309.64	2.50	2.70	17.5	23.3	186.2				186	0	0	102	32		
307.14	2.50	1.80	13.4	15.5	210.8				211	0	0	116	34		
304.64	2.50	3.10	19.3	26.7	213.7				214	0	0	118	37		
302.14	2.50	1.20	10.1	10.3	227.2				227	0	0	125	39		
294.14	8.00	1.60	39.6	13.8	259.0				259	0	0	142	47		
289.14	5.00	0.70	12.9	6.0	271.1				271	0	0	149	52		
284.14	5.00	0.60	11.3	5.2	297.0				297	0	0	163	57		
279.14	5.00	2.30	31.3	19.8	319.7				320	0	0	176	62		
274.14	5.00	1.30	21.4	11.2	342.0				342	0	0	188	67		
269.14	5.00	1.40	22.6	12.1	372.3				372	0	0	205	72		
264.14	5.00	2.30	31.3	19.8	395.9				396	0	0	218	77		
254.14	10.00	1.40	45.1	12.1	433.2				433	0	0	238	87		
244.14	10.00	0.50	19.2	4.3	456.7				457	0	0	251	97		
234.14	10.00	1.00	34.9	8.6	488.2				488	0	0	268	107		
224.14	10.00	0.60	22.6	5.2	604.5				604	0	0	332	117		
212.14	12.00		89.4	98.9	1089.4				1089	0	0	599	129		
211.14	1.00		395.5	494.4	1485.0				1485	0	0	817	130.4		
210.14	1.00		395.5	494.4	1880.5				1880	0	0	1034	131.4		
209.14	1.00		395.5	494.4	2276.0				2276	0	0	1252	132.4		
208.14	1.00		395.5	494.4	2671.5				2672	0	0	1469	133.4		
207.14	1.00		395.5	494.4	3067.1				3067	0	0	1687	134.4		
206.14	1.00		395.5	494.4	3462.6				3463	0	0	1904	135.4		
205.14	1.00		395.5	494.4	3858.1				3858	0	0	2122	136.4		
204.14	1.00		395.5	494.4	4253.6				4254	0	0	2340	137.4		
203.14	1.00			494.4											



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE===== Pier 1

REFERENCE BORING ===== 1-S

LRFD or ASD or SEISMIC ===== LRFD

PILE CUTOFF ELEV. ===== 339.54 ft

GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 326.60 ft

GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) ===== None

BOTTOM ELEV. OF SCOUR, LIQUEF., or DD ===== ft

TOP ELEV. OF LIQUEF. (so layers above apply DD) ===== ft

TOTAL FACTORED SUBSTRUCTURE LOAD ===== 915 kips

TOTAL LENGTH OF SUBSTRUCTURE (along skew)===== 32.00 ft

NUMBER OF ROWS OF PILES PER SUBSTRUCTURE ===== 1

Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 228.63 KIPS

Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 85.73 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req.d Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
392 KIPS	371 KIPS	204 KIPS	86 FT.

PILE TYPE AND SIZE ===== Metal Shell 12"Φ w/.25" walls

Pile Perimeter===== 3.142 FT.

Pile End Bearing Area===== 0.785 SQFT.

BOT. OF LAYER ELEV. (FT.)															
	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL						NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)								
324.50	2.10	3.50	10	Sandy Gravel	17.7		49.6				50	0	0	27	15
322.00	2.50	3.70	10		22.0	31.9	59.5				59	0	0	33	18
319.50	2.50	2.30	10		15.7	19.8	73.4				73	0	0	40	20
317.00	2.50	2.10	6		14.8	18.1	80.4				80	0	0	44	23
314.50	2.50	1.20	5		10.1	10.3	91.3				91	0	0	50	25
312.00	2.50	1.30	5		10.7	11.2	114.1				114	0	0	63	28
309.50	2.50	2.70	6		17.5	23.3	123.8				124	0	0	68	30
307.00	2.50	1.80	6		13.4	15.5	148.4				148	0	0	82	33
304.50	2.50	3.10	2		19.3	26.7	151.3				151	0	0	83	35
302.00	2.50	1.20	4		10.1	10.3	164.8				165	0	0	91	38
294.00	8.00	1.60	4		39.6	13.8	196.6				197	0	0	108	46
289.00	5.00	0.70	5		12.9	6.0	208.7				209	0	0	115	51
284.00	5.00	0.60	4		11.3	5.2	234.6				235	0	0	129	56
279.00	5.00	2.30	5		31.3	19.8	257.3				257	0	0	142	61
274.00	5.00	1.30	9		21.4	11.2	279.5				280	0	0	154	66
269.00	5.00	1.40	11		22.6	12.1	309.9				310	0	0	170	71
264.00	5.00	2.30	8		31.3	19.8	333.4				333	0	0	183	76
254.00	10.00	1.40	10		45.1	12.1	370.8				371	0	0	204	86
244.00	10.00	0.50	11		19.2	4.3	394.2				394	0	0	217	96
234.00	10.00	1.00	11		34.9	8.6	425.7				426	0	0	234	106
224.00	10.00	0.60	9		22.6	5.2	542.0				542	0	0	298	116
212.00	12.00		20		89.4	98.9	1027.0				1027	0	0	565	128
211.00	1.00			Limestone	395.5	494.4	1422.5				1423	0	0	782	128.5
210.00	1.00			Limestone	395.5	494.4	1818.0				1818	0	0	1000	129.5
209.00	1.00			Limestone	395.5	494.4	2213.6				2214	0	0	1217	130.5
208.00	1.00			Limestone	395.5	494.4	2609.1				2609	0	0	1435	131.5
207.00	1.00			Limestone	395.5	494.4	3004.6				3005	0	0	1653	132.5
206.00	1.00			Limestone		494.4									

SUBSTRUCTURE===== Pier 2
 REFERENCE BORING ===== 2-S
 LRFD or ASD or SEISMIC ===== LRFD
 PILE CUTOFF ELEV. ===== 339.54 ft
 GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 326.60 ft
 GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) ===== None
 BOTTOM ELEV. OF SCOUR, LIQUEF., or DD ===== ft
 TOP ELEV. OF LIQUEF. (so layers above apply DD) ===== ft
 TOTAL FACTORED SUBSTRUCTURE LOAD ===== 915 kips
 TOTAL LENGTH OF SUBSTRUCTURE (along skew)===== 32.00 ft
 NUMBER OF ROWS OF PILES PER SUBSTRUCTURE ===== 1
 Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 228.63 KIPS
 Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 85.73 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
392 KIPS	301 KIPS	166 KIPS	61 FT.

PILE TYPE AND SIZE ===== Metal Shell 12"Φ w/.25" walls
 Pile Perimeter===== 3.142 FT.
 Pile End Bearing Area===== 0.785 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL						NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)								
324.50	2.10	0.90	6		6.7		9.3				9	0	0	5	15
322.00	2.50	0.30	4		3.0	2.6	20.0				20	0	0	11	18
319.50	2.50	1.20	8		10.1	10.3	30.1				30	0	0	17	20
317.00	2.50	1.20	4		10.1	10.3	41.1				41	0	0	23	23
314.50	2.50	1.30	2		10.7	11.2	56.1				56	0	0	31	25
312.00	2.50	1.80	8		13.4	15.5	69.4				69	0	0	38	28
309.50	2.50	1.80	9		13.4	15.5	73.3				73	0	0	40	30
307.00	2.50	0.70	4		6.5	6.0	79.8				80	0	0	44	33
304.50	2.50	0.70	4		6.5	6.0	92.3				92	0	0	51	35
299.00	5.50	1.40	5		24.8	12.1	191.2				191	0	0	105	41
294.00	5.00	10.00	10		51.1	86.1	199.2				199	0	0	110	46
289.00	5.00	5.00	5		51.1	43.1	207.3				207	0	0	114	51
284.00	5.00	0.00	0		0.0	0.0	267.6				268	0	0	147	56
279.00	5.00	7.00	7		51.1	60.3	301.5				301	0	0	166	61
274.00	5.00	5.00	5		51.1	43.1	412.9				413	0	0	227	66
269.00	5.00	12.00	12		51.1	103.4	567.4				567	0	0	342	74
264.00	5.00	24.00	24		51.1	206.8	515.1				515	0	0	283	76
254.00	10.00	12.00	12		102.2	103.4	608.7				609	0	0	335	86
244.00	10.00	11.00	11		102.2	94.8	633.4				633	0	0	348	96
234.00	10.00	2.00	2		57.2	17.2	716.5				716	0	0	394	106
224.00	10.00	5.00	5		102.2	43.1	775.6				776	0	0	427	116
214.00	10.00	0.00	0	Sandy Gravel	0.0	0.0	775.6				776	0	0	427	126
212.20	1.80	0.00	8	Sandy Gravel	0.0	0.0	1270.1				1270	0	0	699	127
211.20	1.00			Limestone	395.5	494.4	1665.6				1666	0	0	916	128.3
210.20	1.00			Limestone	395.5	494.4	2061.1				2061	0	0	1134	129.3
209.20	1.00			Limestone	395.5	494.4	2456.6				2457	0	0	1351	130.3
208.20	1.00			Limestone	395.5	494.4	2852.2				2852	0	0	1569	131.3
207.20	1.00			Limestone		494.4									

SUBSTRUCTURE===== **South Abutment**
 REFERENCE BORING ===== **2-S**
 LRFD or ASD or SEISMIC ===== **LRFD**
 PILE CUTOFF ELEV. ===== **340.47** ft
 GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = **338.47** ft
 GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) ===== **None**
 BOTTOM ELEV. OF SCOUR, LIQUEF., or DD ===== ft
 TOP ELEV. OF LIQUEF. (so layers above apply DD) ===== ft

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
392 KIPS	359 KIPS	197 KIPS	61 FT.

TOTAL FACTORED SUBSTRUCTURE LOAD ===== **532** kips
 TOTAL LENGTH OF SUBSTRUCTURE (along skew)===== **32.00** ft
 NUMBER OF ROWS OF PILES PER SUBSTRUCTURE ===== **1**
 Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 132.93 KIPS
 Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 49.85 KIPS

PILE TYPE AND SIZE ===== **Metal Shell 12"Φ w/.25" walls**

Pile Perimeter===== 3.142 FT.
 Pile End Bearing Area===== 0.785 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL						NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)								
337.00	1.47	0.30	3		1.8		9.5				10	0	0	5	3
334.50	2.50	0.90	1		8.0	7.8	33.0				33	0	0	18	6
332.00	2.50	2.70	7		17.5	23.3	48.8				49	0	0	27	8
329.50	2.50	2.50	6		16.6	21.5	57.6				58	0	0	32	11
327.00	2.50	1.60	6		12.4	13.8	63.9				64	0	0	35	13
324.50	2.50	0.90	6		8.0	7.8	66.7				67	0	0	37	16
322.00	2.50	0.30	4		3.0	2.6	77.5				77	0	0	43	18
319.50	2.50	1.20	8		10.1	10.3	87.5				88	0	0	48	21
317.00	2.50	1.20	4		10.1	10.3	98.5				98	0	0	54	23
314.50	2.50	1.30	2		10.7	11.2	113.5				113	0	0	62	26
312.00	2.50	1.80	8		13.4	15.5	126.9				127	0	0	70	28
309.50	2.50	1.80	9		13.4	15.5	130.7				131	0	0	72	31
307.00	2.50	0.70	4		6.5	6.0	137.2				137	0	0	75	33
304.50	2.50	0.70	4		6.5	6.0	149.7				150	0	0	82	36
299.00	5.50	1.40	5		24.8	12.1	248.6				249	0	0	137	41
294.00	5.00	10.00	10		51.1	86.1	256.7				257	0	0	141	46
289.00	5.00	5.00	5		51.1	43.1	264.7				265	0	0	146	51
284.00	5.00	0.00	0		0.0	0.0	325.0				325	0	0	179	56
279.00	5.00	7.00	7		51.1	60.3	358.9				359	0	0	197	61
274.00	5.00	5.00	5		51.1	43.1	470.3				470	0	0	259	66
269.00	5.00	12.00	12		51.1	103.4	624.8				625	0	0	344	71
264.00	5.00	24.00	24		51.1	206.8	572.5				573	0	0	315	76
254.00	10.00	12.00	12		102.2	103.4	666.1				666	0	0	366	86
244.00	10.00	11.00	11		102.2	94.8	690.8				691	0	0	380	96
234.00	10.00	2.00	2		57.2	17.2	773.9				774	0	0	426	106
224.00	10.00	5.00	5		102.2	43.1	833.1				833	0	0	458	116
214.00	10.00	0.00	0	Sandy Gravel	0.0	0.0	833.1				833	0	0	458	126
212.20	1.80	0.00	8	Sandy Gravel	0.0	0.0	1327.5				1327	0	0	730	128
211.20	1.00			Limestone	395.5	494.4	1723.0				1723	0	0	948	129.3
210.20	1.00			Limestone	395.5	494.4	2118.5				2119	0	0	1165	130.3
209.20	1.00			Limestone	395.5	494.4	2514.1				2514	0	0	1383	131.3
208.20	1.00			Limestone	395.5	494.4	2909.6				2910	0	0	1600	132.3
207.20	1.00			Limestone		494.4									