



NOTE:
OTHER METHODS OF ATTACHING HARDWARE FOR SIGNAL HEADS MAY BE USED UPON APPROVAL OF THE BUREAU OF ELECTRICITY.
SIGNALS MUST BE INSTALLED WITH ADEQUATE CLEARANCE FOR RELAMPING WITHOUT REMOVING VISOR OR ROTATING SIGNAL.

| | |
|---------------------------|----|
| APPROVED AS WORKING PLAN | BY |
| REVISIONS OF WORKING PLAN | |

| | | | | |
|--------------------|---------|---------|--------------|-----------|
| FORMER ROUTE NO. | SECTION | COUNTY | TOTAL SHEETS | SHEET NO. |
| FORMER PROJECT NO. | TEL# | PROJECT | | |

| | |
|---|---------------------------|
| A 5-5-98 ADDED TEMP SIGNAL DETAIL | |
| DATE | REVISION |
| WORK ORDER NO. | DATE |
| COST AT LOCATION ACCOUNT | |
| APPROPRIATION ACCOUNT | MATERIAL LABOR |
| TYPICAL TRAFFIC SIGNAL MOUNTING DETAILS | |
| CITY OF CHICAGO DEPT. OF STREETS AND SANITATION BUREAU OF ELECTRICITY DIVISION OF ELECTRICAL ENGINEERING | |
| DRAFTSMAN W. TROMPKA | ENGINEER M. De BARTOLO |
| SUPERVISING ENGINEER K. J. B. | DWG. NO. 835 |
| APPROVED BY ELECTRICITY M. De BARTOLO | |
| DATE 12-10-24 | |