

Girder 12 (Line No. 16)

Location	Station	Offset from EB PGL F.A.I. 57/70	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection & Grinding
Bk. of W. Abutment	2291+40.24	4.65	631.61	631.63
⊕ Bearing W. Abut.	2291+42.19	4.65	631.62	631.64
A	2291+52.19	4.65	631.65	631.73
B	2291+62.19	4.65	631.69	631.82
C	2291+72.19	4.65	631.72	631.91
D	2291+82.19	4.65	631.75	631.98
E	2291+92.19	4.65	631.77	632.04
F	2292+02.19	4.65	631.80	632.09
G	2292+12.19	4.65	631.82	632.12
H	2292+22.19	4.65	631.84	632.13
I	2292+32.19	4.65	631.86	632.13
J	2292+42.19	4.65	631.87	632.11
K	2292+52.19	4.65	631.89	632.09
L	2292+62.19	4.65	631.90	632.06
M	2292+72.19	4.65	631.91	632.03
N	2292+82.19	4.65	631.92	632.00
O	2292+92.19	4.65	631.92	631.98
P	2293+02.19	4.65	631.92	631.96
Q	2293+12.19	4.65	631.93	631.95
⊕ Bearing Pier	2293+22.11	4.65	631.93	631.95
R	2293+32.11	4.65	631.92	631.97
S	2293+42.11	4.65	631.92	631.99
T	2293+52.11	4.65	631.91	632.02
U	2293+62.11	4.65	631.90	632.05
V	2293+72.11	4.65	631.89	632.09
W	2293+82.11	4.65	631.88	632.13
X	2293+92.11	4.65	631.86	632.17
Y	2294+02.11	4.65	631.84	632.20
Z	2294+12.11	4.65	631.82	632.22
AA	2294+22.11	4.65	631.80	632.23
BB	2294+32.11	4.65	631.78	632.23
CC	2294+42.11	4.65	631.75	632.20
DD	2294+52.11	4.65	631.72	632.15
EE	2294+62.11	4.65	631.69	632.09
FF	2294+72.11	4.65	631.66	632.00
GG	2294+82.11	4.65	631.63	631.90
HH	2294+92.11	4.65	631.59	631.79
II	2295+02.11	4.65	631.55	631.67
JJ	2295+12.11	4.65	631.51	631.57
⊕ Bearing E. Abut.	2295+18.45	4.65	631.48	631.50
Bk. of E. Abutment	2295+20.40	4.65	631.47	631.49

Girder 13 (Line No. 17)

Location	Station	Offset from EB PGL F.A.I. 57/70	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection & Grinding
Bk. of W. Abutment	2291+34.27	13.65	631.73	631.75
⊕ Bearing W. Abut.	2291+36.68	13.65	631.74	631.76
A	2291+46.68	13.65	631.77	631.85
B	2291+56.68	13.65	631.81	631.94
C	2291+66.68	13.65	631.84	632.03
D	2291+76.68	13.65	631.87	632.11
E	2291+86.68	13.65	631.90	632.17
F	2291+96.68	13.65	631.92	632.22
G	2292+06.68	13.65	631.95	632.25
H	2292+16.68	13.65	631.97	632.26
I	2292+26.68	13.65	631.99	632.26
J	2292+36.68	13.65	632.01	632.24
K	2292+46.68	13.65	632.02	632.22
L	2292+56.68	13.65	632.03	632.19
M	2292+66.68	13.65	632.04	632.17
N	2292+76.68	13.65	632.05	632.14
O	2292+86.68	13.65	632.06	632.12
P	2292+96.68	13.65	632.06	632.10
Q	2293+06.68	13.65	632.07	632.09
⊕ Bearing Pier	2293+16.60	13.65	632.07	632.09
R	2293+26.60	13.65	632.07	632.11
S	2293+36.60	13.65	632.06	632.13
T	2293+46.60	13.65	632.06	632.16
U	2293+56.60	13.65	632.05	632.20
V	2293+66.60	13.65	632.04	632.24
W	2293+76.60	13.65	632.02	632.28
X	2293+86.60	13.65	632.01	632.32
Y	2293+96.60	13.65	631.99	632.35
Z	2294+06.60	13.65	631.97	632.38
AA	2294+16.60	13.65	631.95	632.39
BB	2294+26.60	13.65	631.93	632.38
CC	2294+36.60	13.65	631.91	632.36
DD	2294+46.60	13.65	631.88	632.31
EE	2294+56.60	13.65	631.85	632.25
FF	2294+66.60	13.65	631.82	632.16
GG	2294+76.60	13.65	631.79	632.06
HH	2294+86.60	13.65	631.75	631.95
II	2294+96.60	13.65	631.71	631.84
JJ	2295+06.60	13.65	631.67	631.73
⊕ Bearing E. Abut.	2295+12.93	13.65	631.65	631.67
Bk. of E. Abutment	2295+14.89	13.65	631.64	631.66

Stage I Construction Joint (Line No. 18)

Location	Station	Offset from EB PGL F.A.I. 57/70	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection & Grinding
Bk. of W. Abutment	2291+33.28	16.00	631.76	631.78
⊕ Bearing W. Abut.	2291+35.24	16.00	631.77	631.79
A	2291+45.24	16.00	631.81	631.88
B	2291+55.24	16.00	631.84	631.97
C	2291+65.24	16.00	631.87	632.06
D	2291+75.24	16.00	631.90	632.14
E	2291+85.24	16.00	631.93	632.20
F	2291+95.24	16.00	631.96	632.25
G	2292+05.24	16.00	631.98	632.28
H	2292+15.24	16.00	632.00	632.29
I	2292+25.24	16.00	632.02	632.29
J	2292+35.24	16.00	632.04	632.28
K	2292+45.24	16.00	632.05	632.26
L	2292+55.24	16.00	632.07	632.23
M	2292+65.24	16.00	632.08	632.20
N	2292+75.24	16.00	632.09	632.17
O	2292+85.24	16.00	632.10	632.15
P	2292+95.24	16.00	632.10	632.14
Q	2293+05.24	16.00	632.10	632.13
⊕ Bearing Pier	2293+15.16	16.00	632.10	632.12
R	2293+25.16	16.00	632.10	632.15
S	2293+35.16	16.00	632.10	632.17
T	2293+45.16	16.00	632.09	632.20
U	2293+55.16	16.00	632.09	632.23
V	2293+65.16	16.00	632.08	632.28
W	2293+75.16	16.00	632.06	632.32
X	2293+85.16	16.00	632.05	632.36
Y	2293+95.16	16.00	632.03	632.39
Z	2294+05.16	16.00	632.01	632.41
AA	2294+15.16	16.00	631.99	632.43
BB	2294+25.16	16.00	631.97	632.42
CC	2294+35.16	16.00	631.95	632.40
DD	2294+45.16	16.00	631.92	632.35
EE	2294+55.16	16.00	631.89	632.29
FF	2294+65.16	16.00	631.86	632.20
GG	2294+75.16	16.00	631.83	632.10
HH	2294+85.16	16.00	631.79	631.99
II	2294+95.16	16.00	631.75	631.88
JJ	2295+05.16	16.00	631.71	631.78
⊕ Bearing E. Abut.	2295+11.49	16.00	631.69	631.71
Bk. of E. Abutment	2295+13.44	16.00	631.68	631.70