

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	SHEET NO. 2
SA 13	X	KANE	27	8	10 SHEETS
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT			

Contract # 60B81 X 44 B2-1

GENERAL NOTES

1. Reinforcement bars shall conform to the requirements of ASTM A706 GR 60 (IL Modified). See special provisions.
2. Plan dimensions and details relative to existing structure have been taken from existing plans and are subject to nominal construction variations. It shall be the Contractor's responsibility to verify such dimensions and details in the field and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in the scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price for the work.
3. All Construction joints shall be bonded.
4. The minimum thickness of the Concrete overlay shall be 5" and varies as required to adjust for the new profile grade and beam camber.
5. No instream work will be allowed on this project.
6. Repair of the pier caps and abutment shall be completed prior to placement of the new deck beams.
7. The contractor is advised that the existing PPC Deck Beams are in a deteriorated condition with reduced load carrying capacity. It is the contractor's responsibility to account for the condition of the beams when developing construction procedures for removal and replacement of the superstructure.
8. If the contractor's procedure for existing beam removal or placement of new beams involves placement of cranes or other heavy equipment on new beams a detailed procedure shall be submitted to the Engineer for approval. The procedure shall include calculations, prepared and sealed by an Illinois Licensed Structural Engineer, verifying that the equipment and procedure used will not overstress the new beams. To distribute load to multiple beams and protect the concrete, in all cases a double layer mat of heavy timbers shall be used at all times under crane tracks or wheels and any outriggers in the down position. If necessary, shims shall be used under the crane mat to ensure uniform contact with the underlying beams. Prior to placement of the timber mats, the following shall be done: placement and tightening of transverse tie assemblies, grouting and curing the dowel rods 24 hours minimum, and after grouting and curing the shear keys. A temporary means of lateral restraint will be required for fascia beams at expansion ends of beams to prevent movement of the beams.
9. The cut strands at each beam end shall be given two coats of zinc dust spray or paint meeting the requirement of ASTM A780. The zinc dust spray or paint shall be applied before corrosion appears and allowed to dry according to the manufacturer's specifications prior to another coat of zinc. A concrete sealer meeting the requirements of Section 587 of the Standard Specifications shall be applied to the exterior face and 9" in on the underside of the fascia beams. The sealer shall be applied after visible crack growth has subsided. This work shall be performed by the producer and included with the cost of the beam.
10. Concrete Sealer shall be applied to the designated areas of the abutments and pier.

STATION 61+92.50
REBUILT 200_ BY
STATE OF ILLINOIS
S.A. RTE. 13
LOADING HS20
STR. NO. 045-0045

NAME PLATE

See Std. 515001
Relocate existing name plate next to rebuilt name plate, cost included in Name Plates.

TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB	TOTAL
Protective Coat	Sq. Yd.	328		328
Removal of Existing Superstructures	Each	1		1
Bridge Deck Grooving	Sq. Yd.	313		313
Precast Prestressed Concrete Deck Beams (17" Depth)	Sq. Ft.	2,944		2,944
Reinforcement Bars, Epoxy Coated	Pound	4,100		4,100
Steel Railing, Type SM	Foot	128		128
Name Plates	Each	1		1
Concrete Wearing Surface, 5"	Sq. Yd.	328		328
Bar Splicers	Each	65		65
Structural Repair of Concrete (Depth Greater Than 5")	Sq. Ft.		2.5	2.5
Structural Repair of Concrete (Depth Equal to or Less Than 5")	Sq. Ft.		13.4	13.4
Concrete Sealer	Sq. Ft.		865	865
Controlled Low-Strength Material	Cu. Yd.		1.8	1.8

**GENERAL NOTES AND
TOTAL BILL OF MATERIAL
S.A. 13 (IL RTE. 25)
OVER NORTON CREEK
S.A. RTE. 13 (F.A.S. 106)
KANE COUNTY, STA. 61+92.50
STRUCTURE NO. 045-0045**

DESIGNED DDB	200
CHECKED LLV	EXAMINED
DRAWN MGM	PASSED
CHECKED DDB	ENGINEER OF BRIDGE DESIGN
	ENGINEER OF BRIDGES AND STRUCTURES

