


- 2. WOOD POLES SHALL BE EMBEDDED 20' BELOW EXISTING GRADE.
- 3. MULTI-MOUNT LUMINAIRES SHALL BE TILTED 25° OR AS DIRECTED BY THE ENGINEER.
- 4. TEMPORARY LIGHTING SHALL BE INSTALLED AND OPERATIONAL PRIOR TO REMOVAL OF EXISTING LIGHTS.

PAY ITEM	UNIT	ОТҮ
LUMINAIRE, SODIUM VAPOR, MULTI-MOUNT, 400 WATT	EACH	1
LIGHT POLE, WOOD, 70 FOOT, CLASS 3	EACH	1
AERIAL CABLE, 2-1/C NO. 2 WITH MESSENGER WIRE	FOOT	383

SCALE: 1"=50"



FILE NAME =	DESIGNED	-	BENESCH	REVISED	-
\D468620-sht-I-74-TempStg08-light05.dgn	DRAWN	-	NLH	REVISED	-
USER NAME = tblank	CHECKED	-	GHT	REVISED	-
PLOT DATE = 9/5/2012	DATE	-	JULY 20, 2012	REVISED	-



STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

TEMPORARY LIGHTING CONSTRUCTION STAGE 8		F.A.	F.A.I. SECTION		COUNTY	TOTAL SHEETS	SHEE NO.	
		•	90-[14R;(14HB-4,14,14HV	B)BR]	TAZEWELL	2433	179	
CONCINCOTION STAGE S						CONTRACT	NO. 6	8620
SHEET NO. 79 OF 138 SHEETS	STA.	TO STA.		ILLINOIS F	ED. AIC	PROJECT		