

Summary of Quantities

#	Item	Section	Quantities				Unit	Rates/Remarks
			Kickapoo State Park	Woodard Shafts	Brookville Area Shaft #5	Brookville Strip Mine		
1	Special Clearing	201	0.55	0.15	0.15	0.15	1	L.S.
2	Earth Excavation	202	6612	-	1051	76	7739	C.Y. Compaction required IDOT 205
3	Furnished Excavation	204	-	-	-	2430	2430	C.Y. Compaction required IDOT 205
4	Granular Embankment, Special	206	-	-	-	443	443	Ton
5	Porous Granular Backfill	IDOT 209	96	-	-	-	96	C.Y. CA-6 Material
6	Special Excavation	214	-	618	309	-	927	C.Y.
7	CA-6 Fill Material	216	-	495	-	-	495	Ton
8	Seeding, Class 6, Conservation Mix	IDOT 250	3.4	0.4	0.8	1.3	5.9	Acre
9	Nitrogen Fertilizer Nutrient	IDOT 250	408	48	96	156	708	Pound 120 pounds/acre
10	Phosphorous Fertilizer Nutrient	IDOT 250	340	40	80	130	590	Pound 100 pounds/acre
11	Potassium Fertilizer Nutrient	IDOT 250	850	100	200	325	1475	Pound 250 pounds/acre
12	Agricultural Ground Limestone	IDOT 250	34	4	8	13	59	Ton 10 tons/acre
13	Mulch, Method 2, Procedure 2	IDOT 251	2.2	0.4	0.8	1.0	4.4	Acre 2 tons/acre
14	Stone Dumped Riprap, A3	IDOT 281	-	-	-	673	673	Ton
15	Stone Riprap, A3	IDOT 281	143	-	-	-	143	S.Y.
16	Special Excelsior Blanket	286	6045	-	-	1600	7645	S.Y.
17	Aggregate Surface Course, Type A	IDOT 402	350	-	-	-	350	Ton
18	Pipe Culverts, 36" Dia. RCCP	IDOT 542	268	-	-	-	268	Feet
19	Pipe Culverts, 15" Dia. RCCP	IDOT 542	10	-	-	-	10	Feet
20	Precast Reinforced Concrete Flared End Sections, 36" Dia.	IDOT 542	2	-	-	-	2	Each IDOT Standard 542101
21	Precast Reinforced Concrete Flared End Sections, 15" Dia.	IDOT 542	2	-	-	-	2	Each IDOT Standard 542101
22	Grating for Concrete Flared End Sections, 36" Dia.	IDOT 542	1	-	-	-	1	Each IDOT Standard 542311
23	Mine Opening Marker	686	-	2	1	-	3	Each
24	Mobilization (Max. 6% of Bid)	671	-	-	-	-	1	L.S.

GENERAL NOTES

Unless otherwise noted on the plans, all disturbed areas within the construction limits will be amended with agricultural ground limestone, fertilizer nutrients, seeded and mulched at the required rates specified in the plans.

The contractor is responsible for visiting the site and familiarizing himself with the existing conditions and the proposed reclamation work prior to submitting a bid.

The contractor shall provide and pay for all field engineering services to execute the project as specified in the Field Engineering section of the Special Provisions.

The contractor is responsible for locating and protecting all existing utility lines pertaining to the work.

Unless noted on the plans, all onsite access roads may be used for construction and must be maintained during construction and restored to original or better condition at the completion of work by the contractor. Access roads to the site as designated in the plans are to be maintained to the satisfaction of the engineer.

The construction limits will be staked by the contractor prior to construction. The contractor is responsible for the repair and or restitution at his own expense for all damages done to any area outside the construction limits.

Application rates specified in the plans are shown in the Summary of Quantities-Rates/Remarks column.

CONSTRUCTION NOTES

BURIAL/REMOVAL OF MATERIAL-Concrete and masonry debris designated for burial by the engineer shall be buried at least three feet below proposed final grade. Onsite organic debris and trash shall be disposed of in an engineer approved offsite landfill in accordance with Sections 201 and 501 of the Special Provisions.

TREE REMOVAL-Trees removed shall be disposed of onsite per Section 201 of the Special Provisions.

ACID WATER TREATMENT-If acid mine drainage treatment is determined necessary by the engineer, and not otherwise specified in the plans, any water treatment will be paid for in accordance with Article 109.04 of the Standard Specifications.

EROSION CONTROL-The contractor shall schedule his operations and take such precautions that may be necessary to prevent or minimize erosion. Failure to comply with this requirement shall cause the contractor to be fully responsible for repairing any eroded areas and cleaning up areas or drainage structures that have become silted in or damaged.

AGRICULTURAL GROUND LIMESTONE-Immediately prior to seed bed preparation, fertilizer nutrients and agricultural ground limestone shall be uniformly spread at the rates specified in the plans.

MULCHING-Within 24 hours from the time seeding has been performed, the seeded area shall be given a covering of mulch at the rates specified in the plans. The mulch is to be anchored into the soil in accordance with the requirements for method 2, procedure 2 of Article 251.03 of the Standard Specifications. If Excelsior or Special Excelsior Blanket is to be used, the blanket shall be placed the same day that the areas are seeded.

MINE REFUSE TREATMENT -After mine refuse has been graded to the subgrade shown in the plans, agricultural ground limestone shall be uniformly spread at the rate specified in the plans. A 3 inch layer of soil shall then be spread over the mine refuse treatment area and blended to a depth of 6 inches with an industrial offset disk approved by the engineer. Treated areas shall then be covered with 21 inches of soil.