

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
55	2004-119 GRR	WILL	15	2
STA.		TO STA.		
FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT				

CONTRACT 62885

INDEX OF SHEETS

SHEET NO.	DESCRIPTION	STANDARD NO.
1	COVER SHEET	000001-04
2	INDEX OF SHEETS, STANDARDS, AND GENERAL NOTES	601101
3	SUMMARY OF QUANTITIES	630001-05
4	TYPICAL SECTIONS	635006-02
5-10	EXISTING AND PROPOSED ROADWAY PLAN	635011-01
11	PIPE UNDERDRAIN OUTLET EXTENSOIN DETAILS	701101-01
12	CONCRETE COLLAR AND INLET BOX DETAILS	701400-02
13-14	MULTI-LANE FREEWAY PAVEMENT MARKING DETAILS	701401-03
15	TRAFFIC CONTROL FOR FREEWAY SHOULDER CLOSURES PARTIAL RAMP CLOSURES	702001-05

LIST OF STATE STANDARDS

STANDARD NO.	DESCRIPTION
000001-04	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
601101	CONCRETE HEADWALL FOR PIPE DRAIN
630001-05	STEEL PLATE BEAM GUARDRAIL
635006-02	REFLECTOR AND TERMINAL MARKER PLACEMENT
635011-01	REFLECTOR MARKER AND MOUNTING DETAILS
701101-01	OFF-RD OPERATIONS, MULTILANE LESS THAN 4.5 M (15') AWAY FOR SPEEDS > 45 MPH
701400-02	APPROACH TO LANE CLOSURE, FREEWAY/ EXPRESSWAY
701401-03	LANE CLOSURE, FREEWAY/ EXPRESSWAY
702001-05	TRAFFIC CONTROL DEVICES

PLAN NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOURS NOTIFICATION IS REQUIRED.)
- THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
- THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- THE CONTRACTOR SHALL CALL STATE ELECTRICAL CONTRACTOR AT (773) 287-7600 TO LOCATE STATE OWNED FACILITIES.
- THE CONTRACTOR SHALL CONSTRUCT PROJECT IN THE DIRECTION OF TRAFFIC
- THE CONTRACTOR SHALL NOT STORE ANY MATERIALS IN THE GRASS MEDIANS.

**INTERSTATE 55**

INTERSTATE 55 STATIONS	EARTH EXCAVATION (CU. YD.)	UNSUITABLE MATERIAL (CU.YD.)	EXCAVATION USED AS EMBANKMENT (SHRINKAGE 15%) (CU.YD.)	EMBANKMENT (CU. YD.)	EARTH WORK BALANCE SURPLUS (+) OR SHORTAGE (-) (CU. YD.)
1475+84 TO 1487+00	72	307.2	61.2	159	-97.8
1487+00 TO 1502+00	90	416.7	76.5	296	-219.5
1502+00 TO 1517+00	79	416.7	67.2	297	-229.8
1517+00 TO 1532+00	92	416.7	78.2	245	-166.8
1532+00 TO 547+00	112	416.7	95.2	244	-148.8
547+00 TO 562+00	149	377.4	126.6	249	-122.4
562+00 TO 577+00	110	416.7	93.5	258	-164.5
577+00 TO 592+00	89	416.7	75.6	421	-345.4
592+00 TO 600+30	51	222.2	43.4	265	-221.6
TOTAL	844	3407	717.4	2434	-1716.6

MIXTURE REQUIREMENTS

ITEM	AC TYPE	VOID	RAP %
BITUMINOUS SHOULDER, SUPERPAVE, 10"	PG 58-22	2% @ 30 GYR	50

NOTE:

A THICKNESS OF 6 INCHES OF TOPSOIL STRIPPING SHALL BE USED FOR REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL.

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION
NAME	DATE	
		<b>INTERSTATE 55</b> <b>INDEX OF SHEETS</b> <b>LIST OF STATE STANDARDS</b> <b>PLAN NOTES</b>  SCALE: VERT. : NONE HORIZ. : DATE:
DRAWN BY: RK		CHECKED BY: IR