ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.S. 888	00-00065 -00-BR	GALLATIN	22	22
FED. ROAD DIST. NO.		ILLINOIS	FED. AID PROJECT-	

ILLINOIS DEPARTMENT OF TRANSPORTATION
District Nine Materials
Bridge Foundation Boring Log
Sheet 1 of 3

FAS 888 (New Haven Road) Over N. Fork Cypress Creek
Route: FAS 888 Structure Number: 030-3001 Date: 02/20/2003
Section 00-00065-00-BR Bored By: Bryan Keller
County: Gallatin Location: 3.65 MI N ILL 13 Checked By: Rob Graeff

Boring No 4-S
Station 12+25
Offset 6' LT CL
Ground Surface 361.9 Ft

Surf Wat Elev: 349.9
Ground Water Elevation when Drilling 344.9
At Completion
At: Hrs:

DEPTH	BLOW	Qu tsf	W%	Description
				Bituminous Pavement
360.9				
				Crushed Aggregate
359.9				
	5			Medium, moist, brown, fine
	15		12	Sand
	11			86% Sand
				8% Silt
				6% Clay
5.0	2			
	6			
	7			
354.9				
	1			Medium, moist, grey, Clay
	4	0.9S	30	A7-6 with a Gravel Layer
	10			
352.4				
10.0	1			Stiff, moist, grey, Clay A7-6
	4	1.9	53	
	5			
349.9				
	WH			Medium, moist, grey, Clay
	2	0.9S	51	A7-6
	2			
347.4				
15.0	WH			Medium, very moist, grey, Clay
	1	0.7B	55	A7-6
	1			
344.9				
	WH			Loose, wet, grey, very fine
	4		21	Silty Sand
	5			95% Sand
				3% Silt
				2% Clay
342.4				
20.0	WH			Stiff, moist to very moist, grey,
	2	1.8S	35	Clay 7-6
	2			
	WH			
	2	1.5S	36	
	3			
337.4				
25.0	1			

DEPTH	BLOW	Qu tsf	W%	Description
	2	0.7B	45	Medium, very moist, grey, Clay
	2			A7-6
334.9				
	WH			Stiff, very moist, grey, Silty Clay
	2	1.1B	21	to Clay A7-6
	2			
332.4				
30.0	WH			Stiff, very moist, grey, Silty Clay
	2	1.2B	21	to Silty Clay Loam A-6
	3			
329.9				
	1			Medium, very moist, grey,
	6	0.7S	18	Silt Loam A-4
	6			
327.4				
35.0	WH			Soft, very moist, grey, Silt Loam
	WH	0.3B	20	A-4
	WH			
	WH			
	WH	0.3S	21	
	3			
322.4				
40.0	WR			Very soft, very moist to wet, grey,
	WR	0.2E	24	Silt Loam A-4
	WH			
45.0	WR			
	WR	0.4B	25	
	2			
312.4				
50.0	WH			

N-Std Pentr Test: 2" OD Sampler,
140# Hammer, 30" Fall (Type Fail. B-Bulge S-Shear E-Estimated P-Penetrometer)

Sheet 2 of 3
Route: FAS 888
Section: 00-00065-00-BR
Date: 02/20/2003
County: Gallatin

Boring No: 4-S
Station: 12+25
Offset: 6' LT CL
Ground Surface: 361.9 Ft

DEPTH	BLOW	Qu tsf	W%	Description
	1	0.4S	27	Soft, very moist, grey, Silty Clay
	2			A-6 with Sand and Rotten
				Wood Layers
307.4				
55.0	1			Very stiff, moist, grey, Clay
	4	2.1S	28	A7-6
	6			
302.4				
60.0	WH			Very loose, wet, grey, very
	1		21	fine Silty Sand
	1			84% Sand
				8% Silt
				8% Clay
297.4				
65.0	WH			Stiff, very moist, grey, Clay
	WH	1.4S	38	A7-6
	WH			
292.4				
70.0	7			Medium, wet, grey, fine Silty
	8		23	Sand with some Pea Gravel
	11			81% Sand
				5% Silt
				5% Clay
				9% Gravel
287.4				
75.0	8			

DEPTH	BLOW	Qu tsf	W%	Description
	13		17	Medium, wet, grey, Sandy
	15			Gravel
				66% Sand
				1% Silt
				2% Clay
				29% Gravel
282.4				
80.0	8			Medium, wet, grey, fine Sand
	8		21	with some Gravel
	9			86% Sand
				3% Silt
				1% Clay
				11% Gravel
85.0				
272.4				
90.0	6			Medium, wet, grey, fine Sand
	7		23	with some Gravel and Rotten
	10			Wood
				82% Sand
				3% Silt
				2% Clay
				13% Gravel
95.0				
100.0	10			

N-Std Pentr Test: 2" OD Sampler,
140# Hammer, 30" Fall (Type Fail. B-Bulge S-Shear E-Estimated P-Penetrometer)

Sheet 3 of 3
Route: FAS 888
Section: 00-00065-00-BR
Date: 02/20/2003
County: Gallatin

Boring No: 4-S
Station: 12+25
Offset: 6' LT CL
Ground Surface: 361.9 Ft

DEPTH	BLOW	Qu tsf	W%	Description
	8			Medium, wet, grey, fine Sand
	9			with some Gravel and Rotten
				Wood
105.0				
252.4				
110.0	20			Dense, wet, grey, very fine
	49		24	Silty Sand
	17			92% Sand
				6% Silt
				2% Clay
115.0				