

Designed By IMM Checked By GMS  
 Drawn By JJF Checked By GMS  
 9/1/2011 2:29:11 PM  
 O:\Dwr\Proj\Imp\Projects\Rand Park Pump Station Paving Block Repair\DCN Plan Sheets\Summary of Quantities.dgn

SUMMARY OF QUANTITIES			
CODE NO.	PAY ITEM	UNIT	QUANTITY
20300100	CHANNEL EXCAVATION	CU YD	100
28200200	FILTER FABRIC	SQ YD	87
*50500405	FURNISHING AND ERECTING STRUCTURAL STEEL	POUND	500
51100300	SLOPE WALL 6 INCH	SQ YD	207
67100100	MOBILIZATION	L SUM	1
*	TEMPORARY COFFERDAM SYSTEM	L SUM	1

\* SEE SPECIAL PROVISIONS

GENERAL NOTES

1. All elevations refer to N.G.V.D. 29 (National Geodetic Vertical Datum).
2. All lateral drainage that exists prior to construction shall be restored as shown on the plans and as directed by the Engineer. Unless otherwise specified, all costs of restoration shall be considered incidental to the Contract and no additional compensation will be allowed.
3. The Contractor is reminded to protect and restore, at his expense, in accordance with Article 107.20 of the Standard Specifications, any private or public property, including access roads, which may be damaged or destroyed due to construction operations.
4. All excess excavation and unsuitable materials shall be disposed of at locations provided by the Contractor at his expense and at locations inspected and approved by the Engineer.
5. The Contractor shall submit his proposed method of maintaining channel flows to the Engineer for approval prior to beginning construction.
6. The location, maintenance, removal and restoration to original condition of all haul roads shall be approved by the Engineer and all cost shall be incidental to the Contract.
7. All construction operations shall be contained within the easement area or work limits as indicated on the plans. It shall be the full responsibility of the Contractor to secure all rights of ingress and egress to said Right-of-Way including the satisfactory protection and restoration of property as required in article 107.20 and 107.23 of the Standard Specifications.
8. The Contractor shall call J.U.L.I.E. (800-892-0123) for the location of existing utilities 48 hours prior to construction.
9. The Contractor is alerted that the ground may be soft and movement of equipment may be difficult in the channel bottom area where Slope Wall installation is to be performed.
10. The sluice gates can be used as part of the Cofferdam System.
11. Plan dimensions and details relative to the existing structures have been taken from existing plans and/or past surveys and reports, and are subject to nominal construction variations. It shall be the Contractor's responsibility to verify such dimensions and details in the field and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in the scope of the work; however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

UTILITY REFERENCE TABLE

J.U.L.I.E.	Call 48 hours prior to construction	1-800-892-0123
------------	-------------------------------------	----------------