

SCHEDULE OF QUANTITIES

21101615 TOPSOIL FURNISH AND PLACE, 4"

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ YD	
LEFT						
19+25.0	2.0	-	22+18.0	2.0	65.1	
22+18.0	15.0	-	22+68.0	13.5	79.2	
22+68.0	7.0	-	23+15.0	4.0	28.7	
24+68.0	5.5	-	25+19.0	5.5	31.2	
25+19.0	10.0	-	25+53.0	10.0	37.8	
25+53.0	2.0	-	29+00.0	2.0	77.1	
RIGHT						
19+25.0	2.0	-	22+37.0	2.0	69.3	
22+37.0	10.5	-	22+84.0	11.0	56.1	
22+84.0	4.5	-	23+30.0	4.5	23.0	
24+84.0	4.5	-	25+33.0	4.5	24.5	
25+33.0	10.0	-	25+71.0	10.0	42.2	
25+71.0	2.0	-	29+00.0	2.0	73.1	
					TOTAL =	607

25000210 SEEDING, CLASS 2A

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	ACRE	
LEFT						
19+25.0	2.0	-	22+18.0	2.0	0.013	
22+18.0	15.0	-	22+68.0	13.5	0.016	
22+68.0	7.0	-	23+15.0	4.0	0.006	
24+68.0	5.5	-	25+19.0	5.5	0.006	
25+19.0	10.0	-	25+53.0	10.0	0.008	
25+53.0	2.0	-	29+00.0	2.0	0.016	
RIGHT						
19+25.0	2.0	-	22+37.0	2.0	0.014	
22+37.0	10.5	-	22+84.0	11.0	0.012	
22+84.0	4.5	-	23+30.0	4.5	0.005	
24+84.0	4.5	-	25+33.0	4.5	0.005	
25+33.0	10.0	-	25+71.0	10.0	0.009	
25+71.0	2.0	-	29+00.0	2.0	0.015	
					TOTAL =	0.1

25100630 EROSION CONTROL BLANKET

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ YD	
LEFT						
19+25.0	2.0	-	22+18.0	2.0	65.1	
22+18.0	15.0	-	22+68.0	13.5	79.2	
22+68.0	7.0	-	23+15.0	4.0	28.7	
24+68.0	5.5	-	25+19.0	5.5	31.2	
25+19.0	10.0	-	25+53.0	10.0	37.8	
25+53.0	2.0	-	29+00.0	2.0	77.1	
RIGHT						
19+25.0	2.0	-	22+37.0	2.0	69.3	
22+37.0	10.5	-	22+84.0	11.0	56.1	
22+84.0	4.5	-	23+30.0	4.5	23.0	
24+84.0	4.5	-	25+33.0	4.5	24.5	
25+33.0	10.0	-	25+71.0	10.0	42.2	
25+71.0	2.0	-	29+00.0	2.0	73.1	
					TOTAL =	607

28000400 PERIMETER EROSION BARRIER

STATION	OFFSET(FT)	-	STATION	OFFSET(FT)	FOOT
LEFT					
19+25.0	27.5 LT	-	19+26.0	29.5 LT	2.2
19+26.0	29.5 LT	-	22+18.0	29.5 LT	292.0
22+18.0	29.5 LT	-	22+19.0	41.0 LT	11.5
22+19.0	41.0 LT	-	23+15.0	36.0 LT	96.1
23+15.0	36.0 LT	-	23+15.0	26.0 LT	10.0
24+70.0	26.0 LT	-	24+68.0	37.5 LT	11.7
24+68.0	37.5 LT	-	25+53.0	37.5 LT	85.0
25+53.0	29.0 LT	-	29+00.0	30.0 LT	347.0
29+00.0	30.0 LT	-	29+00.0	28.0 LT	2.0

28000400 PERIMETER EROSION BARRIER (CONT)

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	TON	
RIGHT						
19+24.0	27.5 RT	-	19+24.0	30.0 RT	2.5	
19+24.0	30.0 RT	-	22+37.0	31.0 RT	313.0	
22+37.0	31.0 RT	-	22+37.0	39.0 RT	8.0	
22+37.0	39.0 RT	-	23+30.0	37.5 RT	93.0	
23+30.0	37.5 RT	-	23+30.0	27.5 RT	10.0	
24+83.0	27.5 RT	-	24+85.0	37.5 RT	10.2	
25+71.0	37.5 RT	-	25+71.0	30.0 RT	7.5	
25+71.0	30.0 RT	-	29+00.0	30.0 RT	329.0	
29+00.0	30.0 RT	-	29+00.0	27.5 RT	2.5	
					TOTAL =	1,633

28000510 INLET FILTERS

STATION	OFFSET(FT)	EACH	
20+00.0	27.0 LT	1.0	
21+00.0	27.0 LT	1.0	
22+00.0	27.0 LT	1.0	
26+00.0	27.0 LT	1.0	
26+00.0	27.0 RT	1.0	
28+00.0	27.0 LT	1.0	
28+00.0	27.0 RT	1.0	
29+00.0	27.0 RT	1.0	
		TOTAL =	8

31101400 SUBBASE GRANULAR MATERIAL, TYPE B 6"

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ YD	
COMBINATION CURB AND GUTTER						
19+25.0	2.6	-	22+38.0	2.6	89.8	
25+19.0	2.6	-	29+00.0	2.6	109.4	
19+25.0	2.6	-	22+54.0	2.6	94.4	
25+33.0	2.6	-	29+00.0	2.6	105.3	
CORRUGATED MEDIAN						
15+00.0	4.0	-	23+06.0	4.0	358.2	
24+78.0	4.0	-	25+25.0	4.0	20.9	
					TOTAL =	778

40600635 LEVELING BINDER (MACHINE METHOD), N70

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	TON	
COMBINATION CURB AND GUTTER						
19+25.0	2.6	-	22+38.0	2.6	89.8	
25+19.0	2.6	-	29+00.0	2.6	109.4	
19+25.0	2.6	-	22+54.0	2.6	94.4	
25+33.0	2.6	-	29+00.0	2.6	105.3	
CORRUGATED MEDIAN						
15+00.0	4.0	-	23+06.0	4.0	358.2	
24+78.0	4.0	-	25+25.0	4.0	20.9	
					TOTAL =	218

40600982 HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ YD	
28+95.5	52.0	-	29+00.0	52.0	26.0	
					TOTAL =	26

40600985 PORTLAND CEMENT CONCRETE SURFACE REMOVAL - BUTT JOINT

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ YD	
19+25.0	24.0	-	19+55.0	24.0	80.0	
19+25.0	24.0	-	19+55.0	24.0	80.0	
					TOTAL =	160

40603340 HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	TON	
SEE TEMPORARY PAVEMENT						
RATE = 112.0 POUND / SQ YD / INCH						
DEPTH = 1.5 INCH						
19+25.0	48.0	-	22+40.0	48.0	141.1	
25+15.0	48.0	-	25+25.0	48.0	4.5	
25+25.0	52.0	-	29+00.0	52.0	182.0	
					TOTAL =	328

42001420 BRIDGE APPROACH PAVEMENT CONNECTOR (PCC)

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ YD	
22+39.2	26.0	-	22+45.2	26.0	17.3	
22+40.2	26.0	-	22+46.2	26.0	17.3	
25+08.7	26.0	-	25+14.7	26.0	17.3	
25+09.5	26.0	-	25+15.5	26.0	17.3	
					TOTAL =	69

44000100 PAVEMENT REMOVAL

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ YD	
22+39.2	26.0	-	22+45.2	26.0	17.3	
22+40.2	26.0	-	22+46.2	26.0	17.3	
25+08.7	26.0	-	25+14.7	26.0	17.3	
25+09.5	26.0	-	25+15.5	26.0	17.3	
					TOTAL =	448

44000159 HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/2"

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ YD	
25+15.0	48.0	-	25+25.2	48.0	54.1	
25+25.2	52.0	-	28+95.5	52.0	2,139.8	
					TOTAL =	2,194

44000500 COMBINATION CURB AND GUTTER REMOVAL

STATION	OFFSET(FT)	-	STATION	OFFSET(FT)	FOOT	
19+25.0	26.5 LT	-	23+00.0	27.0 LT	375.0	
24+73.0	27.0 LT	-	29+00.0	28.0 LT	427.0	
19+25.0	26.0 RT	-	23+13.0	27.0 RT	388.0	
24+84.0	27.0 RT	-	29+00.0	25.5 RT	416.0	
					TOTAL =	1,606

44000600 SIDEWALK REMOVAL

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ FT	
25+03.0	6.0	-	25+19.0	6.0	96.0	
25+15.0	6.0	-	25+33.0	6.0	108.0	
					TOTAL =	204

54213447 END SECTIONS 12"

STATION	OFFSET(FT)	EACH	
CRAWFORD AVE			
22+43.0	101.0 LT	1.0	
22+48.0	101.0 LT	1.0	
		TOTAL =	2

60100945 PIPE DRAINS 12"

STATION	OFFSET(FT)	-	STATION	OFFSET(FT)	FOOT	
CRAWFORD AVE						
22+49.0	26.0 LT	-	22+43.0	101.0 LT	75.2	
22+55.0	3.0 RT	-	22+48.0	101.0 LT	104.2	
					TOTAL =	179

60300105 FRAMES AND GRATES TO BE ADJUSTED

STATION	OFFSET(FT)	EACH	
20+00.0	26.5 LT	1.0	
21+00.0	26.5 LT	1.0	
22+00.0	26.5 LT	1.0	
26+00.0	26.5 LT	1.0	
26+00.0	26.5 RT	1.0	
28+00.0	26.5 LT	1.0	
28+00.0	26.5 RT	1.0	
29+00.0	26.5 RT	1.0	
MOT			
15+99.6	2.6 RT	2.0	
		TOTAL =	10

60603800 COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12

STATION	OFFSET(FT)	-	STATION	OFFSET(FT)	FOOT	
19+25.0	26.5 LT	-	23+00.0	27.0 LT	375.0	
24+73.0	27.0 LT	-	29+00.0	28.0 LT	427.0	
19+25.0	26.0 RT	-	23+13.0	27.0 RT	388.0	
24+84.0	27.0 RT	-	29+00.0	25.5 RT	416.0	
					TOTAL =	1,606

60624600 CORRUGATED MEDIAN

STATION	WIDTH(FT)	-	STATION	WIDTH(FT)	SQ FT	
15+00.0	4.0	-	23+06.0	4.0	3,224.0	
24+78.0	4.0	-	25+25.0	4.0	188.0	
					TOTAL =	3,412

60900140 TYPE B INLET BOX, STANDARD 609006

STATION	OFFSET(FT)	EACH
CRAWFORD AVE		
22+49.0	25.0 LT	1.0
22+55.0	4.0 RT	1.0
		TOTAL =