## TRAFFIC SIGNAL LEGEND

DRAWN - XXX   REVISED -			STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION			SCALE: N.T	STRICT 1 - STANDARD TRAFFIC SIGNAL DESIGN D  "S. SHEET NO. 6 OF 9 SHEETS STA. TO	JETAILS 3887	R-VB-R DIST. NO.   ILLINOIS   FED.	KANE 83 CONTRACT NO. 6C	
/IRELESS ACCESS POINT  LE NAME = USER NAME =	\$USER\$	DESIGNED - XXX	REVISED -	NO. 6 SOLID COPPER (GREEN)					F.A.U. RTE.	SECTION	COUNTY TOTAL SHEETS
VIRELESS DETECTOR SENSOR	P		(W)	GROUND CABLE IN CONDUIT				CROSSBUCK		75	*
AN, TILT, ZOOM CAMERA	Pilli Rom			DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED		- <u>(5)</u> -	-(5)-	CROSSING GATE		X0X	X0X-
	R			RADIO REPEATER	RERR	ERR	RR	FLASHING SIGNAL	×	XOX	XOX
DEO DETECTION ZONE	124			RADIO INTERCONNECT	<del>   </del>   **o		+++•	RAILROAD CANTILEVER MAST ARM		<u>2-3</u> XO <u>X</u> ————————X	X <b>0X</b> ————X
DEO DETECTION CAMERA	R	(V)	<b>©</b>	SYMBOL, WITH COUNTDOWN TIMER	na (R		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	RAILROAD CONTROL CABINET		EXISTING  B×B	PROPOSED
CROWAVE VEHICLE SENSOR	r Imp	M)	<b>₩</b>	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL			♥ C		- Common State of the Comm		PRODUCEN
REFORMED DETECTOR LOOP		P	P	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		<b>X</b>	<b>9</b>	RAILROAD SYMBOLS			
O RIGHT TURN" TECTOR LOOP, TYPE I				12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		[PS]	PS
LUMINATED SIGN	R.	8	<b>©</b>	WALK/DON'T WALK SYMBOL				(SYSTEM) DETECTOR		PS	PIS
UMINATED SIGN O LEFT TURN"	R		<b>(5)</b>	12" (300mm) PEDESTRIAN SIGNAL HEAD		vp··· бw	wpn.	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) PREFORMED INTERSECTION AND SAMPLING		PP	•
CCESSIBLE PEDESTRIAN PUSHBUTTON DE	TECTOR APS	@aps	APS				<del>∢</del> Υ <b>∢</b> G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) I EXISTING PREFORMED INTERSECTION LOOP DETECTO			
DESTRIAN PUSHBUTTON DETECTOR	P <sub>O</sub>	<b>©</b>	<b>®</b>	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			Y	EXISTING INTERSECTION LOOP DETECTOR		<u>E</u>	the state of the s
DESTRIAN SIGNAL HEAD	ħ	<b>-</b> []	<b></b>			(R)	R	SAMPLING (SYSTEM) DETECTOR			<u> </u>
ASHER INSTALLATION DENOTES SOLAR POWER)	O-D-47"	O-t⊃ <sub>c,E,,,</sub>	<b>€ –</b> "F"			(*) (*)	<u>4 Υ</u> <b>4</b> 6	INTERSECTION & SAMPLING		[15]	IS
SNAL HEAD OPTICALLY PROGRAMMED	R P	-t>opo	<b>-&gt;</b> "p"	SIGNAL FACE			e Y	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF		
JMBERS INDICATE THE CONSTRUCTION S SNAL HEAD WITH BACKPLATE	TAGE)	+>				R	R	AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVED	RMF O-X		
GNAL HEAD GNAL HEAD CONSTRUCTION STAGES	— <del>———</del>		2	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY	Seiten view		
Y WIRE	₹ R	>	<b>&gt;</b>	12" (30Cmm) TRAFFIC SIGNAL SECTION			R	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
MPORARY WOOD POLE (CLASS 5 OR TTER) 45 FOOT (13.7m) MINIMUM	* ⊗	<b>⊗</b>	•	ABANDON ITEM	A	ra <del>nda</del> n		STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	O <sup>RMF</sup>		
GNAL POST	80	O	•	REMOVE ITEM RELOCATE ITEM	RL RL			FOUNDATION TO BE REMOVED			
EEL COMBINATION MAST ARM SEMBLY AND POLE WITH PTZ CAMERA	Company of the Compan		PZK	INTERSECTION ITEM	m.	1	1P	OR (S) SERVICE  CONTROLLER CABINET AND	RCF		
SEMBLY AND POLE WITH LUMINAIRE	**************************************	0-16		SYSTEM ITEM		S	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		¢.	c <sub>II</sub> -
UMINUM MAST ARM ASSEMBLY AND POLI TEEL COMBINATION MAST ARM	0	0		COMMON TRENCH COILABLE NONMETALLIC CONDUIT (EMPTY)			CT CNC	(NUMBER OF FIBERS & TYPE TO BE NOTED ON PLANS)		<b></b>	<del>-</del> O-
TEEL MAST ARM ASSEMBLY AND POLE	6	<u> </u>	<u> </u>	AND CABLE	<del>1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1</del>	. De mainte de la descripción de la contractiva de la company (		FIBER OPTIC CABLE NO. 62.5/125,		· ·	
LEPHONE CONNECTION POLE OR (G) GROUND MOUNT	R	P <sub>I</sub>	P	IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	19			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		<b>−</b> €4f∕−	-(24F)
RVICE INSTALLATION, POLE OR (G) GROUND MOUNT		HOP .	<b>■</b> P	JUNCTION BOX GALVANIZED STEEL CONDUIT	<u>u</u>		12	FIBER OPTIC CABLE NO. 62.5/125, MM12F		<u>95</u> -	
INTERRUPTIBLE POWER SUPPLY	UPS P	EUPS	UPS	DOUBLE HANDHOLE	R D		<b>SS</b>	COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		-(6)-	-6-
STER MASTER CONTROLLER		EMMC	MMC	HEAVY DUTY HANDHOLE	R	H	B	VENDOR CABLE FOR CAMERA		<del>-</del> Ø	—©—
MMUNICATIONS CABINET STER CONTROLLER	[cc]"	E C C	.Cε MC	HANDHOLE	g	N					· ''\$
ILROAD CONTROL CABINET	<b></b>			CONFIRMATION BEACON	Rø-(J	<del>0-</del> 0	••	COAXIAL CABLE		—(ō)—	— <u>©</u> —
NTROLLER CABINET	No.	X	H	EMERGENCY VEHICLE LIGHT DETECTOR	₽₩	<b>⊗</b>	•4	NO. 14 I/C, UNLESS NOTED OTHERWISE		<u> </u>	0-
<u>M</u>	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED